

Tibero

에러 참조 안내서

Tibero 7

TMAXTibero

Copyright © 2025 TmaxTibero Co., Ltd. All Rights Reserved.

Copyright Notice

Copyright © 2025 TmaxTibero Co., Ltd. All Rights Reserved.

대한민국 경기도 성남시 분당구 정자일로 45, 티맥스소프트타워 우)13613

Website

<http://www.tmaxtibero.com>

기술서비스센터

Tel : +82-1544-8629

E-Mail : info@tmax.co.kr

Restricted Rights Legend

All TmaxTibero Software (Tibero®) and documents are protected by copyright laws and international convention. TmaxTibero software and documents are made available under the terms of the TmaxTibero License Agreement and this document may only be distributed or copied in accordance with the terms of this agreement. No part of this document may be transmitted, copied, deployed, or reproduced in any form or by any means, electronic, mechanical, or optical, without the prior written consent of TmaxTibero Co., Ltd. Nothing in this software document and agreement constitutes a transfer of intellectual property rights regardless of whether or not such rights are registered) or any rights to TmaxTibero trademarks, logos, or any other brand features.

This document is for information purposes only. The company assumes no direct or indirect responsibilities for the contents of this document, and does not guarantee that the information contained in this document satisfies certain legal or commercial conditions. The information contained in this document is subject to change without prior notice due to product upgrades or updates. The company assumes no liability for any errors in this document.

이 소프트웨어(Tibero®) 사용설명서의 내용과 프로그램은 저작권법과 국제 조약에 의해서 보호받고 있습니다. 사용설명서의 내용과 여기에 설명된 프로그램은 TmaxTibero Co., Ltd.와의 사용권 계약 하에서만 사용이 가능하며, 사용설명서는 사용권 계약의 범위 내에서만 배포 또는 복제할 수 있습니다. 이 사용설명서의 전부 또는 일부분을 TmaxTibero의 사전 서면 동의 없이 전자, 기계, 녹음 등의 수단을 사용하여 전송, 복제, 배포, 2차적 저작물작성 등의 행위를 하여서는 안 됩니다.

이 소프트웨어 사용설명서와 프로그램의 사용권 계약은 어떠한 경우에도 사용설명서 및 프로그램과 관련된 지적 재산권(등록 여부를 불문)을 양도하는 것으로 해석되지 아니하며, 브랜드나 로고, 상표 등을 사용할 권한을 부여하지 않습니다. 사용설명서는 오로지 정보의 제공만을 목적으로 하고, 이로 인한 계약상의 직접적 또는 간접적 책임을 지지 아니하며, 사용설명서 상의 내용은 법적 또는 상업적인 특정한 조건을 만족시키는 것을 보장하지는 않습니다. 사용설명서의 내용은 제품의 업그레이드나 수정에 따라 그 내용이 예고 없이 변경될 수 있으며, 내용상의 오류가 없음을 보장하지 아니합니다.

Trademarks

Tibero® is a registered trademark of TmaxTibero Co., Ltd. Other products, titles or services may be registered trademarks of their respective companies.

Tibero®는 TmaxTibero Co., Ltd.의 등록 상표입니다. 기타 모든 제품들과 회사 이름은 각각 해당 소유주의 상표로서 참조용으로만 사용됩니다.

Open Source Software Notice

Some modules or files of this product are subject to the terms of the following licenses. : OpenSSL, RSA Data Security, Inc., Apache Foundation, Jean-loup Gailly and Mark Adler, Paul Hsieh's hash

Detailed Information related to the license can be found in the following directory : \${INSTALL_PATH}/license/oss_licenses

본 제품의 일부 파일 또는 모듈은 다음의 라이선스를 준수합니다. : OpenSSL, RSA Data Security, Inc., Apache Foundation, Jean-loup Gailly and Mark Adler, Paul Hsieh's hash

관련 상세한 정보는 제품의 다음의 디렉터리에 기재된 사항을 참고해 주십시오. : \${INSTALL_PATH}/license/oss_licenses

안내서 정보

안내서 제목: Tibero 에러 참조 안내서

발행일: 2025-09-30

소프트웨어 버전: Tibero 7.2.4

안내서 버전: v7.2.4

내용 목차

안내서에 대하여	vii
제1장 1000 ~ 1999	1
제2장 2000 ~ 2999	29
제3장 3000 ~ 3999	59
제4장 4000 ~ 4999	63
제5장 5000 ~ 5999	69
제6장 6000 ~ 6999	89
제7장 7000 ~ 7999	91
제8장 8000 ~ 8999	205
제9장 9000 ~ 9999	237
제10장 10000 ~ 10999	265
제11장 11000 ~ 11999	279
제12장 12000 ~ 12999	293
제13장 14000 ~ 14999	321
제14장 15000 ~ 15999	379
제15장 16000 ~ 16999	419
제16장 17000 ~ 17999	421
제17장 18000 ~ 18999	425
제18장 21000 ~ 21999	431
제19장 22000 ~ 22999	441
제20장 23000 ~ 23999	443
제21장 24000 ~ 24999	445
제22장 25000 ~ 25999	473
제23장 26000 ~ 26999	477
제24장 27000 ~ 27999	481
제25장 28000 ~ 28999	485
제26장 29000 ~ 29999	489
제27장 30000 ~ 30999	491
제28장 60000 ~ 60999	497
제29장 70000 ~ 70999	509
제30장 80000 ~ 80999	523

제31장	90000 ~ 90999	535
제32장	110000 ~ 110999	567
제33장	120000 ~ 120999	569
제34장	130000 ~ 130999	571
제35장	140000 ~ 140999	591
제36장	150000 ~ 150999	595
제37장	160000 ~ 160999	597
제38장	190000 ~ 190999	599
제39장	400000 ~ 400999	601
제40장	410000 ~ 410999	603
제41장	528000 ~ 528999	613

안내서에 대하여

안내서의 대상

본 안내서는 Tiberio[®](이하 Tiberio)를 사용하는 도중에 발생할 수 있는 에러에 대한 원인과 해결 방법을 참고하려는 모든 데이터베이스 사용자를 대상으로 기술한다.

안내서의 전제 조건

본 안내서를 원활히 이해하기 위해서는 다음과 같은 사항을 미리 알고 있어야 한다.

- 데이터베이스의 이해
- RDBMS의 이해
- SQL의 이해
- 프로그래밍의 기본 지식

안내서의 제한 조건

본 안내서는 Tiberio를 실무에 적용하거나 운용하는 데 필요한 모든 사항을 포함하지 않는다. 따라서 설치, 환경설정 등 운용 및 관리에 대해서는 각 제품 안내서를 참고하기 바란다.

안내서 규약

표기	의미
<<AaBbCc123>>	프로그램 소스 코드의 파일명
<Ctrl>+C	Ctrl과 C를 동시에 누름
[Button]	GUI의 버튼 또는 메뉴 이름
진하게	강조
""(따옴표)	다른 관련 안내서 또는 안내서 내의 다른 장 및 절 언급
'입력항목'	화면 UI에서 입력 항목에 대한 설명
하이퍼링크	메일 계정, 웹 사이트
>	메뉴의 진행 순서
+----	하위 디렉터리 또는 파일 있음
----	하위 디렉터리 또는 파일 없음
참고	참고 또는 주의사항
주의	주의할 사항
[그림 1.1]	그림 이름
[예 1.1]	예제 이름
AaBbCc123	Java 코드, XML 문서
[command argument]	옵션 파라미터
< xyz >	'<'와 '>' 사이의 내용이 실제 값으로 변경됨
	선택 사항. 예) A B: A나 B 중 하나
...	파라미터 등이 반복되어서 나옴
\${ }	환경변수

시스템 사용 환경

	요구 사항	
Platform	Solaris (Solaris 11)	
	AIX (AIX 7.1/AIX 7.2/AIX 7.3)	
	GNU (X86, 64, IA64)	
	Red Hat Enterprise Linux 7 kernel 3.10.0 이상	
	Windows(x86) 64bit	
	Hardware	최 소 2.5GB 하 드 디 스 크 공 간
1GB 이상 메모리 공간		
Compiler	PSM (C99 지원 필요)	
	tbESQL/C (C99 지원 필요)	

관련 안내서

안내서	설명
Tibero 설치 안내서	설치 과정에 필요한 시스템 요구사항과 설치 및 제거 방법을 기술한 안내서이다.
Tibero tbCLI 안내서	Call Level Interface인 tbCLI의 개념과 구성요소, 프로그램 구조를 소개하고 tbCLI 프로그램을 작성하는 데 필요한 데이터 타입, 함수, 에러 메시지를 기술한 안내서이다.
Tibero 애플리케이션 개발자 안내서	각종 애플리케이션 라이브러리를 이용하여 애플리케이션 프로그램을 개발하는 방법을 기술한 안내서이다.
Tibero External Procedure 안내서	External Procedure를 소개하고 이를 생성하고 사용하는 방법을 기술한 안내서이다.
Tibero JDBC 개발자 안내서	Tibero에서 제공하는 JDBC 기능을 이용하여 애플리케이션 프로그램을 개발하는 방법을 기술한 안내서이다.
Tibero tbESQL/C 안내서	C 프로그래밍 언어를 사용해 데이터베이스 작업을 수행하는 각종 애플리케이션 프로그램을 작성하는 방법을 기술한 안내서이다.
Tibero tbESQL/COBOL 안내서	COBOL 프로그래밍 언어를 사용해 데이터베이스 작업을 수행하는 각종 애플리케이션 프로그램을 작성하는 방법을 기술한 안내서이다.
Tibero tbPSM 안내서	저장 프러시저 모듈인 tbPSM의 개념과 문법, 구성요소를 소개하고, 프로그램을 작성하는 데 필요한 제어 구조, 복합 타입, 서브프로그램, 패키지 및 SQL 문장을 실행하고 에러를 처리하는 방법을 기술한 안내서이다.
Tibero tbPSM 참조 안내서	저장 프러시저 모듈인 tbPSM의 패키지를 소개하고, 이러한 패키지에 포함된 각 프러시저와 함수의 프로토타입, 파라미터, 예제 등을 기술한 참조 안내서이다.
Tibero 관리자 안내서	Tibero의 동작과 주요 기능의 원활한 수행을 보장하기 위해 DBA가 알아야 할 관리 방법을 논리적 또는 물리적 측면에서 설명하고, 관리를 지원하는 각종 도구를 기술한 안내서이다.
Tibero 유틸리티 안내서	데이터베이스와 관련된 작업을 수행하기 위해 필요한 유틸리티의 설치 및 환경설정, 사용 방법을 기술한 안내서이다.
Tibero TAS 안내서	Tibero Active Storage(TAS)를 사용해서 Tibero의 파일을 관리하고자 하는 관리자를 대상으로 기술한 안내서이다.

안내서	설명
Tibero 참조 안내서	Tibero의 동작과 사용에 필요한 초기화 파라미터와 데이터 사전, 정적 뷰, 동적 뷰를 기술한 참조 안내서이다.
Tibero SQL 참조 안내서	데이터베이스 작업을 수행하거나 애플리케이션 프로그램을 작성할 때 필요한 SQL 문장을 기술한 참조 안내서이다.
Tibero TDP.NET 안내서	Tibero Data Provider for .NET 기능을 기술하는 안내서이다.
Tibero IMCS 안내서	Tibero에서 제공하는 In-Memory Column Store(이하 IMCS) 기능을 기술하는 안내서이다.

제1장 1000 ~ 1999

1001: Unable to create file %1\$s.

Cause	Cannot create the file.
Action	Check the file path and permissions.

1002: Unable to lock file %1\$s.

Cause	Cannot lock the file.
Action	Check the file path and permissions.

1003: Unable to open file %1\$s.

Cause	Cannot open the file.
Action	Check the file path and permissions.

1004: Unable to read file %1\$s.

Cause	Cannot read the file.
Action	Check the file path and permissions.

1005: Unable to write to file %1\$s.

Cause	Cannot write to the file.
Action	Check the file path and permissions.

1006: Unable to open log file in group %1\$d.

Cause	Cannot open the log file.
--------------	---------------------------

Action	Check the log file path and permissions.
---------------	--

1007: Unable to read log file in group %1\$d, block %2\$d.

Cause	Cannot read the log file.
Action	Check the log file path and permissions.

1008: Unable to write to log file in group %1\$d, block %2\$d.

Cause	Cannot write to the log file.
Action	Check the log file path and permissions.

1009: Unable to read corrupt block: file# %1\$u, block# %2\$u.

Cause	Cannot read the corrupted data block.
Action	Perform a media recovery and try again.

1010: Unable to read fractured block: file# %1\$u, block# %2\$u.

Cause	Cannot read the data block due to inconsistency.
Action	Perform a media recovery and try again.

1011: File is not %1\$s file: %2\$s.

Cause	Invalid file type.
Action	Check the data file type and try again.

1012: Log file group mismatch: GROUP %1\$d <> %2\$d (%3\$s)

Cause	The log file is not the one from the specified log group.
Action	Check the log file and try again.

1013: Unable to create log file %1\$s.

Cause	Failed to create a log file.
Action	Check the log file path and permissions.

1014: Unable to create datafile %1\$s.

Cause	Failed to create a data file.
Action	Check the file path and permissions.

1015: Unable to pin more blocks.

Cause	The size of buffer cache is insufficient.
Action	Check the size of buffer cache and try again.

1016: Log group %1\$d is corrupt.

Cause	One of the log group members is corrupt.
Action	Perform a recovery of the log file.

1017: Duplicate log file %1\$d exists.

Cause	Tried to create a log file with a duplicate log file number.
Action	Check the log file.

1018: Bad log group %1\$d (%2\$s).

Cause	One of the log group members is abnormal.
Action	Perform a recovery of the log file.

1019: Bad log file %2\$s (%1\$s).

Cause	Log file is abnormal.
--------------	-----------------------

Action	Check the log file.
---------------	---------------------

1020: Bad datafile %1\$s.

Cause	The data file is from another database.
Action	Check the data file.

1021: Duplicate datafile %1\$s exists.

Cause	Tried to create a file with a duplicate data file number.
Action	Check the data file.

1022: Resetlogs failed: %1\$s (%2\$s)

Cause	Resetlogs failed.
Action	Locate the cause of the failure and try again.

1023: Resetlogs is required.

Cause	Reboot the system with resetlogs.
Action	Perform any required recovery processes and try again.

1024: Database needs media recovery: %1\$s(%2\$s).

Cause	Media Recovery is needed.
Action	Perform media recovery.

1025: Media recovery is already in progress. Please retry after recovery work done.

Cause	Media recovery is already in progress.
Action	Check media recovery is already ongoing.

1026: Media Recovery has not started.

Cause	Media Recovery has not started.
Action	Locate the cause of the failure and try again.

1027: No log files found for thread %1\$d from recovery start tsn "UINT64_FMT(2\$)".

Cause	Cannot locate the log file needed for Media Recovery.
Action	Check the log file and try again.

1028: Log file is invalid: %1\$s (seq=%2\$d), %3\$s.

Cause	The log file is invalid.
Action	Choose a valid log file and try again.

1029: Log network write failed.

Cause	Failed to transmit a redo log to standby DB.
Action	Check the condition of standby DB and try again.

1030: Log network protocol failure (type=%1\$d req_type=%2\$d).

Cause	The communications protocol does not match that of standby DB.
Action	Verify the server versions of the primary DB and standby DB match and then try again.

1032: Invalid cache replication configuration (%1\$s).

Cause	The settings for the standby DB are invalid.
Action	Modify the settings in primary DB and try again.

1033: Unable to open log file (%1\$d).

Cause	Cannot open the redo log file to be transmitted to standby DB.
Action	Verify the log file exists and try again.

1034: Database requires recovery.

Cause	Database requires recovery.
Action	Check the cause of the failure and try again.

1035: Database is open in read-only mode.

Cause	DB has been opened in read-only mode.
Action	Reopen in another mode and try again.

1036: Standby consistency check failed.

Cause	A consistency check for the standby DB failed.
Action	Create a new standby DB.

1037: Log network read failed.

Cause	No response has arrived from standby DB.
Action	Verify the standby DB is running, and check the server version.

1038: Log network connect failed (%1\$s).

Cause	The primary DB failed to connect with the standby DB.
Action	Examine the configuration files of the primary and standby DBs and try again.

1039: LF#%1\$d - %2\$s.

Cause	Error with online redo log file.
--------------	----------------------------------

Action	Check the online redo log file and restart the server.
---------------	--

1040: Not permitted while standby database is connected.

Cause	The action is not permitted while the standby DB is connected.
Action	Disconnect the standby DB and try again.

1041: Unable to start partial recovery - %1\$s (%2\$s).

Cause	A partial recovery cannot be started because an invalid recovery finish time has been specified.
Action	Contact the technical support team.

1042: Unable to read log member file in group %1\$d, member %2\$d (%3\$s), block %4\$d.

Cause	Failed to read the log member file.
Action	Perform a recovery of invalid log file members.

1043: Unable to finish media recovery - %1\$s (%2\$s).

Cause	Cannot finish media recovery now.
Action	Finish the media recovery after satisfying the conditions necessary for completion.

1044: Unable to read log file: file %1\$s, blk %2\$d.

Cause	Failed to read the log file.
Action	Verify the log file is error free and try again.

1045: Redo thread #%1\$d is not enabled.

Cause	Cannot use redo threads.
--------------	--------------------------

Action	Enable redo threads and try again.
---------------	------------------------------------

1046: Unable to add log file - %1\$s (%2\$s).

Cause	Cannot add a log file.
Action	Contact the technical support team.

1047: Datafile requires redo thread #%1\$d to be enabled - %2\$s.

Cause	Cannot use redo threads.
Action	Enable redo threads and try again.

1048: Light work rule violated.

Cause	The light work rule was violated.
Action	Internal flag. This error can be safely ignored.

1049: Datafile #%1\$d needs Media Recovery.

Cause	Media Recovery is required.
Action	Perform media recovery.

1050: Datafile #%1\$d needs Media Recovery.

Cause	The checkpoints should be set first.
Action	Set the checkpoints first and try again.

1051: Instance recovery cascaded.

Cause	The instance recovery was canceled due to the activation of another instance recovery.
Action	Internal flag. This error can be safely ignored.

1052: Log members in group %1\$d, block %2\$d are not identical.

Cause	The members of the log group are not identical.
Action	Ensure all log members identical.

1053: Unable to run database in single instance mode.

Cause	Unable to start database in a single instance mode.
Action	Use a clustered database.

1054: Redo thread %1\$d already used.

Cause	The redo thread is already in use.
Action	Check the status of the redo threads and try again.

1055: Unable to automatically recover media from change "UINT64_FMT(1\$)".

Cause	Cannot perform automatic Media Recovery.
Action	Continue Media Recovery through manual recovery.

1056: Unable to proceed while other instances are running.

Cause	Some other instances are running.
Action	End the active instances and try again.

1057: Unable to start a Media Recovery - %1\$s.

Cause	Unable to start the Media Recovery with the information given.
Action	Specify another argument or a different Media Recovery.

1058: Unable to recover corrupt/corruptible media.

Cause	Media Recovery stops due to an invalid redo log or a data block.
Action	Check the redo log or the data block.

1059: Cannot access the file at instance %1\$d - %2\$s.

Cause	Cannot access the file at instance.
Action	Check the file path and try again.

1060: Unable to read afferent DBA block: file# %1\$u, block# %2\$u.

Cause	Cannot read the data block due to unformatted or corrupted block.
Action	Perform Media Recovery and try again.

1061: Instance recovery is ongoing.

Cause	Cannot complete boot since instance recovery is ongoing.
Action	Try to boot later.

1062: Cannot decrypt block.

Cause	Cannot decrypt block.
Action	Verify the wallet is valid or check if the block is corrupt.

1063: Log writer is waiting for all logfiles to be archived.

Cause	Unable to proceed while all logfiles are being archived.
Action	Check that the archive log destination device or directory is not full.

1064: Unable to recover specified block(s).

Cause	The size of buffer cache is insufficient.
--------------	---

Action	Check the size of buffer cache and try again.
---------------	---

1065: Unable to read spanned log: file %1\$s, blk %2\$d.

Cause	Failed to read the log file.
Action	Verify the log file is error free and try again.

1066: Block Change Tracker is not configured.

Cause	Block Change Tracker is not configured.
Action	Verify Block Change Tracker configuration.

1067: Block Change Tracker setting (%1\$s) should be %2\$s across the cluster.

Cause	Block Change Tracker is not configured correctly for TAC.
Action	Verify Block Change Tracker configuration.

1068: The memory space in the system is insufficient.

Cause	ERROR : malloc failed due to a lack of memory space in the system.
Action	Increase the memory space in the system.

1069: Media recovery has stopped due to cluster reconfiguration.

Cause	Media recovery has stopped.
Action	Try again.

1070: Incomplete media recovery is finished, but resetlogs is required.

Cause	Incomplete media recovery is finished.
--------------	--

Action	Resetlogs is required.
---------------	------------------------

1071: Media recovery is not needed, but resetlogs is required.

Cause	Media recovery is not needed.
Action	Resetlogs is required.

1072: Current online log file (thread %1\$d seq %2\$d) is outdated.\nNeed a log with seq %3\$d to recover from TSN %4\$s\nRecovery is incomplete and resetlogs is required.

Cause	Current online log file is outdated. Recovery is incomplete.
Action	Resetlogs is required.

1073: Unable to read flushed redo blocks. logfile #%1\$d, blk %2\$d, remain %3\$d

Cause	Read flushed redo blocks partially. Redo buffer wasn't completely flushed.
Action	Verify the log file is error free and try again.

1074: Incomplete media recovery is finished, but resetlogs is required.\n%1\$s

Cause	Incomplete media recovery is finished.
Action	Resetlogs is required.

1075: Redo thread #%1\$d is has missing logfiles.

Cause	Cannot use this redo thread.
Action	Resetlogs is required to use this redo thread.

1076: Unable to create online datafile in current boot mode.

Cause	In the current boot mode, this DDL cannot be executed.
Action	Change the boot mode and run the DDL statement again.

1077: Bitmap already set on block #%1\$d

Cause	Bitmap already set on block #%1\$d
Action	Check backup data file.

1078: Bitmap overflow. Bitmap size was %1\$d

Cause	Bitmap overflow. Bitmap size was %1\$d
Action	Check backup data file.

1079: Datafile's DB names differ. ('%1\$s' != '%2\$s')

Cause	Datafile's DB names differ. ('%1\$s' != '%2\$s')
Action	Check data files.

1080: Datafile's DB ids differ. (%1\$d != %2\$d)

Cause	Datafile's DB ids differ. (%1\$d != %2\$d)
Action	Check data files.

1081: Datafile's DB versions differ. (%1\$d != %2\$d)

Cause	Datafile's DB versions differ. (%1\$d != %2\$d)
Action	Check data files.

1082: Datafile file number mismatch. (%1\$d != %2\$d)

Cause	Datafile file number mismatch. (%1\$d != %2\$d)
--------------	---

Action	Check data files.
---------------	-------------------

1083: Datafile file block size mismatch. (%1\$d != %2\$d)

Cause	Datafile file block size mismatch. (%1\$d != %2\$d)
Action	Check data files.

1084: Can't setup new uid to data file.

Cause	Can't setup new uid to data file.
Action	Check data file.

1085: Backup must have %1\$d blocks, but %1\$d blocks copied.

Cause	Backup must have %1\$d blocks, but %1\$d blocks copied.
Action	Check backup data file.

1086: Decompress error while restore.

Cause	Decompress error while restore.
Action	Check backup data file.

1087: Compress error while backup.

Cause	Compress error while backup.
Action	Check data file.

1088: Block is not bitmap header.

Cause	Block is not bitmap header.
Action	Check backup data file.

1089: Invalid backup file %1\$s.

Cause	Invalid backup file %1\$s.
Action	Check backup data file.

1090: Invalid backup block # %1\$d in %2\$s.

Cause	Invalid backup block # %1\$d in %2\$s.
Action	Check backup data file.

1091: Unable to recover corrupted media.

Cause	Unable to perform a Crash Recovery due to invalid log or data block.
Action	Restore the datafile and try again.

1092: Unable to find backup path for backup archiving.

Cause	Unable to find backup path for backup archiving.
Action	Please specify path of archive of backup files.

1093: Buffer size(%1\$d) is not multiple of compress unit(%2\$d).

Cause	Buffer size(%1\$d) is not multiple of compress unit(%2\$d).
Action	Please make buffer size to be multiple of compress unit.

1094: Tablespace # %1\$d isn't included in backupset id # %2\$d.

Cause	Tablespace # %1\$d isn't included in backupset id # %2\$d.
Action	Please make sure this backup set contains tablespace # %1\$d.

1095: Can't find proper backup set to restore

Cause	Can't find proper backup set to restore
--------------	---

Action	Check there is a backup set containing all required tablespaces.
---------------	--

1096: Can't perform standby side controlfile operation: %1\$s

Cause	Can't perform standby side controlfile operation: %1\$s
Action	Recreate the standby database.

1097: Flashback thread #%1\$d is not enabled.

Cause	Cannot use flashback threads.
Action	Enable flashback threads and try again.

1098: Database in standby mode. Failover is required to boot as primary.

Cause	Reboot the system with failover.
Action	Perform any required recovery processes and try again.

1099: Cannot find marker before change "UINT64_FMT(1\$)" for thread %2\$d. (Deprecated)

Cause	Cannot perform flashback database operation. (Deprecated)
Action	Check flashback marker status and try again. (Deprecated)

1100: Unable to access tape device

Cause	Cannot perform tape backup.
Action	Check path of tape device.

1101: No more free space available in tape device

Cause	Cannot perform tape backup.
--------------	-----------------------------

Action	Change tape to new one.
---------------	-------------------------

1102: Log network connection disconnected.

Cause	Log network connection disconnected.
Action	Examine network connection between the primary and standby DBs and try again.

1107: Set the parameter USE_STANDBY_REDO_LOG to Y.

Cause	Set the parameter USE_STANDBY_REDO_LOG to Y.
Action	Set the parameter USE_STANDBY_REDO_LOG to Y.

1108: A bitmap header block is unformatted while accessing the datafile header view.

Cause	Creating a datafile may cause this error.
Action	Query the datafile header view again.

1109: Set the parameter ENCRYPT_GLOBAL_KEY_FILE to recover encrypted tablespace.

Cause	Set the parameter ENCRYPT_GLOBAL_KEY_FILE to recover encrypted tablespace.
Action	Set the parameter ENCRYPT_GLOBAL_KEY_FILE to recover encrypted tablespace.

1110: Failed to read ENCRYPT_GLOBAL_KEY_FILE: %1\$s

Cause	Failed to read ENCRYPT_GLOBAL_KEY_FILE: %1\$s
Action	Set the correct path for the parameter ENCRYPT_GLOBAL_KEY_FILE

1111: Cannot read log blocks of invalid range for logfile %1\$d.

Cause	Cannot read log blocks of invalid range for logfile %1\$d.
--------------	--

Action	Logfile %1\$d might have been cleared.
---------------	--

1112: Invalid log file found: %1\$s, seq#%2\$d (expected: seq#%3\$d)

Cause	Invalid log file found: %1\$s, seq#%2\$d (expected: seq#%3\$d)
Action	Invalid log file found: %1\$s, seq#%2\$d (expected: seq#%3\$d)

1113: Unable to recover corrupt/corruptible media.

Cause	Crash/Instance Recovery stops due to an invalid redo log or a data block.
Action	Check the redo log or the data block.

1114: Not permitted while some standby databases are disconnected.

Cause	The action is not permitted while some standby DBs are disconnected.
Action	Examine network connection between the primary and standby DBs and try again.

1115: Failed to set the status of flashback %1\$s %2\$s.

Cause	Flashback %1\$s is already %2\$s.
Action	Check flashback %1\$s is already %2\$s.

1116: FLASHBACK_LOG_BUFFER parameter must be set as non-zero when flashback logging is activated, and vice versa.

Cause	FLASHBACK_LOG_BUFFER parameter must be set as non-zero when flashback logging is activated, and vice versa.
Action	Check the value of FLASHBACK_LOG_BUFFER.

1117: Unable to open flashback log file in group %1\$d.

Cause	Cannot open the flashback log file.
Action	Check the flashback log file path and permissions.

1118: Unable to read flashback log file in group %1\$d, block %2\$d.

Cause	Cannot read the flashback log file.
Action	Check the flashback log file path and permissions.

1119: Unable to write to flashback log file in group %1\$d, block %2\$d.

Cause	Cannot write to the flashback log file.
Action	Check the flashback log file path and permissions.

1120: LF#%1\$d - %2\$s.

Cause	Error with online flashback log file.
Action	Check the online flashback log file and restart the server.

1121: Unable to find flashback archive log file for thread %1\$d from change "UINT64_FMT(2\$)".

Cause	Cannot locate the flashback log file needed for Flashback.
Action	Check the flashback log file and try again.

1122: File fstat failed: %1\$s

Cause	File fstat failed: %1\$s
Action	File fstat failed: %1\$s

1123: Standby reverse sync is not possible

Cause	Standby reverse sync is not possible
Action	Need to reconstruct standby.

1124: Reconfiguration occurred during the gca lock operation.

Cause	Reconfiguration occurred during the gca lock operation.
Action	Internal flag. This error can be safely ignored.

1125: Insufficient buffer size(%1\$d) to serve the requested read operation. (Requested block count %2\$d)

Cause	Insufficient buffer size(%1\$d) to serve the requested read operation. (Requested block count %2\$d)
Action	Contact the technical support team.

1126: Standby redo log is necessary for snapshot standby.

Cause	Standby redo log is necessary for snapshot standby.
Action	Configure standby redo log first.

1127: Database not in standby mode.

Cause	Database not in standby mode.
Action	Database not in standby mode.

1128: Database not in snapshot standby mode.

Cause	Database not in snapshot standby mode.
Action	Database not in snapshot standby mode.

1129: Database in snapshot standby mode. Convert to standby first to boot as standby.

Cause	Convert to standby first and reboot as standby.
Action	Perform any required recovery processes and try again.

1130: Block Change Tracking is not supported yet when LGWR_USE_AIO is set Y.

Cause	Block Change Tracking is not supported yet when LGWR_USE_AIO is set Y.
Action	Block Change Tracking is not supported yet when LGWR_USE_AIO is set Y.

1131: Standby redo thread #%1\$d is not enabled.

Cause	Cannot use standby redo threads.
Action	Enable standby redo threads and try again.

1132: The size of standby logfile is too small.

Cause	The size of standby logfile must be larger than or equal to the size of redo log file.
Action	Increase the size of standby logfile and try again.

1133: Global log flush failed.

Cause	Failed to execute the query due to global log flush failure.
Action	Re-execute the query.

1134: Unable to recover corrupt/corruptible media.

Cause	SMR stops due to an invalid redo log or a data block.
Action	Check the redo log or the data block.

1135: An invalid bucket has been found.

Cause	Unable to proceed because the bucket is invalid.
Action	Check the dump file.

1136: Cannot raise to read only server mode until standby managed recovery recovers until TSN %1\$u.

Cause	Standby managed recovery need to recover until TSN %1\$u to raise to read only server mode.
Action	Wait for the standby managed recovery recovers until TSN %1\$u and try again.

1137: Failover is not allowed. Database is not in standby mode.

Cause	Reboot the system with another bootmode.
Action	Perform any required recovery processes and try again.

1138: Unable to unlink file %1\$s.

Cause	Cannot delete the file.
Action	Check the file path and permissions.

1139: Standby reverse sync is not possible: %1\$s

Cause	Standby reverse sync is not possible: %1\$s
Action	Need to reconstruct standby.

1140: Too many LNWs. (%1\$d, max: %2\$d)

Cause	Number of LNWs is limited to %2\$d.
Action	Modify the tip file and try again.

1141: Request to Block Change Tracker failed.

Cause	Block Change Tracker failed the action requested.
Action	Investigate the sys.log about BCT(Block Change Tracking).

1142: Standby redo log feature is not activated.

Cause	Standby redo log feature is not activated.
Action	Activate standby redo log feature and try again.

1143: Standby redo log feature is already activated.

Cause	Standby redo log feature is already activated.
Action	Standby redo log feature is already activated.

1144: Standby redo log feature is already deactivated.

Cause	Standby redo log feature is already deactivated.
Action	Standby redo log feature is already deactivated.

1145: Deactivating standby redo log feature is not allowed for snapshot standby.

Cause	Deactivating standby redo log feature is not allowed for snapshot standby.
Action	Deactivating standby redo log feature is not allowed for snapshot standby.

1146: SMR read archive log.

Cause	SMR stopped because it had been reading archive log.
Action	Contact the technical support team.

1147: Need log file (thread %1\$d seq %2\$d) to recover from TSN %3\$s\nRecovery is incomplete and resetlogs is required.

Cause	Current online log file is outdated. Recovery is incomplete.
Action	Resetlogs is required.

1148: Unable to boot standby instance while other instances are running.

Cause	Some other standby instances are running.
Action	End the active standby instances and try again.

1149: Failed to inititalize log network reader: %1\$s

Cause	Error occured while initializing log network reader.
Action	Contact the technical support team.

1150: Standby redo log feature in TAC environment is not supported in this version.

Cause	Standby redo log feature in TAC environment is not supported in this version.
Action	Upgrade Tiberio version to use this feature.

1151: Offline datafile #%1\$d requires media recovery. When reset log, the file may be lost.

Cause	Offline datafile #%1\$d requires media recovery. When resetlog, the file may be lost.
Action	Take a backup file and recover it or take it offline using the IMMEDIATE option.

1152: Unable to read dp corrupt block: file# %1\$u, block# %2\$u.

Cause	Cannot read the dp corrupted data block.
--------------	--

Action	Perform a media recovery and try again.
---------------	---

1153: Flashback logging is activated in standby database.

Cause	Flashback logging is not allowed in standby database.
Action	Deactivate flashback logging and try again.

1154: Flashback logging is disabled in snapshot standby database.

Cause	Flashback logging must be enabled in snapshot standby database.
Action	Activate flashback logging and try again.

1155: Block media recovery target block is out of range: block# %1\$u.

Cause	Target block number must be within valid range.
Action	Try block range within (1 ~ %2\$u).

1156: Cannot read bitmap header block while performing block media recovery: %1\$s

Cause	Need to read bitmap header block to perform block media recovery.
Action	Recover bitmap header block first and try again.

1157: Incomplete recovery has progressed up to TSN %1\$d, but it needs to reach at least TSN %2\$d.

Cause	The process must continue up to the maximum checkpoint value in all datafiles.
Action	Check the log file and retry.

1158: Database trying to recover is not a snapshot database.

Cause	Snapshot database recovery should only be performed on snapshot database.
Action	Try other recovery options.

1159: Unable to read archive log file: file %1\$s, block %2\$d.

Cause	Cannot read the archive log file.
Action	Check the archive log file path and permissions.

1160: A pin self-deadlock has occurred.

Cause	An attempt was made to pin a block that is already pinned.
Action	Retry the canceled query. If the issue persists, contact Tiberio Technical Support or Tiberio R&D.

1161: Need archive log file (thread %1\$d seq %2\$d) to complete block media recovery.\nBlock media recovery is incomplete.

Cause	Need archive log file (thread %1\$d seq %2\$d) to complete block media recovery.
Action	Check the log file and try again.

1162: Cannot perform crash recovery again.

Cause	In TAC environment, once crash recovery has failed, it cannot be performed again.
Action	Reboot the system.

1163: Cannot perform media recovery when crash recovery failed.

Cause	If crash recovery has failed in TAC environment, media recovery cannot be performed.
Action	Reboot the system.

1164: Unable to read file %1\$s: file# %2\$u, block# %3\$u, tsid# %4\$u, dba %5\$u_%6\$u.

Cause	Cannot read the file.
Action	Check the file path and permissions.

1165: No log files found for thread %1\$d from recovery start tsn "UINT64_FMT(2\$)" seq %3\$d.\nRequired archive log: %4\$s.

Cause	Cannot locate the log file needed for Media Recovery.
Action	Check the log file and try again.

1166: Database in switchover mode. Switchover is required to boot as standby.

Cause	Database in switchover mode. Switchover is required to boot as standby.
Action	Reboot as standby.

1167: Set the parameter _USE_STANDBY_REDO_LOG to Y.

Cause	Set the parameter _USE_STANDBY_REDO_LOG to Y.
Action	Set the parameter _USE_STANDBY_REDO_LOG to Y.

1168: Bh blk has invalid address: tsid# %1\$u, dba %2\$u_%3\$u.

Cause	Bh blk has invalid address.
Action	Contact the technical support team.

1169: Bh lcb has invalid address: tsid# %1\$u, dba %2\$u_%3\$u.

Cause	Bh lcb has invalid address.
Action	Contact the technical support team.

1170: Invalid lkid found.

Cause	Invalid lkid found.
Action	Contact the technical support team.

제2장 2000 ~ 2999

2001: Completed successfully with warnings or additional information.

Cause	The function has concluded successfully but with warnings or additional information related to the results.
Action	Check the warnings and additional information with the GetDiagField() function.

2002: DSN (Database Source Name) file was not found.

Cause	DSN file could not be found.
Action	Check the dsn file in the 'client/config' directory under the database home directory.

2003: DSN (Database Source Name) file is corrupted.

Cause	DSN file is corrupted.
Action	Check the dsn file in the 'client/config' directory under the database home directory.

2004: DSN (Database Source Name) file format is invalid.

Cause	DSN file format is invalid.
Action	Check the dsn file in the 'client/config' directory under the database home directory.

2005: Username is too long: must be less than 128 bytes.

Cause	The user name is too long. User names may not be longer than 128 bytes.
Action	Check the size of the user name in the argument.

2006: Password is too long: must be less than 64 bytes.

Cause	The password is too long. Passwords may not be longer than 63 bytes.
Action	Check the size of the password in the argument.

2007: Table name is too long: must be less than 128 bytes.

Cause	The table name is too long. Table names may not be longer than 128 bytes.
Action	Check the size of the table name in the argument.

2008: Column name is too long: must be less than 128 bytes.

Cause	The column name is too long. Column names may not be longer than 127 bytes.
Action	Check the size of the column name in the argument.

2009: Schema name is too long: must be less than 128 bytes.

Cause	The schema name is too long. Schema names may not be longer than 127 bytes.
Action	Check the size of the schema name in the parameter.

2010: String data was right-truncated.

Cause	Actual data is larger than the buffer.
Action	Check the size of the data buffer.

2011: Wrong parameter number given.

Cause	Invalid parameter number.
Action	Check the parameter number.

2012: Prepared statement is not a cursor specification.

Cause	The prepared statement does not provide a valid cursor specification.
--------------	---

Action	Verify the statement is a SELECT statement.
---------------	---

2013: Invalid column index at descriptor.

Cause	Invalid column index.
Action	Check the descriptor column index.

2014: Invalid record index at descriptor.

Cause	Invalid record index.
Action	Check the descriptor record index.

2015: Client was unable to establish connection.

Cause	Cannot connect to the server.
Action	Verify that the server is running, and check the DB connection settings.

2016: OCIServer or OCISession is not set in OCISvcCtx.

Cause	Server or session handle is not registered as an attribute of OCISvcCtx.
Action	Verify that the OCISvcCtx handle is correctly created.

2017: Open connection already exists.

Cause	Already connected to the server.
Action	Disconnect the server and retry, or continue with desired actions.

2018: No open connection.

Cause	Not connected to the server.
Action	Reconnect to the server and try action again.

2019: Program type out of range.

Cause	The SQL_C type is not supported.
Action	Check the SQL_C type and change it.

2020: Invalid SQL data type.

Cause	Unsupported SQL data type.
Action	Check the SQL data type and change it.

2021: Associated statement is not prepared.

Cause	SQL statement has not been prepared.
Action	Execute when SQL statement is prepared.

2022: Invalid use of null pointer.

Cause	Invalid null pointer was used.
Action	Check the null pointer.

2023: Invalid argument type.

Cause	Invalid argument type.
Action	Check the argument type.

2024: Invalid argument value.

Cause	Invalid argument value.
Action	Check the argument value.

2025: Function sequence error.

Cause	Invalid function sequence.
--------------	----------------------------

Action	Check the sequence of functions.
---------------	----------------------------------

2026: Attribute was not set.

Cause	Failed to set attributes.
Action	Check the attributes.

2027: Invalid transaction operation.

Cause	Invalid transaction operation.
Action	Check whether the current transaction operation is valid.

2028: Cannot modify the implementation row descriptor.

Cause	Cannot modify IRD (Implementation Row Descriptor).
Action	Check the target descriptor type to modify.

2029: Invalid use of an automatically allocated descriptor handle.

Cause	Invalid use of an automatically allocated descriptor handle.
Action	Create a new descriptor handle.

2030: Inconsistent descriptor information.

Cause	Invalid descriptor information.
Action	Check the binding descriptor.

2031: Invalid attribute value.

Cause	Invalid attribute value.
Action	Confirm that the value can be specified for the current attribute.

2032: Invalid string or buffer length.

Cause	Invalid length of character string.
Action	Change the length of the string.

2033: Invalid descriptor field identifier.

Cause	The descriptor field identifier is undefined or not implemented.
Action	Check the descriptor field identifier.

2034: Invalid descriptor field identifier.

Cause	The specified descriptor field is read-only.
Action	Check the attributes of the descriptor field.

2035: Invalid attribute/option identifier.

Cause	Invalid attribute or option.
Action	Recheck the attribute or option.

2036: Invalid parameter index.

Cause	Invalid parameter index.
Action	Check the parameter index.

2037: Invalid parameter type.

Cause	Invalid parameter type.
Action	Check the parameter type.

2038: Invalid cursor position.

Cause	Invalid cursor position.
--------------	--------------------------

Action	Verify that the cursor position is correct.
---------------	---

2039: Optional feature not yet implemented.

Cause	The function has not yet been implemented.
Action	Use an alternative function.

2040: Invalid cursor state.

Cause	Invalid cursor state.
Action	Check the cursor state.

2041: Required indicator variable was not specified.

Cause	No indicator has been specified.
Action	Specify the indicator.

2042: Savepoint exception.

Cause	Invalid name for the savepoint.
Action	Check the name of the savepoint.

2043: Duplicate cursor name exists.

Cause	Duplicate cursor name detected.
Action	Change the cursor name.

2044: Invalid cursor name.

Cause	Invalid cursor name
Action	Change the cursor name.

2045: Invalid record index number.

Cause	Invalid diagnostics record index
Action	Check the diagnostics record index.

2046: Not yet implemented.

Cause	The function has not been implemented.
Action	Use an alternative function.

2047: Attribute has not been implemented.

Cause	The attribute has not been implemented.
Action	Use an alternative attribute.

2048: Data source was not found.

Cause	Unable to find DSN.
Action	Check whether DSN configuration is valid.

2049: Invalid offset for LOB.

Cause	Invalid offset value for large object (LOB).
Action	Check the offset value of LOB.

2050: Invalid length for LOB.

Cause	Invalid LOB length
Action	Check the LOB length.

2051: Invalid authorization.

Cause	Not authorized to perform this task.
--------------	--------------------------------------

Action	Check the user name and password.
---------------	-----------------------------------

2052: Invalid parameter.

Cause	Invalid environment parameter type.
Action	Check the environment parameter type.

2053: Invalid plan executed.

Cause	Invalid plan was executed.
Action	Check whether the plan ID is valid.

2054: Cursor is already open.

Cause	The cursor is already open.
Action	Check the cursor state.

2055: Cursor is not open.

Cause	Cursor is not open.
Action	Check the cursor state.

2056: Specified SQL statement is NULL.

Cause	Executed SQL statement is NULL.
Action	Check the SQL statement again.

2057: Invalid scroll option.

Cause	Invalid scrollable cursor fetch.
Action	Check whether the cursor type is scrollable.

2058: Invalid data type.

Cause	Data type is unsupported by server.
Action	Check the data type again.

2059: Invalid data length.

Cause	Exceeds the maximum data length supported by server.
Action	Check the data length.

2060: Invalid diagnostics index.

Cause	Invalid diagnostics index
Action	Check the diagnostics index.

2061: Data type is currently unsupported.

Cause	Data type is currently unsupported.
Action	Use an alternative data type.

2062: Type casting is not allowed.

Cause	Unable to change the data type.
Action	Check the data type.

2063: Invalid parameter in/out mode.

Cause	Invalid parameter mode.
Action	Check the parameter mode.

2064: Trailing NULL missing from string bind value.

Cause	There is no NULL at the end of string bind value.
--------------	---

Action	Check the bind value.
---------------	-----------------------

2065: Data was truncated.

Cause	Data was too long and was truncated.
Action	Check the data length.

2067: Index out of range.

Cause	Index value was out of range.
Action	Check the index.

2068: Invalid indicator type.

Cause	Invalid indicator type.
Action	Check the indicator type.

2069: I/O read error.

Cause	There is a problem reading from the server.
Action	Check the connection.

2070: I/O write error.

Cause	There is a problem writing to the server.
Action	Check the connection.

2071: I/O close error.

Cause	There is a problem closing the communication with server.
Action	Check the connection.

2072: Invalid buffer length.

Cause	Invalid buffer length.
Action	Check the buffer length.

2073: Invalid handle.

Cause	Invalid handle.
Action	Check whether the handle is valid.

2074: Invalid handle type.

Cause	Invalid handle type.
Action	Check whether or not the handle type is valid.

2075: Invalid DBC handle.

Cause	Invalid connection handle.
Action	Check the connection handle.

2076: Invalid statement handle.

Cause	Invalid statement handle.
Action	Check the statement handle.

2077: Failed to initialize the handle manager.

Cause	Failed to initialize the handle manager.
Action	Check the handle allocation.

2080: CLI Driver manager has not been initialized.

Cause	CLI Driver manager has not been initialized.
--------------	--

Action	Initialize the CLI Driver Manager.
---------------	------------------------------------

2081: Invalid attempt to fetch before the first row of the result set.

Cause	The specified fetch location is before the first record of the result set.
Action	Specify a valid fetch location.

2082: Invalid socket file descriptor.

Cause	Invalid socket file descriptor.
Action	Check the connection with the server.

2083: Failed to close socket.

Cause	Failed to close socket.
Action	Verify the connection with the server is still available.

2084: Invalid protocol.

Cause	Invalid server connection protocol.
Action	Check the condition of the server and clients.

2085: Invalid LOB locator from server.

Cause	Invalid LOB locator received from server.
Action	Check the LOB locator.

2086: No data.

Cause	No data.
Action	Check the fetch state.

2087: Data is needed.

Cause	The server requires some data.
Action	Ensure the data to be sent is available.

2088: Connection failed.

Cause	Failed to connect to server.
Action	Check the server state.

2089: Failed to disconnect.

Cause	Failed to disconnect.
Action	Check the server state.

2090: Execution failed.

Cause	Failed to execute SQL statements.
Action	Recheck the SQL statements.

2091: Fetching failed.

Cause	Failed to fetch.
Action	Check the cursor state.

2092: Preparation failed.

Cause	Failed to prepare a statement.
Action	Check the execution statement.

2093: Failed to close the cursor.

Cause	Failed to close the cursor.
--------------	-----------------------------

Action	Check the cursor state.
---------------	-------------------------

2094: Failed to commit.

Cause	Failed to commit.
Action	Check the transaction state.

2095: Failed to close session.

Cause	Failed to close the session.
Action	Check the server state.

2096: Session kill failed.

Cause	Failed to end the session.
Action	Check the server state.

2097: Rollback failed.

Cause	Failed to roll back.
Action	Check the transaction state.

2098: Savepoint failed.

Cause	Failed to set a savepoint.
Action	Check the transaction state.

2099: Put data failed.

Cause	Failed to transfer the data.
Action	Verify the data is valid.

2100: Cancel failed.

Cause	Failed to cancel.
Action	Check the transaction state.

2101: Failed to get the length of LOB.

Cause	Failed to obtain the LOB type length.
Action	Check the LOB locator.

2102: Failed to read LOB data.

Cause	Failed to read LOB data.
Action	Check the LOB locator.

2103: Failed to write LOB data.

Cause	Failed to write LOB data.
Action	Check the LOB locator.

2104: Failed to truncate LOB data.

Cause	Failed to truncate LOB data.
Action	Check the LOB locator.

2105: Unable to find specified cursor.

Cause	Unable to find a cursor with the specified name.
Action	Verify the cursor is valid.

2107: DPL is unprepared.

Cause	Failed to prepare DPL.
--------------	------------------------

Action	Verify the operation is valid.
---------------	--------------------------------

2108: Failed to load stream.

Cause	DPL load stream operation failed.
Action	Verify the operation is valid.

2109: Failed to save data.

Cause	DPL data save operation failed.
Action	Verify the operation is valid.

2110: Failed to abort

Cause	DPL abort operation failed.
Action	Verify the operation is valid.

2111: Failed to finish.

Cause	DPL finish operation failed.
Action	Verify the operation is valid.

2112: Failed to flush rows.

Cause	Failed to flush a particular record.
Action	Verify the operation is valid.

2113: More rows needed after loadstream().

Cause	Additional data is needed after DPL load stream operation.
Action	Provide the necessary data.

2114: No rows to be inserted after loadstream().

Cause	No data has been inserted after DPL load stream operation.
Action	Verify the data is valid.

2115: Failed to read DSN info from ODBC.INI.

Cause	Failed to read DSN information from ODBC.INI.
Action	Check the DSN information.

2116: Completed row delivery to users.

Cause	Data fetch process is complete.
Action	Perform the next required action.

2118: Invalid communication ID.

Cause	Invalid communication ID.
Action	Check the communication ID.

2119: Shutdown failed.

Cause	Failed to shut down.
Action	Check the server state.

2120: Unable to get information about the last SQL statement.

Cause	Failed to obtain information on the last executed SQL statement.
Action	Check whether the operation was valid.

2121: Duplicate request exists.

Cause	The request is a duplicate.
--------------	-----------------------------

Action	Verify the operation is valid.
---------------	--------------------------------

2122: Handle is in use.

Cause	The handle is in use.
Action	Check the handle state.

2123: No accessible element exists in data structure.

Cause	There is no error of the descriptor.
Action	Check the index.

2127: Invalid chunk index.

Cause	The chunk index is invalid.
Action	Check the chunk index.

2131: Generic I/O error.

Cause	There is a problem communicating with the server.
Action	Check the connection with the server.

2133: Specified index is greater than number of diagnostics records.

Cause	There are more indexes than diagnostics records.
Action	Check the diagnostics record index.

2134: More data exists for this column.

Cause	There is additional data for the column.
Action	Receive the remaining data by calling the SQLGetData() function.

2135: Current cursor is not updatable.

Cause	The cursor is not updatable.
Action	Change to an updatable cursor and retry.

2136: Row index is out of range.

Cause	The record index is out of range.
Action	Specify a record index smaller than the total number of records in the result set.

2137: Invalid integer buffer size.

Cause	An invalid size was specified for the integer buffer.
Action	Choose a value between 1 to 8 bytes.

2138: Invalid floating point buffer size.

Cause	An invalid size was specified for the floating point buffer.
Action	Choose a value between 4 and 8 bytes.

2139: Connection to server was interrupted but the fail-over successfully reconnected.

Cause	The server connection was terminated but a new connection was made to a server instance with the same DNS name.
Action	The job being executed by the user was canceled and must be restarted.

2140: Unable to connect to unsupported DBMS server.

Cause	An attempt was made to connect to a server that is not supported by the current client.
Action	Use a client that supports connections to this server.

2141: IP address specified in DSN file is too long: cannot be longer than 128 bytes.

Cause	The length of the IP address in the DSN file is longer than 128 bytes.
Action	Check the length of the IP address.

2142: Invalid date/time format.

Cause	Invalid date/time format.
Action	Check the date/time format.

2143: Out of range for numeric.

Cause	Out of range for numeric.
Action	Check the buffer size or the data type.

2144: Invalid bookmark value.

Cause	Invalid bookmark value.
Action	Check if the bookmark value is null or a valid value.

2145: Invalid fetch direction for the current cursor type.

Cause	Invalid fetch direction for the current cursor type.
Action	Verify the cursor type is scrollable.

2146: Current result set cursor type downgraded.

Cause	The current cursor type does not support this query type. The query type will be changed.
Action	Check the query type.

2147: Fractional truncation.

Cause	The numbers after the decimal point are truncated.
Action	Check the buffer size or the data type.

2148: Invalid character value for casting the type.

Cause	Invalid character string value for changing the type.
Action	Verify the character string is valid to change to the specified type.

2149: No available connection exists in the connection pool.

Cause	No available connection exists in the connection pool.
Action	Modify the parameter to change the number of connections available in the connection pool.

2150: Failed to create a daemon thread.

Cause	Failed to create a daemon thread.
Action	Internal error. Contact the technical support team.

2151: Failed to detach the daemon thread.

Cause	Failed to detach the daemon thread.
Action	Internal error. Contact the technical support team.

2152: Invalid descriptor index.

Cause	Invalid descriptor index.
Action	Check if the column/parameter exists for the descriptor index.

2153: Date/time field overflow.

Cause	Invalid date type value.
Action	Check the data value of the date type.

2154: Invalid chunk index.

Cause	The chunk index is invalid.
Action	Check the chunk index.

2155: Option value changed.

Cause	The specified option is not supported. The option value has been changed to other one.
Action	Check the option value.

2156: Cannot find connection information of JEPA (JAVA External Procedure Agent).

Cause	Cannot find connection information of JEPA.
Action	Check the dsn file in the 'client/config' directory under the database home directory.

2157: Failed to execute psm.

Cause	Failed to execute psm.
Action	Internal error. Contact the technical support team.

2158: Cannot set the size of TCP Send Buffer.

Cause	Failed to set the size of TCP Send Buffer.
Action	Contact the technical support team.

2159: Cannot set the size of TCP Receive Buffer.

Cause	Failed to set the size of TCP Receive Buffer.
Action	Contact the technical support team.

2160: Unable to set the size of TCP Send Buffer.

Cause	Failed to set the size of TCP Send Buffer.
Action	Contact the technical support team.

2161: Unable to set the size of TCP Receive Buffer.

Cause	Failed to set the size of TCP Receive Buffer.
Action	Contact the technical support team.

2162: Unable to get the size of TCP Send Buffer.

Cause	Failed to get the size of TCP Send Buffer.
Action	Contact the technical support team.

2163: Unable to get the size of TCP Receive Buffer.

Cause	Failed to get the size of TCP Receive Buffer.
Action	Contact the technical support team.

2164: Unable to set the size of TCP Send Buffer.

Cause	Failed to set the size of TCP Send Buffer.
Action	Contact the technical support team.

2165: Unable to set the size of TCP Receive Buffer.

Cause	Failed to set the size of TCP Receive Buffer.
--------------	---

Action	Contact the technical support team.
---------------	-------------------------------------

2166: Unable to get the size of TCP Send Buffer.

Cause	Failed to get the size of TCP Send Buffer.
Action	Contact the technical support team.

2167: Unable to get the size of TCP Receive Buffer.

Cause	Failed to get the size of TCP Receive Buffer.
Action	Contact the technical support team.

2168: Unable to determine the speed of data transmission between server and client.

Cause	Failed to determine the speed of data transmission between server and client.
Action	Contact the technical support team.

2169: Multi thread mode is not set.

Cause	Multi thread mode is not set.
Action	Use the SQLAllocHandle2 or SQLAllocEvn2 API with a true value in the last argument when allocating the env handle.

2170: The necessary attributes are not set in subs handle.

Cause	Topic, callback functions, and listen port information are not set in subscription.
Action	Set all the necessary attributes for the subscription.

2171: The subscription topic has already been registered.

Cause	A client tried to register the same topic using the same DBC handle.
--------------	--

Action	Registering the same topic in the same dbc handle is not allowed.
---------------	---

2172: The subscription topic has not been registered.

Cause	The topic to unregister is not in the list of subscriptions.
Action	Register the topic first.

2173: Unable to find the listener.

Cause	There is no listener listening for the port of the unregistering subscription.
Action	Check if the port of the subscription and the subscription are registered.

2174: Failed to recover select.

Cause	An I/O error occurred during select failover.
Action	Try again later.

2175: Failed to fetch a row.

Cause	Application fetched too many rows.
Action	Reduce the number of fetch request.

2176: Unable to use the parallel DPL option.

Cause	The current server does not support the parallel DPL option.
Action	Use the latest version of the server.

2177: The password has expired(grace).

Cause	The password has expired(grace).
Action	Update the password and then try again.

2178: Unable to fetch subsequent rows.

Cause	Failover was not able to restore the result set to its original state to continue fetching rows.
Action	Re-execute the query to fetch from the first row.

2179: Invalid subscription name.

Cause	The subscription name is invalid or too long.
Action	Use a valid subscription name.

2180: Failed to register the subscription.

Cause	An unregistered subscription name is used or there is a server error.
Action	Use a valid subscription name and check if TQ can be used on the server.

2181: Failed to unregister the subscription.

Cause	There is a server error.
Action	Check if TQ can be used on the server.

2182: DSN configuration is invalid or incomplete .

Cause	Connection information is incorrect or insufficient.
Action	Check if the DSN configuration is incorrect or incomplete.

2183: Unable to handle unexpected incoming message type.

Cause	An unexpected protocol was received.
Action	Check that the protocol is from a valid context.

2184: Cannot read a LOB object in a remote server.

Cause	Cannot read a LOB object in a remote server.
--------------	--

Action	Change the query.
---------------	-------------------

2185: The password will expire within %1\$s days.

Cause	The password will expire within %1\$s days.
Action	Update the password.

2186: Failed to compress batch update messages.

Cause	Failed to compress batch update messages.
Action	Check the client library.

2187: Failed to compress DPL messages.

Cause	Failed to compress DPL messages.
Action	Check the client library.

2188: Too many rows returned on exact fetch mode.

Cause	Too many rows returned on exact fetch mode.
Action	Check the requested rows.

2189: Information type out of range.

Cause	Information type is not valid.
Action	Check the information type.

2190: Ending byte of string is invalid.

Cause	Character set cannot interpret the ending of string.
Action	Check the client charset.

2191: Kerberos authentication failed.

Cause	Establishing a GSS-API context was unsuccessful.
Action	Check the kerberos configuration and the service name in the DSN file.

제3장 3000 ~ 3999

3001: Out of memory (shared memory).

Cause	Insufficient shared memory remaining.
Action	To increase the shared memory space, specify a larger value for the TOTAL_SHM_SIZE parameter.

3002: Out of memory (unable to allocate %1\$d bytes of shared pool memory).

Cause	Insufficient shared pool memory remaining.
Action	To increase the shared memory space, specify a larger value for the TOTAL_SHM_SIZE parameter.

3003: Out of memory (unable to allocate in system memory).

Cause	Insufficient system memory remaining. It maybe one of three cases. 1) The OS memory is full. 2) Total allocated size in DB system is closed to memory limit. 3) Total allocated size in a session is closed to session limit.
Action	Increase the system memory space and close other running programs, or specify a larger value for the MEMORY_TARGET(DB version is above 7).

3004: Unable to open log file.

Cause	Cannot open the log file.
Action	Check the log file path and permissions.

3005: Insufficient space in buffer.

Cause	Insufficient buffer space.
--------------	----------------------------

Action	Increase the size of the buffer.
---------------	----------------------------------

3006: Feature not yet implemented.

Cause	This feature is not yet implemented.
Action	Check whether a feature which is not yet implemented was used.

3007: Environment variable (database home and database sid) is not set.

Cause	An environment variable (database home and database sid) has not been defined.
Action	Define the variable.

3009: Unable to change log directory because the target directory is the same as the old destination.

Cause	The target directory is the same as the log directory currently being used.
Action	Specify a directory that is different from the current log directory.

3010: Unable to change log directory because of a failure in renaming log file.

Cause	Unable to rename the log file. Refer to the server error log for more detail.
Action	Examine the log file permissions and check the server error log. For more information, contact the technical support team.

3011: Unable to change log directory because of a failure in generating new log file.

Cause	The target directory has insufficient space.
--------------	--

Action	Examine the target directory space and initial parameters such as LOG_TOTAL_SIZE_LIMIT. Ensure the directory has sufficient space by deleting or moving unnecessary files. For more information, contact the technical support team.
---------------	--

3012: Unable to change log directory.

Cause	An error occurred while remapping a new log file. Check the error log at server.
Action	Examine the error log in the server. For more information, contact the technical support team.

3013: Unable to change log directory because filenames conflict.

Cause	There is already a log file with identical name in the target directory.
Action	Modify the filename or remove the log file in the target directory.

3014: Unable to create a directory for the new log file.

Cause	Unable to create a directory for the new log file due to invalid path or authority.
Action	Check whether a path and its authority of the new log file are valid. Also examine the error log of the server. For more information, contact the technical support team.

3015: Type of the JSON value is different from expected type.

Cause	Type of the JSON value is different from expected type.
Action	Examine the error log in the server. For more information, contact the technical support team.

3016: Expected JSON key not found.

Cause	Expected JSON key not found.
Action	Check the inventory of Horde.

3017: Too many objects referred (%1\$d).

Cause	Too many objects referred (%1\$d).
Action	Contact the technical support team.

3018: Out of memory (unable to allocate %1\$d bytes of shared pool memory for %2\$s).

Cause	Insufficient shared pool memory remaining.
Action	To increase the shared memory space, specify a larger value for the TOTAL_SHM_SIZE parameter.

3019: String buffer overflow detected.

Cause	An overflow occurred while generating a text string.
Action	Contact Technical Support.

제4장 4000 ~ 4999

4001: Invalid DBA found.

Cause	Invalid DBA (Database Administrator) has been entered.
Action	Enter valid DBA.

4002: Invalid row number.

Cause	Invalid row number was entered.
Action	Enter a valid row number.

4003: Invalid serialized long locator discovered.

Cause	Invalid serialized long locator was entered.
Action	Enter a valid serialized long locator.

4004: Duplicate unique key found during index fast build.

Cause	A duplicate key exists in the table; the index cannot be made.
Action	Delete the duplicate key or make a non-unique index.

4005: Referential constraint violation: foreign key exists.

Cause	A foreign key exists with the same value; the primary key cannot be deleted.
Action	Delete the foreign key and then delete the primary key.

4006: Referential constraint violation: primary key not found.

Cause	A foreign key cannot be inserted; the primary key does not exist.
--------------	---

Action	Enter the primary key and then insert the foreign key.
---------------	--

4007: Unable to find LONG cursor.

Cause	In order to use the LONG function, an open cursor is necessary.
Action	Call the LONG function before closing the cursor.

4008: Duplicate unique key found during multi insert.

Cause	Cannot insert the entered key into the index, as the key is a duplicate.
Action	Check the duplicate key.

4009: LOB snapshot too old

Cause	The LOB value for CR was overwritten by another tx.
Action	Check the cause of the failure and try again.

4010: LOB information requested by a client is invalid.

Cause	LOB directory information is no longer valid.
Action	Because the directory of the table in which LOB exists is changed, the LOB locator cannot be used for the access.

4011: Data being inserted into an index-organized table via mutli insert must be sorted.

Cause	The data being inserted into the index-organized table is not sorted.
Action	Sort data before using mutli insert to insert rows into an index-organized table.

4012: unsupported operation on multi-column compressed tables

Cause	unsupported update/delete operation on multi-column compressed tables
--------------	---

Action	uncompress tables before update/delete operation
---------------	--

4013: Level of the index has reached maximum depth allowed.

Cause	The index has deficient nodes and the shape of the index is skewed.
Action	Index reorganization is required.

4014: Directory object was not found.

Cause	Directory object could not be found.
Action	Check the directory name.

4015: File path is too long.

Cause	File path is too long.
Action	Check the directory name and the file name.

4016: Can't open empty file.

Cause	The file to open is empty.
Action	Check the parameter.

4017: Can't open the specified binary file.

Cause	Can't open the specified binary file.
Action	Check the parameter.

4018: Can't get the length of the specified binary file.

Cause	Can't get the length of the specified binary file.
Action	Check the parameter.

4019: Failed to lseek because of the invalid offset

Cause	Failed to lseek because of the invalid offset
Action	Check the parameter.

4020: Failed to read the specified binary file.

Cause	Failed to read the specified binary file.
Action	Check the parameter.

4021: Failed to open the binary file

Cause	The specified binary file is not opened.
Action	Check the parameter.

4022: Specified binary file does not exist.

Cause	Specified binary file does not exist.
Action	Check the parameter.

4027: Access to the directory object was denied.

Cause	Access to the directory object was denied.
Action	Check the directory object and modify the permission.

4028: Stored data in long type column is too long

Cause	
Action	

4029: Shared pool memory space for a sort segment extent list cannot be allocated.

Cause	Insufficient shared pool memory remaining.
Action	To increase the shared memory space, specify a larger value for the TOTAL_SHM_SIZE parameter.

4031: Failed to repopulate segment ID: %1\$d.

Cause	Insufficient in-memory space for the segment.
Action	Convert another in-memory table to "no in-memory" or drop it to free space.

4032: Failed to %1\$suncompress. (return code: %2\$d)

Cause	An error occurred during decompression.
Action	Check the cause of the failure with return code and try again.

제5장 5000 ~ 5999

5001: Datetime/interval precision is out of range.

Cause	The values of DATETIME and INTERVAL do not match with the specified precision.
Action	Correct the specified precision and try again.

5002: Invalid data type for this operation.

Cause	An invalid data type was entered for an operation or function.
Action	Check the entered data type.

5003: Invalid TIME value.

Cause	Invalid TIME value.
Action	Check each field of TIME.

5004: Invalid TIMESTAMP value.

Cause	Invalid TIMESTAMP value.
Action	Check each field of TIMESTAMP.

5005: Invalid DATE value.

Cause	Invalid DATE value.
Action	Check each field of DATE.

5006: Invalid DATETIME unit type.

Cause	Invalid unit type for the entered DATETIME type.
--------------	--

Action	Check the entered unit type.
---------------	------------------------------

5007: Invalid string length.

Cause	Invalid format string or input string length.
Action	Check if format string or input string is null or less than 0.

5008: Invalid precision specified for fractions of a second.

Cause	The precision specified for fraction of a second in TIMESTAMP and TIME is invalid.
Action	Check whether the precision is between 0 and 9.

5009: Input string is too short for DATE format.

Cause	The input string to be converted into the specified format string is incomplete.
Action	Lengthen the input string to match the given format string.

5010: Format ends before the entire input string is converted.

Cause	Additional unconverted data exists in the input string after conversion.
Action	Check the definition of the DATETIME format code and correct the input string.

5011: Invalid DATE format.

Cause	Invalid format code for DATE type is entered.
Action	Verify the DATE format code used is valid.

5012: Invalid TIME format.

Cause	Invalid format code for TIME/TIMESTAMP type is entered.
Action	Verify the TIME/TIMESTAMP format code used is valid.

5013: Specified format code cannot be used as input format.

Cause	The given format code cannot be used as input format.
Action	Delete the invalid format code from format string.

5014: Specified format code is invalid.

Cause	Unable to verify the specified format code.
Action	Delete the invalid format code from format string.

5015: Duplicated YEAR format exists.

Cause	A YEAR format code has already been provided.
Action	Delete the duplicate YEAR format code.

5016: Duplicated MONTH format exists.

Cause	A MONTH format code has already been provided.
Action	Delete the duplicate MONTH format code.

5017: Duplicated DAY format exists.

Cause	A DAY format code has already been provided.
Action	Delete the duplicate DAY format code.

5018: Duplicated HOUR format exists.

Cause	An HOUR format code has already been provided.
Action	Delete the duplicate HOUR format code.

5019: Duplicated MINUTE format exists.

Cause	A MINUTE format code has already been provided.
--------------	---

Action	Delete the duplicate MINUTE format code.
---------------	--

5020: Duplicated SECOND format exists.

Cause	A SECOND format code has already been provided.
Action	Delete the duplicate SECOND format code.

5021: Duplicated fractions of a second format exists.

Cause	Fractions of a second format code has already been provided.
Action	Delete the duplicate fractions of a second format code.

5022: Duplicated AD/BC format exists.

Cause	An AD/BC format code has already been provided.
Action	Delete the duplicate AD/BC format code.

5023: Duplicated AM/PM format exists.

Cause	An AM/PM format code has already been provided.
Action	Delete the duplicate AM/PM format code.

5024: Month conflicts with Julian date.

Cause	DDD format code and month-related format code cannot be used together.
Action	Delete the month-related format code to use the DDD format code.

5025: Day of the month conflicts with Julian date.

Cause	DDD format code and date-related format code cannot be used together.
Action	Delete the date-related format code to use the DDD format code.

5026: Hour of the day conflicts with seconds in the day.

Cause	SSSSS format code and hour-related format code cannot be used together.
Action	Delete the hour-related format code to use the SSSSS format code.

5027: Minutes of the hour conflicts with seconds in the day.

Cause	SSSSS format code and minute-related format code cannot be used together.
Action	Delete the minute-related format code to use the SSSSS format code.

5028: Seconds of the minute conflicts with seconds in the day.

Cause	SSSSS format code and second-related format code cannot be used together.
Action	Delete the second-related format code to use the SSSSS format code.

5029: Invalid year value: must be a non-zero integer between -4713 and +9999.

Cause	Invalid value specified for the year.
Action	Input a non-zero integer value between -4713 and +9999.

5030: Invalid month value.

Cause	Invalid value specified for the month.
Action	Input an integer value between 1 and 12.

5031: Invalid month name.

Cause	Invalid value specified for the month name.
Action	Input a valid month name.

5032: Invalid day value.

Cause	Invalid value specified for the day name.
Action	Input a valid day name.

5033: Invalid hour value.

Cause	Invalid value specified for the hour.
Action	Input an integer value between 0 and 23.

5034: Invalid minute value.

Cause	Invalid value specified for the minutes.
Action	Input an integer value between 0 and 59.

5035: Invalid second value.

Cause	Invalid value specified for the seconds.
Action	Input an integer value between 0 and 60.

5036: Invalid fractions of a second value.

Cause	Invalid value specified for the fractions of a second.
Action	Input an integer value between 0 and 999999999.

5037: Invalid AD/BC value.

Cause	Invalid value specified for AD/BC.
Action	Input a valid value for AD/BC.

5038: Invalid AM/PM value.

Cause	Invalid value specified for AM/PM.
--------------	------------------------------------

Action	Input a valid value for AM/PM.
---------------	--------------------------------

5039: Signed year cannot be used with AD/BC.

Cause	The signed year format cannot be used with the AD/BC format.
Action	Delete one of the two formats to make a valid format string.

5040: HH24 cannot be used with AM/PM.

Cause	The HH24 format cannot be used with the AM/PM format simultaneously.
Action	Delete one of the two formats to make a valid format string.

5041: Invalid precision specified for fractions of a second.

Cause	The precision for fractions of a second in TIMESTAMP and TIME is invalid in the format string.
Action	Verify the precision is between 0 and 9.

5042: Invalid decimal input.

Cause	Invalid value specified for decimal.
Action	Input a valid decimal number ('.').

5043: Invalid seconds of the day input.

Cause	Invalid value was entered in SSSSS format.
Action	Input an integer value between 0 and 86400.

5044: Insufficient space in string buffer for DATETIME type.

Cause	The buffer is not large enough to convert the DATETIME type to a string.
Action	Increase the buffer size.

5045: Only TIME format can be omitted.

Cause	All format codes except hour/minute/second/fraction of a second are omitted from the input string.
Action	Input valid values for the format codes or delete the formats.

5046: Day of the year must be between 1 and 365 (366 for leap year).

Cause	Invalid value specified for a day of the year
Action	Input an integer value between 1 and 366.

5047: Invalid day name.

Cause	Invalid value specified for a day of the week
Action	Input a valid value for a day of the week.

5048: Too many truncation format specifiers.

Cause	More than one truncate format code is set.
Action	Input only one format code.

5049: Too many round-up format specifiers.

Cause	More than one round-up format code is set.
Action	Input only one format code.

5050: Invalid use of the escape character.

Cause	Invalid use of the escape character.
Action	Check the search pattern string of LIKE function.

5051: Invalid hexadecimal number.

Cause	The given character is not a valid hexadecimal number.
Action	Check the character to be converted to hexadecimal number.

5052: Invalid string sequence.

Cause	The character is not included in the given character set.
Action	Check the input string and character set.

5053: Invalid Unicode.

Cause	Invalid Unicode.
Action	Check the input string.

5054: Not implemented.

Cause	Unsupported format string.
Action	Check the input format string.

5055: Invalid type of UNIT used for INTERVAL.

Cause	Invalid UNIT type for the INTERVAL type that was entered.
Action	Check the UNIT type.

5056: Invalid input string for INTERVAL.

Cause	An error occurred while converting the input string to INTERVAL type.
Action	Check the input string.

5057: Invalid input precision for interval.

Cause	Invalid leading precision value.
--------------	----------------------------------

Action	Check the leading precision value.
---------------	------------------------------------

5058: Invalid precision value for fractions of a second.

Cause	Invalid precision value for fractions of a second.
Action	Input a valid precision value for fractions of a second.

5059: Invalid INTERVAL format.

Cause	Unsupported interval format string.
Action	Check the input format string.

5060: Month value is out of range.

Cause	Value of months in YEAR-TO-MONTH INTERVAL type is out of range.
Action	Input a valid month value.

5061: Hour value is out of range.

Cause	Value of hour in DAY-TO-SECOND INTERVAL type is out of range.
Action	Input a valid hour value.

5062: Minutes value is out of range.

Cause	Value of minutes in DAY-TO-SECOND INTERVAL type is out of range.
Action	Input a valid minutes value.

5063: Seconds value is out of range.

Cause	Value of seconds in DAY-TO-SECOND INTERVAL type is out of range.
Action	Input a valid seconds value.

5064: INTERVAL exceeds given precision value.

Cause	The INTERVAL value does not match the given precision value.
Action	Correct the values and try again.

5065: Divide by zero error.

Cause	The INTERVAL type was divided by 0.
Action	Modify the expression to remove the error.

5066: Insufficient space in buffer for conversion.

Cause	The buffer is not large enough to convert the INTERVAL type into string.
Action	Increase the buffer size.

5067: Output was altered or truncated to fit into buffer, resulting in a possible loss of precision.

Cause	The buffer is not large enough to contain the results of the converted string.
Action	Increase the buffer size.

5068: Overflow error.

Cause	Overflow occurred as a result of an operation.
Action	Decrease the value of an operand.

5069: Underflow error.

Cause	Underflow occurred as a result of an operation.
Action	Increase the value of an operand.

5070: Divide by zero error.

Cause	The NUMBER type was divided by 0.
Action	Modify the expression to remove the error.

5071: NUMBER exceeds given precision.

Cause	The NUMBER value does not match the given precision value.
Action	Correct the values and try again.

5072: Failure converting NUMBER to or from a native type.

Cause	An error occurred while converting the NUMBER value.
Action	Check that the value is within the appropriate range.

5073: Invalid NUMBER provided for the operation.

Cause	An invalid NUMBER value was entered for the operation or function.
Action	Change the value and try again.

5074: Given string does not represent a number in proper format.

Cause	The given string does not represent a proper number.
Action	Check the type of string.

5075: Invalid format string.

Cause	Invalid format string.
Action	Correct the format string.

5076: NUMBER is not printable in this format. Numbers were filled in output buffer.

Cause	The NUMBER value does not match the given format.
Action	Modify the NUMBER value or format string.

5077: NUMBER precision is out of range.

Cause	The precision of the NUMBER type is out of range.
Action	Specify a precision value for the NUMBER type between 1 and 38.

5078: NUMBER scale is out of range.

Cause	The scale of the NUMBER type is out of range.
Action	Specify a scale value for the NUMBER type between -125 and +130.

5079: Data type length is out of range.

Cause	The length is out of range.
Action	Modify the length to the one that is defined for each type.

5080: Invalid ROWID.

Cause	Invalid ROWID
Action	Choose a valid ROWID.

5081: Invalid ROWID segment info.

Cause	Invalid ROWID segment information.
Action	Input valid segment information for the ROWID.

5082: Invalid ROWID file.

Cause	Invalid ROWID file information.
Action	Input valid file information for the ROWID.

5083: Invalid ROWID block.

Cause	Invalid ROWID block information.
Action	Input valid block information for the ROWID.

5084: Invalid ROWID row.

Cause	Invalid ROWID row information.
Action	Input valid row information for the ROWID.

5085: Invalid IP string.

Cause	Invalid IP string.
Action	Check the input IP string.

5086: String buffer is too small for string conversion or copy.

Cause	The string buffer is too small to handle the task.
Action	Check the size of the input string.

5087: The date value is out of range.

Cause	The date value of the YEAR-TO-MONTH INTERVAL type is out of range.
Action	Input a valid date value.

5088: Numeric digits are not matched.

Cause	The number of digits of a given number and the length of the datetime format are not matched.
Action	Use the same number of digits as the length of the datetime format.

5089: Punctuation characters are not matched.

Cause	The character of a given punctuation mark does not match the character of the datetime format.
Action	Use the same character as that of the datetime format.

5090: Not a numeric value.

Cause	Cannot use a character for numeric data.
Action	Use numeric data.

5091: Invalid timezone format.

Cause	Invalid timezone format is used for the TIMESTAMP type.
Action	Verify that you have entered a valid timezone format.

5092: Duplicate TZh format.

Cause	The TZh format code already exists.
Action	Delete the duplicated timezone (hour) format code.

5093: Duplicate TZM format.

Cause	The TZM format code already exists.
Action	Delete the duplicated timezone (minute) format code.

5094: Duplicate TZR format.

Cause	The TZR format code already exists.
Action	Delete the duplicated timezone (region) format code.

5095: Duplicate TZD format.

Cause	The TZD format code already exists.
Action	Delete the duplicated timezone (abbreviation) format code.

5096: TZR/TZD format conflicts with TZH/TZM format.

Cause	timezone region format cannot be used with timezone time format.
Action	Delete the region format.

5097: TZH/TZM format conflicts with TZR/TZD format.

Cause	timezone time format cannot be used with timezone region format.
Action	Delete the time format.

5098: Invalid hour value of UTC offset.

Cause	The hour value of UTC offset must be between -12 and 14.
Action	Verify that you have entered a valid hour value of UTC offset.

5099: Invalid minute value of UTC offset.

Cause	The minute value of UTC offset must be between 0 and 59.
Action	Verify that you have entered a valid minute value of UTC offset.

5100: Invalid second value of UTC offset.

Cause	The second value of UTC offset must be between 0 and 59.
--------------	--

Action	Verify that you have entered a valid second value of UTC offset.
---------------	--

5101: Invalid hour value of daylight saving time.

Cause	The hour value of daylight saving time must be between 0 and 24.
Action	Verify that you have entered a valid hour value of daylight saving time.

5102: Invalid minute value of daylight saving time.

Cause	The minute value of daylight saving time must be between 0 and 59.
Action	Verify that you have entered a valid minute value of daylight saving time.

5103: Invalid timezone offset.

Cause	The timezone offset value must be in the format of '[+ -]hh:mm'.
Action	Verify that you have entered a valid timezone offset.

5104: Invalid timezone region value.

Cause	The timezone region value is invalid or unsupported.
Action	Verify that you have entered a valid timezone region value.

5105: Invalid timezone index '%1\$d'.

Cause	The timezone index value is not supported.
Action	Contact the technical support team.

5106: Invalid timezone hour value.

Cause	The timezone hour value is invalid.
Action	Verify that you have entered a valid timezone hour value.

5107: Invalid timezone minute value.

Cause	The timezone minute value is invalid.
Action	Verify that you have entered a valid timezone minute value.

5108: Invalid timezone region value.

Cause	The timezone region value is invalid.
Action	Verify that you have entered a valid timezone region value.

5109: Invalid timezone abbreviation value.

Cause	The timezone abbreviation value is invalid.
Action	Verify that you have entered a valid timezone abbreviation value.

5110: Invalid date/time period according to the daylight saving time rule.

Cause	The date/time period is invalid according to the daylight saving time rule.
Action	Check the daylight saving time rule.

5111: NUMBER exceeds given precision. (n:%1\$s, p:%2\$d, s:%3\$d)

Cause	The NUMBER value does not match the given precision value.
Action	Correct the values and try again.

5112: Duplicated '%1\$s' format exists.

Cause	A format code has already been provided.
Action	Delete the duplicated format code.

5113: Invalid %1\$s value '%2\$s'. (%3\$s)

Cause	Invalid value specified for the %1\$s.
Action	Input a valid value for %1\$s.

5114: Invalid %1\$s value '%2\$d': must be an integer between %3\$d and %4\$d.

Cause	Invalid value specified for the %1\$s.
Action	Input a valid value for %1\$s.

5115: Cannot find the timezone file.

Cause	The timezone file does not exist, or you don't have permission to read the file.
Action	Check the timezone file.

5116: NULL object instance access violation.

Cause	An attempt was made to access the attributes of an object instance whose value is null.
Action	Check that the value of the object instance is not null.

5117: Invalid user-defined type.

Cause	The specified user-defined type does not exist or has been altered.
Action	Check if the user-defined type has been altered on the server.

5118: FLOAT precision is out of range.

Cause	The precision of the FLOAT type is out of range.
Action	Specify a precision value for the FLOAT type between 1 and 120.

5119: Invalid number type.

Cause	Invalid number type.
Action	Check the type.

제6장 6000 ~ 6999

6001: Internal error: DD search failed.

Cause	Failed to search DD (Data Dictionary) due to an internal error.
Action	Contact the technical support team.

6002: Synonym translation is no longer valid.

Cause	The target schema or object does not exist.
Action	Change the definition of the synonym so that the synonym refers to a valid object.

6003: Sequence \"%1\$s\" has not been accessed in this session: no CURRVAL available.

Cause	CURRVAL cannot be used since the indicated sequence has not been used in the current session.
Action	CURRVAL can be used only after NEXTVAL has been used in the same session.

6004: Sequence \"%1\$s\" has exceeded its available range.

Cause	All values available in sequence are already used.
Action	Modify the range of the sequence by using an ALTER SEQUENCE statement.

6005: DB data dictionary version does not match binary DD version.

Cause	The version of the DD in the DB is different from the version of DD in the binary.
Action	The binary cannot be used in the database.

6006: ALTERDD must be run on data dictionary.

Cause	The ALTERDD process must be run to use the DD as the binary.
Action	Execute the ALTERDD process to change DD.

6007: Table \"%1\$s\" cannot be loaded because the size of the constraints on the table is too large.

Cause	The size of the constraints on the table is too large.
Action	Check if the table has unnecessary constraints. Drop unnecessary constraints.

6009: Failed to add a pair in a DD object search key map.

Cause	An internal error occurred during adding a pair in a DD object search key map.
Action	Contact the technical support team.

6010: Failed to add a pair in a DD user search key map.

Cause	An internal error occurred during adding a pair in a DD user search key map.
Action	Contact the technical support team.

6011: Cannot execute the current sequence Nextval with the SCALE_NOEXTEND option.

Cause	The sequence value conflicts with the SCALE prefix value.
Action	Increase the number of digits in the sequence by \"%1\$u\", or use the SCALE EXTEND option.

제7장 7000 ~ 7999

7001: General syntax error.

Cause	Syntax error occurred.
Action	Correct the SQL statement.

7002: Unsupported DDL.

Cause	Unsupported DDL (Data Definition Language).
Action	The statement cannot be executed.

7003: The SQL statement is not valid DDL.

Cause	The statement is not valid DDL.
Action	The statement cannot be executed.

7004: This DDL statement is not permitted in the current boot mode.

Cause	In the current boot mode, this DDL cannot be executed.
Action	Change the boot mode and run the DDL statement again.

7005: Missing right parenthesis at line %1\$d, column %2\$d.

Cause	The right parenthesis is missing.
Action	Check parentheses and try again.

7006: Filename is too long. %1\$s.

Cause	The specified filename is too long.
--------------	-------------------------------------

Action	Use a shorter filename and try again.
---------------	---------------------------------------

7007: The specified value is out of range.

Cause	The specified value is either too small or too large.
Action	Specify a valid value and try again.

7008: START WITH is not allowed for ALTER sequences.

Cause	The START WITH option was specified for an ALTER sequence.
Action	The START WITH option is allowed only for CREATE sequences.

7009: Maximum number of columns was exceeded.

Cause	The number of columns exceeds the maximum number allowed.
Action	Specify a number of columns less than the maximum.

7010: Unable to grant privileges other than INSERT, REFERENCE, and UPDATE on column.

Cause	A column privilege was granted to an operation other than INSERT, REFERENCE or UPDATE.
Action	The privilege cannot be granted.

7011: Number of specified files and target files do not match.

Cause	The number of specified files is different from the number of target files.
Action	Ensure that the numbers of files match.

7012: Log group number is invalid.

Cause	The specified log group number is invalid.
--------------	--

Action	Specify a valid log group number.
---------------	-----------------------------------

7013: This option cannot be specified.

Cause	The specified option is invalid.
Action	Specify a valid option.

7014: A filename is required for this DDL statement.

Cause	The filename is not specified.
Action	Specify a valid filename.

7015: Duplicate FORCE LOGGING clause exists.

Cause	A duplicate FORCE LOGGING clause exists.
Action	Delete the duplicate clause.

7016: Duplicate LOGGING clause exists.

Cause	A duplicate LOGGING clause exists.
Action	Delete the duplicate clause.

7017: Duplicate PCTFREE setting exists.

Cause	A duplicate PCTFREE setting exists.
Action	Delete the duplicate setting.

7018: Duplicate INITRANS setting exists.

Cause	A duplicate INITRANS setting exists.
Action	Delete the duplicate setting.

7019: Duplicate STORAGE clause exists.

Cause	A duplicate STORAGE clause exists.
Action	Delete the duplicate clause.

7020: Duplicate MINEXTENTS setting exists.

Cause	A duplicate MINEXTENTS setting exists.
Action	Delete the duplicate setting.

7021: Duplicate MAXEXTENTS setting exists.

Cause	A duplicate MAXEXTENTS setting exists.
Action	Delete the duplicate setting.

7022: Duplicate EXTENT MANAGEMENT clause exists.

Cause	A duplicate EXTENT MANAGEMENT clause exists.
Action	Delete the duplicate clause.

7023: Duplicate ENABLE or DISABLE clause exists on a constraint.

Cause	A duplicate ENABLE or DISABLE clause exists.
Action	Delete the duplicate clause.

7024: Duplicate USING INDEX clause exists.

Cause	A duplicate USING INDEX clause exists.
Action	Delete the duplicate clause.

7025: Duplicate NULL or NOT NULL setting exists.

Cause	A duplicate NULL or NOT NULL setting exists.
--------------	--

Action	Delete the duplicate setting.
---------------	-------------------------------

7026: Duplicate primary key exists.

Cause	A duplicate primary key exists.
Action	Delete the duplicate.

7027: Duplicate unique key exists.

Cause	A duplicate unique key exists.
Action	Delete the duplicate.

7028: Duplicate ENABLE IN ROW or DISABLE IN ROW setting exists.

Cause	A duplicate ENABLE or DISABLE IN ROW setting exists.
Action	Delete the duplicate setting.

7029: Duplicate CHUNK SIZE setting exists.

Cause	A duplicate CHUNK SIZE setting exists.
Action	Delete the duplicate setting.

7030: Duplicate USER SYS clause exists.

Cause	A duplicate USER SYS clause exists.
Action	Delete the duplicate clause.

7031: Duplicate MAXLOGGROUPS setting exists.

Cause	A duplicate MAXLOGGROUPS setting exists.
Action	Delete the duplicate setting.

7032: Duplicate MAXLOGMEMBERS setting exists.

Cause	A duplicate MAXLOGMEMBERS setting exists.
Action	Delete the duplicate setting.

7033: Duplicate MAXDATAFILES setting exists.

Cause	A duplicate MAXDATAFILES setting exists.
Action	Delete the duplicate setting.

7034: Duplicate NATIONAL CHARACTER SET setting exists.

Cause	A duplicate NATIONAL CHARACTER SET setting exists.
Action	Delete the duplicate setting.

7035: Duplicate ARCHIVELOG or NOARCHIVELOG setting exists.

Cause	A duplicate ARCHIVELOG or NOARCHIVELOG setting exists.
Action	Delete the duplicate setting.

7036: Cannot mix a log group definition that specifies a group number with a definition that does not.

Cause	A definition that specifies a log group number cannot be used with one that does not specify a log group number.
Action	To specify a log group number, ensure log group definitions are not mixed-type.

7037: Duplicate ONLINE or OFFLINE clause exists.

Cause	A duplicate ONLINE or OFFLINE clause exists.
Action	Delete the duplicate clause.

7038: Duplicate TABLESPACE setting exists.

Cause	A duplicate TABLESPACE setting exists.
Action	Delete the duplicate setting.

7039: Unspecified column type.

Cause	A column type was omitted.
Action	Specify a column type.

7040: Unspecified column definition.

Cause	The column definition was omitted.
Action	Specify the definition.

7041: Too many LONG columns are specified.

Cause	Two or more LONG-type columns are specified in one table.
Action	Specify only one LONG-type column.

7042: New column cannot be added to this table.

Cause	The table has a LOB or LONG type column or the number of columns in the table is at the maximum.
Action	Unable to add a new column.

7043: Specified number of columns does not match number of subquery columns.

Cause	The number of specified columns is different from the number of columns in subquery.
Action	Ensure that the numbers of columns match.

7044: Column datatypes cannot be specified with a subquery.

Cause	Cannot specify a column data type with a subquery.
Action	Do not specify a data type.

7045: A column contains a NULL value: cannot create or enable the constraint.

Cause	A column contains a NULL value: NOT NULL or primary key cannot be created.
Action	Check columns for NULL values.

7046: Duplicate INCREMENT BY setting exists.

Cause	A duplicate INCREMENT BY setting exists.
Action	Delete the duplicate setting.

7047: Duplicate START WITH setting exists.

Cause	A duplicate START WITH setting exists.
Action	Delete the duplicate setting.

7048: Duplicate MAXVALUE or NOMAXVALUE setting exists.

Cause	A duplicate MAXVALUE or NOMAXVALUE setting exists.
Action	Delete the duplicate setting.

7049: Duplicate MINVALUE or NOMINVALUE setting exists.

Cause	A duplicate MINVALUE or NOMINVALUE setting exists.
Action	Delete the duplicate setting.

7050: Duplicate CYCLE or NOCYCLE setting exists.

Cause	A duplicate CYCLE or NOCYCLE setting exists.
Action	Delete the duplicate setting.

7051: Duplicate CACHE or NOCACHE setting exists.

Cause	A duplicate CACHE or NOCACHE setting exists.
Action	Delete the duplicate setting.

7052: New password is invalid.

Cause	The new password is invalid.
Action	Specify a valid password.

7053: Password is too long: maximum %1\$d characters allowed.

Cause	The password is too long.
Action	Use a shorter password.

7054: Invalid password was entered.

Cause	The previous password was not entered or was invalid.
Action	Recheck the previous password and check that permission to use ALTER USER statement is granted.

7055: Encrypted password is invalid.

Cause	The encrypted password is invalid.
Action	Use a password that is encrypted in a valid style.

7056: Duplicate password exists.

Cause	A duplicate password exists.
Action	Change to a unique password.

7057: Duplicate REPLACE old password statement exists.

Cause	A duplicate REPLACE old password statement exists.
Action	Delete the duplicate statement.

7058: Duplicate DEFAULT TABLESPACE setting exists.

Cause	A duplicate DEFAULT TABLESPACE setting exists.
Action	Delete the duplicate setting.

7059: Duplicate DEFAULT ROLE clause exists.

Cause	A duplicate DEFAULT ROLE clause exists.
Action	Delete the duplicate clause.

7060: Duplicate PASSWORD EXPIRE setting exists.

Cause	A duplicate PASSWORD EXPIRE setting exists.
Action	Delete the duplicate setting.

7061: Duplicate ACCOUNT_LOCK setting exists.

Cause	A duplicate ACCOUNT_LOCK setting exists.
Action	Delete the duplicate setting.

7062: DROP option cannot be used if datafile is online.

Cause	The online datafile cannot be dropped.
--------------	--

Action	Execute the OFFLINE FOR DROP option first.
---------------	--

7063: END BACKUP option cannot be used for a temporary file.

Cause	The END BACKUP option cannot be used for a temporary file.
Action	Unable to execute.

7064: File '%1\$s' was not found in this database.

Cause	The file was not found in the current database.
Action	Specify a valid file name.

7065: File number %1\$d was not found in this database.

Cause	The file was not found in the current database.
Action	Specify a valid file number.

7066: A log member clause was expected.

Cause	The log member clause was omitted.
Action	Specify the log member clause.

7067: Specified database name '%1\$s' does not match parameter database name in tip file '%2\$s'.

Cause	The specified database name does not match the database name specified in the parameter file.
Action	Match with information in the parameter file. Distinguish but only when using double quotation marks.

7068: Specified schema '%1\$s' was not found.

Cause	The specified schema was not found.
--------------	-------------------------------------

Action	Specify a valid schema name.
---------------	------------------------------

7069: Specified user '%1\$s' was not found.

Cause	The specified user was not found.
Action	Specify a valid user name.

7070: Specified role '%1\$s' was not found.

Cause	The specified role was not found.
Action	Specify a valid role.

7071: Schema object '%1\$s.%2\$s' was not found or is invalid.

Cause	The specified object was not found or is an invalid type.
Action	Specify a valid object name.

7072: Specified column '%1\$s' was not found or is invalid.

Cause	The specified column was not found or is an invalid type column.
Action	Specify a valid column name.

7073: Specified tablespace '%1\$s' was not found.

Cause	The specified tablespace does not exist.
Action	Specify a valid tablespace name.

7074: Specified tablespace '%1\$s' cannot be used as a user's default tablespace.

Cause	The specified tablespace cannot be used for a default tablespace.
Action	Specify a different tablespace name.

7075: Specified role '%1\$s' was not found.

Cause	The specified role does not exist.
Action	Specify a valid role.

7076: Specified constraint '%1\$s' was not found.

Cause	The specified constraint does not exist.
Action	Specify a valid constraint name.

7077: Specified target of grant '%1\$s' does not exist.

Cause	The specified grantee does not exist.
Action	Specify a valid target name.

7078: Specified target of revoke '%1\$s' does not exist.

Cause	The specified revokee does not exist.
Action	Specify a valid target name.

7079: Duplicate column name '%1\$s' exists.

Cause	A duplicate column name exists.
Action	Use a unique column name.

7080: Specified column '%1\$s'. '%2\$s' must be empty before changing datatypes.

Cause	In order to change the column datatype, all columns must be empty.
Action	Clear all columns.

7081: Specified column '%1\$s'. '%2\$s' must be empty before reducing column length.

Cause	Column lengths cannot be reduced if the column is not empty.
Action	Make the columns null.

7082: Duplicate segment name '%1\$s' exists.

Cause	A duplicate segment name exists.
Action	Use a unique segment name.

7083: Duplicate constraint name '%1\$s' exists.

Cause	A duplicate constraint name exists.
Action	Use a unique constraint name.

7084: Expression requires a column alias.

Cause	The expression requires a column alias.
Action	Specify a column alias.

7085: Number of column aliases does not match the number of required columns.

Cause	The number of aliases is different from the number of required columns.
Action	Specify a valid number of aliases.

7086: An index cannot be created from columns of type LONG, LONG RAW, LOB, OBJECT, or COLECTION.

Cause	An index cannot be made of certain type columns.
Action	Unable to execute.

7087: '%1\$s' is not a table or view so it cannot have columns.

Cause	The object does not have columns.
Action	Check again.

7088: Duplicate grant target name '%1\$s' exists.

Cause	A duplicate grantee name exists.
Action	Delete the duplicate grantee name.

7089: Duplicate revoke target name '%1\$s' exists.

Cause	A duplicate revokee name exists.
Action	Delete the duplicate revokee name.

7090: Duplicate privilege exists.

Cause	A duplicate privilege exists.
Action	Delete the duplicate privilege.

7091: Duplicate role '%1\$s' exists.

Cause	A duplicate role exists.
Action	Delete the duplicate role.

7092: LONG column type cannot be specified in this statement.

Cause	In the CREATE TABLE AS SELECT statement, the LONG type column cannot be specified.
Action	Do not specify a LONG type column.

7093: Synonym cannot have the same name as its target.

Cause	The synonym and its target have the same name.
--------------	--

Action	Try a different synonym.
---------------	--------------------------

7094: Unable to decrease column size: a value in the column is too long.

Cause	The data in the existing column is too long.
Action	Specify a column size larger than the length of the data in the existing column.

7095: Unable to create a unique file name.

Cause	Unable to create a new file name.
Action	Change the directory or check to see if the name of the directory is too long.

7096: Unable to create a unique object name.

Cause	Unable to create a new object name.
Action	Avoid any names used internally by DBMS server.

7097: Duplicate filename '%1\$s' exists.

Cause	A file with that name already exists.
Action	Specify another file name.

7098: Duplicate tablespace '%1\$s' exists.

Cause	A tablespace with that name already exists.
Action	Specify another tablespace name.

7099: Duplicate partition name '%1\$s' exists.

Cause	A partition with that name already exists.
Action	Specify another partition name.

7100: Username '%1\$s' conflicts with another user or role name.

Cause	A role or user with that name already exists.
Action	Specify another username.

7101: Role name '%1\$s' conflicts with another user or role name.

Cause	A role or user with that name already exists.
Action	Specify another role name.

7102: Duplicate schema object '%1\$s.%2\$s' exists.

Cause	A schema object with that name already exists.
Action	Specify another object name.

7103: Column name '%1\$s' is already used in the table.

Cause	A column with that name already exists.
Action	Specify another column name.

7104: Constraint name '%1\$s' is already used or is duplicated in the SQL statement.

Cause	The specified constraint name is already being used.
Action	Specify another constraint name.

7105: Unable to rebuild the index of a temporary table.

Cause	An attempt was made to rebuild the index of the temporary table.
Action	It is impossible to rebuild the index of a temporary table.

7106: Size of next extent is out of range.

Cause	The specified size for the new extent is either too small or too large.
Action	Specify a valid size for the new extent.

7107: File size is out of range.

Cause	The specified file size is either too small or too large.
Action	Specify a valid file size.

7108: INITRANS value is out of range.

Cause	The value of INITRANS is either too small or too large.
Action	Specify an integer value between 1 and 255.

7109: PCTFREE value is out of range.

Cause	The value of PCTFREE is either too small or too large.
Action	Specify an integer value between 0 and 99.

7110: MAXDATAFILES value is out of range.

Cause	The value of MAXDATAFILES is either too small or too large.
Action	The number of MAXDATAFILES should be between 10 and 65533.

7111: MAXLOGGROUPS (MAXLOGFILES) must be between 2 and %1\$d (inclusive).

Cause	The value of MAXLOGGROUPS is invalid.
Action	Specify a new value for MAXLOGGROUPS.

7112: MAXLOGMEMBERS must be less than %1\$d.

Cause	The value of MAXLOGMEMBERS is invalid.
Action	Specify a new value for MAXLOGMEMBERS.

7113: Invalid next extent size or max extent size.

Cause	The next extent or max extent size is invalid.
Action	Specify a valid extent size.

7114: Specified CHARACTER SET is not supported.

Cause	Unsupported character set.
Action	Specify a supported character set.

7115: Log file size is out of range.

Cause	The specified log file size is either too small or too large.
Action	Specify a log file size between 512KB and 1GB.

7116: Invalid data type for default expression.

Cause	The data type of the default expression is invalid.
Action	Specify a valid expression data type.

7117: Unable to create segment in temporary tablespace.

Cause	A segment could not be created in a temporary tablespace.
Action	Specify a valid tablespace.

7118: Unable to create segment in undo tablespace.

Cause	A segment could not be created in an undo tablespace.
--------------	---

Action	Specify a valid tablespace.
---------------	-----------------------------

7119: Object does not fit into tablespace.

Cause	Permanent objects cannot be created in a temp DB. Temp objects cannot be created in a permanent DB.
Action	Recheck the object.

7120: Unable to define foreign key for temporary table.

Cause	Unable to define foreign key constraint for columns of a global temporary table.
Action	Unable to execute this command.

7121: This clause cannot be specified for the temporary table.

Cause	Tried to specify an invalid clause for the global temporary table.
Action	Unable to execute this command.

7122: Circular view detected.

Cause	The view referred to itself or the view reference object referred to the view.
Action	Delete the circular reference(s) from the view definition.

7123: Too many columns in the index.

Cause	There are more than 32 columns in the index.
Action	Reduce the number of columns in the index to 32 or less.

7124: Duplicate index exists.

Cause	The specified index already exists.
Action	Unable to execute this command.

7125: Maximum key length (%1\$u) exceeded.

Cause	The index key length exceeds the maximum length.
Action	Decrease the length of index key by reducing the number of columns in the index.

7126: Unable to alter or drop a LOB index.

Cause	An ALTER or DROP statement cannot be used in an LOB index.
Action	Unable to execute.

7127: Unable to drop the system tablespace.

Cause	System tablespaces cannot be dropped.
Action	Unable to execute this command.

7128: Unable to drop default temporary or undo tablespaces.

Cause	The default temporary or default undo tablespaces cannot be dropped.
Action	Unable to execute this command.

7129: Segments still exist in the specified tablespace.

Cause	Segments still exist in the tablespace to be dropped.
Action	Set the INCLUDING option, or drop the segment and retry.

7130: Unable to drop a user's default tablespace.

Cause	The tablespace to be dropped is the default tablespace for a user.
Action	Change the user's default tablespace with ALTER USER and retry.

7131: The user's default tablespace is invalid.

Cause	A tablespace for the user does not exist.
--------------	---

Action	Specify the default tablespace for ALTER USER.
---------------	--

7132: Unable to drop the (sub)partitions.

Cause	One of the partitions in the table belongs to another tablespace.
Action	Drop the partitioned table and retry.

7133: The sequence INCREMENT must be a non-zero value.

Cause	INCREMENT may not be 0.
Action	Specify a valid INCREMENT value.

7134: The next (start) value of the sequence is out of range.

Cause	The next or start value of the sequence must be between MINVALUE and MAXVALUE.
Action	Specify the MINVALUE and MAXVALUE.

7135: In descending sequences, the CYCLE option must be used with MINVALUE.

Cause	The CYCLE option must be used with MINVALUE.
Action	Specify a MINVALUE.

7136: In ascending sequences, the CYCLE option must be used with MAXVALUE.

Cause	The CYCLE option must be used with MAXVALUE.
Action	Specify a MAXVALUE.

7137: MINVALUE must be less than MAXVALUE.

Cause	MINVALUE must be less than MAXVALUE.
--------------	--------------------------------------

Action	Set MINVALUE to be smaller than MAXVALUE.
---------------	---

7138: Unable to drop the system user.

Cause	The system user cannot be dropped.
Action	Unable to execute this command.

7139: Cascade is required to remove this user from the system.

Cause	If objects owned by the user still exist, the user cannot be removed.
Action	Specify the cascade option, or drop the objects and try again.

7140: Specified object is not partitioned.

Cause	The requested object is not partitioned.
Action	Check whether the specified object is valid.

7141: Specified partition '%1\$s' does not exist.

Cause	The requested partition does not exist.
Action	Check whether the specified object is valid.

7142: Last partition cannot be dropped.

Cause	The last partition cannot be dropped.
Action	Unable to execute.

7143: Too many columns in a constraint.

Cause	There are more than 32 columns in the constraint.
Action	Reduce the number of columns in the constraint to 32 or less.

7144: Referenced key does not exist.

Cause	The constraint for that reference does not exist.
Action	Specify a valid constraint.

7145: Primary/unique is not specified for the table.

Cause	The constraint on the key is not specified.
Action	Specify a valid constraint.

7146: Specified column type cannot be a constraint.

Cause	The specified column cannot be used as a constraint.
Action	Specify a valid column.

7147: A table can have only one primary key.

Cause	A table may have only one primary key.
Action	Specify one primary key.

7148: Duplicate unique or primary key exists.

Cause	A unique or primary key with that name already exists.
Action	Delete the duplicate constraint.

7149: Duplicate referential key exists.

Cause	A reference key with that name already exists.
Action	Delete the duplicate constraint.

7150: Duplicate NOT NULL constraint exists.

Cause	A NOT NULL constraint with that name already exists.
--------------	--

Action	Delete the duplicate constraint.
---------------	----------------------------------

7151: Unable to use existing index as a constraint for a new object.

Cause	The existing index cannot be used as a constraint for a new object.
Action	Specify another index.

7152: Indexes are unnecessary for some constraints.

Cause	An index was specified for a constraint which does not require an index.
Action	Retry without specifying an index.

7153: Index already exists for another object.

Cause	The specified index already exists for another object.
Action	Specify another index.

7154: Column(s) of the specified index do not match that (those) of the new constraint.

Cause	Columns in the specified index do not match with those of the new constraint.
Action	Specify another index.

7155: Only NULL or NOT NULL constraints are available for MODIFY COLUMN statement.

Cause	For the MODIFY COLUMN statement, only NULL or NOT NULL can be specified.
Action	Unable to execute this command.

7156: Referenced by foreign keys.

Cause	Referred by other reference constraint.
--------------	---

Action	Specify the CASCADE CONSTRAINTS clause and retry.
---------------	---

7157: Specified column is already NULL.

Cause	The column is already specified as NULL.
Action	Unable to execute this command.

7158: Unable to set specified column to NULL.

Cause	The specified column cannot be NULL.
Action	Make sure that the column is not specified as containing primary keys.

7159: Number of local index partitions does not match the number of table partitions.

Cause	The specified number of local index partitions is different from the number of partitions in the table.
Action	Specify the valid number of partitions.

7160: Unable to create local partitioned index for non-partitioned table.

Cause	Unable to create a local partition index for a non-partitioned table.
Action	Unable to execute this command.

7161: Unable to validate (%1\$s.%2\$s): constraint violated.

Cause	The table has a row which violates one or more constraints.
Action	Modify the row or change the constraint state.

7162: Unable to activate (%1\$s.%2\$s): referenced key is not enabled.

Cause	The referenced key is disabled: therefore, the foreign key is not available.
Action	Enable the referenced key first.

7163: Specified partition values are incorrect.

Cause	The specified partition value is invalid.
Action	Specify a valid partition value.

7164: Indexes that are used as primary/unique key constraints cannot be dropped.

Cause	Indexes used as primary/unique key constraints cannot be dropped.
Action	Unable to execute this command.

7165: Unable to drop a user that is currently connected.

Cause	A connected user cannot be dropped.
Action	Disconnect the user and try again.

7166: Unable to grant privileges or roles to oneself.

Cause	Privileges and roles cannot be granted to oneself.
Action	Unable to execute this command.

7167: Roles cannot be granted to themselves.

Cause	Roles cannot be granted to themselves.
Action	Unable to execute this command.

7168: Unable to revoke privileges or roles from oneself.

Cause	Unable to revoke one's own privileges or roles.
Action	Unable to execute this command.

7169: Role has not been granted to the user.

Cause	Unable to revoke a role that has not been granted.
Action	Specify a role that has been granted and try again.

7170: Object privilege has not been granted to the user.

Cause	Unable to revoke an object privilege that has not been granted.
Action	Specify a privilege that has been granted and try again.

7171: System privilege has not been granted to user.

Cause	Unable to revoke a system privilege that has not been granted.
Action	Specify the granted system privilege and try again.

7172: Unable to revoke a privilege granted by another user.

Cause	Unable to revoke a privilege granted by another user.
Action	First receive the privilege to revoke and then revoke the user's privilege.

7173: Circular role grant detected.

Cause	Roles cannot be granted circularly.
Action	Delete the circular GRANT option.

7174: Unable to grant privileges to a role with GRANT option

Cause	Roles cannot be specified when using the GRANT option.
--------------	--

Action	Unable to execute this command.
---------------	---------------------------------

7175: There is no privilege to grant.

Cause	No privilege to grant.
Action	Specify a privilege to grant.

7176: The ADMIN option can only be specified for system privileges or roles.

Cause	The ADMIN option can be specified only for system privileges or roles.
Action	Use the GRANT option instead of the ADMIN option.

7177: The ADMIN option can only be specified for system privileges.

Cause	The ADMIN option can be specified only for system privileges.
Action	Use the GRANT option instead of the ADMIN option.

7178: Specified object privilege is invalid for this object.

Cause	The specified schema object privilege cannot be granted to the object.
Action	Check that a valid privilege or object is specified.

7179: Unable to activate a role '%1\$s' that has not been granted.

Cause	A role that has not been granted cannot be enabled.
Action	Specify a role that has been granted to you.

7180: Password specified for the role is incorrect.

Cause	Invalid password specified for the role.
--------------	--

Action	Specify a valid password.
---------------	---------------------------

7181: Password is necessary to enable the role.

Cause	The password is needed to enable roles.
Action	Enter the password.

7182: Package specification for the body was not found.

Cause	A package specification for the body was not found.
Action	Check whether or not the package specification exists.

7183: Package body is already defined.

Cause	The body is already defined for the package.
Action	Specify or replace and redefine.

7184: Circular dependency detected.

Cause	The object about to be created or updated is dependent on itself.
Action	Examine the dependencies and modify the source code.

7185: Unable to drop specified undo tablespace.

Cause	The specified undo tablespace cannot be dropped because it does not exist in <code>_CORRUPTEDCORRUPTED_ UNDO_TS</code> .
Action	Specify undo tablespace as <code>_CORRUPTED_UNDO_TS</code> parameter in init file.

7186: Unable to modify objects created by the system.

Cause	Objects made by the system cannot be modified.
Action	Unable to execute this command.

7187: Duplicate parameter name exists.

Cause	Parameter name is duplicated.
Action	Delete the duplicate name.

7188: Unable to rename objects inside other schema.

Cause	The name of an object belonging to another schema cannot be changed.
Action	Unable to execute this command.

7189: Unable to replace '%1\$s.%2\$s': object is of a different type.

Cause	Unable to replace an object with another of a different type.
Action	Unable to execute this command.

7190: Unable to ALTER/DROP '%1\$s.%2\$s': object is of a different type.

Cause	Unable to ALTER or DROP an object of a different type.
Action	Unable to execute this command.

7191: Unable to execute SET TRANSACTION: transaction has already started.

Cause	Transaction is already started. SET TRANSACTION cannot be executed.
Action	Unable to execute this command.

7192: Failed to load DDL file '%1\$s'.

Cause	Failed to load a DDL file.
Action	Make sure that the file exists.

7193: Invalid local transaction ID.

Cause	Invalid local transaction ID.
Action	Check that the specified local transaction ID is valid.

7194: Unable to (re-)create system datafile (file #0).

Cause	The first file of a system tablespace cannot be regenerated.
Action	Unable to execute this command.

7195: Update check constraint has \"OR\" node.

Cause	For example \"update A or B\" is invalid.
Action	Unable to execute this command.

7196: Invalid directory path. Please enter the absolute path.

Cause	Invalid directory path.
Action	Enter an absolute path.

7197: Invalid initialization parameter name '%1\$s'.

Cause	Invalid initialization parameter name.
Action	Recheck the parameter name.

7198: Unable to modify parameter '%1\$s' dynamically.

Cause	This initialization parameter cannot be modified dynamically.
Action	Restart the server or regenerate the database.

7199: Type mismatch for parameter '%1\$s': %2\$s required.

Cause	The type of initialization parameter required is different from the one defined in DDL.
--------------	---

Action	Recheck the parameter type.
---------------	-----------------------------

7200: Value of parameter '%1\$s' is invalid (condition check failed: '%2\$s').

Cause	This initialization parameter is out of range.
Action	Check the parameter range again.

7201: Parameter '%1\$s' cannot be modified by ALTER SESSION.

Cause	This initialization parameter cannot be adjusted by sessions.
Action	Use ALTER SYSTEM statements, instead of ALTER SESSION.

7202: Too many partition key columns are specified.

Cause	The number of columns used in a constraint exceeds 32.
Action	Specify a number of columns less than 32.

7203: File '%1\$s' does not exist or is not accessible.

Cause	File does not exist or is not accessible.
Action	Check file name and permissions.

7204: Requested session does not exist. Session id: %1\$d

Cause	The session does not exist.
Action	Check the session id.

7205: %1\$s.

Cause	Performs dump.
Action	Normal action.

7206: Specified column is already NOT NULL.

Cause	The specified column is already specified as NOT NULL.
Action	Unable to execute this command.

7207: New identifier required: '%1\$s' is a reserved word.

Cause	Reserved words cannot be used as identifiers.
Action	Use another name.

7208: Partition value is too long.

Cause	The length of partition bound value is longer than that of the corresponding partitioning key column.
Action	Ensure that lengths of partition bound values do not exceed those of corresponding partitioning columns.

7209: Duplicate clause exists (type %1\$s, previously at line %2\$d, column %3\$d).

Cause	Duplicate clause was found.
Action	Use only one instance of a clause.

7210: Internal SQL execution failed (%1\$s).

Cause	Failed to execute an SQL statement used internally in DDL.
Action	Contact the technical support team.

7212: Unable to create permanent object in a temporary tablespace or temporary object in a permanent tablespace.

Cause	The object about to be created does not match the tablespace type.
Action	Recheck the statement.

7213: Number of log groups or log files exceeds MAXLOGGROUPS or MAXLOGFILES.

Cause	The number of defined log groups or log files is larger than MAXLOGGROUPS or MAXLOGFILES.
Action	Decrease the number of log group or file definitions, or increase the value of MAXLOG GROUPS or MAXLOGFILES.

7214: Number of log members exceeds MAXLOGMEMBERS.

Cause	The number of defined log members is larger than MAXLOGMEMBERS.
Action	Decrease the number of log members or increase the value of MAXLOGMEMBERS.

7215: Too many partitions are specified.

Cause	The number of defined partitions exceeds 10,000.
Action	Reduce the number of partitions to less than 10,000.

7216: MAXSIZE is less than the specified (default) file size.

Cause	The value of MAXSIZE is smaller than the size of the file.
Action	Increase the value of MAXSIZE and the file size.

7217: Unable to disable constraint (%1\$s.%2\$s). Dependencies exist.

Cause	There are constraints that reference the specified constraint.
Action	Disable or drop the constraints that reference the specified constraint.

7218: Unable to drop active undo tablespace.

Cause	In the undo tablespace, active transactions exist or undo retention has not yet finished.
Action	Retry after active transactions and undo retention are finished.

7219: RemoteDB name is too long (maximum of %1\$d characters).

Cause	RemoteDB name is too long.
Action	Use a shorter RemoteDB name.

7220: Host name is too long (maximum of %1\$d characters).

Cause	Host name is too long.
Action	Use a shorter host name.

7221: Duplicate RemoteDB name '%1\$s' exists.

Cause	The specified RemoteDB name is already being used.
Action	Specify a different RemoteDB name.

7222: Specified RemoteDB '%1\$s' does not exist or is an invalid type.

Cause	The specified RemoteDB does not exist or is an invalid type.
Action	Provide a valid RemoteDB name.

7223: DDL operations are not allowed on a remote database.

Cause	DDL cannot be executed in the remote database.
Action	Unable to execute this command.

7224: Specified table '%1\$s' is of a different partition type.

Cause	The partition type of the given table does not match the input statement type.
Action	Correct the partition type and retry.

7225: Global partition index must be prefixed by the partition key column.

Cause	Partition key column of global partition index should come first before index key column.
Action	Adjust the order of index key columns or partition key columns.

7226: Specified subpartition name '%1\$s_%2\$s' is too long (maximum of %3\$d characters).

Cause	The specified subpartition name is too long.
Action	Use a shorter partition or subpartition name.

7227: Default partition must be the last partition specified.

Cause	A partition other than the last one (or no partition) was set as the default.
Action	Set the last partition as the default.

7228: DEFAULT cannot be specified with other values.

Cause	DEFAULT cannot be used with the values of other partitions.
Action	Delete the values of other partitions from the default partition.

7229: Duplicate partition '%1\$s' exists.

Cause	The partition value is duplicated.
Action	Delete the duplicate partition value.

7230: List partitioning allows only a single partitioning key column.

Cause	For list partitioning, only one partitioning column can be specified.
Action	Specify one partitioning column.

7231: Unable to use this clause for an external table.

Cause	Invalid clause is specified for an external table.
Action	Unable to execute this command.

7232: Duplicate option was specified.

Cause	Duplicate option was specified.
Action	Delete the duplicate option and retry.

7233: Unable to drop columns of a SYS-owned table.

Cause	Tables owned by SYS cannot execute DROP COLUMN.
Action	Unable to execute this command.

7234: Unable to drop partitioning key column '%1\$s'.

Cause	An attempt was made to delete a column that is used as a partitioning key.
Action	Unable to execute this command.

7235: Unable to drop all columns within a table.

Cause	An attempt was made to delete all columns in the table.
Action	Unable to execute this command.

7236: Reference key column '%1\$s' cannot be dropped.

Cause	An attempt was made to drop the reference key column.
Action	Remove the constraint first, or use CASCADE CONSTRAINTS.

7237: Specified column '%1\$s' cannot be modified.

Cause	The column cannot be modified.
--------------	--------------------------------

Action	LOB, LONG, or partitioning key columns cannot be modified. Delete them or add new columns.
---------------	--

7238: Specified column '%1\$s'.'%2\$s' must be empty to decrease precision or scale.

Cause	To decrease column's precision or scale, columns of the all existing rows should be NULL.
Action	Set column to NULL.

7239: Referencing or referenced key column '%1\$s' cannot be modified.

Cause	An attempt was made to modify a referencing or referenced key column.
Action	Remove the constraint first and try again.

7240: Tables with LONG-type columns cannot be partitioned.

Cause	An attempt was made to partition tables with LONG-type columns.
Action	Unable to execute this command.

7241: Partitioning column cannot be of type BLOB, CLOB, or ROWID.

Cause	An attempt was made to use BLOB, CLOB or ROWID-type columns as partitioning columns.
Action	Unable to execute this command.

7242: New partitions cannot be added if a DEFAULT partition exists.

Cause	A new partition cannot be added because one of the partition values is DEFAULT.
Action	Unable to execute this command.

7243: Unable to resolve data type of column '%1\$s'.

Cause	Invalid data type is included in the column.
Action	Unable to execute this command.

7244: Operation not supported on external tables.

Cause	The statement is not supported on external tables.
Action	Unable to execute this command.

7245: Duplicate username '%1\$s' exists.

Cause	Duplicate username exists.
Action	Delete the duplicate user.

7246: BY ACCESS/SESSION clause not allowed for NOAUDIT clauses.

Cause	BY ACCESS/SESSION clauses cannot be used for NOAUDIT clauses.
Action	Delete the BY ACCESS/SESSION clause.

7247: Unable to drop the LOB column.

Cause	An LOB-type column also exists in a table that belongs to another tablespace.
Action	Delete the LOB-type column or table first and then retry.

7248: Unable to drop the LOB (sub)partitions.

Cause	An LOB partition also exists in a table that belongs to another tablespace.
Action	Delete the LOB-type column or table first and then retry.

7249: Index '%1\$s' is being built or rebuilt.

Cause	The index is being built or rebuilt.
Action	Wait until the online build is completed.

7250: Table is not partitioned by RANGE or LIST method.

Cause	An attempt was made to remove a partition of a table partitioned in a way other than RANGE or LIST partitioning.
Action	Unable to execute this command.

7251: Unable to perform this task on a disabled index.

Cause	An attempt was made to perform this task on a disabled index.
Action	Unable to execute this command.

7252: Unable to execute a savepoint while performing a PDML transaction.

Cause	An attempt was made to execute a savepoint while performing a PDML transaction.
Action	Perform the PDML transaction after committing or rolling back.

7253: Table is not partitioned by RANGE, HASH, or LIST methods.

Cause	A table which is not partitioned by RANGE, HASH or LIST methods cannot be moved.
Action	Unable to execute this command.

7254: ON COMMIT attribute is incompatible with START WITH or NEXT options.

Cause	An ON COMMIT statement is not compatible with START WITH or NEXT options.
Action	Delete the ON COMMIT statement, or remove the START WITH or NEXT option.

7255: START WITH or NEXT should be followed by a date value.

Cause	A date value should come after a START WITH or NEXT option.
Action	Specify a date value after START WITH or NEXT option.

7256: Unable to use AUDIT or NODAUDIT on SYS user operations.

Cause	An attempt was made to execute AUDIT or NODAUDIT on user SYS.
Action	Unable to execute this command.

7257: Invalid encryption algorithm.

Cause	Invalid encryption algorithm name.
Action	Specify a value encryption algorithm name.

7258: Encryption specification does not match.

Cause	Invalid encryption algorithm or password.
Action	Check the encryption algorithm or password again.

7259: Unable to encrypt columns of that type.

Cause	Unable to encrypt data columns of that type.
Action	Unable to execute this command.

7260: Specified object is not encrypted.

Cause	The requested object is not encrypted.
Action	Verify that this is correct.

7261: Unable to drop container table of materialized view.

Cause	The table is used as a container table of materialized view.
--------------	--

Action	Remove the materialized view first.
---------------	-------------------------------------

7262: PCTTHRESHOLD is out of range.

Cause	The specified PCTTHRESHOLD is either too large or too small.
Action	Specify a valid PCTTHRESHOLD value.

7263: Primary key constraint was not found.

Cause	A primary key is necessary.
Action	Specify a primary key.

7264: Composite partitioning is not supported for index-organized tables.

Cause	Composite partitioning is not supported.
Action	Use another partitioning method.

7265: Unable to drop or disable the primary key constraint for index-organized tables.

Cause	A primary key for an index-organized table must exist at all times.
Action	Unable to execute this command.

7266: WHEN clauses may not be used in INSTEAD OF triggers.

Cause	A WHEN clause cannot be used in INSTEAD OF triggers.
Action	Delete the WHEN clause when creating an INSTEAD OF trigger.

7267: INSTEAD OF triggers may not be created on tables.

Cause	Cannot create INSTEAD OF triggers on tables.
--------------	--

Action	Unable to execute this command.
---------------	---------------------------------

7268: INSTEAD OF triggers may not be created on a read-only view.

Cause	Cannot create INSTEAD OF triggers on a read-only view.
Action	Unable to execute this command.

7269: Column lists are not valid for this trigger type.

Cause	Cannot specify a column list for the trigger.
Action	Delete the column list.

7270: Table or view '%1\$s.%2\$s' was not found.

Cause	A table or view with the specified name could not be found.
Action	Verify the table or view name.

7271: A view is not allowed for this clause.

Cause	A view cannot be used for the specified clause.
Action	Unable to execute.

7272: This clause may not be used for a HASH partition.

Cause	The clause cannot be used for a hash partition.
Action	Delete the clause.

7273: Unable to convert specified value '%1\$s' of the column.

Cause	The specified value does not match the column type.
Action	Specify a value that matches the column.

7274: Specified value '%1\$s' is too large for the column.

Cause	The specified value is too long.
Action	Specify a value that matches the length of the column.

7275: This clause is only available for TAC.

Cause	The clause is only available for TAC, and cannot be used for a single instance.
Action	Remove the clause.

7276: Subpartition descriptions cannot be specified.

Cause	Cannot specify subpartition definitions.
Action	Delete the description.

7277: This command cannot be used for a composite partitioned index.

Cause	Cannot be executed for a composite partitioned index.
Action	Unable to execute this command.

7278: Numbers of columns do not match.

Cause	The numbers of columns in the tables do not match.
Action	Unable to execute this command.

7279: Column datatypes do not match.

Cause	The types of columns in the tables do not match.
Action	Unable to execute this command.

7280: Index key columns do not match.

Cause	Index key columns in the tables do not match.
Action	Unable to execute this command.

7281: Allowed only for a local partitioned index.

Cause	Can be executed only for a local partitioned index.
Action	Unable to execute this command.

7282: Index types do not match.

Cause	Index types and attributes do not match.
Action	Unable to execute this command.

7283: Success with compilation errors.

Cause	The object is not available due to compiler error(s) that occurred during its creation.
Action	Check and correct the compiler error(s).

7284: Specified object '%1\$s.%2\$s!' was not dropped.

Cause	The specified object was not removed.
Action	Unable to execute this command.

7285: Not allowed in clustered database mode.

Cause	Not supported in TAC mode.
Action	Retry this command in single instance mode.

7286: Encrypted column '%1\$s!' is not allowed.

Cause	Unable to use an encrypted column.
--------------	------------------------------------

Action	Unable to execute this command.
---------------	---------------------------------

7287: Some rows in the table are invalid for the specified partition.

Cause	Some rows cannot be inserted in the specified partition.
Action	Remove the invalid rows and try again.

7288: Unable to encrypt index key column(s) with SALT.

Cause	An attempt was made to encrypt index key columns with the SALT option.
Action	The SALT option cannot be used to encrypt index key columns.

7289: R-tree index allows only one index key column.

Cause	An attempt was made to specify two or more key columns for an R-tree index.
Action	Specify only one key column for an R-tree index.

7290: R-tree index cannot be partitioned.

Cause	An attempt was made to partition an R-tree index.
Action	An R-tree index cannot be partitioned.

7291: R-tree index can be created only on a column of GEOMETRY type.

Cause	The R-tree index key column is not of GEOMETRY type.
Action	An R-tree index key column must be of GEOMETRY type.

7292: Table '%1\$s' does not contain a primary key constraint.

Cause	The WITH PRIMARY KEY was specified but the table did not contain a primary key constraint or the constraint was disabled.
--------------	---

Action	Specify the WITH ROWID option only and try again. Create a primary key constraint in the table.
---------------	---

7293: Invalid filter column detected.

Cause	No filter column exists, or the filter column is a primary key.
Action	Check if all filter columns exist, and ensure that the primary key column is not in a filter column.

7294: There is no materialized view log on table '%1\$s'.'%2\$s'.

Cause	There is no materialized view log on the table.
Action	Check the table name or create a materialized view log on the table.

7295: Table '%1\$s' does not contain a primary key constraint.

Cause	The table does not have a primary key constraint.
Action	Create a primary key constraint and try again.

7296: Materialized view does not include all primary key columns.

Cause	A primary key column does not exist in the SELECT statement.
Action	Specify a primary key column in the SELECT or FAST statement.

7297: Prebuilt table '%1\$s'.'%2\$s' does not exist.

Cause	The specified prebuilt table does not exist.
Action	Try again with the BUILD IMMEDIATE and BUILD DEFERRED options.

7298: Materialized view cannot use a prebuilt table.

Cause	An attempt was made to use a prebuilt table.
Action	Try again with the BUILD IMMEDIATE and BUILD DEFERRED options.

7299: Table \"%1\$s\".\"%2\$s\" is currently being redefined.

Cause	The table is currently being online redefined.
Action	Wait until the online redefinition is finished.

7300: Table \"%1\$s\".\"%2\$s\" is currently not being redefined.

Cause	The table is not being online redefined.
Action	Unable to execute this command.

7301: Column \"%1\$s\" is not encrypted.

Cause	The column is not encrypted.
Action	Unable to execute this command.

7302: Column \"%1\$s\" is already encrypted.

Cause	The column is already encrypted.
Action	Unable to execute this command.

7303: Referenced or referencing foreign key constraint column cannot be encrypted.

Cause	An attempt was made to encrypt a referenced or referencing column in a foreign key constraint.
Action	Referenced or referencing columns in foreign key constraints cannot be encrypted.

7304: DOMAIN index allows only one index key column.

Cause	An attempt was made to specify more than one DOMAIN index key column.
Action	Specify only one DOMAIN index key column.

7305: DOMAIN index cannot be partitioned.

Cause	An attempt was made to partition a DOMAIN index.
Action	Unable to partition the DOMAIN index.

7306: XML index can be created only on a column of XMLTYPE type.

Cause	XML index key column is not of XMLTYPE type.
Action	XML index key column must be of XMLTYPE type.

7307: XML index cannot be created in a partitioned table.

Cause	An attempt was made to create an XML index in a partitioned table.
Action	Unable to create an XML index in a partitioned table.

7308: Function-based index cannot be created in an encrypted column (\'"%1\$s\").

Cause	An attempt was made to create a function-based index in an encrypted column.
Action	Unable to create a function-based index in an encrypted column.

7309: Prebuilt table dimensions do not match the definition query.

Cause	The query that defined a materialized view does not match the prebuilt table.
Action	Ensure the prebuilt table matches the query or modify the query using BUILD IMMEDIATE and BUILD DEFERRED and try again.

7310: A non-cacheable expression is not valid for query rewrite.

Cause	An attempt was made to use a non-cacheable expression for the query rewrite function.
Action	Unable to use a non-cacheable expression for the query rewrite function.

7311: Operation is unnecessary.

Cause	The command does not need to be executed.
Action	Do not execute the command.

7312: Original name being used.

Cause	The original name is currently being used by another object.
Action	Use RENAME clause.

7313: Specified undo tablespace name '%1\$s' does not match parameter undo tablespace name in tip file '%2\$s'.

Cause	The specified undo tablespace name '%1\$s' does not match parameter undo tablespace name in tip file '%2\$s'.
Action	Match the two names.

7314: Partitioning columns must be contained in index key columns.

Cause	Partitioning columns must be contained in index key columns.
Action	Use non-unique index or ensure the index key columns include partitioning columns.

7315: Table '%1\$s'. '%2\$s' does not have a materialized view log.

Cause	Fast refresh is unavailable because the master table does not have a materialized view log.
Action	Create a master table materialized view log.

7316: Materialized view log for \"%1\$s\".\"%2\$s\" does not record the primary key.

Cause	Fast refresh is unavailable because the materialized view log does not have a primary key.
Action	Create a materialized view log with a primary key.

7317: Unable to use rowid column from materialized view log on \"%1\$s\".\"%2\$s\"

Cause	The materialized view log does not have a rowid column.
Action	Create a materialized view log with rowid.

7318: Unable to create a fast refresh materialized view from a complex query.

Cause	ROWIDs and primary key constraints are not supported for complex queries.
Action	Use the 'REFRESH FORCE' or the 'REFRESH COMPLETE' option and try again.

7319: Materialized view log on \"%1\$s\".\"%2\$s\" does not have new values.

Cause	The materialized view log has no new values information.
Action	Create a materialized view log containing new values.

7320: Unable to use filter columns of the materialized view log on \"%1\$s\".\"%2\$s\"

Cause	The materialized view log is not recording necessary filter columns.
Action	Add filter columns to the materialized view log.

7321: Schema object '%1\$s.%2\$s.%3\$s' does not exist or is of incompatible type.

Cause	The specified object does not exist or is of incompatible type.
Action	Specify the name of valid object.

7322: Materialized view log already exist on table '%1\$s'.

Cause	A materialized view log already exists on the table.
Action	Use 'alter materialized view log'.

7323: Materialized view log on '%1\$s'. '%2\$s' already has primary keys.

Cause	The materialized view log already has primary keys.
Action	The materialized view log does not need more primary keys.

7324: Materialized view log on '%1\$s'. '%2\$s' already has a rowid.

Cause	The materialized view log already has a rowid.
Action	The materialized view log does not need another rowid.

7325: Materialized view log on '%1\$s'. '%2\$s' already has a sequence.

Cause	The materialized view log already has a sequence.
Action	The materialized view log does not need another sequence.

7326: Materialized view log on \"%1\$s\".\"%2\$s\" already has new values.

Cause	The materialized view log already has new values.
Action	The materialized view log does not need more new values.

7327: Materialized view \"%1\$s\".\"%2\$s\" is INVALID and needs a complete refresh.

Cause	The materialized view is currently invalid.
Action	Perform a complete refresh of the materialized view.

7328: Materialized view '%1\$s'.'%2\$s' does not exist.

Cause	The materialized view does not exist.
Action	Check the materialized view.

7329: Unable to explicitly refresh a NEVER REFRESH materialized view (\"%1\$s\")

Cause	An attempt was made to explicitly refresh a NEVER REFRESH materialized view (\"%1\$s\")
Action	The materialized view cannot be refreshed.

7330: Materialized view log on \"%1\$s\".\"%2\$s\" younger than last refresh

Cause	The materialized view log is younger than the last refresh.
Action	Perform a complete refresh.

7331: CTXCAT index allows only char/varchar type key columns.

Cause	An attempt was made to specify an invalid type key column.
--------------	--

Action	Specify only char/varchar type key columns.
---------------	---

7332: Specified parameter value is invalid.

Cause	An attempt was made to specify an invalid parameter value.
Action	Check the parameter value.

7333: Unable to alter or drop a domain indexed column.

Cause	An ALTER or DROP statement cannot be used in the domain indexed column.
Action	Unable to execute.

7334: Domain index is invalid.

Cause	Domain index is invalid.
Action	Unable to execute.

7335: Partitioning columns must form a subset of key columns of a UNIQUE index.

Cause	Partition key column of local partition index should be a subset of index key column.
Action	Unable to execute.

7336: Cannot perform a fast refresh of the materialized view \'"%1\$s\'.\'"%2\$s\'

Cause	ROWIDs of certain tables were missing in the definition.
Action	Specify the FORCE or COMPLETE option.

7337: Fast refresh of \"%1\$s\".\"%2\$s\" is unsupported after deletion/update.

Cause	This materialized view does not support the fast refresh after deletion or updates.
Action	Use the complete refresh.

7338: Cannot set the ON COMMIT refresh attribute for the materialized view.

Cause	Conditions for refresh at commit time were not satisfied.
Action	Specify valid options.

7339: Cannot replace the trigger. The trigger is already on other table \"%1\$s.%2\$s\".

Cause	Cannot replace a trigger that exists on a different table than the one currently being replaced.
Action	Drop and create a trigger instead of replacing it.

7340: Sequence cache size must be less than one cycle.

Cause	Sequence cache size is larger than one cycle.
Action	Increase the cycle, or decrease the cache size.

7341: Unable to resolve the index key column expression \"%1\$s\".

Cause	An expression that cannot be resolved is included in the index key column.
Action	Unable to execute the command.

7342: Unable to resolve the check condition \"%1\$s\".

Cause	An expression that cannot be resolved is included in the check condition.
--------------	---

Action	Unable to execute the command.
---------------	--------------------------------

7343: Up to %1\$d error codes can be specified to dump the call stack.

Cause	Too many error codes are specified.
Action	Decrease the number of error codes.

7344: Too many primary key columns specified in the Index-Organized Table.

Cause	The number of primary keys specified in the Index-Organized Table is between 1 and 32.
Action	Specify 32 or less primary keys in Index-Organized Table.

7345: The PCTTHRESHOLD value (%1\$d) is incorrectly specified.

Cause	The specified PCTTHRESHOLD is incorrect.
Action	Specify PCTTHRESHOLD between 1 and 50.

7346: Index-Organized Table cannot include a LONG type column.

Cause	Index-Organized Table cannot include a LONG type column.
Action	Delete the LONG type column.

7347: The INCLUDING column (%1\$s) is incorrectly specified.

Cause	The INCLUDING column must be specified as the last column of a primary key or a non-primary key column.
Action	Specify the INCLUDING column according to the conditions.

7348: An OVERFLOW segment is not specified.

Cause	An OVERFLOW segment must be specified when INCLUDING is specified or the number of column exceeds 255.
Action	Specify an OVERFLOW segment.

7349: The primary key column is not located before other columns.

Cause	When creating an IOT, the primary key column must be described before other columns.
Action	Describe the primary key column before other columns in the IOT create DDL statement.

7350: This DDL statement is not permitted in the massive cluster system.

Cause	In the massive cluster system, this DDL cannot be executed.
Action	Unable to execute.

7351: DDL to be executed in a slave node failed.

Cause	A slave node is not operating.
Action	Unknown cause of error.

7352: The specified event conditional clause ('%1\$s') is incorrect.

Cause	The specified event conditional clause is incorrect.
Action	Check the conditional clause of the event to be handled.

7353: The profile '%1\$s' was not found or is invalid.

Cause	The specified profile was not found or is an invalid type.
Action	Specify a valid profile name.

7354: Cannot drop the profile '%1\$s'.

Cause	There is a user who uses the profile.
Action	Try again using the CASCADE option.

7355: Cannot drop the specified temporary tablespace.

Cause	The specified temporary tablespace cannot be dropped because it is in use.
Action	Wait until the temporary tablespace is inactive.

7356: Unable to rename the system tablespace.

Cause	System tablespaces cannot be renamed.
Action	Unable to execute this command.

7357: The initialization parameter value, '%1\$s', is not an absolute path.

Cause	The value of the initialization parameter is not an absolute path.
Action	Ensure the value of the initialization parameter is an absolute path.

7358: A log group that does not exist cannot be dropped.

Cause	The specified log group does not exist.
Action	Check the log group.

7359: The supplemental logging, '%1\$s', does not exist thus cannot be deleted.

Cause	The supplemental logging attribute does not exist.
Action	Check the supplemental logging attribute.

7360: The supplemental logging attribute, '%1\$s', already exists.

Cause	The supplemental logging attribute already exists.
Action	Check the supplemental logging attribute.

7361: Integer value required.

Cause	The input value must be an integer.
Action	Use an integer value expression as the input.

7362: This DDL statement is not allowed on a bitmap indexed table.

Cause	The table must not have any bitmap indexes.
Action	Ensure bitmap indexes do not exist on this table.

7363: The resource limit, '%1\$s', is invalid.

Cause	The appropriate resource limit should be provided.
Action	Ensure the resource limit is valid.

7364: Partitioning is not supported for index-organized tables.

Cause	Partitioned IOT is not supported.
Action	Unable to execute this command.

7365: The unique index needs hash data sharding in the massive cluster system.

Cause	In the massive cluster system, this DDL cannot be executed.
Action	Unable to execute. The table needs a hash data sharding property.

7366: It is impossible to delete or modify the type due to a dependency.

Cause	The type has a dependency on another type or table.
Action	Delete the types or tables between which a dependency is set, or use the force option to drop the type or table which has a dependency.

7367: BUCKET option is not permitted on non-hash data sharding.

Cause	BUCKET option is not permitted on non-hash data sharding.
Action	Unable to execute. The table needs a hash data sharding property.

7368: Specified bucket not found: %1\$d.

Cause	Specified bucket number is not correct.
Action	Check bucket number by _DD_TABLET_MEMBER.

7369: Cannot delete the last bucket of hash data sharding.

Cause	Specified bucket is the last bucket tablet.
Action	Add a new bucket and create a new last bucket tablet. Delete the 2nd to last bucket.

7370: Cannot create the diskpace.

Cause	Creating the diskpace failed due to an unknown reason.
Action	Check the logs.

7371: The diskpace name already exists.

Cause	A diskpace with the same name already exists.
Action	Check the diskpace name.

7372: The disk is already in use.

Cause	Another disk space is already using the disk.
Action	Check the path to the disk.

7373: The disk has been assigned already.

Cause	The disk has been assigned already.
Action	Check the path to the disk.

7374: Cannot create a new disk space.

Cause	The number of disk space is full.
Action	Check the number of available disk space.

7375: DISK OPEN failed.

Cause	Failed to open the disk.
Action	Check the logs.

7376: DISK READ failed.

Cause	Failed to read from the disk.
Action	Check the logs.

7377: DISK WRITE failed.

Cause	Failed to write to the disk.
Action	Check the logs.

7378: The device type is invalid.

Cause	Only file, raw device, or symbolic link can be used as device type.
--------------	---

Action	Check the device type.
---------------	------------------------

7379: The disk size is invalid.

Cause	The specified disk size is too big or invalid.
Action	Check the disk size.

7380: The file size is invalid.

Cause	The specified file size is too large or invalid.
Action	Compare the file size to the number and size of disks.

7381: The sector size is invalid.

Cause	The specified sector size does not match the device sector size.
Action	Check the device sector size.

7382: Cannot find the path to the disk.

Cause	The DISK_PATH is not set in the configuration file or the DISK_PATH value is invalid.
Action	Check the DISK_PATH setting in the configuration file.

7383: The shared memory space in the system is insufficient.

Cause	The diskspace information cannot be created due to a lack of shared memory space in the system.
Action	Increase the shared memory space in the system.

7384: The specified number of disks exceeds the maximum number allowed.

Cause	The maximum number of disks allowed for a disk space is 65535.
--------------	--

Action	Check the number of disks required for the DDL statement.
---------------	---

7385: Specified group not found: %1\$s.

Cause	Specified group name is not correct.
Action	Check group name by horde configuration.

7386: Table is not a global table.

Cause	Table is a local table which is created when TMC_LOCAL_SESS=N.
Action	Use another name or drop the table in local session.

7387: Table is not a local table.

Cause	Table is a global table which is created when TMC_LOCAL_SESS=Y.
Action	Use another name or drop the table in global session.

7388: Specified group not match the original group.

Cause	Cannot move to another group.
Action	Check group name or use FORCE keyword.

7389: Specified group has no node member.

Cause	Specified group name is not correct or group is empty.
Action	Check group name or group configuration.

7390: Specified tablet number not found.

Cause	Specified tablet number is not correct.
Action	Check tablet number by _dd_tablet_member.

7391: Index-organized tables are not supported in TMC.

Cause	Index-organized tables are not supported.
Action	Use supported sharding methods.

7392: Delete cascade feature is not supported in TMC.

Cause	Delete cascade feature is not supported.
Action	Do not use the delete cascade feature in TMC.

7393: Bucket number should be specified.

Cause	Bucket number should be specified on hash shading.
Action	Specify a bucket number from _DD_TABLET_MEMBER.

7394: Specified node number not found: %1\$d.

Cause	Specified node number is not correct.
Action	Check node number by horde (show TMC).

7395: This DDL statement is only permitted in the massive cluster system.

Cause	In the single system, this DDL cannot be executed.
Action	Unable to execute.

7396: Delete set null feature is not supported in TMC.

Cause	Delete set null feature is not supported.
Action	Do not use the delete set null feature in TMC.

7397: Primary index on an IOT cannot be rebuilt.

Cause	Primary index on an IOT cannot be rebuilt.
Action	Use Alter table MOVE to reorganize the IOT.

7398: DDL alter system recompile was interrupted by other DDLs.

Cause	Try again.
Action	Try again.

7399: A partitioning key for an index-organized table must consist of one or more columns of a primary key.

Cause	One or more columns which are not included in a primary key were used for a partitioning key.
Action	Use a different partitioning key.

7400: Primary key constraints cannot be dropped, disabled, or deferred for index-organized tables.

Cause	An attempt was made to drop, disable, or defer a primary key constraint for an index-organized table.
Action	Do not drop, disable, or defer the primary key of index-organized tables.

7401: Invalid index option for an index-organized table.

Cause	An attempt was made to specify the REVERSE option for an index-organized table.
Action	Do not use the REVERSE option with index-organized tables.

7402: Invalid redefinition method: %1\$s.

Cause	An attempt was made to specify an invalid redefinition method.
--------------	--

Action	OPTIONS_FLAG must be DBMS_REDEFINITION.CONST_USE_PK (1) or DBMS_REDEFINITION.CONST_USE_ROWID (2).
---------------	---

7403: Serial number of the target session is invalid. Serial#: %1\$u

Cause	A valid serial number must be provided to apply a SESSION KILL request to a session.
Action	Check the session serial number.

7404: Status of the target session is not ACTIVE or RUNNING. Status: %1\$d

Cause	SESSION KILL request can be only applied to a ACTIVE or RUNNING session.
Action	Check the session status.

7405: Unable to modify the primary key column value of an index-organized table.

Cause	Unable to modify the primary key column value of an index-organized table.
Action	Modify the column using the DBMS.REDEFINITION package.

7406: Unable to drop the primary key column of an index-organized table.

Cause	Unable to drop the primary key column of an index-organized table.
Action	Do not drop the primary key column of an index-organized table.

7407: Unable to execute this command while using Text-TIP.

Cause	Current database uses Text-TIP.
Action	Restart the server using btip.

7408: BTIP file open error: file is not found.

Cause	Verify the file name is valid.
Action	Verify the file name is valid.

7409: The BTIP extension name input is invalid.

Cause	Verify the BTIP file name.
Action	Verify the BTIP file name.

7410: The TIP extension name input is invalid.

Cause	Verify the TIP file name.
Action	Verify the TIP file name.

7411: A file with the same name already exists.

Cause	The specified file already exists.
Action	Unable to execute this command.

7412: Failed to create the file.

Cause	Ensure the file path and permissions are correct.
Action	For more information, check the errno in tracelog.

7413: Unable to decrease the column length because the column data will not fit in the new column length.

Cause	Unable to decrease the column length because the column data will not fit in the new column length.
Action	Use a larger column length.

7414: The data type conversion attempted is invalid.

Cause	There was an attempt to change the column type to an LOB type.
Action	Create a new column using an appropriate type and copy the data from the current column to the new column.

7415: A read-only table cannot be truncated.

Cause	An attempt was made to truncate a read-only table.
Action	Read-only tables cannot be truncated.

7416: Cannot alter the SYS account into a LOCK status.

Cause	There has been an attempt to change the SYS account into a LOCK status.
Action	Cannot execute the DDL statement.

7417: Error occurred while trying to refresh the materialized view \"%1\$s\".\"%2\$s\".

Cause	An unexpected error occurred due to an unknown reason while trying to refresh the materialized view (ec=%3\$d).
Action	Check other error messages saved in the error stack.

7418: Auto increment is allowed only on one column in a table

Cause	More than one auto increment exists in the table.
Action	Specify only one auto increment column in the table.

7419: Cannot recompile \"%1\$s(%2\$s)\" while executing a parallel query.

Cause	Cannot recompile a PSM object while executing a parallel query.
Action	Serially execute the query, or retry after recompiling the invalid OBJ.

7420: The tablespace that the table belongs to is already encrypted.

Cause	Cannot perform the encryption operation for the encrypted tablespaces.
Action	Cannot perform the command.

7421: Cannot rename a materialized view.

Cause	Cannot rename a materialized view or its base table.
Action	Cannot execute the command.

7422: An index cannot be created from column of type ROWID.

Cause	An index cannot be made of ROWID type column.
Action	Unable to execute.

7423: Another session is using the temporary table, so this DDL operation cannot be performed.

Cause	This DDL statement can only be used when the temporary table is not being used by any other session.
Action	Check the session information for details about the session that is using the temporary table.

7424: INCREMENT must be less than MAXVALUE minus MINVALUE.

Cause	INCREMENT must be less than MAXVALUE minus MINVALUE.
Action	Unable to execute.

7425: IOT cannot be compressed.

Cause	The function has yet been implemented.
Action	The command cannot be run.

7426: This clause cannot be specified for the virtual table.

Cause	Tried to specify an invalid clause for the virtual table.
Action	Unable to execute this command.

7427: Specified tablespace '%1\$s' cannot be used as a user's temporary tablespace.

Cause	The specified tablespace cannot be used for a temporary tablespace.
Action	Specify a different tablespace name.

7428: Status of the target session is not ASSIGNED and status of thread is not THR_STAT_WAITING

Cause	SESSION CLEAN request can be only applied to a ASSIGNED session.
Action	Check the session status.

7429: When creating global range partitioned index, the partition whose partitioning key columns' values are all MAXVALUE should be specified.

Cause	When creating global range partitioned index, the values of the partitioning key columns of the last partition must all be MAXVALUE.
Action	Please check the value of the partitioning key columns.

7430: The specified value must be a positive integer greater than or equal to MINEXTENTS.

Cause	The specified value must be a positive integer greater than or equal to MINEXTENTS.
Action	Specify an appropriate value.

7431: The specified value must be a positive integer less than or equal to MAXEXTENTS.

Cause	The specified value must be a positive integer less than or equal to MAXEXTENTS.
Action	Specify an appropriate value.

7432: The memory space in the system is insufficient.

Cause	ERROR : malloc failed due to a lack of memory space in the system.
Action	Increase the memory space in the system.

7433: Duplicate ip '%1\$s' exists in LSNR_INVITED_IP.

Cause	IP already exists.
Action	Specify another IP.

7434: The datafile path('%1\$s') has no @SID@.

Cause	The absolute path of a datafile have to include @SID@ in TMC.
Action	Insert @SID@ into absolute path.

7435: The datafile path('%1\$s') is not correct.

Cause	The absolute path of a datafile is not correct.
Action	Please check the path of a datafile.

7436: IP address '%1\$s' is invalid.

Cause	An invalid IP address is given as a DDL paramter.
Action	Check the parameter and specify an appropriate value.

7437: Can't exchange partition with the specified table.

Cause	Properties of the specified table is different with partition
Action	Change properties of the table.

7438: Failed to obtained the lock to refresh the materialized view \"%1\$s\".\"%2\$s\".

Cause	Another session is holding the lock.
Action	Try again later.

7439: Unable to perform DDL on the AQ table \"%1\$s\".

Cause	Unable to perform DDL on an AQ table.
Action	Confirm that the table the operation is to be performed on is an AQ table.

7440: The user defined error is called.

Cause	This error is called by the user defined error in PSM.
Action	Check the PSM that contains the user defined error.

7441: Objects other than tables cannot be flash backed.

Cause	Flashback operation attempts to flash back objects other than tables.
Action	Check the type of the object being flash backed.

7442: Flashback table is not allowed on this table.

Cause	The table is not supposed to be flash backed.
Action	Check whether the table is allowed to be flash backed.

7443: The specified remote database does not exist.

Cause	The specified remote database does not exist.
Action	Check the remote database name.

7444: Cannot make a remote container table for a DBMS remote database except for Tiberio or Oracle.

Cause	The remote container table function of the materialized view is only supported for Tiberio and Oracle.
Action	Confirm that the remote database is for Tiberio or Oracle.

7445: Prebuilt table does not exist in the specified remote database position.

Cause	When using a remote database, only the ON PREBUILT TABLE option is supported.
Action	When creating a materialized view, use the statement <code>"ON PREBUILT TABLE AT remote_database_name."</code>

7446: Prebuilt table does not exist in the specified remote database position.

Cause	Prebuilt table does not exist in the specified remote database position.
Action	When creating a materialized view, create a prebuilt table first.

7447: The rowid column does not exist in the prebuilt table at the specified remote database position.

Cause	To use REFRESH WITH ROWID when a remote database is specified, the column to store the rowid value must be manually created in the prebuilt table.
Action	Add the column <code>(M_ROW\$\$ VARCHAR2(255))</code> to the prebuilt table, and then add a unique index to the column.

7448: cannot reuse lower-bound partitions resulting partition.

Cause	cannot reuse lower-bound partitions resulting partition.
Action	use upper_bound partition.

7449: range partitions being merged are not adjacent

Cause	range partitions being merged are not adjacent
Action	specify two partition that are adjacent

7450: The specified partition and table cannot be exchanged.

Cause	The table and the partition of the composite partition cannot be exchanged.
Action	Specify a subpartition.

7451: Cannot redefine an object online that is not a table

Cause	Cannot redefine an object online that is not a table
Action	Specify a table

7452: The specified plan table has incorrect format.

Cause	Cannot update the plan table because its format does not match the correct format.
Action	Make sure plan_table have the correct field definitions

7453: The specified thread ID is invalid.

Cause	An invalid thread ID given as a DDL parameter.
Action	Specify a valid thread ID as a DDL parameter.

7454: Datatype '%1\$s.%2\$s' is invalid.

Cause	Specified data type is invalid, or the user-defined type does not exist.
--------------	--

Action	Please recheck the data type specified in the column.
---------------	---

7455: To use shrink space, row movement must be enabled for the object.

Cause	Cannot use shrink space on an object with disabled row movement.
Action	Enable row movement for the object.

7456: Cannot use shrink space on an object that has a long column.

Cause	Cannot use shrink space on an object that has a long column.
Action	Unable to execute this command.

7457: The interval value is not an appropriate constant type.

Cause	The interval value is invalid.
Action	Change the interval value to an appropriate type.

7458: The number of partition columns in the interval table is greater than one.

Cause	The number of partition columns in an interval table must be one.
Action	Set the number of partition columns to 0

7459: The type of a partition column in the interval table is invalid.

Cause	The type of a partition column in an interval table must be NUMBER or DATE.
Action	Set the partition column type to NUMBER or DATE.

7460: Constraints do not match in \"ALTER TABLE EXCHANGE PARTITION\".

Cause	The constraints of two tables do not match in \"ALTER TABLE EXCHANGE PARTITION\".
Action	Please check the constraints.

7461: Invalid user name or role.

Cause	User name or role does not conform to a user rule.
Action	Check the user rule for CREATE USER.

7462: Cannot create an external table with a long column type.

Cause	At least one column has long type.
Action	Avoid using a long column type when creating an external table.

7463: The table \"%1\$s\".\"%2\$s\" cannot be redefined online.

Cause	Online redefinition was attempted on tables that cannot be redefined such as temporary tables, the overflow table of an index-organization table, or tables where fine-grained access control or row-level security is enabled.
Action	Do not attempt online redefinition of tables that cannot be redefined online.

7464: INITRANS value is out of range.

Cause	The value of INITRANS is either too small or too large.
Action	Specify an integer value between 2 and 255.

7465: Cannot have a default value on a virtual column.

Cause	The virtual column is altered to have a default value.
Action	Remove the default value from the virtual column.

7466: Cannot have an expression on a real column.

Cause	The real column is altered to have an expression.
Action	Remove the expression from the real column.

7467: Cannot alter the primary index on an IOT unusable.

Cause	A primary key on an IOT cannot be unusable.
Action	Unable to execute.

7468: Bitmap index cannot be created on an IOT.

Cause	User attempted to create a bitmap index on an index-organized table.
Action	Unable to execute this command.

7469: Listener timeout.

Cause	Verify the port is valid.
Action	Verify the port is valid.

7470: Unable to add or delete listener port.

Cause	Verify the port is valid.
Action	Verify the port is valid.

7471: Cannot modify the default listener port. This port is currently in use internally.

Cause	Verify the port is valid.
Action	Verify the port is valid.

7472: Unable to add or delete listener port. Maximum number of ports was exceeded.

Cause	Verify the port is valid.
Action	Verify the port is valid.

7473: Unable to add or delete listener port. Port value is out of range (1024 - 65535).

Cause	Verify the port is valid.
Action	Verify the port is valid.

7474: The reference partitioning constraint is not found.

Cause	The constraint in reference partition is not one of foreign keys.
Action	Check if the reference partitioning constraint is defined as a foreign key.

7475: The parent table of the reference partition is not partitioned.

Cause	The reference partition can be created only if its parent table is partitioned.
Action	Check if the parent table referenced is partitioned.

7476: The option %1\$s is invalid.

Cause	The specified option is invalid.
Action	Specify a valid option.

7477: The BTIP name input is invalid.

Cause	Verify the BTIP file name.
Action	Verify the BTIP file name.

7478: The TIP name input is invalid.

Cause	Verify the TIP file name.
Action	Verify the TIP file name.

7479: RENAME cannot be used in series.

Cause	Database cannot be renamed in series.
Action	Reboot to mount mode.

7480: Cannot alter a refence-partitioned table

Cause	A reference-partitioned table cannot be altered.
Action	Unable to execute this command.

7481: Cannot make SYS a client for a proxy user, or vice versa.

Cause	A proxy user option cannot be applied to SYS.
Action	Unable to execute this command.

7482: Index-Organized Table cannot include a LOB or LONG type column.

Cause	Index-Organized Table cannot include a LOB or LONG type column.
Action	Delete the LOB or LONG type column.

7483: The snapshot users to be compared not matched.

Cause	The user names of the snapshots are not the same.
Action	Check the user names of the snapshots.

7484: The change management package is not set up.

Cause	Some components of of change manage package are missing.
Action	Check the requirements of DBMS_CMGT package.

7485: Cannot create a snapshot for SYS user.

Cause	The dd snapshot for SYS user cannot be created.
Action	Try other users for snapshots.

7486: DBMS_CMGT not found.

Cause	Snapshot(s) or object(s) are not found.
Action	Check if inputs associated with snapshots are correct.

7487: Unable to shrink the temporary file %1\$s ('%2\$s' in tablespace '%3\$s').

Cause	Unable to shrink the temporary file.
Action	Check the properties of the temporary file.

7488: The value of 'KEEP' parameter is out of range.

Cause	The specified value of 'KEEP' paramter is either too small or too large.
Action	Check the parameter and specify an appropriate value.

7489: ADT is declared as a unique or primary key.

Cause	ADT cannot be declared as a unique or primary key.
Action	ADT cannot be declared as a unique or primary key.

7490: Index-Organized Table cannot include a ADT column.

Cause	Index-Organized Table cannot include a ADT column.
Action	Delete the ADT column.

7491: Current DDL is not allowed during instance recovery

Cause	Current DDL is not allowed during instance recovery
Action	Current DDL is not allowed during instance recovery

7492: 'SYS._SGMT_BM_STAT_STATUS' table does not exist.

Cause	'SYS._SGMT_BM_STAT_STATUS' may be deleted or not be created.
Action	Contact the technical support team.

7493: 'SYS._SGMT_BM_STAT_STATUS' table already exists.

Cause	'SYS._SGMT_BM_STAT_STATUS' table may be created by the previous same DDL that failed.
Action	Contact the technical support team.

7494: The specified segment does not exist.

Cause	The specified sgmt_id is invalid
Action	Specify a valid value and try again.

7495: The constraint column is not a REF column.

Cause	This constraint can only be specified on a REF column.
Action	Check the type of the constraint column.

7496: Multiple domain indexes cannot be created on a single column.

Cause	A domain index already exists on the specified column.
Action	Delete the existing domain index first.

7497: The specified type is missing the %1\$s member function.

Cause	An attempt was made to bind the type without the %1\$s member function.
Action	Add the %1\$s member function to the type.

7498: Package body recompile failed by invalid package spec.

Cause	Package body recompile failed by invalid package spec.
Action	Try again.

7500: Recompile failed by other DDL. Try again.

Cause	Recompile failed by other DDL. Try again.
Action	Try again.

7501: Not allowed in standby replication.

Cause	Not supported in standby replication.
Action	

7502: Remote Information of %1\$s is missing.

Cause	Remote Information is needed.
Action	Specify Remote Information.

7503: Cannot export/import data files from TAS to None TAS due to '+'.

Cause	Cannot export/import data files from TAS to None TAS due to '+'.
Action	Do not use prefix '+' when exporting/importing data files from TAS to NONE TAS.

7504: Cannot set undo_tablespace parameter while setting others.

Cause	Set undo_tablespace parameter exclusively.
Action	Set undo_tablespace parameter exclusively.

7505: Tablespace is already default tablespace.

Cause	Check tablespace name.
Action	Chekc tablespce name.

7506: This command is allowed for only SYS user.

Cause	This command is allowed for only SYS user.
Action	Login as SYS user and try again.

7507: Cannot create/add context local partition(s) index with more than 127 partitions.

Cause	The maximum local partition count allowed for context index is 127.
Action	Check the partition count for the table.

7508: Unable to shrink permanent tablespace.

Cause	Shrink space is not allowed on non-temporary tablespace.
Action	Check the type of tablespace.

7509: cannot grant '%1\$s' to a role.

Cause	cannot grant '%1\$s' to a role.
Action	cannot grant '%1\$s' to a role.

7510: Old password file exists. Unable to create new password file.

Cause	Move(or remove) the old password file before newmounting database.
Action	Move(or remove) the old password file before newmounting database.

7512: Not permitted while standby database is enabled.

Cause	The action is not permitted while the standby DB is enabled.
Action	Disable the standby DB and try again.

7513: Both bitmap index and unique key cannot co-exists.

Cause	Choose bitmap index or unique constraint.
Action	Choose bitmap index or unique constraint.

7514: The standby is not RUNNING status.

Cause	The action is not permitted while the standby DB is not RUNNING.
Action	Wait for complete operation of booting the standby.

7515: At least one LGWR SYNC standby DB is required.

Cause	At least one LGWR SYNC standby DB is required.
Action	At least one LGWR SYNC standby DB is required.

7516: The LNW is not ready to start.

Cause	The LNW is not ready to start.
Action	The LNW is not ready to start.

7517: Must specify table name for nested table column or attribute.

Cause	Nested table column or attribute is not specified on the storage clause.
Action	Specify the nested table storage clause.

7518: XMLSchema '%1\$s' is not registered.

Cause	XMLSchema is not registered before creating table.
Action	Register XMLSCHEMA first.

7519: Tag name '%1\$s' in XMLSchema '%2\$s' is invalid.

Cause	Tag name is not invalid.
Action	Check XMLSCHEMA.

7520: Referential constraint is not allowed on nested table column.

Cause	Referential constraint is not allowed on nested table column.
Action	Unable to execute.

7521: Specified column '%1\$s' is not a nested table type.

Cause	Specified column type is invalid for nested table.
Action	Check the specified column type or nested table storage clause.

7522: DDL need retry.

Cause	DDL need retry as DDL cannot proceed.
--------------	---------------------------------------

Action	DDL need retry.
---------------	-----------------

7523: Memory tablespace already exists.

Cause	Memory tablespace already exists.
Action	Drop the existing memory tablespace first.

7524: Memory tablespace cannot have datafiles more than '%1\$d'.

Cause	Memory tablespace has too many datafiles.
Action	Check the number of datafiles.

7525: No free space for memory tablespace.

Cause	The size of memory tablespace exceeds the maximum size allowed.
Action	Check the size of memory tablespace.

7526: The size of Memory tablespace is undefined.

Cause	The size of Memory tablespace is undefined.
Action	Check MEMORY_TABLESPACE_SIZE parameter.

7527: Fail to invalidate cursors due to missing pp main info.

Cause	Fail to invalidate cursors due to missing pp main info.
Action	Invalidate all existing PP cache.

7528: Memory tablespace cannot have auto-extended datafiles.

Cause	Memory tablespace cannot have auto-extended datafiles.
Action	Check the datafile spec.

7529: Memory tablespace cannot be offline.

Cause	Memory tablespace cannot be offline.
Action	Unable to execute.

7530: Sdisk member clause required.

Cause	Sdisk member clause is missing.
Action	Specify an Sdisk member clause.

7531: Gdisk member clause required.

Cause	Gdisk member clause is missing.
Action	Specify a Gdisk member clause.

7532: SFC member clause required.

Cause	SFC member clause is missing.
Action	Specify an SFC member clause.

7533: IORM member clause required.

Cause	IORM member clause is missing.
Action	Specify an IORM member clause.

7534: A table can have only one identity column.

Cause	A table may have only one identity column.
Action	Specify one identity column.

7535: Identity column can be created only on a column of numeric type.

Cause	Identity column is not a numeric type.
Action	Identity column be a numeric type.

7536: Invalid NOT NULL constraint used on an identity column.

Cause	A NOT NULL constraint was not used properly on an identity column.
Action	Identity column with a NOT NULL constraint must be enabled and nondeferrable.

7537: INVALID trigger in FOLLOWS option.

Cause	INVALID trigger in FOLLOWS option.
Action	Check FOLLOWS option.

7538: Materialized view '%1\$s' cannot be dropped internally.

Cause	Materialized view cannot be dropped internally.
Action	Drop materialized view '%1\$s' externally and retry drop user.

7539: Cannot include an LOB column in a compressed table.

Cause	LOB column is not supported in compressed tables.
Action	Modify the DDL statement.

7540: Multiple datafiles specified for bigfile tablespace.

Cause	A bigfile tablespace can contain only one datafile.
Action	Check the number of datafiles specified for the bigfile tablespace.

7541: Failed to backup archive logfiles due to another archive logfile backup ongoing.

Cause	Failed to backup archive logfiles due to another archive logfile backup ongoing.
Action	Please use '--archive-only' or '--with-archivelog' only when another ongoing doesn't exist.

7542: Failed to backup due to none of the RECO slaves are free to use.

Cause	Failed to backup due to none of the RECO slaves are free to use.
Action	Please retry with smaller value of '-p, --parallel' option (max. %1\$d).

7543: Another RMGR datafile backup/restore/delete job already ongoing.

Cause	Cannot execute more than one RMGR datafile backup/restore/delete job at a time.
Action	Please retry after the ongoing RMGR finishes.

7544: Lob columns do not match in \"ALTER TABLE EXCHANGE PARTITION\".

Cause	The lob columns of two tables do not match in \"ALTER TABLE EXCHANGE PARTITION\".
Action	Please check the lob columns.

7545: Failed to add backup archivelog due to no backup archivelog in the backup set.

Cause	Actual backup set doesn't contain the archivelog backups.
Action	Please check the query for adding the archivelog backups.

7546: There is no visible column in the table.

Cause	A table must have at least one visible column.
Action	Please check the visibility of the columns in the table.

7547: Data integrity is violated.

Cause	Query result from index scan is different from that from table scan
Action	Please check the physical plan dump and log.

7548: A column to be modified is not an identity column.

Cause	The specified column cannot be identity column.
Action	Make sure that the column to be modified to identity column is an identity column.

7549: Failed to backup/delete archive logfiles due to another archive logfile backup/delete ongoing.

Cause	Failed to backup/delete archive logfiles due to another archive logfile backup/delete ongoing.
Action	Please retry only when another archive logfile backup/delete is not ongoing.

7550: Failed to execute RMGR backup due to another RMGR backup already ongoing.

Cause	Failed to execute RMGR backup due to another RMGR backup already ongoing.
Action	Please retry after the ongoing RMGR backup finishes.

7551: Invalid COMPRESS prefix length value

Cause	The prefix length value must be an integer between 1 and the number of key columns (number of key columns - 1 for unique index).
Action	Retry with a valid prefix length value.

7552: Cannot use COMPRESS option for a single column key

Cause	A single column unique index cannot be compressed.
Action	Retry with a valid prefix length value.

7553: Cannot use %1\$s as a lob segment name.

Cause	You cannot use SECUREFILE or BASICFILE as a lob segment name.
Action	Retry with a valid lob segment name.

7554: Cannot enforce to use specified types of index for constraint.

Cause	The specified type of index cannot be enforced to use as a constraint.
Action	Check the type of the specified index.

7555: Cannot use supplemental logging and nologging together.

Cause	Supplemental logging cannot be used together with nologging.
Action	Retry after changing the object status or modifying the statement.

7556: Cannot create a unique local partitioned index on a system partitioned table.

Cause	A unique local partitioned index cannot be created on a system partitioned table.
Action	Create a non-unique index or change the index partition option.

7557: Cascading standby only supports PERFORMANCE mode.

Cause	Cascading standby only supports PERFORMANCE mode.
Action	Cascading standby only supports PERFORMANCE mode.

7558: Cascading standby only supports ASYNC log transport mode.

Cause	Cascading standby only supports ASYNC log transport mode.
Action	Cascading standby only supports ASYNC log transport mode.

7559: instance id of the target session is invalid or failed to send a request to target instance. instance_id: %1\$u

Cause	A valid instance id must be provided to apply a SESSION KILL request to a session.
Action	Check the instance id or status of the target instance.

7560: The tablespace (id: %1\$s) is online.

Cause	The tablespace must be offline.
Action	Please retry after offline the tablespace.

7561: dependent object \"%1\$s\".\"%2\$s\" already registered

Cause	You cannot register an already registered dependent object.
Action	Check the name of the dependent object.

7562: Partitioned table specified as target table for exchange statement.

Cause	The target table for an exchange statement must be a non-partitioned table.
Action	Specify a non-partitioned table.

7563: Cannot alter temporary tablespace.

Cause	You cannot alter the temporary tablespace because it is currently in use.
Action	Retry the operation when the temporary tablespace becomes available.

7564: LOG_REPLICATION_DEST_%1\$d is already %2\$s.

Cause	LOG_REPLICATION_DEST_%1\$d is already %2\$s.
Action	Check the status of log replication destination.

7565: Too many columns in a table with a UDT column.

Cause	A table with a UDT column can have up to 255 columns.
Action	Modify the CREATE TABLE statement.

7566: Cannot reverse a bitmap index.

Cause	Bitmap indexes cannot be reversed. This operation is not supported.
Action	Modify the DDL statement.

7568: Cannot execute 'alter session current schema' in trigger.

Cause	This operation is not supported here.
Action	'alter session current schema' is not allowed to execute in ddl trigger.

7569: Another RMGR archivelog backup/restore/delete job already ongoing.

Cause	Cannot execute more than one RMGR archivelog backup/restore/delete job at a time.
Action	Please retry after the ongoing RMGR finishes.

7570: Another Media Recovery or RMGR job is already ongoing.

Cause	Cannot execute RMGR and Media Recovery at the same time.
Action	Retry one at a time.

7571: A duplicate column expression was specified.

Cause	The expression of a virtual column being created conflicts with an existing index expression or a virtual column expression.
Action	Change the expression to a unique virtual column expression.

7572: A virtual column for this expression already exists.

Cause	'%"1\$s\'' matches an existing virtual column.
Action	Replace the expression used for indexes with the matching virtual column and then try again.

7573: The specified virtual database '%"1\$s\'' does not exist.

Cause	The specified virtual database does not exist.
Action	Specify a valid virtual database and try again.

7574: The name '%"1\$s\'' is already used by another virtual database or remote database.

Cause	The specified virtual database name is already in use.
Action	Specify another virtual database name.

7575: Cannot purge LOB indexes.

Cause	Purging LOB indexes is not allowed.
Action	Check the index name.

7576: Cannot shrink file %1\$s because it is being backed up or copied.

Cause	The datafile is involved in an online backup.
Action	Check if the end backup has been completed. Try again after the online backup is complete.

7577: Media Recovery without for standby option is not allowed in standby replication.

Cause	Media Recovery without for standby option is not allowed in standby replication.
Action	Retry media recovery with for standby option.

7578: Media Recovery with for standby option is not allowed if the database is not standby replication.

Cause	Media Recovery with for standby option is not allowed if the database is not standby replication.
Action	Retry media recovery without for standby option.

7579: The virtual column is referenced in a column expression.

Cause	The virtual column is referenced in an expression of another virtual column.
Action	Make sure that the column expression definition for the virtual column does not refer to any other virtual column.

7580: Virtual columns are not allowed in functional index expressions.

Cause	One or more virtual columns were used to define the expression of a functional index.
Action	Specify the index expression using only regular columns.

7581: The column to be dropped or modified is used in a virtual column expression.

Cause	A column used in a virtual column expression cannot be dropped or modified.
Action	Drop the virtual column first or change the virtual column expression to eliminate dependency on the column to be dropped.

7582: The column to be renamed is used in a virtual column expression.

Cause	A column used in a virtual column expression cannot be renamed.
Action	Drop the virtual column first or change the virtual column expression to eliminate dependency on the column to be renamed.

7583: Cannot access the sequence '%1\$s' in use.

Cause	The sequence has been dropped or attempted to be dropped in another session.
Action	Check whether the sequence exists and retry.

7584: Media Recovery with _STANDBY_ALLOW_TEMPFILE_ADD_IN_MOUNT_MODE=Y is not allowed.

Cause	Media Recovery with _STANDBY_ALLOW_TEMPFILE_ADD_IN_MOUNT_MODE=Y is not allowed..
Action	Set _STANDBY_ALLOW_TEMPFILE_ADD_IN_MOUNT_MODE=N and retry media recovery.

7585: The %1\$s cannot be %2\$s than the current value.

Cause	The next value or start value must be between MINVALUE and MAXVALUE.
Action	Specify MINVALUE or MAXVALUE within the valid range.

7586: The number of partitions of the reference-partitioned table is different from that of the parent table.

Cause	The number of partitions of the reference-partitioned table is different from that of the parent table.
Action	Check the CREATE TABLE statement.

7587: The reference partitioning constraint is not supported.

Cause	The reference partitioning constraint is not supported.
Action	Correct the reference partitioning constraint.

7588: The reference partitioning key is not supported.

Cause	The reference partitioning key is not supported.
Action	Correct the reference partitioning key.

7589: The parent table of the reference-partitioned table is an index-organized table.

Cause	A reference-partitioned table is not supported for an index-organized table.
Action	Check the CREATE TABLE statement.

7590: The partitioning method is not supported for an index-organized table.

Cause	The partitioning method is not supported for an index-organized table.
Action	Check the CREATE TABLE statement.

7591: Failed to set LOG_REPLICATION_DEST_%1\$d: %2\$s

Cause	Invalid LOG_REPLICATION_DEST_%1\$d.
Action	Check the LOG_REPLICATION_DEST_%1\$d and retry.

7592: Tablespace cannot be dropped because invalid _DD_FILE row found.

Cause	Tablespace cannot be dropped because invalid _DD_FILE row found.
Action	Contact the technical support team.

7593: An unusable index exists on the constraint key.

Cause	An unusable index exists on the constraint key.
Action	Drop the unusable index or rebuild it using ALTER INDEX REBUILD.

7594: The operation is not supported for reference-partitioned tables.

Cause	The operation is not supported for reference-partitioned tables.
Action	Do not perform the unsupported operation.

7595: Indexes and their index partitions must have the same compression attribute.

Cause	The user attempted to exchange an index with an index partition using different compression attributes.
Action	Make sure that the compression attributes match. If they don't, drop and rebuild the index with the same compression attribute.

7596: Virtual columns were used as supplemental log columns.

Cause	Virtual columns are not supported in supplemental log columns.
Action	Exclude virtual columns from the supplemental log column group.

7597: Failed to create controlfile because MAXINSTANCES and IPARAM(MAX_INSTANCE_COUNT) did not match.

Cause	Failed to create controlfile because MAXINSTANCES and IPARAM(MAX_INSTANCE_COUNT) did not match.
Action	Modify the value of MAXINSTANCES or IPARAM(MAX_INSTANCE_COUNT) and try again.

7598: The index type is unsupported for the operation.

Cause	The index type is unsupported for the operation.
Action	Check the index type.

7599: The name of the text index is too long.

Cause	The name of the text index exceeds the maximum allowed length.
Action	Change the name of the text index.

7600: Already enabled sequence scalability cannot be turned off.

Cause	Already enabled sequence scalability cannot be turned off.
Action	If the option needs to be changed to NO SCALE, DROP and CREATE the sequence.

7601: The data type of the virtual column is not supported.

Cause	The data type of the specified expression is not supported in virtual columns. Only scalar data types are supported for virtual columns. LONG, LOB, OBJECT, REF and VARRAY data types are not supported for virtual columns.
Action	Specify the virtual column expression to return a scalar data type.

7602: Cannot specify a monthly interval with existing upper limits whose number of days is greater than 28.

Cause	The specified interval conflicts with the existing upper limit for the last partition. This combination may result in invalid dates for upper limits in the future.
Action	If this is a CREATE TABLE, try specifying a different upper limit for the last partition or a different interval. If this is an ALTER TABLE SET INTERVAL, choose either a different interval or modify the table to change the upper limit for the last partition.

7603: Table is not partitioned by Interval method.

Cause	The table was not partitioned by the Interval method.
--------------	---

Action	ALTER TABLE SET STORE IN is only valid for Interval partitioned tables. Check if the table is an Interval partitioned table.
---------------	--

7604: SET INTERVAL or SET STORE IN is invalid in this table.

Cause	SET INTERVAL or SET STORE IN clause was specified. ALTER TABLE SET INTERVAL or ALTER TABLE SET STORE IN is only valid on a range partitioned table with a single partitioning column. Additionally, this table cannot have a maxvalue partition and cannot be the parent table for any reference partitioned table.
Action	Use SET INTERVAL or SET STORE IN only on a valid table.

7605: Interval cannot be zero.

Cause	This interval was mapped to zero.
Action	You must use a non-zero interval.

7606: Cannot grant ts_quota on the tablespace.

Cause	It is not possible on grant ts_quota in UNDO or TEMP tablespaces.
Action	Check the tablespace to grant ts_quota.

7607: Cannot open database to NORMAL mode due to %1\$s.

Cause	It is not possible to open database due to %1\$s.
Action	Check the condition to open the database.

7608: Unavailable to rename system/undo files on NORMAL mode.

Cause	It is not possible to rename system or undo files on NORMAL mode.
Action	Try renaming it on MOUNT mode.

7609: Cannot use the PROFILE option in the current configuration for the user DDL.

Cause	The PROFILE option cannot be used without the USE_PROFILE parameter.
Action	Check the USE_PROFILE parameter.

7610: Unique keyword is not allowed for domain index.

Cause	An attempt was made to domain index with unique option.
Action	Remove unique keyword from create index ddl.

7611: An invalid ALTER TABLE option was specified for an index-organized table.

Cause	The ALTER TABLE option is not valid for an index-organized table.
Action	Remove the invalid option.

7612: TCC table cannot include a %1\$s type column.

Cause	TCC table cannot include a %1\$s type column.
Action	Delete the %1\$s type column.

7613: Compressed table cannot include a LONG type column.

Cause	A LONG type column added to compressed table.
Action	Do not specify a LONG type column.

7614: The schema name '%1\$s' is invalid.

Cause	The schema name '%1\$s' is invalid.
Action	Specify a valid schema name.

7615: Restart option is not allowed for create sequence

Cause	Restart option is not allowed for create sequence
Action	Remove restart option

7616: In-memory tables cannot be compressed.

Cause	Compressing in-memory tables is not supported.
Action	Unable to process.

7617: During a table redefinition, it is not possible to specify a column in an interim table that is mapped to the original table.

Cause	Such action is not supported.
Action	Retry after removing the parameter.

7618: The external table cannot be used for redefinition.

Cause	External tables cannot be used as an original table or interim table for redefinition.
Action	Unable to process.

7619: The partitioned table cannot be redefined online.

Cause	Online redefinition was attempted on partitioned tables that cannot be redefined such as tables containing lob type column, index-organized tables or tables consist of subpartitions.
Action	Do not attempt online redefinition of partitioned tables that cannot be redefined online.

7620: The table cannot be used as an interim table for table redefinition.

Cause	Partitioned tables cannot be used as an interim table for partition redefinition.
Action	Unable to process.

7621: Cannot redefine due to redundant names of table and constraint.

Cause	The table and constraint have the same name.
Action	Unable to process.

7622: Cannot move the table to another tablespace.

Cause	Partitioned tables, virtual tables, index-organized tables, system tables, global temporary tables, or tables with xml indexes cannot be moved.
Action	Unable to process.

7624: A partition containing a usable local context index cannot be exchanged with another table.

Cause	The partition cannot be exchanged because it holds a usable local context index.
Action	Ensure that the local context index is unusable to exchange the partition, and then rebuild the local context index.

7625: Unable to add or delete listener ip.

Cause	Verify the ip is valid.
Action	Verify the ip is valid.

7626: Unable to add or delete listener ip. Maximum number of ips was exceeded.

Cause	Verify the ip is valid.
Action	Verify the ip is valid.

7627: Cannot alter type rename attribute to same name '%1\$s'.

Cause	An attempt was made to change attribute name to same name.
--------------	--

Action	Rename attribute to different name.
---------------	-------------------------------------

7628: Cannot find attribute name '%1\$s'.

Cause	The attribute name '%1\$s' is not found from the object type.
Action	Specify the attribute name correctly.

7629: Duplicate attribute name '%1\$s' exists.

Cause	The attribute name '%1\$s' is already found in the object type.
Action	Rename attribute to different name.

7630: Failed to compile the type.

Cause	The use of the ALTER TYPE statement caused a compilation error.
Action	Correct the error reported and resubmit the statement.

7631: Cannot do this ALTER TYPE operation to collection types.

Cause	This ALTER TYPE operation is only valid for object types.
Action	Specify a valid object type name.

7632: Cannot alter a type that is not valid.

Cause	An attempt was made to perform ALTER TYPE on an invalid type.
Action	Use the CREATE OR REPLACE TYPE command to modify the type.

7633: Method '%1\$s' does not have matching signature among existing methods.

Cause	The method to be dropped does not match to any existing method.
Action	Make sure that a matching method signature is provided for dropping a method.

7634: Cannot ADD or DROP values to the DEFAULT partition.

Cause	Values of the DEFAULT partition cannot be added or dropped.
Action	Do not modify any values of the DEFAULT partition.

7635: DEFAULT cannot be used for ADD or DROP VALUES statements.

Cause	An attempt was made to add or drop DEFAULT value.
Action	ADD or DROP PARTITION containing DEFAULT instead of modifying the partition.

7636: Values already exist in the partition '%1\$s'.

Cause	Cannot add or drop values existing in the partition.
Action	If necessary, delete rows containing corresponding values before ADD/DROP values of the partition.

7637: '%1\$s' does not exist in the partition '%2\$s'.

Cause	Cannot drop the partition values because the values do not exist in the partition.
Action	Drop values that exist in the partition.

7638: Cannot drop all partition values.

Cause	An attempt was made to drop all values of the partition.
Action	This command cannot be executed.

7639: Cannot alter the SYS account into an UNLOCK status in SOD.

Cause	There has been an attempt to change the SYS account into an UNLOCK status.
Action	Cannot execute the DDL statement.

7640: Unable to DROP or REPLACE the object due to an existing dependency.

Cause	The object has a dependency on another table.
Action	DROP the dependent table or use the FORCE option.

7641: Cannot create a TDE range index in non-TTE tablespaces.

Cause	An attempt was made to create a TDE range index in a tablespace that does not support TTE.
Action	Create the TDE range index in a TTE tablespace.

7642: Cannot create a TDE range index on non-encrypted columns.

Cause	An attempt was made to create a TDE range index on a non-encrypted column.
Action	Create the TDE range index on an encrypted column.

7643: Cannot disable the TDE range option for indexes on encrypted columns with salt applied.

Cause	An attempt was made to disable the TDE range option for an index on an encrypted column with salt applied.
Action	Remove the salt or decrypt the column before disabling the TDE range option.

7644: '%1\$s' mode is not supported if multi log buffer is enabled.

Cause	Only PERFORMANCE mode is allowed if multi log buffer is enabled.
Action	Try other replication mode or disable multi log buffer.

7645: SYNC mode is not supported if multi log buffer is enabled.

Cause	Only ASYNC mode is allowed if multi log buffer is enabled.
Action	Try ASYNC log transport mode or disable multi log buffer.

7646: Unable to drop LOB column '%1\$s': its table '%2\$s.%3\$s' is in a different tablespace.

Cause	An LOB-type column is in the tablespace user trying to drop. However, the base table is in a different tablespace.
Action	Drop the LOB-type column or the table first and then retry.

7647: Unable to drop (sub)partition '%1\$s' with LOB: its table '%2\$s.%3\$s' is in a different tablespace.

Cause	A (sub)partition with LOB is in the tablespace user trying to drop. However, the base table is in a different tablespace.
Action	Drop the partition with LOB or the table first and then retry.

7648: Unable to drop (sub)partition '%1\$s' in table '%2\$s.%3\$s': (sub)partition is in a different tablespace.

Cause	A table is in the tablespace user trying to drop. However, its (sub)partition is in a different tablespace.
Action	Drop the (sub)partition or the table first and then retry.

7649: Unable to drop (sub)partition '%1\$s': its table '%2\$s.%3\$s' is in a different tablespace.

Cause	A (sub)partition is in the tablespace user trying to drop. However, the base table is in a different tablespace.
Action	Drop the (sub)partition or the table first and then retry.

7650: Unable to drop (sub)partition '%1\$s' in index '%2\$s.%3\$s': (sub)partition is in a different tablespace.

Cause	An index is in the tablespace user trying to drop. However, its (sub)partition is in a different tablespace.
--------------	--

Action	Drop the index partition or the index first and then retry.
---------------	---

7651: Unable to drop index (sub)partition '%1\$s': index '%2\$s.%3\$s' is in a different tablespace.

Cause	A (sub)partition is in the tablespace user trying to drop. However, the base index is in a different tablespace.
Action	Drop the index partition or the index first and then retry.

7652: cannot drop index '%1\$s.%2\$s' used for enforcement of primary/unique key '%3\$s'.

Cause	the index used for enforcement of primary/unique key is in the tablespace user trying to drop.
Action	Drop the constraint and/or the index first and then retry.

7653: unique/primary keys in table '%1\$s.%2\$s' referenced by foreign key constraint '%3\$s'.

Cause	Referred by other reference constraint.
Action	Drop child table first and/or drop foreign key constraint and retry.

7654: Unable to drop materialized view '%1\$s.%2\$s' in the tablespace.

Cause	cannot drop materialized view in the tablespace user trying to drop.
Action	Drop the materialized view first and then retry.

7655: The value entered for the MAXSIZE option is invalid.

Cause	The specified MAXSIZE value is either less than 0 or exceeds the allowed range.
Action	Enter a valid value.

7656: The value entered for the INITIAL option is invalid.

Cause	The INITIAL option value must be in BYTES and smaller than the MAXSIZE value.
Action	Enter a valid value.

7657: Partition value '%1\$s' already exists in partition '%2\$s'.

Cause	The partition value already exists.
Action	Delete the duplicate partition value.

7658: Partition value '%1\$s' is specified twice in partition '%2\$s'.

Cause	The partition value is specified twice in the same partition.
Action	Specify the partition value once.

7659: Partition value '%1\$s' is specified twice in partition '%2\$s', '%3\$s'.

Cause	The partition value is specified twice in other partition.
Action	Specify the partition value once.

7660: Subpartition value '%1\$s' already exists in subpartition '%2\$s'.

Cause	The subpartition value already exists.
Action	Delete the duplicate subpartition value.

7661: Subpartition value '%1\$s' is specified twice in subpartition '%2\$s'.

Cause	The subpartition value is specified twice in the same subpartition.
Action	Specify the subpartition value once.

7662: Subpartition value '%1\$s' is specified twice in subpartition '%2\$s', '%3\$s'.

Cause	The partition value is specified twice in other subpartition.
Action	Specify the partition value once.

7663: '%1\$s' does not exist in the subpartition '%2\$s'.

Cause	Cannot drop the subpartition values because the values do not exist in the subpartition.
Action	Drop values that exist in the subpartition.

7664: Cannot drop all subpartition values.

Cause	An attempt was made to drop all values of the subpartition.
Action	This command cannot be executed.

7665: The two tables have different owners.

Cause	Date correlation can only be created between tables owned by the same user.
Action	Use two tables owned by the same user.

7666: The two specified tables are the same.

Cause	Date correlation requires two distinct tables.
Action	Specify two different tables.

7667: The specified column '%1\$s' does not exist or is not a valid date type.

Cause	Date correlation constraints must be created on date-type columns.
Action	Specify a valid date-type column.

7668: The specified column '%1\$s' does not exist or is not a referencing (foreign key) column.

Cause	A column with a foreign key constraint must be used.
Action	Specify a column with a foreign key constraint.

7669: The table must have a primary key constraint for date correlation.

Cause	Date correlation constraints require a table with a primary key.
Action	Define a primary key before creating a date correlation constraint.

7670: The specified column '%1\$s' is not used as a partitioning key.

Cause	Date correlation requires a date-type column used as a partitioning key.
Action	Specify a partitioning key column with a date type.

7671: Date correlation cannot use the same column twice.

Cause	Use two distinct date-type columns.
Action	Specify two different date-type columns.

7672: The specified column '%1\$s' does not exist, is not a date type, or lacks a NOT NULL or primary key constraint.

Cause	Date correlation requires a date-type column with a NOT NULL or primary key constraint.
Action	Specify a date-type column with a NOT NULL or primary key constraint.

7673: The date correlation constraint cannot be modified.

Cause	Modifying date correlation constraints is not supported.
--------------	--

Action	This operation is not allowed.
---------------	--------------------------------

7674: Duplicate date correlation exists.

Cause	A date correlation constraint with that conditions already exists.
Action	Delete the duplicate constraint.

제8장 8000 ~ 8999

8002: Invalid DML statement.

Cause	The statement is not a valid DML (Data Manipulation Language) statement.
Action	Check the syntax.

8003: Unable to execute DML statement.

Cause	Unable to execute the DML statement.
Action	Check if DML is executable in the current DB state.

8004: Syntax error.

Cause	There is a syntax error.
Action	Check the statement syntax.

8005: Identifier is too long.

Cause	The identifier is too long.
Action	Adjust the length to less than 30 characters.

8006: Missing FROM keyword.

Cause	The FROM keyword is missing.
Action	Check the statement syntax.

8007: Missing boolean expression.

Cause	A conditional expression is missing or contains syntax errors.
--------------	--

Action	Check the statement syntax.
---------------	-----------------------------

8008: Missing expression.

Cause	Invalid or missing expression.
Action	Check the expression syntax.

8009: Missing keyword.

Cause	There is a syntax error.
Action	Check the statement syntax.

8010: Missing INTO keyword.

Cause	INTO keyword is missing.
Action	Check the statement syntax.

8011: Missing VALUES keyword.

Cause	VALUES keyword is missing.
Action	Check the statement syntax.

8012: Missing comma.

Cause	A comma is missing.
Action	Check the statement syntax.

8013: Missing SELECT keyword.

Cause	SELECT keyword is missing.
Action	Check the statement syntax.

8014: Missing NULL keyword.

Cause	NULL keyword is missing.
Action	Check the statement syntax.

8015: Missing right parenthesis.

Cause	Right parenthesis is missing.
Action	Check the statement syntax.

8016: Missing BY keyword.

Cause	BY keyword is missing after the ORDER, GROUP or CONNECT keyword.
Action	Check the statement syntax.

8017: Missing CONNECT BY clause.

Cause	In a hierarchical query, the CONNECT BY clause should be specified.
Action	Check the statement syntax.

8018: Missing equal sign.

Cause	In a SET clause, an \"=\" is missing.
Action	Check the statement syntax.

8019: Missing WITH keyword.

Cause	WITH keyword is missing after a START keyword.
Action	Check the statement syntax.

8020: Missing SET keyword.

Cause	In an UPDATE statement, a SET clause is missing.
--------------	--

Action	Check the statement syntax.
---------------	-----------------------------

8021: Invalid table name.

Cause	The specification of the table, view or inline view in the FROM clause uses invalid syntax.
Action	Check the statement syntax.

8022: Invalid end of SQL.

Cause	The SQL statement is invalid.
Action	Check the statement syntax.

8023: Invalid qualifier specification.

Cause	Invalid qualifier specification.
Action	Check the qualifier syntax.

8024: Duplicate derived column name exists.

Cause	A derived column with this name already exists.
Action	Rename the column.

8025: Number of derived columns and table columns do not match.

Cause	The number of derived columns does not match the number of columns in a base table, view or inline view.
Action	Modify the query.

8026: Invalid identifier.

Cause	Unable to interpret the column or identifier.
Action	Check the identifier.

8027: Column name is ambiguous.

Cause	Columns with the same name exist in more than one table, view or inline view.
Action	Specify a qualifier for the column name.

8028: FOR UPDATE clause is not allowed here.

Cause	The FOR UPDATE clause was used in a SELECT query block other than the top one.
Action	Check the query block syntax.

8029: FOR UPDATE clause is not allowed for this query.

Cause	The FOR UPDATE statement cannot be used in a query that uses GROUP BY, DISTINCT or set functions.
Action	Modify the query.

8030: Not enough values.

Cause	The number of expressions specified in a VALUE statement is less than the number of columns.
Action	Ensure that the numbers match.

8031: Too many values.

Cause	The number of expressions specified in a VALUE statement is greater than the number of columns.
Action	Ensure that the numbers match.

8032: ORDER BY position must be the same as an entry number in a SELECT-list expression.

Cause	The position specified in ORDER BY clause is out of range.
Action	Specify a valid position.

8033: Specified schema object was not found.

Cause	The specified schema object does not exist.
Action	Check the schema object name.

8034: Specified sequence was not found.

Cause	The sequence does not exist.
Action	Check the sequence name.

8035: Specified synonym was not found.

Cause	The synonym does not exist.
Action	Check the synonym name.

8036: Specified procedure or function was not found.

Cause	Procedure or function does not exist.
Action	Check the procedure name.

8037: Invalid use of group functions.

Cause	Set functions cannot be used in SELECT LIST, HAVING, or ORDER BY clauses.
Action	Check the statement syntax.

8038: Expression is not in a GROUP BY clause.

Cause	An expression that was not specified in a GROUP BY clause was used.
Action	Modify the query.

8039: The ORDER BY clause must contain constants or SELECT list expressions.

Cause	When DISTINCT is specified in a SELECT LIST clause, it must be used in an ORDER BY clause.
Action	Modify the query.

8040: Duplicate column name exists.

Cause	A column name is used more than once.
Action	Modify the query.

8041: Invalid table reference.

Cause	In a FROM clause, schema objects other than tables and views cannot be used.
Action	Modify the query.

8042: Outer join operator (+) cannot be used in a clause with a subquery.

Cause	Sub queries cannot be used along with the outer join condition.
Action	Modify the query.

8043: Outer join operator (+) cannot be used in a clause with OR.

Cause	The OR operator cannot be used along with the outer join condition.
Action	Modify the query.

8044: Outer join operator (+) cannot be used in a clause with IN.

Cause	The IN operator cannot be used along with the outer join condition.
Action	Modify the query.

8045: Outer join operator (+) cannot be used on both sides simultaneously.

Cause	Outer joining of two tables is not allowed.
Action	Delete one of the outer join conditions.

8046: Outer join operator (+) cannot be used between more than two tables.

Cause	Outer joining between more than two tables is not allowed.
Action	Modify the query.

8047: Outer join operator (+) cannot be used with ANSI joins.

Cause	Outer joins cannot be used with ANSI joins.
Action	Modify the query.

8048: Virtual table (dynamic performance view) cannot be updated.

Cause	An attempt was made to update virtual table.
Action	Virtual table cannot be updated.

8049: The ORDER BY clause in a SET clause is invalid: use ordinal numbers.

Cause	In an ORDER BY clause in a query where SET the operator was used, invalid expressions were used.
Action	Modify the query.

8050: Procedures are prohibited in the DML expression.

Cause	Procedure cannot be used in DML statement.
--------------	--

Action	Unable to use procedure.
---------------	--------------------------

8051: User-defined functions are not permitted in the expression.

Cause	Functions cannot be used in a CALL clause which requires a procedure.
Action	Use a valid procedure.

8052: Invalid object status.

Cause	The current object is disabled.
Action	Recreate the object.

8053: Not authorized.

Cause	An attempt was made to access unauthorized objects or columns.
Action	Unable to access the object.

8054: Subquery cannot be used in GROUP BY clause.

Cause	Subquery cannot be used in GROUP BY clause.
Action	Modify the query.

8055: The number of expressions in the RETURNING clause and the number of INTO columns do not match.

Cause	The number of expressions specified in the RETURNING clause and that of columns to be updated do not match with each other.
Action	Modify the query.

8056: Invalid number of columns in query.

Cause	The number of PROJECTIONS between blocks used in SET operation do not match.
--------------	--

Action	Modify the query.
---------------	-------------------

8057: Columns are non-updatable.

Cause	The column cannot be updated.
Action	Check whether or not the column is in a key-preserved table.

8058: Too many key-preserved tables specified.

Cause	More than two key-preserved tables cannot be updated at once.
Action	Modify the query to update only one key preserved table.

8059: A key-preserved table was not found.

Cause	The view cannot be updated.
Action	Check whether or not it is a key-preserved table.

8060: A deletable table was not found.

Cause	A key preserved table, which can be deleted, does not exist in view.
Action	Check the definition of the view.

8061: Columns in USING clauses or NATURAL joins cannot have a qualifier.

Cause	Columns in USING clauses or NATURAL joins cannot have a qualifier.
Action	Delete the qualifier.

8062: Nesting level of aggregation functions is too deep.

Cause	The nesting level of aggregation functions is too deep.
Action	Modify the query.

8063: LONG columns are not permitted.

Cause	LONG type columns cannot be used.
Action	Modify the query.

8064: LOB columns are not permitted.

Cause	LOB type columns cannot be used.
Action	Modify the query.

8065: Invalid host variable name.

Cause	An invalid host variable name was used.
Action	Ensure the host variable name uses proper syntax.

8066: Circular view detected.

Cause	View definition cannot reference itself.
Action	Check the view definition.

8067: Invalid window value used in analytic clause.

Cause	Invalid window range expression in analytic function.
Action	Modify the query.

8068: ORDER BY cannot be used here.

Cause	The ORDER BY clause cannot be used in a subquery.
Action	Modify the query.

8069: Invalid single-group group function.

Cause	Columns which are not used in a GROUP BY clause are used outside aggregation functions.
--------------	---

Action	Change the query.
---------------	-------------------

8070: Subqueries are not allowed in SELECT LIST clauses that use nested aggregation.

Cause	SELECT LIST clauses that use the nested aggregation function cannot use subqueries.
Action	Delete the subquery.

8071: Partition name cannot be used with view.

Cause	View cannot use partition name.
Action	Delete the partition name.

8072: Subqueries cannot be used in this clause.

Cause	A subquery cannot be used in DEFAULT, CHECK or RETURNING clauses.
Action	Delete the subquery.

8073: UDF cannot be used in this clause.

Cause	UDF cannot be used in DEFAULT or CHECK clauses.
Action	Modify the query.

8074: Sequence cannot be used here.

Cause	Sequence being is used in an invalid position.
Action	Modify the query.

8075: ROWNUM cannot be used in this clause.

Cause	ROWNUM cannot be used in DEFAULT or CHECK clauses, or as a join condition.
Action	Modify the query.

8076: LEVEL cannot be used in this clause.

Cause	LEVEL cannot be used in DEFAULT or CHECK clauses.
Action	Modify the query.

8077: Bind variable cannot be used in this clause.

Cause	The bind variable cannot be used in DEFAULT or CHECK clauses.
Action	Modify the query.

8078: Aggregation function cannot be used in this clause.

Cause	The aggregation function cannot be used in DEFAULT or CHECK columns.
Action	Modify the query.

8079: Analytic function cannot be used in this clause.

Cause	The analytic function cannot be used in DEFAULT clauses, CHECK clauses, and in index columns.
Action	Modify the query.

8080: PRIOR keyword cannot be used in this clause.

Cause	PRIOR keyword can be used only in a CONNECT BY clause.
Action	Modify the query.

8081: Column cannot be used in this clause.

Cause	Column cannot be used in DEFAULT or VALUES clauses.
Action	Modify the query.

8082: Non-deterministic functions, date or system variables cannot be used in this clause.

Cause	Non-deterministic functions cannot be used in DEFAULT clauses, CHECK clauses, and in index columns.
Action	Modify the query.

8083: Table is not partitioned.

Cause	PARTITION or SUBPARTITION keywords cannot be used in non-partitioned tables.
Action	Modify the query.

8084: The specified partition does not exist.

Cause	Unable to find the partition name.
Action	Check the partition name and retry.

8085: The specified sub-partition does not exist.

Cause	Unable to find the sub-partition name.
Action	Check the sub-partition name and retry.

8086: %1\$s is not supported.

Cause	The syntax is not supported by the current version.
Action	Modify the query.

8087: Invalid SET clause.

Cause	The expression in a SET clause is incomplete.
Action	Correct the expression.

8088: View %1\$s has errors.

Cause	View definition, referenced schema object or authority check has errors.
Action	Correct the error.

8089: Tuple expression must have a degree of 2.

Cause	Invalid number of argument of the OVERLAP function.
Action	Verify the use of the OVERLAP function.

8090: Invalid bind variable name.

Cause	Bind variable names starting with ':SYS_B_' cannot be used.
Action	Change the name.

8091: INSERT/UPDATE/DELETE cannot be performed on tables with constraints (%1\$s.%2\$s) in the DISABLE VALIDATE state.

Cause	An attempt was made to execute INSERT/UPDATE/DELETE on a table with constraints in a DISABLE VALIDATE state.
Action	Modify the constraints condition.

8092: SIBLINGS keyword cannot be used in this clause.

Cause	SIBLINGS cannot be specified in the ORDER BY clause.
Action	Modify the query.

8093: INTO clauses cannot be used here.

Cause	INTO and BULK COLLECT INTO clauses can be specified only in the top query block.
Action	Modify the query.

8094: LEVEL, PRIOR or ROWNUM keywords cannot be used here.

Cause	LEVEL, PRIOR and ROWNUM keywords cannot be used with the PRIOR operator.
Action	Modify the query.

8095: Percentage in a SAMPLE clause must be in the range [0.000001, 100).

Cause	Percentage in a SAMPLE clause must be between 0.000001 and 100 (must be less than 100).
Action	Modify the value to fall within the range.

8096: CONNECT_BY_ROOT operator cannot be used here.

Cause	The CONNECT_BY_ROOT operator cannot be used here.
Action	Modify the query.

8097: CONNECT_BY_ISLEAF operator cannot be used here.

Cause	The CONNECT_BY_ISLEAF operator cannot be used here.
Action	Modify the query.

8098: SYS_CONNECT_BY_PATH operator cannot be used here.

Cause	The SYS_CONNECT_BY_PATH operator cannot be used here.
Action	Modify the query.

8099: CONNECT_BY_ISCYCLE operator cannot be used here.

Cause	The CONNECT_BY_ISCYCLE operator cannot be used here.
Action	Modify the query.

8100: Target must be a table.

Cause	Target of MERGE INTO statement must be a table.
Action	Check the target object.

8101: Column used in the ON clause cannot be updated.

Cause	The column used in an ON clause cannot be updated.
Action	Modify the query.

8102: Outer join cannot be specified for a correlation column.

Cause	An outer join cannot be specified for a correlation column.
Action	Change the query.

8103: Circular synonym detected.

Cause	Synonyms cannot reference themselves.
Action	Check the definition of the synonym.

8104: DECODE function has too many arguments.

Cause	More than 255 arguments were used.
Action	Reduce the number of arguments in the DECODE function.

8105: The CASE function has too many arguments.

Cause	More than 65535 arguments were used.
Action	Reduce the number of arguments in the CASE function.

8106: Outer join operator may not be used in this clause.

Cause	The outer join operator can only be used in ON and WHERE clauses.
--------------	---

Action	Modify the query.
---------------	-------------------

8107: Distributed operation is not supported.

Cause	The MERGE statement attempted to process more than two DB instances.
Action	Modify the query.

8108: Invalid relational operator.

Cause	Invalid condition expression.
Action	Modify the condition expression.

8109: Argument must be a constant expression.

Cause	Only expressions with the same value in GROUP BY clauses are allowed.
Action	Use only expressions which are used in a constant expression or GROUP BY clause.

8110: Too many WHEN clauses used.

Cause	A single multitable insert statement contained more than 127 WHEN clauses.
Action	Reduce the number of WHEN clauses in the statement.

8111: View or remote table cannot be the target of a multitable insert.

Cause	View or remote table cannot be the target of a multitable insert.
Action	Modify the query.

8112: Reference cursor table has too many arguments.

Cause	More than 10,000 arguments were used.
Action	Reduce the number of arguments in the PSM function.

8113: Insufficient arguments specified for a function.

Cause	An argument required for the function was omitted.
Action	Specify the omitted argument again.

8114: Too many arguments specified for a function.

Cause	The number of arguments specified for a function exceeds the number required.
Action	Delete extraneous arguments.

8115: Flashback query clause is not valid here.

Cause	The flashback query clause was used in an invalid location.
Action	Modify the query.

8116: DISTINCT option cannot be used for this function.

Cause	The DISTINCT option cannot be used for this function.
Action	Delete the DISTINCT option and try again.

8117: Invalid datatype used in function.

Cause	The datatype used in the function is invalid.
Action	Check the arguments of the function.

8118: Unable to select rowid column from the index-organized table.

Cause	Unable to select rowid column from the index-organized table.
Action	Remove the rowid column and try again.

8119: Revalidation of trigger '%1\$s' failed

Cause	Failed to recompile the invalid trigger.
--------------	--

Action	Modify the trigger source code and create again.
---------------	--

8120: A column '%1\$s' for the error log table '%2\$s' is missing.

Cause	A column required for the error log table is missing.
Action	Check the error log table.

8121: Invalid number of arguments.

Cause	The number of arguments is incorrect.
Action	Check the syntax and change it.

8122: Internal hint cannot be used.

Cause	Internal hint cannot be used.
Action	Remove internal hint.

8124: The query defined in the RECURSIVE WITH clause is not valid.

Cause	The query defined in the RECURSIVE WITH clause violates an integrity constraint.
Action	Define the query in the format of (anchor member) UNION ALL (recursive member).

8125: A column alias list was not defined in the RECURSIVE WITH clause.

Cause	Column name aliases were not defined for the query names.
Action	Add a column alias list for the query names in the RECURSIVE WITH clause.

8126: There are statements that are not supported as a recursive member of the recursive WITH clause.

Cause	The following statement cannot be used as a recursive member to the right of UNION ALL statement within the recursive WITH query: GROUP BY, HAVING, DISTINCT, CONNECT BY, window functions, set operations, and aggregate functions.
Action	Rewrite the recursive WITH query so that the unsupported statements are not used.

8127: This join is not supported by the recursive WITH query.

Cause	The recursive WITH clause contains the recursive query name at one of the following positions: the right side of the LEFT OUTER JOIN, the left side of the RIGHT OUTER JOIN, the FULL OUTER JOIN, or in the subquery.
Action	Rewrite the query with the supported join.

8128: Read-only table cannot be updated.

Cause	An attempt was made to execute DML on a read-only table.
Action	Read-only table cannot be updated.

8129: Index by that name was not found.

Cause	Unable to find the index name.
Action	Check the index name and retry.

8130: Index is not partitioned.

Cause	INDEX_PARTITION or INDEX_SUBPARTITION keywords cannot be used in non-partitioned indexes.
Action	Modify the query.

8131: Circular RLS policy has been detected.

Cause	The predicate returned by the policy function refers to the object that the policy is attached to.
Action	Check the definition of the policy function.

8132: The policy predicate contains an error.

Cause	The predicate string generated by the policy function is not valid for this object.
Action	Check the definition of the policy function.

8133: Invalid use of association operator (=>).

Cause	Association operator (=>) can only be used as an UDF argument.
Action	Modify the query.

8134: A user-defined aggregate function can have only one parameter.

Cause	Check the definition or the call of the user-defined aggregate function.
Action	Modify the definition of the user-defined aggregate function and regenerate it.

8135: The '%1\$s' interface function is undefined.

Cause	Check the definition of the object type.
Action	Modify the object type definition and regenerate it.

8136: The parameter of the user-defined aggregate function and the parameter of the 'TUDIAGGREGATEITERATE' function defined in the object type are not compatible.

Cause	Check the query and the definition of the object type.
--------------	--

Action	Modify the query or the definition of the object type and regenerate it.
---------------	--

8137: The result type of the object type and the result type of the user-defined aggregate function are not compatible.

Cause	Check the query and the definition of the object type.
Action	Modify the query or the definition of the object type and regenerate it.

8138: A single unique index must be specified in the index hint.

Cause	An index was not specified in the IGNORE_ROW_ON_DUPKEY_INDEX hint.
Action	Specify a unique index defined in the table.

8139: Index specified in the index hint is invalid.

Cause	The unique index was not found.
Action	Specify a unique index defined in the table.

8140: Multiple unique indexes were specified in the index hint.

Cause	Multiple unique indexes were specified in the index hint.
Action	Specify a single unique index.

8141: Argument must be a constant expression.

Cause	The specified function argument is invalid.
Action	Check the declaration of the function.

8142: This DML statement is not permitted in the current boot mode.

Cause	In the current boot mode, this DML cannot be executed.
--------------	--

Action	Change the boot mode and run the DML statement again.
---------------	---

8143: Cannot insert a value in a virtual column.

Cause	Attempted to insert a value in a virtual column.
Action	Write insert statements except for this column.

8144: Cannot update a value in a virtual column.

Cause	Attempted to update a value in a virtual column.
Action	Remove the SET clause for this column in UPDATE statements.

8145: The value set to AUTO_INCREMENT COLUMN in the insert statement is incorrect.

Cause	A value other than null cannot be inserted into the AUTO_INCREMENT COLUMN.
Action	Remove AUTO_INCREMENT COLUMN or set the AUTO_INCREMENT COLUMN to null in the insert statement.

8146: A WITH query name has been duplicated in a recursive node in a recursive WITH.

Cause	Self reference can be used only once in a recursive node in a recursive WITH.
Action	Rewrite the query so that a WITH query name can be used only once.

8147: Expressions that return a user-defined type is not allowed in the current context.

Cause	Only expressions that return a built-in type are allowed in the current context.
Action	Check the return type of the expression in the current context.

8148: Expression is not in a SUBQRY LIST clause.

Cause	An expression that was not specified in a SUBQRY LIST clause was used.
Action	Modify the query.

8149: An object table is required.

Cause	This syntax expects an object table.
Action	Check the table specified in the query.

8150: Invalid data type for the split key in the WITH clause.

Cause	The specified type cannot be converted into a string type.
Action	Modify the split key value in the WITH clause.

8151: Expression is not in a SUBQRY LIST clause.

Cause	An expression that was not specified in a SUBQRY LIST clause was used.
Action	Modify the query.

8152: Cannot specify a correlated column.

Cause	A correlated column is not allowed in this context.
Action	Modify the query.

8153: The cursor function was used incorrectly.

Cause	A cursor function must be placed in the outer most select list or used as a psm argument.
Action	Modify the query.

8154: User defined type columns are not permitted.

Cause	User defined type type columns cannot be used.
--------------	--

Action	Modify the query.
---------------	-------------------

8155: Index or partition of such index is in unusable state.

Cause	Index or partition of such index is in unusable state.
Action	DROP the specified index, or REBUILD the specified index.

8156: Logical error in parser.

Cause	
Action	

8157: Data redaction does not support the specified SQL format.

Cause	The query includes operations that are not supported by data redaction.
Action	Modify the query.

8158: Permission denied due to redaction policy.

Cause	The user has insufficient privileges on the redacted table.
Action	Modify the query.

8159: Memory exhausted while parsing the query.

Cause	Memory exhausted while parsing the query.
Action	Increase the memory limit using <code>_PARSE_ALLOWED_MEMORY_DEPTH</code> .

8160: The type of value does not match the type of column.

Cause	The type of value to insert cannot be converted into the type of column.
Action	Check the type of column and value.

8161: Integer value required.

Cause	The input value must be an integer.
Action	Use an integer value expression as the input.

8162: Cannot insert into an always identity column.

Cause	An attempt was made to insert a value into an identity column created with the GENERATED ALWAYS keywords.
Action	A value cannot be inserted directly into an always identity column. The value must be generated by the associated sequence generator.

8163: Cannot update an always identity column.

Cause	An attempt was made to update an identity column created with the GENERATED ALWAYS keywords.
Action	An always identity column cannot be directly updated.

8164: Unable to convert data due to a character set mismatch.

Cause	If the character sets of different instances do not match, the data may be read incorrectly. Therefore, conversion is not allowed in this case.
Action	Ensure that the character sets match between instances. To force the conversion, modify the _ALLOW_DIFF_CHARSET_INSTANCE setting.

8165: Invalid identifier '%1\$s' .

Cause	Unable to interpret the column or identifier.
Action	Check the identifier.

8166: A partition name must be specified for a system partitioned table.

Cause	The partition extended syntax was not used for the system partitioned table.
--------------	--

Action	Use the partition extended syntax to specify the system partitioned table.
---------------	--

8167: The computed column length is too long.

Cause	The column length calculated based on the source and target DB character sets is too long.
Action	Check the target database's character set and the target column length.

8168: Table does not contain visible columns.

Cause	A query was attempted on a table that does not contain any visible columns.
Action	Retry the operation on a table with a visible column.

8169: Cannot find argument in expressions of PARTITION BY.

Cause	The argument must be in the expressions of the PARTITION BY clause.
Action	Check if the argument exists in the expressions of the PARTITION BY clause.

8170: '%1\$s' argument is not function of expressions in PARTITION BY clause.

Cause	The argument must be a function of expressions in PARTITION BY clause.
Action	Check the argument.

8171: COLLECTION columns are not permitted.

Cause	COLLECTION type columns cannot be used.
Action	Modify the query.

8172: Elements in sort specification list of SEARCH clause must be found from the column alias list.

Cause	Cannot find elements in sort specification list of SEARCH clause from the column alias list.
Action	Change the sort specification list to use only names that are listed in the column alias list.

8173: An ordering column name for SEARCH clause must not be part of the column alias list.

Cause	The ordering column name is already in use in the column alias list.
Action	Specify a different name for the ordering column or change the name in the column alias list.

8174: Elements in cycle column list of CYCLE clause must be found from the column alias list.

Cause	Cannot find elements in cycle column list of CYCLE clause from the column alias list.
Action	Change the cycle column list to use only names that are listed in the column alias list.

8175: A cycle mark column name for CYCLE clause must not be part of the column alias list.

Cause	The cycle mark column name is already in use in the column alias list.
Action	Specify a different name for the cycle mark column or change the name in the column alias list.

8176: The ordering column for SEARCH clause must be different from the cycle mark column for CYCLE clause.

Cause	The ordering column for SEARCH clause matches the cycle mark column for CYCLE clause.
Action	Change either the ordering column or the cycle mark column so that they no longer match.

8177: The cycle value for CYCLE clause must be different from the non-cycle value.

Cause	The cycle value for CYCLE clause is the same as the non-cycle value.
Action	Change either the cycle or the non-cycle values so that they no longer match.

8178: SEARCH and CYCLE clauses can only be specified for recursive WITH clause elements.

Cause	A SEARCH or CYCLE clause is specified for a non-recursive WITH clause element.
Action	Remove the SEARCH or CYCLE clause, or add recursion to the WITH clause element.

8179: MAXVALUE partition cannot be specified for Interval partitioned objects.

Cause	An attempt was made to create a partition with a MAXVALUE highbound on an Interval partitioned object.
Action	Do not create a partition with a MAXVALUE highbound.

8180: Interval expression is not a constant of the correct type.

Cause	You attempted to use either a nonconstant interval or an interval whose data type does not correspond to the partitioning column.
Action	Use only constant expressions for the interval. If the data type of partitioning column is numeric, the interval must be a numeric constant. If the data type is of type date/time, the interval must be a constant of interval type.

8181: partition bound element must be one of: string, datetime or interval literal, number, or MAXVALUE.

Cause	Partition bound list contained an element of invalid type (i.e. not a number, non-empty string, datetime or interval literal, or MAXVALUE).
Action	Ensure that all elements of partition bound list are of valid type.

8182: The number of variables in the tuple exceeds the maximum allowed count.

Cause	The tuple cannot contain more variables than the maximum count.
Action	Modify the query and ensure that the tuple contains fewer variables than the maximum count, or specify the iparam (_PARAM_CNT_LIMIT_IN_TUPLE) value to adjust the maximum count for the tuple.

8183: JSON columns are not permitted.

Cause	JSON type columns cannot be used.
Action	Modify the query.

8184: ORDER SIBLINGS BY clause not allowed here.

Cause	ORDER SIBLINGS BY clause cannot be used with the PRIOR operator.
Action	Modify the query.

8185: Access to objects targeted for parallel Create Table As Select (CTAS) operation is not permitted.

Cause	An attempt was made to access an object involved in a parallel CTAS operation.
Action	Check if a parallel CTAS operation is currently in progress on the object.

제9장 9000 ~ 9999

9001: File '%1\$s' was not found.

Cause	The file does not exist.
Action	Check if the file exists or use another file.

9002: Input file was not specified.

Cause	An input file was not specified.
Action	Specify an input file.

9003: Multiple input files were specified.

Cause	Two or more input files were specified.
Action	Specify only one input file.

9004: Unable to open file '%1\$s'.

Cause	Cannot open the output file.
Action	Verify that the file name is correct.

9005: Unable to locate configuration file '%1\$s'.

Cause	The configuration file could not be found.
Action	Verify that the path to the configuration file is correct.

9006: Unrecognized file format.

Cause	Invalid file extension.
--------------	-------------------------

Action	The input file name must have an extension.
---------------	---

9007: File name is too long.

Cause	The input file name is over 256 bytes long.
Action	Reduce the length of the file name.

9008: Cursor '%1\$s' is undefined.

Cause	Undefined cursor name.
Action	Verify that the cursor name is correct.

9009: Database '%1\$s' is undefined.

Cause	Undefined DB name.
Action	Verify that the DB name is correct.

9010: Invalid DML statement.

Cause	The DML statement syntax is incorrect.
Action	Verify that the syntax of the DML statement is correct.

9011: Invalid dynamic SQL syntax.

Cause	The dynamic SQL statement is invalid for the ANSI mode.
Action	Use a dynamic SQL statement that is valid for the ANSI mode.

9012: CONTEXT USE statement was not found.

Cause	A CONTEXT USE statement was not used to specify context application.
Action	Use a CONTEXT USE statement.

9013: THREADS option is not enabled.

Cause	To use a thread-related command, the THREADS option needs to be set to YES.
Action	Set the THREADS option to YES.

9014: Context not allocated.

Cause	The context is not allocated.
Action	Allocate the context.

9015: Invalid parameter expression '%1\$s'.

Cause	The parameter expression is invalid.
Action	Check the expression syntax.

9016: Host variable '%1\$s' must be declared in the declare section.

Cause	The host variable is not declared in the declare section.
Action	In ANSI or ISO mode, only variables declared between the EXEC be used as a host variable.

9017: Array size of host variable '%1\$s' is out of range.

Cause	The array size of the host variable is invalid.
Action	Modify the array size of the host variable so that it is an integer greater than 1.

9018: Undeclared identifier '%1\$s'.

Cause	The identifier is not defined.
Action	Define the identifier.

9019: Undefined structure '%1\$s'.

Cause	The structure is not defined.
Action	Define the structure.

9020: Undefined type '%1\$s'.

Cause	The type is not defined.
Action	Define the type.

9021: '%1\$s' is not defined as a struct.

Cause	Only objects defined as structures may be used in that manner.
Action	Use an object that is defined as a structure.

9022: Invalid indirection object '%1\$s'.

Cause	Accessed a pointer with a period (.), or accessed non-pointer with an arrow (->).
Action	Review the item and use the correct access method.

9023: '%1\$s' is not a member of structure '%2\$s'.

Cause	Undefined member of a structure.
Action	Define the object as a member of the structure.

9024: Parameter '%1\$s' cannot be multi-dimensional.

Cause	An attempt was made to bind a multi-dimensional array type.
Action	Modify the bind parameter.

9025: Arrays of structs must be named.

Cause	No name is defined for the host structure declared as array.
--------------	--

Action	Specify a name for the structure.
---------------	-----------------------------------

9026: Structure variable '%1\$s' has a nested structure.

Cause	A structure cannot be bound in another structure.
Action	Delete the nested structure definition.

9027: Structure '%1\$s' cannot have members that are arrays.

Cause	An array cannot be a member of the structure.
Action	Remove the array from the members of the structure.

9028: Invalid VARCHAR format: must be a 1 or 2 dimensional array.

Cause	The format of VARCHAR is invalid.
Action	If VARCHAR is an invalid array, modify it and re-declare it.

9029: Cursor '%1\$s' is already defined.

Cause	The cursor name is already defined.
Action	Use another cursor name.

9030: Database '%1\$s' is already defined.

Cause	The DB name is already defined.
Action	Use another DB name.

9031: Prepared statement '%1\$s' was not found.

Cause	No SQL statement is prepared yet.
Action	Prepare an SQL statement.

9033: Indicator variable '%1\$s' must be a SHORT type.

Cause	The indicator variable is not a SHORT type.
Action	Declare the indicator variable as a SHORT type.

9034: Indicator variable '%1\$s' for host variable '%2\$s' cannot be a structure.

Cause	The indicator variable cannot be a structure because the host variable is not a structure.
Action	Match the type of host variable to the type of indicator variable.

9035: Indicator variable '%1\$s' must be a structure.

Cause	The indicator variable must be a structure because the host variable is a structure.
Action	The indicator variable must be defined as a structure.

9036: Indicator variable '%1\$s' must have the same dimensions as the param variable

Cause	The host variable has different dimensions as the indicator variable.
Action	The indicator variable must have the same dimensions as the host variable.

9037: Invalid use of signed or unsigned operator.

Cause	Invalid signed or unsigned operator has been used to defined variables.
Action	Delete signed or unsigned operator.

9038: Invalid type declared.

Cause	Invalid type declared.
Action	Check if a structure or typedef definition is used with a primitive type.

9039: Two or more data types are in declaration.

Cause	Invalid type declaration.
Action	Check if the declaration of structure or typedef is duplicated.

9040: Duplicate signed or unsigned operators exist.

Cause	More than one signed or unsigned operator.
Action	Correctly mark signed or unsigned.

9041: Array value '%1\$s' is not allowed in WHERE clauses of a SELECT statement.

Cause	Array variables cannot be used in WHERE clauses of a SELECT statement.
Action	Change array variables in WHERE clauses of the SELECT statement into general variables.

9042: When updating, if any host variable is an array type, all host variables must be.

Cause	When updating, if at least one of host variables is an array type, all host variables should be array type, and vice versa.
Action	Declare all host variables as array.

9043: Table was not found.

Cause	The table does not exist or is not declared in any clause.
Action	Declare the table.

9044: Invalid column name(s).

Cause	The column(s) could not be found.
Action	Check the name of the column(s).

9045: Invalid DML syntax %1\$s.

Cause	Invalid DML syntax.
Action	Verify that the DML syntax is correct.

9046: Invalid ESQL syntax %1\$s.

Cause	Invalid ESQL syntax .
Action	Verify that the ESQL syntax is correct.

9047: Invalid C syntax.

Cause	Invalid C syntax.
Action	Verify that the C syntax is correct.

9048: Failure while preprocessing %1\$s.

Cause	Failed to preprocess C programming language.
Action	Locate the cause of the error and modify it.

9049: Unexpected identifier %1\$s.

Cause	The SQL statement starts with a string that is not an ESQL directive.
Action	Verify that the ESQL syntax is correct.

9050: Invalid use of AT clause.

Cause	The syntax should not contain an AT clause.
Action	Delete the AT clause.

9051: Host variable type is not compatible with column type.

Cause	The host variable type is not compatible with the column type of the table.
--------------	---

Action	Check the type of host variable.
---------------	----------------------------------

9052: Parameter count does not match column count.

Cause	The number of parameters is different from the number of columns.
Action	Check the number of parameters.

9053: Semantics check failed at server.

Cause	Failed to check semantics using server.
Action	Verify that the semantics are correct.

9054: Invalid option.

Cause	Unsupported option.
Action	Delete the option.

9055: Option '%1\$s' cannot be used here.

Cause	The option cannot be used here.
Action	Check the location (config file, command line, etc.) where location.

9056: Option value type '%1\$s' is invalid.

Cause	Invalid type of option value.
Action	Check the type of the option value.

9057: Option value '%1\$s' of %2\$s is invalid.

Cause	Invalid option value.
Action	Check the option value.

9058: Option '%1\$s' was not found.

Cause	Undefined option.
Action	Verify that the option exists.

9059: Incomplete multiple option value.

Cause	Invalid format of the option value.
Action	Check the format of the option value.

9060: USERID option should be specified when SQLCHECK=SEMANTICS or FULL.

Cause	If SQLCHECK=SEMANTICS (or FULL), USERID should be also specified.
Action	Specify the USERID option.

9061: User ID '%1\$s' is too long.

Cause	User ID must be less than 128 bytes.
Action	Reduce the size of the user ID.

9062: Password is too long.

Cause	Password must be less than 63 bytes.
Action	Reduce the size of the password.

9063: SQLCHECK=SEMANTICS must be specified when embedded PSM blocks are used.

Cause	Embedded PSM block was used without the SQLCHECK=SEMANTICS option.
Action	Specify the SQLCHECK=SEMANTICS option.

9064: Unable to connect to server.

Cause	Failed to access the server for semantics check.
Action	Check the connection information and server status.

9067: Improperly terminated C comment.

Cause	A C comment beginning with '/' was not terminated.
Action	Terminate the comment properly.

9068: Improperly terminated UNION.

Cause	UNION is not properly terminated.
Action	Check the syntax.

9069: C preprocessing failed.

Cause	Failure while preprocessing C programming language.
Action	Correct the error as shown in the additional messages.

9071: Not logged into the server.

Cause	Not properly connected to the server.
Action	Connect to the server and retry.

9074: Host variable address is NULL.

Cause	The address of the host variable is NULL.
Action	Specify a valid host variable.

9075: Cursor was not found.

Cause	The cursor to be used is not declared.
--------------	--

Action	Declare the cursor first.
---------------	---------------------------

9076: In ANSI mode, already-closed cursors may not be closed again.

Cause	Closed cursors cannot be closed again in ANSI mode.
Action	Make sure that the specified cursor isn't already closed.

9077: In ANSI mode, already-opened cursors may not be opened again.

Cause	Opened cursors cannot be opened again in ANSI mode.
Action	Make sure that the specified cursor isn't already open.

9078: Invalid parameter type.

Cause	Invalid parameter type.
Action	Verify that the parameter type is correct.

9079: Invalid connection string.

Cause	Invalid connection string.
Action	Verify that the connection string is correct.

9080: Invalid use of output parameter.

Cause	Invalid use of output parameter.
Action	Check the output parameter.

9081: Invalid use of input parameter.

Cause	Invalid use of input parameter.
--------------	---------------------------------

Action	Check the input parameter.
---------------	----------------------------

9082: Unspecified cursor name.

Cause	A cursor name was not specified.
Action	Specify the cursor name.

9083: Unspecified prepared statement name.

Cause	The prepared statement name is unspecified.
Action	Specify the name of the prepared statement.

9084: Unspecified database name.

Cause	The database name is unspecified.
Action	Specify the name of the database.

9085: Invalid database name

Cause	The length of database name is 0.
Action	Specify a DB name.

9086: Undefined prepared statement name.

Cause	The prepared statement that was used is not defined..
Action	Verify that the name of the prepared statement is correct.

9087: Input descriptor has not been described.

Cause	Describe input for descriptor has not been performed.
Action	Perform describe input first.

9088: Undefined SQLDA variable.

Cause	The SQLDA variable that was used is not defined.
Action	Define the SQLDA variable first.

9089: No connection to database.

Cause	The connection opened with the database name does not exist.
Action	Make a connection first.

9090: Database connection is closed.

Cause	The specified database connection is closed.
Action	Try to reconnect.

9091: Cursor operation on wrong database.

Cause	This cursor is not defined for the specified database.
Action	Specify the correct database name.

9092: Number of output parameters does not match number of output columns.

Cause	The number of output parameters does not match the number of output columns.
Action	Ensure that the quantities match.

9093: Number of bind variables does not match number of parameters.

Cause	The number of bind variables does not match the number of parameters.
Action	Ensure that the quantities match.

9094: Indicator variable was not specified in INTO clause.

Cause	The indicator variable was not specified in the INTO clause.
Action	Specify the indicator variable for the INTO clause.

9095: Too many rows were returned by SELECT statement.

Cause	Too many rows were returned by a select statement.
Action	Ensure that the expected number of rows does not violate any constraints.

9096: Charmap failed.

Cause	The result does not match the given charmap.
Action	Make sure the result value is not null or an invalid value.

9097: Fetch out of sequence.

Cause	The statement has been executed in wrong sequence.
Action	Execute ESQL statements according to the fetch execution sequence.

9098: Duplicate descriptor name exists.

Cause	The descriptor name already exists.
Action	Use another name for the descriptor.

9099: Unknown descriptor.

Cause	The descriptor has not been assigned.
Action	Assign the descriptor first.

9100: Undefined descriptor name.

Cause	An attempt was made to use an undefined descriptor.
--------------	---

Action	Verify that the name of the descriptor is correct.
---------------	--

9102: Host structure '%1\$s' cannot be used in embedded PSM or dynamic SQL.

Cause	An attempt was made to use a host structure for embedded PSM or dynamic SQL.
Action	Use a general variable type, not a structure.

9103: Include file '%1\$s' does not exist.

Cause	The file to be included does not exist.
Action	Specify a valid file path with the INCLUDE option.

9104: Option '%1\$s' cannot be used for this host language.

Cause	This option cannot be used for this host language.
Action	Check the locations where this option can be used (config file, command line, etc.).

9105: Invalid COBOL syntax.

Cause	Invalid COBOL syntax.
Action	Verify that the COBOL syntax is correct.

9106: Preprocessing failed at line %1\$d because of %2\$s.

Cause	Preprocessing of COBOL language failed.
Action	Locate the cause of the failure and fix it.

9107: Invalid argument '%1\$s'.

Cause	Invalid argument.
Action	Check the help file for the Precompile utility.

9108: Invalid include file\n%1\$s.

Cause	An invalid header file has been included.
Action	Verify that the header file is correct.

9109: Reserve word 'defined' cannot be used as macro name.

Cause	An attempt was made to use 'defined' as a macro name.
Action	Change the macro name.

9110: Macro name not specified in #%1\$s directive.

Cause	A macro name was not specified in #%1\$s directive.
Action	Modify the macro.

9111: Invalid macro name.

Cause	The macro name is inappropriate.
Action	Modify the macro to follow the syntax of C programming language.

9112: Invalid #%1\$s syntax.

Cause	#%1\$s syntax is invalid.
Action	Use #%1\$s "file name" or #%1\$s <file name>.

9113: Recursive #include file.

Cause	The #include file is recursive.
Action	Check the #include files and fix the recursion problem.

9114: Invalid #%1\$s directive.

Cause	The #%1\$s directive is invalid.
--------------	----------------------------------

Action	Modify the #%%1\$s directive.
---------------	-------------------------------

9115: Invalid #pragma GCC poison directive.

Cause	The #pragma GCC poison directive is invalid.
Action	Modify the #pragma GCC poison directive.

9116: Invalid pragma.

Cause	The pragma is invalid.
Action	Modify the pragma syntax.

9117: Invalid conditional syntax (if-else-endif).

Cause	The syntax of the conditional clause (IF-ELSE-ENDIF) is invalid.
Action	Correct the clause syntax.

9118: Non-terminated #%%1\$s directive.

Cause	The #%%1\$s directive is non-terminated.
Action	Fix the directive syntax.

9119: Invalid predicate syntax in #assert and #unassert.

Cause	Predicate syntax used in #assert and #unassert is invalid.
Action	Modify the syntax.

9120: Unable to paste %1\$s and %2\$s because they generate an invalid preprocessing token.

Cause	Cannot paste the two specified tokens together.
Action	Modify the setting syntax.

9121: Too many arguments specified for '%1\$s' macro: %2\$u arguments accepted, %3\$u arguments specified.

Cause	The '%1\$s' macro accepts %2\$u arguments, but %3\$u arguments were specified.
Action	Modify the clause with the '%1\$s' macro.

9122: Arguments specified for '%1\$s' macro are not terminated.

Cause	One or more arguments of the '%1\$s' macro are not terminated.
Action	Modify the setting syntax.

9123: Duplicate parameter '%1\$s' exists in macro.

Cause	The '%1\$s' parameter of the macro is specified twice.
Action	Delete one of the duplicate parameters.

9124: Unknown '%1\$s' parameter in macro.

Cause	'%1\$s' is not in the macro parameter list.
Action	Verify that the parameter name is correct.

9125: Invalid macro parameter syntax.

Cause	Macro parameter syntax is invalid.
Action	Correct the macro parameter syntax.

9126: The # token is not in macro parameter list.

Cause	# token is not in the macro parameter list.
Action	Modify the setting syntax.

9127: Invalid syntax near '###' operator.

Cause	The syntax of the part using the '###' operator is bad.
Action	Modify the setting to meet the syntax.

9128: Conditional expression contains a division by zero error.

Cause	The conditional expression contains division by 0 error.
Action	Modify the conditional expression.

9129: Invalid syntax when using the 'defined' operator.

Cause	The 'defined' operator uses invalid syntax.
Action	Modify the syntax used with the operator.

9130: Unable to open the '%1\$s' file.

Cause	Unable to open the '%1\$s' file.
Action	Specify a valid file path.

9131: Invalid size of VARCHAR '%1\$s'.

Cause	The length of the given VARCHAR is invalid.
Action	Change the length of the VARCHAR.

9132: Invalid use of REF clause.

Cause	A REF clause may not be used here.
Action	Delete the invalid REF clause.

9133: Copy/include file '%1\$s' in line %2\$d was not found.

Cause	No file to copy or include.
--------------	-----------------------------

Action	Specify a valid file to copy or include with the INCLUDE option.
---------------	--

9134: Invalid line continuation.

Cause	The continued line does not follow COBOL programming language syntax.
Action	Locate out the cause of the error and fix it.

9135: Host variable '%1\$s' is of an invalid type.

Cause	This type of host variable is not supported.
Action	Find out the cause of the failure, and modify the part having the problem in the message.

9136: Indicator variable '%1\$s' must be int type because of IND_TYPE option

Cause	Indicator variable must be int type because IND_TYPE is 32bit.
Action	Declare indicator variable as int type.

9137: Unhandled character '%1\$s'.

Cause	Invalid character.
Action	Check that the character is placed in the correct location.

9138: Invalid host variable '%1\$s'.

Cause	Invalid host variable.
Action	Check that the variable is placed in the correct location.

9139: Missing trailing NULL character.

Cause	A host variable of external data type 5 was not terminated with a NULL character.
Action	Add NULL to the end of the character string.

9140: Invalid iteration count.

Cause	Invalid iteration count.
Action	Iteration count must contain an integer value of 1 or greater.

9141: Invalid parameter data length (dynamic method 4)

Cause	Invalid parameter data length (dynamic method 4)
Action	Set the variable length to a correct value.

9142: Semantics check failed during the communication process.

Cause	Failed to check semantics with the server due to communication problems.
Action	Check the communication status with server.

9143: Fails to read ESQL Configuration File.

Cause	Possible causes include insufficient permissions, the file not existing, or an I/O error.
Action	Execute the 'gen_esql_cfg.sh' file from the '\$TB_HOME/client/config' directory or check if the current user has read and write access to the configuration file.

9144: Invalid 'EXEC SQL INCLUDE' statement.

Cause	Invalid EXEC SQL INCLUDE statement.
Action	Modify the syntax of the EXEC SQL INCLUDE statement.

9145: Invalid parameter data type (dynamic method 4)

Cause	Invalid parameter data type (dynamic method 4)
Action	Check whether the variable type is valid.

9146: Invalid parameter data type (ANSI dynamic method 4)

Cause	Invalid type of bind variable (ANSI type dynamic SQL method 4).
Action	Verify that the bind variable type is valid.

9147: Expression was previously declared with a specific database connection.

Cause	The expression used in PREPARE was previously declared to use a particular database connection.
Action	Do not use an AT clause, or modify the DECLARE clause.

9148: Unable to use ESQL statement in ordinary C include file.

Cause	An ESQL statement is used in an included header file.
Action	To use an ESQL statement, use an EXEC SQL INCLUDE statement.

9150: Unable to open directory '%1\$s': Permission denied.

Cause	Not authorized to access this directory.
Action	Receive authorization to open the directory.

9151: '%1\$s' is not a directory.

Cause	The path after #include does not specify a valid directory.
Action	Specify a valid directory.

9152: Precision or scale is out of range.

Cause	The precision or scale of the declared type is out of range.
Action	Check the precision or scale, and enter a value that is within range.

9153: Dynamic SQL is not DML.

Cause	The SQL is not DML.
Action	Check the SQL.

9154: Dynamic SQL is DDL.

Cause	The SQL is DDL.
Action	Check the SQL.

9155: Dynamic SQL is PSM.

Cause	The SQL is PSM.
Action	Check the SQL.

9156: The size of esql log file is wrong.

Cause	The size of log file is too large or too small.
Action	Check the esql config file, enter a value that is within the range(>= 1M and <= 1G).

9157: The length in the host variable is wrong.

Cause	The lengths in the host variable and in the length field do not match.
Action	Check the code and fix the length field of SQLDA or the length in the host variable(VAR CHAR or other type).

9158: The number of bind variables does not match the number of attributes.

Cause	The number of bind variables does not match the number of attributes.
Action	Check the numbers of bind variables and attributes.

9159: Unable to create output file '%1\$s'.

Cause	Output file name is same with Input file name.
Action	Verify that the output file name is different from input file name.

9160: Multiple output files were specified.

Cause	Two or more output files were specified.
Action	Specify only one output file.

9161: Ambiguous variable '%1\$s' is referenced.

Cause	Ambiguous variable '%1\$s' is referenced.
Action	Check the host variable.

9162: Database name is too long.

Cause	Database name must be less than 128 bytes.
Action	Reduce the size of the database name.

9163: Invalid dynamic SQL method-2.

Cause	The dynamic SQL statement must not be a query (SELECT statement).
Action	Use a dynamic SQL method 3, 4 or modify the dynamic SQL.

9164: Struct Indicator member count does not match struct host variable member count.

Cause	The number of struct indicator members is different from the number of struct host variable members.
Action	Check the number of struct indicator members.

9165: Invalid PL/1 syntax.

Cause	Invalid PL/1 syntax.
Action	Verify that the PL/1 syntax is correct.

9166: Database was not installed successfully.

Cause	Database was not installed successfully.
Action	Execute the install batch file in the bin directory of the Database Home.

9167: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function has yet to be implemented.

9168: Failed to free CLI ENVIRONMENT HANDLE.

Cause	Failed to free CLI ENVIRONMENT HANDLE while deleting esql context manager
Action	Check the statements related to ENVIRONMENT HANDLE.

9169: Not yet Implemented

Cause	This feature is currently not available.
Action	Please go around the problem or contact the manufacturer.

9170: Error code from Oracle

Cause	Error has occurred while interacting with Oracle binary.
Action	Please check error code(sqlca.oracode) from Oracle's error utility.

9171: Failed to return CLI HANDLE.

Cause	Unable to find expected CLI HANDLE.
--------------	-------------------------------------

Action	Check the status of the connection or the parameters for ESQGetHandle().
---------------	--

9172: ODBC connection is closed or failed to connect.

Cause	ODBC connection is closed or failed to connect.
Action	Check the status of the connection or ID/PASSWD.

9173: Invalid COBOL syntax '%1\$s'.

Cause	Invalid COBOL syntax.
Action	Verify that the COBOL syntax is correct.

9174: using WHERE CURRENT OF on cursor defined without FOR UPDATE clause

Cause	using WHERE CURRENT OF on cursor defined without FOR UPDATE clause
Action	Check the cursor statement whether FOR UPDATE clause is defined or not

9175: ODBC general error

Cause	General error(HY000) caused by ODBC
Action	Check the error message on application

제10장 10000 ~ 10999

10001: Cursor pool overflow.

Cause	The cursor pool is full.
Action	Increase the size of the pool.

10003: Data is too long to be bound to the specified type.

Cause	The amount of data exceeds the maximum allowed of the type to which it will be bound.
Action	Modify the length of the data.

10004: Cannot use UNION command on these tables or views.

Cause	Cannot perform the UNION operation for the given tables or views.
Action	Check that the numbers of columns are equal and that the types of each column are compatible.

10005: NOT NULL constraint violation (\'%1\$s\'.\'%2\$s\'.\'%3\$s\').

Cause	An attempt was made to insert the NULL value into a column where the NOT NULL constraint is specified.
Action	Remove the NOT NULL constraint, or insert a value that is not NULL.

10006: CHECK constraint violation (\'%1\$s\'.\'%2\$s\').

Cause	The inserted value(s) do(es) not satisfy the existing CHECK condition.
Action	Insert a value that satisfies the CHECK condition.

10007: UNIQUE constraint violation ('%1\$s'. '%2\$s').

Cause	An attempt was made to insert a duplicate value into a column where the UNIQUE constraint is specified.
Action	Cancel the UNIQUE constraint, or insert a unique value.

10008: INTEGRITY constraint violation ('%1\$s'. '%2\$s'): primary key not found.

Cause	A primary key does not exist for the foreign key.
Action	Delete the foreign key, or add a primary key.

10009: INTEGRITY constraint violation ('%1\$s'. '%2\$s'): foreign key exists.

Cause	An attempt was made to delete a primary key that is referenced by a foreign key.
Action	Delete the foreign key first and then try again.

10010: Statement does not satisfy the WHERE clause of the view.

Cause	The INSERT or UPDATE statement of the view does not satisfy the WHERE clause when the WITH CHECK OPTION is specified.
Action	Modify the DML statement to satisfy the WHERE condition clause of the view, or delete WITH CHECK OPTION of the view.

10011: SORT_AREA_SIZE is too small to accommodate all active sort operators.

Cause	There are not enough allocated sort areas.
Action	Increase the value of SORT_AREA_SIZE.

10012: Cannot pin more blocks.

Cause	Cannot process all data because the buffer cache is not big enough.
Action	Increase the value of DB_CACHE_SIZE.

10013: HASH_AREA_SIZE is too small to accommodate all active sort operators.

Cause	There are not enough allocated hash areas.
Action	Increase the value of HASH_AREA_SIZE.

10014: Maximum LEVEL value exceeded during a CONNECT BY operation.

Cause	The LEVEL value of a node exceeded the maximum during a CONNECT BY operation.
Action	Contact the technical support team.

10015: Loop detected during a CONNECT BY operation.

Cause	A loop was detected during a CONNECT BY operation.
Action	Modify the CONNECT BY clause and data so that a loop does not occur.

10016: Table mutation occurred during trigger execution.

Cause	Table mutation occurred during trigger execution.
Action	Delete the mutation.

10017: Unable to open file '%1\$s' in file scan mode.

Cause	The specified file could not be found.
Action	Check the name and directory of the specified datafile.

10018: Partition key does not map to a partition.

Cause	There is no defined partition to which the partition key is mapped.
Action	Check the definition of the partition in the corresponding table.

10019: Updating partition key column would cause a partition change.

Cause	Updating the partitioned table key will cause a partition change.
Action	Check the definition of the partition in the corresponding table.

10020: Specified row no longer exists.

Cause	The specified row does not exist.
Action	Verify that the specified row is correct.

10021: Inconsistent set of rows in source tables.

Cause	Inconsistent DML result due to a non-deterministic WHERE condition.
Action	Modify the non-deterministic WHERE condition.

10022: Empty pivot column must not exist.

Cause	There is an empty pivot column.
Action	Modify the PIVOT_PICK_COL parameter.

10023: Invalid pivot aggregation alias.

Cause	An error occurred in the string pattern that determines a column name when performing a pivot operation.
Action	Check to see if a percent (%) character is missing in the string pattern.

10024: Pivot column name must be unique for CASE or DECODE operations.

Cause	Results with the same pivot column name were selected when performing a CASE/DECODE operation.
Action	Modify the string pattern for the column names given to each set operation when performing a pivot operation.

10025: Too many pivot column names generated after calculation.

Cause	There are too many pivot column names created after calculation.
Action	Decrease the number of calculations.

10026: The REFCUR table contains invalid number of columns.

Cause	The number of columns defined in the REFCUR table does not match the actual number.
Action	Modify the REFCUR table clause to match the actual number.

10027: REFCUR table contains invalid column type.

Cause	The data type of a column defined in the REFCUR table does not match the actual data type.
Action	Modify the REFCUR table clause to match the actual data type.

10028: Number of columns specified in file '%1\$s*' and in data dictionary do not match.

Cause	The number of columns specified in the file does not match the number of columns in the data dictionary.
Action	Check the number of columns of specified in the file.

10029: Unable to read table (or index) with old snapshot.

Cause	Unable to read a table or index with an old snapshot.
Action	Use a snapshot from after the table or index was modified.

10030: Invalid WKB geometry data.

Cause	The entered WKB data is invalid.
Action	Check the WKB data.

10031: Invalid geometric object type.

Cause	An invalid geometric object type was executed.
Action	Check to see if the geometric object type is executable.

10032: Index number is out of range.

Cause	The value of N is less than 1 or larger than the number of Points in LineString.
Action	Check the N value.

10033: Invalid WKT geometry data.

Cause	The entered WKT data is invalid.
Action	Check the WKT data.

10034: Internal error: %1\$s.

Cause	An internal error occurred.
Action	Check the data.

10035: Invalid pivot expression.

Cause	Too many pivot columns were created after the operation.
--------------	--

Action	Check the query.
---------------	------------------

10036: Invalid XML.

Cause	An invalid type of XML was entered.
Action	Check the XML.

10037: Invalid XQuery.

Cause	Invalid XQuery.
Action	Check the XQuery syntax.

10038: Comparing multi-valued pivot columns is restricted.

Cause	Comparing multi-valued pivot columns is restricted.
Action	Check whether the pivot columns have multi values.

10039: Invalid text query syntax.

Cause	Invalid query syntax of the text.
Action	Check the query syntax.

10040: No more stop words can be inserted.

Cause	Cannot add another stop word for the text.
Action	Check the number of stop words.

10041: The text index is invalid.

Cause	The text index is not available.
Action	Check the text index status.

10042: A multi valued result is not allowed.

Cause	Multi valued results are not allowed.
Action	There are multiple results for XPath in the XML.

10043: Invalid XPath expression.

Cause	Invalid XPath expression.
Action	Check the XPath expression.

10044: Invalid child value.

Cause	Invalid child value.
Action	Check the child value.

10046: XML library error '%1\$s'.

Cause	An error occurred in an external XML library.
Action	Check the error message.

10047: XQuery type mismatch.

Cause	The return type of XQuery does not match the declared column type.
Action	Change the type of the column.

10048: XPath does not point to a leaf node.

Cause	The given XPath does not indicate a leaf node.
Action	Modify XPath to indicate a leaf node.

10049: XPath does not point to a single node.

Cause	The given XPath has multiple nodes.
--------------	-------------------------------------

Action	Modify XPath to have only one node.
---------------	-------------------------------------

10050: Size of datatype is too small to serialize the XML document.

Cause	The size of the data type to serialize the XML document is too small.
Action	Increase the data type size.

10051: Invalid XML namespace.

Cause	The format of the XML namespace is invalid.
Action	Check whether the format is 'xmlns:<prefix>=<href>'.

10052: The XML document is too big for the DOM tree.

Cause	The XML document is too big for the DOM tree.
Action	Decrease the size of the XML document.

10053: It is impossible to bind two or more LOBs or LONG data together.

Cause	It was attempted to bind two or more LOBs or LONG data through the remote database.
Action	Check the SQL and change it.

10054: The table needs more tablets.

Cause	Add tablets to the table
Action	

10055: The table needs more tablets for bucketno '%1\$d'.

Cause	Add '%1\$d' bucketno tablets to table.
Action	

10062: Unable to access LONG or LOB columns through RemoteDB.

Cause	An attempt was made use RemoteDB to refer to an object with LONG or LOB columns.
Action	Modify the query.

10063: The cached remote table information does not match the actual remote table's information.

Cause	The remote table definition (number of columns, type, or length) has changed.
Action	Try again.

10064: Loop detected during %1\$s operation.

Cause	A loop was detected during a %1\$s operation.
Action	Modify the %1\$s clause or data so that a loop does not occur.

10065: There are too many Aggregate functions.

Cause	Cannot be executed in parallel or in multiple passes.
Action	Cannot be executed in parallel or in multiple passes.

10066: Invalid TSN value.

Cause	The TSN value of the flashback query must be greater than 0.
Action	Use a valid TSN value.

10067: The policy check constraint is violated.

Cause	The data to be added or updated does not satisfy the policy predicate.
Action	None

10068: The number of columns in the cached remote table does not match the number of columns in the remote table. (local: %1\$d, remote: %2\$d)

Cause	The number of columns in the remote table has changed, or the number of columns in the REFCUR/PROC table has been incorrectly set.
Action	Retry or modify the number of columns in the REFCUR/PROC table.

10069: The column length of the cached remote table is shorter than the column length of the remote table. (column: %1\$d, local: %2\$d bytes, remote: %3\$d bytes)

Cause	The column length of the remote table has changed, or the column length of the REFCUR/PROC table has been incorrectly set.
Action	Retry or modify the column length of the REFCUR/PROC table so that it is longer than or the same as the column length of the remote table.

10070: The column type of the cached remote table does not match the column type of the remote table. (column: %1\$d, local: %2\$s, remote: %3\$s)

Cause	The column type of the remote table has changed, or the column type of the REFCUR/PROC table has been incorrectly set.
Action	Retry or modify the column type in the REFCUR/PROC table.

10071: Cannot assign a process to execute the global view.

Cause	All processes are currently in use.
Action	Increase the number of processes or terminate another session.

10072: Cannot assign a thread to execute the global view.

Cause	All threads are currently in use.
Action	Increase the number of threads or terminate another session.

10073: Response time for the global view exceeded threshold.

Cause	Global view search is taking a long time or there is a network problem.
Action	Increase the response time limit for the global view.

10074: An error occurred while executing the '%1\$s' function.

Cause	Check the definition of the object type.
Action	Modify the definition of the object type and regenerate it.

10075: Exceeds the reject limit.

Cause	Exceeds the reject limit.
Action	Modify the data or increase the reject limit.

10076: Received a GV error reply(ec=%1\$d) from session %2\$d.

Cause	One of GV sessions sent an error reply.
Action	Check the error of the error-occurred session in the log file.

10077: The pattern used with the LIKE operator is too long.

Cause	The pattern used with the LIKE operator is too long.
Action	Check the pattern used with the LIKE operator.

10078: Partial multibyte character found.

Cause	Character set conversion did not occur due to partial multibyte character or buffer overflow.
--------------	---

Action	Check the data.
---------------	-----------------

10079: catsearch does not support functional invocation.

Cause	catsearch does not support functional invocation.
Action	Check the catsearch syntax.

10080: DML rolled back due to index integrity.

Cause	The current DML was rolled back because it caused index integrity violation.
Action	Check the tracedump.

10081: Communication between Tibero and storage server failed.

Cause	Communication between Tibero and storage server failed.
Action	Check the information of storage server.

10082: This function is not supported in current envrionment.

Cause	This function is not supported in current envrionment.
Action	Contact the technical support team.

10083: Cannot assign a process to execute the in-memory column store.

Cause	All processes are currently in use.
Action	Increase the number of processes or terminate another session.

10084: Cannot assign a thread to execute the in-memory column store.

Cause	All threads are currently in use.
--------------	-----------------------------------

Action	Increase the number of threads or terminate another session.
---------------	--

10085: Response time for the in-memory column store exceeded threshold.

Cause	In-memory column store scan is taking a long time or there is a network problem.
Action	Increase the response time limit for the in-memory column store scan.

10086: Received an in-memory column store error reply(ec=%1\$d) from session %2\$d.

Cause	One of in-memory column store sessions sent an error reply.
Action	Check the error of the error-occurred session in the log file.

10087: The status of a remote node has been changed while executing in-memory column store scan.

Cause	The status of a remote node has been changed.
Action	Check the status of the remote node and execute the SQL statement again.

10088: Invalid token length (Allowable length: 1 to 64 bytes, current length: %1\$d bytes)

Cause	An invalid token length was encountered while generating a text index.
Action	Check the column to be indexed.

10089: The value for argument number %1\$d is not valid.

Cause	The value entered as the function argument is not valid.
Action	Check the value entered.

제11장 11000 ~ 11999

11001: Subquery returned a tuple where a scalar value was expected.

Cause	More than one column was returned by a subquery.
Action	Check if there are more than two columns in the selection list of the scalar subquery.

11002: Subquery returned multiple rows where a scalar value was expected.

Cause	A subquery expected to return a scalar value returned more than two rows.
Action	Check the scalar subquery.

11003: Invalid function argument type.

Cause	The function argument type is invalid.
Action	Check the declaration of the function.

11004: Invalid function argument.

Cause	The specified function argument is invalid.
Action	Check the declaration of the function.

11005: Specified value '%1\$s' is invalid for mathematical function argument(s).

Cause	The specified mathematical function argument is invalid.
Action	Check the declaration of the function.

11006: Invalid USERENV parameter.

Cause	The input is invalid for the USERENV function parameter.
Action	Ensure that the function parameter is CLIENT_INFO, ENTRYID, ISDBA, LANG, LANGUAGE, SESSIONID or TERMINAL.

11007: The TRIM set may not contain more than one character.

Cause	The first parameter of the TRIM function contains more than one character.
Action	Specify only one character for the first parameter.

11008: Escape character must be one character long.

Cause	The length of the escape character in the LIKE clause does not equal 1.
Action	Set a single character for the escape argument.

11009: Invalid use of escape character.

Cause	Invalid use of escape character.
Action	The percent sign "%", underscore "_", and the escape character itself are the only characters permitted to follow an escape character.

11010: TO_CHAR format cannot be specified for this data type.

Cause	The TO_CHAR format cannot be specified for this type.
Action	Remove the format from the function formula.

11011: TO_DATE format cannot be specified for this data type.

Cause	The TO_DATE format cannot be specified for this type.
Action	Remove the format from the function formula.

11012: TO_TIME format cannot be specified for this data type.

Cause	The TO_TIME format cannot be specified for this type.
Action	Remove the format from the function formula.

11013: TO_TIMESTAMP format cannot be specified for this data type.

Cause	The TO_TIMESTAMP format cannot be specified for this type.
Action	Remove the format from the function formula.

11014: TO_NUMBER format cannot be specified for this data type.

Cause	The TO_NUMBER format cannot be specified for this type.
Action	Remove the format from the function formula.

11015: Input parameter string is too long.

Cause	Part of the input parameter string was too long.
Action	Shorten the length of the string.

11016: Unsupported multi-byte character set in CLOB.

Cause	An attempt was made to use a CLOB with a multi-byte character set.
Action	Use single-byte character sets, or do not use a CLOB.

11017: The relational operator accepts only boolean values.

Cause	A non-boolean operand was specified for the relational operator.
Action	Verify that the operand is a boolean operand.

11018: Operator does not accept operands of the given data type.

Cause	The operand type is invalid.
Action	Input a valid operand type for the operator.

11019: Concatenation applied to invalid data type.

Cause	The CONCAT operation may not be used on this data type.
Action	Use CHAR, VARCHAR or CLOB, or use a value that can be converted to one of those data types.

11020: String concatenation result is too long.

Cause	The result of a string concatenation is too long.
Action	Make sure that the total length of the concatenation result 65,531.

11021: Error occurred during type casting.

Cause	An attempt was made to convert the data type to an invalid data type.
Action	Check the specified data type.

11022: Values are from incompatible data types.

Cause	The values are from incompatible data types.
Action	Modify the data types to be compatible.

11023: Values are from data types that cannot be compared.

Cause	The values are from incomparable data types.
Action	Modify the data types to be comparable.

11024: Cardinality mismatch found during group comparison.

Cause	During a group comparison operation, the number of values on either side did not match.
Action	Match the lengths of tuples on both sides of the comparison.

11025: Data is too long for the column.

Cause	The data length is too long for the column.
Action	Shorten the data length.

11026: Data is too long to be converted to CHAR/VARCHAR/RAW data type.

Cause	The data length exceeds the allowed length of a RAW, CHAR or VARCHAR type.
Action	Modify the data length or change the data type.

11027: String is not in hexadecimal form.

Cause	The string is not in hexadecimal form.
Action	Check that the string correctly follows hexadecimal form.

11028: Parameter mismatch occurred in the user-defined function.

Cause	Either the number of specified parameters does not match the required number or the omitted parameter is undefined.
Action	Ensure the number of specified parameters is correct and the parameters are valid.

11029: No function matches the specified argument(s).

Cause	No function matches the specified list of arguments.
Action	Check the argument data type.

11030: Multiple functions match the specified argument(s).

Cause	More than one function matches the specified list of arguments.
Action	Check the argument data type.

11031: A function in the SQL statement has output parameter(s).

Cause	Functions that have the output parameter(s) can only be call in a CALL statement.
Action	Check the definition of the function.

11032: An invalid data type was returned by the PSM function.

Cause	The return type of the PSM function is invalid.
Action	Check that the return type of the PSM function can be processed in an SQL statement.

11033: Insufficient columns for update.

Cause	The number of columns returned by the subquery in the UPDATE SET clause is insufficient.
Action	Check the number of columns in the UPDATE SET clause.

11034: Too many columns for update.

Cause	The number of columns returned by the subquery in the UPDATE SET clause is too large.
Action	Check the number of columns in the UPDATE SET clause.

11035: Invalid NLS parameter exists in SQL function.

Cause	An invalid NLS parameter exists in an SQL function.
Action	Check the NLS parameter.

11036: Alias is required.

Cause	An alias was not specified for a non-column expression.
--------------	---

Action	Specify an alias.
---------------	-------------------

11038: Percentile value must be between 0 and 1.

Cause	The percentile value must be between 0 and 1.
Action	Verify that the percentile is correct.

11039: Invalid SYS_CONTEXT namespace.

Cause	The namespace is invalid for the SYS_CONTEXT function.
Action	Ensure that the parameter of the function is USERENV.

11040: Invalid NLSSORT linguistic definition.

Cause	The linguistic definition is invalid for the NLSSORT function.
Action	Verify that the parameter is correct.

11041: Unsupported character set in regexp function.

Cause	The character set is not supported in the regexp function.
Action	Specify another character set.

11042: Invalid regular expression in regexp function.

Cause	An invalid regular expression was used in the regexp function.
Action	Correct the regular expression.

11043: Unsupported character set was described.

Cause	The character set is not supported.
Action	Check the character set.

11044: Invalid UNISTR argument.

Cause	The UNISTR argument is invalid.
Action	Check the UNISTR function.

11045: A function in the SQL statement has non-primitive type parameter(s).

Cause	Functions that have the non-primitive parameter(s) can only be called from a CALL statement.
Action	Check the definition of the function.

11046: A function in the SQL statement has non-primitive type parameter(s).

Cause	Functions that have the non-primitive parameter(s) can only be called from a CALL statement.
Action	Check the definition of the function.

11047: Bind parameter or expression is not allowed in the given position.

Cause	A bind parameter or expression cannot be used in the given position.
Action	Use a constant(number or string literal).

11048: \"%1\$s\".\"%2\$s\".\"%3\$s\" The value is too large for the column. (Actual value: %4\$d, Maximum value: %5\$d)

Cause	The data length is not appropriate for the column.
Action	Shorten the data length.

11050: The length of the source document used in the regular expression function is too long.

Cause	The length of the source document used in the regular expression function is too long.
Action	Check the value of iparam_EX_REGEX_CLOB_MAX_LEN.

11051: The length of the result returned by the REGEXP_REPLACE function is too long.

Cause	The length of the result returned by the REGEXP_REPLACE function is too long.
Action	Check the query.

11052: The object cannot be updated or inserted as NULL.

Cause	The value of an object in an object table or a nested table cannot be NULL.
Action	Check the query.

11053: The file name specified for With Materialization is invalid.

Cause	The specified file cannot be created.
Action	Check the file name.

11054: The input type is invalid.

Cause	This data type cannot be used when the method is invoked using a call statement.
Action	Check how the method was invoked, and that you are not using a psm data type as a parameter.

11055: The output format is invalid.

Cause	The output format does not comply with the format rule.
Action	Check the output format.

11056: The mask character is too long.

Cause	The mask character must be in one character.
Action	Check if the mask character has more than one character.

11057: The input column data have inconsistent lengths.

Cause	The input column data must have consistent length.
Action	Check if the input column data have consistent length.

11058: The input format is invalid.

Cause	The input format must consist of 'V' or 'F'.
Action	Check if the input format has characters other than 'V' or 'F'.

11059: This character set conversion is not supported.

Cause	The CONVERT function does not support conversion between the two character sets.
Action	Use a character set that is supported by the CONVERT function.

11060: The JSON document is invalid.

Cause	The JSON document does not conform to JSON syntax.
Action	Check the JSON document.

11061: The JSONPath is invalid.

Cause	The JSONPath does not conform to JSONPath syntax.
Action	Check the JSONPath.

11062: JSON Function Error.

Cause	An error occurred in JSON Function.
--------------	-------------------------------------

Action	Check the JSON function arguments.
---------------	------------------------------------

11063: The number of elements exceeds the maximum varray size allocated to varray.

Cause	Cannot insert an element in excess of the maximum varray size.
Action	Modify the query to insert fewer elements than the varray size.

11064: Cycle mark and non-cycle mark values must be one-byte character string values.

Cause	The cycle mark or non-cycle mark values specified in the CYCLE clause of a recursive WITH query are not one-byte character string values.
Action	Specify a one-byte character string for the cycle mark and non-cycle mark values.

11065: The result value is too large. (Actual value: %1\$d, Maximum value: %2\$d)

Cause	The length of the result data does not match the length of the output type.
Action	Extend the length of the output type.

11066: JSON_VALUE has no result.

Cause	There is no result for JSONPath expression.
Action	Check the JSONPath expression.

11067: The JSON_VALUE result is a non-scalar value.

Cause	The result for JSONPath expression is a non-scalar value.
Action	Check the JSONPath expression.

11068: The JSON_QUERY result is a scalar value.

Cause	The JSON_QUERY result without the WRAPPER clause is a scalar value.
Action	Check the WRAPPER clause.

11069: The JSON_VALUE nested expressions are not separated.

Cause	The JSON_VALUE nested expressions are not separated.
Action	Check the nested path expressions.

11070: The result value is too large (Maximum value: %1\$d)

Cause	The length of the result data does not match the length of the output type.
Action	Extend the length of the output type.

11071: The Patch JSON document is invalid.

Cause	The Patch JSON document does not conform to JSON syntax.
Action	Check the Patch JSON document.

11072: The Truncate keyword is not supported with data type in RETURNING clause.

Cause	The Truncate keyword is not supported with data type in RETURNING clause.
Action	Check the data type in RETURNING clause.

11073: The default value is not compatible with the data type in RETURNING clause.

Cause	The default value is not compatible with the data type in RETURNING clause.
Action	Check the data type of default value.

11074: The key in the JSON object created by the JSON function is null.

Cause	A key in a JSON object created by the JSON function cannot be null.
Action	Check the value corresponding to the key of the JSON object.

11075: The JSON object has duplicate keys.

Cause	The JSON object has duplicate keys.
Action	Check the value corresponding to the key of the JSON object.

11076: The return data type cannot be used with the PRETTY or ASCII option.

Cause	The data type specified in the RETURN clause cannot be used with the PRETTY or ASCII option.
Action	Check the data type specified in the RETURN clause.

11077: The column used for sorting is LOB type.

Cause	Column of LOB type cannot be used for sorting.
Action	Check the column type used for sorting.

11078: Unable to create the collation key.

Cause	The argument is too long to create a collation key.
Action	Shorten the argument.

11079: Offset or offset+amount does not align with a character boundary.

Cause	Offset or offset+amount does not align with a character boundary.
--------------	---

Action	Ensure that the offset and/or offset+amount values are adjusted to align with a character boundary.
---------------	---

제12장 12000 ~ 12999

12001: Session has been closed.

Cause	The session was terminated by a system administrator or system timer.
Action	Try to reconnect.

12002: Requested session was not found.

Cause	The required session could not be found.
Action	Double check the session ID and serial number.

12003: Unable to open a session.

Cause	The maximum number of sessions are already open.
Action	Close the other open sessions, or shut down the server, increase the maximum number of sessions, and restart the server.

12004: Unable to connect: DBMS server is in recovery mode.

Cause	Unable to connect to the server since the DBMS server is currently in a recovery process.
Action	Wait until the recovery process is completed.

12005: Unable to connect to the DBMS server.

Cause	The listener blocked the current client's IP address from access to the DBMS server.
Action	Contact the DBA or the technical support team about the IP filtering policy.

12006: Session is not open for this connection.

Cause	A request occurred for a session that was not opened.
Action	Open the session or log on.

12007: Requested cursor [%1\$d] was not found.

Cause	The required cursor has been closed.
Action	If the request was to close a cursor, the request was fulfilled.

12008: Unable to open new cursor: too many cursors are in use.

Cause	The maximum number of cursors was already open.
Action	Close the other open cursors, or modify the OPEN_CURSORS initialization parameter.

12009: Unable to change isolation level of an active transaction.

Cause	The transaction is in progress.
Action	Retry after committing or rolling back the transaction.

12010: No transaction exists to set a savepoint.

Cause	There is no transaction to set a savepoint.
Action	A transaction is necessary to set a savepoint.

12011: Unable to open the session.

Cause	One of the session slots has an internal problem.
Action	To use the session slot, reboot the system or contact the technical support team.

12012: Session is already open.

Cause	The session is already ACTIVE or RUNNING.
--------------	---

Action	To change the session state, use the 'session kill' command.
---------------	--

12013: A session cannot terminate itself.

Cause	A session attempted to terminate itself through a 'session kill' command.
Action	Double check the session ID and serial number.

12014: Transaction control statements are not allowed in XA transactions.

Cause	An attempt was made to use a transaction control statement in XA mode.
Action	Transaction control statements cannot be used in XA mode.

12015: Active autonomous transaction detected and rolled back.

Cause	An autonomous transaction has not been closed.
Action	Commit or roll back within the trigger or in the procedure.

12016: Specified DATE/TIME/TIMESTAMP format is too long: '%1\$s'.

Cause	The format of DATE, TIME or TIMESTAMP is too long.
Action	Shorten the format string.

12017: Temporary table '%1\$s' is being used by another transaction.

Cause	Another transaction is using the temporary table.
Action	Commit the transaction, and try to access the table again.

12018: Invalid PPID.

Cause	The PPID is invalid.
Action	Check the protocol version.

12019: Unable to execute batch update: invalid array binding count detected.

Cause	Invalid number of bindings.
Action	Check the protocol version.

12020: Unable to execute SQL statement.

Cause	The SQL statement cannot be executed in the current server mode.
Action	Change the server mode and retry the statement.

12021: Only SYS user can log on in restricted boot mode.

Cause	Only the SYS user can log on in the current boot mode.
Action	Log on as SYS user.

12022: Authentication failed: invalid password.

Cause	The password is invalid.
Action	Enter the correct password.

12023: Unrecognized SQL statement: invalid grammar.

Cause	The SQL statement cannot be parsed.
Action	Verify that the SQL statement is correct and retry.

12024: SQL queries cannot be submitted during batch updates.

Cause	Queries are not allowed during a batch update.
Action	Don't use queries during batch updates.

12025: Only procedure-type PSMs are allowed during batch updates.

Cause	Function-type PSMs are not allowed during batch update.
Action	Use only procedure-type PSM during batch update.

12026: Output parameters cannot be used during batch updates.

Cause	An attempt was made to use an output parameter during a batch update.
Action	Output parameters are not allowed during batch updates.

12027: Database name is too long.

Cause	The DB name is too long.
Action	Choose a shorter name for the DB.

12028: Only DDL statements are allowed in NOMOUNT boot mode.

Cause	Only DDL statements are allowed in the NOMOUNT mode.
Action	Check the boot mode and the SQL statement.

12029: Unable to execute the prepared statement: invalid number of parameters.

Cause	The number of parameters specified does not match the number required by the physical plan.
Action	Check the protocol version.

12030: Unable to handle unexpected incoming message type %1\$d.

Cause	An unexpected protocol was received.
Action	Check that the protocol is from a valid context.

12031: Invalid cursor state.

Cause	The cursor state is invalid because the DDL statement was executed during fetch.
Action	Check the object at which the cursor was pointed.

12032: Deadlock detected.

Cause	Deadlock detected.
Action	Retry the transaction.

12033: Lock acquisition failed in NOWAIT mode.

Cause	Lock acquisition failed in NOWAIT mode.
Action	Wait a moment and try again.

12034: Lock acquisition timed out in WAIT mode.

Cause	Lock acquisition failed after the maximum wait time expired (lock timeout).
Action	Wait a moment and try again.

12035: Internal error %1\$d occurred.

Cause	An internal error occurred.
Action	Contact the technical support team.

12039: Server instance is shutting down.

Cause	The server instance is shutting down the system.
--------------	--

Action	The server instance is shutting down the system.
---------------	--

12040: Statement canceled.

Cause	The SQL statement was canceled during execution.
Action	Execute the SQL statement again.

12041: Local COMMIT/ROLLBACK/SAVEPOINT is not allowed in XA transactions.

Cause	Local COMMIT, ROLLBACK or SAVEPOINT was specified in an XA transaction.
Action	Local COMMIT, ROLLBACK or SAVEPOINT cannot be executed in an XA transaction.

12042: Authentication timed out.

Cause	User authentication failed after the maximum wait time expired.
Action	The connection request might have come from an invalid client; if not, increase the timeout value.

12043: RemoteDB information was not found.

Cause	No RemoteDB information could be found.
Action	Check the RemoteDB name and permissions.

12044: Unable to connect to remote database.

Cause	Cannot access the remote DB.
Action	Check the RemoteDB host information.

12048: Unknown service requested.

Cause	The request is for an unknown service.
--------------	--

Action	Verify the request is from a valid context.
---------------	---

12049: Return clauses cannot be used during batch updates.

Cause	A return clause cannot be used during batch updates.
Action	Remove the return clause.

12050: Connection error. Connect to a different server.

Cause	The server may be in standby or not yet open.
Action	Access a different server.

12051: Unable to change server mode (%1\$s).

Cause	The server mode cannot be changed.
Action	Check the cause of failure and try again.

12052: Cannot commit with RemoteDB.

Cause	Two-phase commit with remote database has failed.
Action	Check the target DB server and restart transaction.

12054: In-doubt transactions.

Cause	The transactions are in an in-doubt state.
Action	Check the status of the remote DB and resolve the in-doubt state.

12055: Transaction rolled back. Some remote DBs may be in doubt.

Cause	There is a possibility that a remote DB is in an in-doubt state after the transaction was rolled back.
Action	Check the status of the remote DB.

12056: Remote database is in use.

Cause	A transaction is using the remote database.
Action	Try again after the transaction is completed.

12057: Remote database is not open.

Cause	The remote database is not connected.
Action	Check the remote database name.

12058: Remote connection was lost. Transaction rollback required.

Cause	The connection to the remote server was severed, so the current transaction must be rolled back.
Action	Roll back the current transaction.

12059: Remote statement failed due to (ec=%1\$d): \n%2\$s.

Cause	An error occurred with the remote server.
Action	Resolve the problem by referring to the remote server, and then try again.

12060: DBMS server is experiencing heavy load: connect to another instance.

Cause	Unable to connect to DBMS server; the server is under heavy load.
Action	Try to connect to another instance, or tweak load balancing settings.

12064: Unable to alter the session PDML state within a transaction.

Cause	PDML cannot be enabled or disabled in the middle of a transaction.
Action	Commit or roll back the active transaction.

12066: Unable to read or modify an object after modifying it with PDML.

Cause	An attempt was made to read or modify a table which was already modified with PDML in the current transaction.
Action	This command cannot be executed.

12067: Unable to modify an object with PDML after modifying it.

Cause	An attempt was made to modify a table that has already been modified with PDML in the current transaction.
Action	This command cannot be executed.

12068: Wallet is already open.

Cause	The wallet is already open.
Action	Proceed to the step following the opening of the wallet.

12069: Failed to open wallet.

Cause	Failed to open wallet.
Action	Check the password, or request the security administrator to create a new wallet.

12070: Target DB returned this message: %1\$s (target DB error code = %2\$d).

Cause	An error occurred in the target database system.
Action	Check the message received from the target database system.

12071: Unable to allocate a block transaction entry for parallel execution.

Cause	The block does not have an enough space to store transaction entries, or the DOP (Degree of Parallelism) is too large.
Action	Decrease DOP, or increase PCTFREE of the segment.

12072: Unable to allocate a slave session.

Cause	Unable to allocate a slave session for parallel processing.
Action	Increase the maximum number of server sessions, or wait until there is an available session.

12073: Wallet is not open.

Cause	Wallet is not yet open.
Action	Try again after opening the wallet.

12074: Unable to begin a global transaction.

Cause	The target database system cannot start a global transaction.
Action	Check the state of the target database system and gateway.

12075: Workload repository table does not exist.

Cause	There is no workload repository table.
Action	Try again after opening the wallet.

12076: Retry the attempted action.

Cause	The SQL need to be run again because the materialized view freshness has been corrupted.
Action	Try again.

12077: Commit request from the remote DB to commit the global transaction.

Cause	(Internal Error) The remote DB requested to commit the global transaction.
Action	Contact the technical support team.

12078: Rollback request from the remote DB for the global transaction.

Cause	The remote DB requested to roll back the global transaction.
Action	Internal message.

12079: The requested DB_NAME does not match with the server DB_NAME.

Cause	The DB_NAME specified in the client does not match the DB_NAME in the server.
Action	Check the DB_NAME in the server and try to connect again.

12080: Unable to generate SSL ctx.

Cause	Unable to create the SSL ctx structure.
Action	Check the server status and try again.

12081: Failed to load the SSL user certificate file.

Cause	Failed to load the server certificate.
Action	Check the path of the server certificate file.

12082: Failed to load the SSL private file.

Cause	Failed to load the private key.
Action	Check the path of the private key file.

12083: Unmatched SSL public key.

Cause	The certificate and the private key do not match.
Action	Check the certificate and the private key.

12084: Failed to generate the SSL structure.

Cause	Failed to generate the SSL structure from the SSL ctx.
Action	Check the server status and try again.

12085: Failed to accept from client ssl connection.

Cause	Failed to connect to the client.
Action	Check the client status and the server status.

12086: Incoming SQL is empty.

Cause	The requested SQL is empty.
Action	Check the SQL statement and try again.

12087: Failed to open the wallet.

Cause	The wallet is not yet closed.
Action	Check if the wallet is completely closed and retry the statement.

12088: The table for the performance monitoring function does not exist.

Cause	The table for the performance monitoring function does not exist or user does not have admin authority.
Action	Get admin authority or create the table again with the system.sh.

12089: The specified snapshot between '%1\$s' and '%2\$s' does not exist.

Cause	Among the saved snapshots, the snapshot between '%1\$s' and '%2\$s' does not exist.
Action	Check if the snapshot exists and try again.

12090: Unable to open the report file '%1\$s'.

Cause	Failed to create the file '%1\$s' in order to generate the report file.
Action	Ensure files can be created and try again.

12091: The performance monitoring function is deactivated.

Cause	Unable to execute the function due to the deactivated performance monitoring function.
Action	Set the performance monitoring on.

12092: Binding a deferred parameter is not allowed in an anonymous block.

Cause	Binding a deferred parameter in an anonymous block has not yet been implemented.
Action	Bind a non-deferred parameter.

12093: Invalid protocol message is arrived.

Cause	There is a problem in the slave server or the session.
Action	Check the status of the slave server or the session.

12094: The remote session is closed.

Cause	The remote session is closed.
Action	Do not send a message to the remote session.

12096: Unable to modify the size of TCP send buffer.

Cause	The TCP send buffer size was not modified.
Action	Contact the technical support team.

12097: Unable to modify the size of TCP send buffer.

Cause	The TCP send buffer size was not modified.
Action	Contact the technical support team.

12098: There are too many open cursors using the same physical plan object or data dictionary object.

Cause	This error occurs if clients leave cursors open for an extended amount of time.
Action	Contact the technical support team.

12099: Read message timeout.

Cause	Reading message from the client failed after the maximum wait time expired. Server closed connection to client.
Action	Check the status of the client.

12100: Active session timed out.

Cause	Active session timed out after the maximum wait time expired.
Action	Increase the active session timeout value.

12101: Can't fill the shared pool with dummy chunks. The reserve size is invalid.

Cause	The reserve size is negative or larger than the maximum chunk size limit of the shared pool.
Action	Check the reserve size.

12102: Can't fill the shared pool with dummy chunks. Reserve size is too big.

Cause	The available shared pool size is smaller than the reserve size.
Action	Check the reserve size.

12103: Can't fill the shared pool with dummy chunks. A Fill or Sweep operation is in progress by another session.

Cause	A Fill or Sweep operation is in progress by another session.
Action	Retry after the other session has ended.

12104: Can't sweep off the dummy chunks in the shared pool. A Fill or Sweep operation is in progress by another session.

Cause	A Fill or Sweep operation is in progress by another session.
Action	Wait a while and retry the command.

12105: The mode 2 batch update failed.

Cause	The mode 2 batch update failed for the bound data.
Action	Check the bound data.

12106: SQL Plan History table does not exist.

Cause	One or more SQL Plan History tables do not exist.
Action	Create the tables.

12107: Parameter value is out of range.

Cause	One or more SQL Plan History parameter values are out of range.
Action	Check the parameter values first.

12108: Fatal error occurred during loading initialization parameter.

Cause	Initialization parameter is invalid.
Action	Check the initialization parameter first.

12109: Appropriate node not found.

Cause	No node found in given condition.
Action	Check the node group mapping.

12110: Session has been cleaned.

Cause	The session was cleaned by a system administrator
Action	Check the target session is clean

12111: Unable to read or modify an object after modifying it with DPL/DPI.

Cause	An attempt was made to read or modify a table which was already modified with DPL/DPI in the current transaction.
Action	This command cannot be executed.

12112: The database trigger '%1\$s' contains an error.

Cause	An existing database trigger may be invalid or has generated an error during execution.
Action	Check the trigger.

12113: The policy function or package %1\$s.%2\$s contains an error.

Cause	The policy function cannot be executed because it is invalid or has an error.
Action	Recheck the function definition.

12114: The RLS policy cannot be attached to this object.

Cause	RLS policy can only be attached to tables, views, and synonyms.
Action	Check the object.

12115: The performance monitoring function is not started.

Cause	The performance monitoring function is being started.
Action	Wait a moment and try again.

12116: Encryption not supported.

Cause	This version does not support encryption.
Action	Try another version of the product.

12117: The ASH function is deactivated.

Cause	Unable to execute the function due to the deactivated ASH function.
Action	Set the ACTIVE_SESSION_HISTORY to 'Y'

12119: User argument error for Benchmark execution.

Cause	Check the argument values specified in the DDL.
Action	Change the argument values and try again.

12120: Transaction rolled back.

Cause	Transaction rolled back.
Action	Check constraints.

12121: The given set of wlock id and tid is invalid.

Cause	No wlock is found using the given wlock id and tid.
--------------	---

Action	Check the wlock id and tid.
---------------	-----------------------------

12122: Only SYSADM user can log on in restricted boot mode.

Cause	Only the SYSADM user can log on in the current boot mode.
Action	Log on as SYSADM user.

12123: An attempt to begin sysdump has failed.

Cause	An attempt to stop processes for sysdump has failed.
Action	Wait a moment and try again.

12124: Invalid error code - %1\$u.

Cause	The specified error code was not found.
Action	Check the error code.

12125: Remote database is read-only.

Cause	The remote database is read-only, so the DML is not allowed.
Action	Check the configuration of the remote database, and remake the remote database as normal mode if needed.

12126: Remote database client API error - %1\$s

Cause	An error occurred while using the client API via remote database.
Action	Check the error message for the client API.

12127: Invalid PPID.

Cause	The PPID is invalid.
Action	Check the protocol version.

12128: Statement canceled by DDL.

Cause	The SQL statement was canceled by DDL execution.
Action	Execute the SQL statement again.

12129: Failed to decompress batch update messages.

Cause	Failed to decompress batch update messages.
Action	Check the client library.

12130: Unable to connect to remote database(RemoteDB_name=%1\$s).

Cause	Cannot access the remote DB.
Action	Check the RemoteDB host information.

12131: External TDE package is not open.

Cause	External TDE package is not yet open.
Action	Try again after opening the external TDE package.

12132: External TDE package is already opened.

Cause	Function can not be used simultaneously.
Action	Remove parameter in tip file.

12134: Remote database is not allowed in distributed transaction.

Cause	Remote Database is not allowed in distributed transaction.
Action	Retry after distributed transaction is over.

12135: Commit/Rollback force is allowed for prepared transaction only.

Cause	Commit/Rollback force is allowed for prepared transaction only.
Action	Prepare RemoteDB transaction or rollback.

12136: The address of initialization parameter is NULL.

Cause	The address of initialization parameter is NULL.
Action	The address of initialization parameter is NULL.

12137: The requested SERVICE_NAME does not match with the server SERVICE_NAME.

Cause	The SERVICE_NAME specified in the client does not match the SERVICE_NAME in the server.
Action	Check the SERVICE_NAME in the server and try to connect again.

12138: The requested ILOG_NAME does not match with the server ILOG_NAME.

Cause	The ILOG_NAME specified in the client does not match the ILOG_NAME in the server.
Action	Check the ILOG_NAME in the server and try to connect again.

12139: The requested ILOG_TAG does not match with the server ILOG_TAG.

Cause	The ILOG_NAME specified in the client does not match the ILOG_TAG in the server.
Action	Check the ILOG_TAG in the server and try to connect again.

12140: The requested GENERATE_KEY is not working properly.

Cause	The requested GENERATE_KEY is not working properly.
Action	The requested GENERATE_KEY is not working properly.

12141: The requested GET_KEY is not working.

Cause	The requested GET_KEY is not working.
Action	The requested GET_KEY is not working.

12142: The requested GET_KEY or GENERATE_KEY is not working.

Cause	The requested GET_KEY or GENERATE_KEY is not working.
Action	The requested GET_KEY or GENERATE_KEY is not working.

12143: The requested GET_KEY or GENERATE_KEY is not working.

Cause	The requested GET_KEY or GENERATE_KEY is not working.
Action	The requested GET_KEY or GENERATE_KEY is not working.

12144: AD authentication has failed.

Cause	AD authentication has failed.
Action	Check service ticket(expiration), keytab file path and AD initialization paramters.

12145: The RemoteDB query must be rerun.

Cause	The RemoteDB query needs to be rerun because the column metas of the remote table have been changed.
Action	Rerun the RemoteDB query.

12146: TTE key migration is failed.

Cause	TTE key migration is failed in the middle of modifying a datafile headerblock.
Action	Need to restore tte keys using a backup file.

12147: TTE key restoration is failed.

Cause	TTE key restoration is failed in the middle of modifying a datafile headerblock.
Action	Retry restore using a backup file.

12148: Failed to change wallet password.

Cause	Failed to change wallet password.
Action	Check status of the wallet file and check syslog for details.

12149: Failed to open service file.

Cause	Failed to open service file.
Action	Check the path of the service file.

12150: Failed to parse service file.

Cause	Failed to parse service file.
Action	Check service file dsn format.

12151: Remote connection is blocked by DBMS server.

Cause	DBMS server only allows local connection now.
Action	Try connecting with localhost.

12152: A pointer variable in the PP structure points to an invalid memory space.

Cause	The memory space preoccupied by the PP is dirty, or an invalid memory address is referenced when creating the PP.
Action	Contact technical support team. If the PP exists in the PP cache, hard parse the PP to temporarily resolve this issue.

12153: Service is not supported.

Cause	This version does not support service.
Action	Try another version of the product.

12154: Service file is not opened.

Cause	Client failed to connect with service name because service file is not opened.
Action	Check the format/path of the service file and try reboot

12156: A fatal error at RMGR session has found by the system administrator.

Cause	Session was to be terminated but hasn't due to being RMGR worker.
Action	If RMGR not working properly, please contact the technical support team.

12157: Failed to load the SSL user certificate file from active storage. (%1\$s)

Cause	Failed to load the server certificate.
Action	Check the path of the server certificate file.

12158: Failed to load the SSL private file from active storage. (%1\$s)

Cause	Failed to load the private key.
--------------	---------------------------------

Action	Check the path of the private key file.
---------------	---

12159: The wallet is in the process of being opened or closed.

Cause	The wallet is already being opened or closed in the same session.
Action	Retry after the wallet is completely opened or closed.

12160: Unable to open a session.

Cause	The maximum number of sessions are already open.
Action	Close the other open sessions, or shut down the server, increase the maximum number of sessions, and restart the server.

12161: Remote database is not set read-only.

Cause	Remote database to specific DB must be set read-only.
Action	Recreate the remote database adding read-only option.

12162: A wallet is already in use.

Cause	The wallet to be decrypted must match the encrypted wallet.
Action	Check the wallet. If you are sure you want to change the wallet, set the corresponding initialization parameters.

12163: Failed to access stack trace tool path (%1\$s).

Cause	Stack trace tool is required to dump session callstack.
Action	Make sure stack trace tool is installed.

12164: Unable to access default wallet file.

Cause	WALLET_FILE must be an accessible path to the default wallet file.
Action	Check the permissions and path of the default wallet file.

12165: Unable to access auto-login wallet file.

Cause	AUTO_LOGIN_WALLET_FILE must be an accessible path to the default wallet file.
Action	Check the permissions and path of the auto-login wallet file.

12166: The default wallet file is corrupted.

Cause	The default wallet file must not be modified arbitrarily.
Action	Replace the default wallet file with a backup copy.

12167: The auto-login wallet file is corrupted.

Cause	The auto-login wallet file must not be modified arbitrarily.
Action	Replace the auto-login wallet file with a backup copy.

12168: Failed to read the file due to a system issue.

Cause	The system must be in a state where it can read the file.
Action	Please try again later.

12169: The performance monitoring function is not started.

Cause	The performance monitoring function is being started.
Action	Wait a moment and try again.

12170: The performance monitoring function is deactivated.

Cause	Unable to execute the function due to the deactivated performance monitoring function.
Action	Set the performance monitoring on.

12171: The password for the auto-login wallet cannot be changed.

Cause	The password for the auto-login wallet cannot be changed.
--------------	---

Action	The password for the auto-login wallet cannot be changed.
---------------	---

12172: The length of the entered password is out of range(4-63).

Cause	The password length must be at least 4 and at most 63.
Action	Please enter a password that is at least 4 and at most 63 characters long.

12173: The USE_HSM parameter of the tip differs from the HSM usage in the executed command.

Cause	USE_HSM value must be set to Y to use the HSM feature, and vice versa.
Action	Update the USE_HSM setting in the TIP to match the command.

제13장 14000 ~ 14999

14001: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

14002: Invalid argument type or value.

Cause	The argument type or value is invalid.
Action	Modify the argument type or value.

14004: Package instance '%1\$s' is invalid.

Cause	The package instance is invalid and has been removed from the session.
Action	Use the package member to recreate the instance.

14009: Error number is out of range.

Cause	The error message number is out of range - error number must be an integer between -20000 and -20999.
Action	Specify a valid error number.

14010: Radian value out of range.

Cause	Radian values must be between -1 and 1 ($-1 < x < 1$).
Action	Specify a valid radian value.

14011: Invalid argument specified for EXTRACT.

Cause	The argument of the extract() function is invalid.
Action	Choose a proper value within the ranges of DATETIME or INTERVAL.

14013: LOB exceeded maximum size (4GB - 1 byte).

Cause	The length of LOB is too long. It cannot be longer than 4GB - 1 byte.
Action	Check the parameter.

14017: Invalid seed value: seed does not exist.

Cause	The seed value is invalid.
Action	Check if the seed value is NULL.

14018: Invalid seed value: seed is too short.

Cause	The length of the seed value is too short.
Action	The seed value must contain more than 80 characters.

14019: Invalid key value: key is too short.

Cause	The key value is invalid.
Action	The key must contain more than eight characters.

14020: Invalid input size: size must be a multiple of 8 bytes.

Cause	The size of the input parameter is invalid.
Action	Set the length of input parameter to a multiple of eight bytes.

14021: Invalid triple DES mode: only TWO KEY MODE and THREE KEY MODE are allowed.

Cause	The DES mode is invalid.
Action	Choose either TWO KEY MODE or TRIPLE KEY MODE only.

14022: Buffer overflow.

Cause	The buffer size exceeded the maximum limit.
Action	Increase the buffer size, or delete some contents of the buffer.

14023: Invalid input value.

Cause	An invalid value was specified.
Action	Verify an identical value was not already set.

14025: Invalid savepoint.

Cause	The savepoint value is invalid.
Action	Verify the parameter is NULL.

14028: Invalid number format for RAW.

Cause	The actual length does not match the length value.
Action	Verify that the number format is correct.

14029: Invalid endian value.

Cause	The endian value is invalid.
Action	Specify big endian (1) or little endian (2) only.

14031: Invalid length value.

Cause	The length value is invalid.
Action	Verify that the length value is correct.

14033: Maximum number of open files has been reached.

Cause	The number of open files has reached the maximum.
Action	Close some open files.

14034: Invalid line size: maximum size exceeded.

Cause	The line size exceeded the maximum limit (32768).
Action	Reduce the value of the MAX_LINESIZE parameter.

14035: Invalid path: path is NULL or does not exist.

Cause	The directory name or path is invalid.
Action	Verify that the path name is correct.

14036: Invalid filename.

Cause	Invalid file name.
Action	Verify that the file name is correct.

14037: Invalid file ID: file must be open.

Cause	The ID of a closed or invalid file was used.
Action	Check the current condition of the file.

14038: Invalid OPENMODE.

Cause	Invalid OPENMODE specified.
--------------	-----------------------------

Action	Specify a valid FILE_OPENMODE_x [x = A, R, W, AB, RB, WB].
---------------	--

14039: Invalid offset.

Cause	Invalid offset value specified.
Action	Specify a valid offset value.

14040: Invalid length: length cannot be negative.

Cause	The length value is invalid.
Action	Specify an integer that is greater than or equal to 0.

14041: Invalid file operation.

Cause	An attempt was made to perform an invalid operation on the file.
Action	Verify the authority for the path is correct.

14042: Invalid write: a single line cannot exceed 32767 bytes.

Cause	The amount of data to be written to a single line exceeds the maximum allowed.
Action	The length of a line cannot exceed the maximum. The maximum size is specified in the max_linesize parameter.

14043: Invalid read: allowed for read-mode files only.

Cause	An attempt was made to perform an invalid read on the file.
Action	Check the file's OPENMODE.

14044: Unable to rename file: duplicate file name exists.

Cause	The specified file name already exists.
Action	Either overwrite or delete the existing file.

14045: Unable to remove file: file was not found.

Cause	The file to be deleted does not exist.
Action	Verify that the file exists.

14046: Internal error.

Cause	Internal system error.
Action	Contact the system administrator.

14047: Character set mismatch.

Cause	The character sets do not match.
Action	Verify that the character sets are correct.

14048: Access denied.

Cause	Access to the file or directory was denied.
Action	Modify permissions or use the user directory.

14049: Unable to execute on an open file.

Cause	The task cannot be executed on an open file.
Action	Close the file and try again.

14050: Specified job was not found in the job queue.

Cause	A job matching the job number has not been added to the job queue.
Action	Check the job number and try again.

14051: Execution of job [%1\$d] failed.

Cause	An error occurred while executing job [%1\$d].
--------------	--

Action	Verify that a DD object related to the job exists.
---------------	--

14052: Invalid argument %1\$s.

Cause	The argument value is invalid, NULL, or out of range.
Action	Correct the argument value.

14053: Specified directory was not found.

Cause	The specified directory could not be found.
Action	Verify that the directory exists.

14054: Access denied.

Cause	Access to the directory or file was denied.
Action	Verify that the user has permission to access the directory or file.

14055: Invalid directory.

Cause	The directory is invalid.
Action	Check the directory or contact the DBA.

14056: Invalid file operation.

Cause	Invalid file access method.
Action	Verify that the file access method is correct.

14057: File must be opened first.

Cause	The file is not open.
Action	Open the file first.

14058: Maximum number of open files has been reached.

Cause	The number of open files has reached the maximum.
Action	Close some open files.

14059: Locked by another user.

Cause	A lock has already been obtained by another user.
Action	Try later.

14060: Fetch out of sequence.

Cause	Statements were executed in the wrong order.
Action	Execute PSM statements following the fetch sequence.

14061: Some variables are not yet bound.

Cause	The bind parameters are not all bound yet.
Action	Perform the bind_variable function for all parameters.

14062: The type of bound value is mismatched.

Cause	The column_value function was executed in a column type other than the defined one.
Action	Execute column_value in a column type that matches the defined type.

14063: Too many cursors opened with DBMS_SQL package.

Cause	Too many cursors were opened in a single session with the DBMS_SQL package.
Action	Decrease the number of cursors to open.

14064: Statement not yet parsed.

Cause	An attempt was made to call a function in a statement that had not yet been parsed.
--------------	---

Action	Parse the statement first and then call the bind_variable, execute and fetch_rows functions.
---------------	--

14065: Variable was not found in SELECT list.

Cause	An attempt was made to define a column that does not exist in the SELECT list, or bring an undefined column.
Action	Verify the definition matches the SELECT list, and the column_value was called by the defined column.

14066: URL contains malformed escape code sequence.

Cause	The URL contains a malformed code sequence.
Action	Check the URL.

14067: HTTP request failed.

Cause	The HTTP server request failed.
Action	Verify the HTTP server is properly running. A request may fail due to timeout.

14068: Invalid URL was requested.

Cause	The URL is invalid.
Action	Check the URL.

14069: URL scheme is unknown or unrecognized.

Cause	Unknown scheme (scheme://) was included in the URL.
Action	Verify it is a supported scheme.

14070: Header was not found.

Cause	Either there is no header in the response from the server, or a header cannot be parsed since the response is not correct.
--------------	--

Action	Verify the response from the server is correct.
---------------	---

14071: Read timeout occurred and no data was read.

Cause	There is no response from the server.
Action	Verify the server is properly running and that the network delay time is under 20 seconds.

14072: Invalid dump option.

Cause	The dump option is invalid.
Action	Verify the dump option is correct.

14073: Invalid tablespace name.

Cause	The tablespace name is invalid.
Action	Verify the tablespace name is correct.

14074: Invalid datafile number.

Cause	The datafile number is invalid.
Action	Verify the datafile number is correct.

14075: Invalid block number.

Cause	The block number is invalid.
Action	Verify the block number is correct.

14076: Invalid segment owner.

Cause	The segment owner is invalid.
Action	Verify the segment owner is correct.

14077: Invalid segment name.

Cause	The segment name is invalid.
Action	Verify the segment name is correct.

14078: Invalid segment type.

Cause	The segment type is invalid.
Action	Verify the segment type is correct.

14079: Invalid partition name.

Cause	The partition name is invalid.
Action	Verify the partition name is correct.

14080: CLUSTER type is not supported.

Cause	CLUSTER type is not supported.
Action	Check if the schema object is CLUSTER type.

14081: Specified owner cannot be found.

Cause	There is no user with the specified name in the argument.
Action	Verify the specified owner name is correct

14082: Specified object name or partition name cannot be found.

Cause	There is no object with the specified names in the argument.
Action	Verify the object and partition names are correct.

14083: No data passed to the obfuscation toolkit.

Cause	Input or input_string is NULL.
--------------	--------------------------------

Action	Input or input_string must have a value.
---------------	--

14084: Invalid argument %1\$s.

Cause	The argument value is invalid, NULL, or out of range.
Action	Correct the argument value.

14085: Invalid SQL statement.

Cause	This procedure cannot be called when the SQL statement is not a %1\$s.
Action	Use this procedure when the SQL statement is a %1\$s.

14086: DBMS_SQL.DESCRIBE_COLUMNS overflow: col_name field in desc_rec.

Cause	col_name_len=%1\$s (> 32).
Action	Use DESCRIBE_COLUMNS2 procedure.

14087: Invalid key value: The length of the key is too short.

Cause	The key value is invalid.
Action	The key must contain %1\$d or more characters.

14088: Invalid initialization vector value: The length of initialization vector is too short.

Cause	The initialization vector value is invalid.
Action	The initialization vector must contain %1\$d or more characters.

14089: Invalid input size: The input size must be multiples of %1\$d bytes.

Cause	The size of the input parameter is invalid.
Action	Set the length of input parameter to multiples of %1\$d bytes.

14090: Internal DBMS_CRYPTO encryption or decryption error.

Cause	An error occurred during encryption or decryption using the DBMS_CRYPTO package.
Action	Contact the system administrator.

**14091: Internal DBMS_CRYPTO encryption or decryption error.
Reason: %1\$s.**

Cause	An error occurred during encryption or decryption using the DBMS_CRYPTO package.
Action	Verify the data is valid and contact the system administrator.

14092: Internal DBMS_OBFUSCATION_TOOLKIT error. Reason: %1\$s.

Cause	An error occurred during encryption or decryption using the DBMS_OBFUSCATION_TOOLKIT package.
Action	Verify the data is valid and contact the system administrator.

14093: The standard function '%1\$s' was not called from the SQL statement.

Cause	The standard function '%1\$s' is called only from the SQL statement.
Action	Call the function in the SQL statement.

14094: A general network error occurred at the UTL_TCP package.

Cause	A general network error occurred at the UTL_TCP package.
Action	Verify the connection is valid.

14095: The length of a line read by a server is too long.

Cause	The length of a line read by the server is too long.
Action	Use another API for reading.

14096: No more data to be read is available from the connection.

Cause	No more input data is available from the connection.
Action	Stop reading.

14097: Timeout for TCP connection, transmit, or reception.

Cause	No reply arrived within timeout (seconds).
Action	Check the status of the TCP connection.

14098: An internal buffer allocated to read the HTTP header has overflowed.

Cause	An HTTP header larger than the internal buffer was received from the HTTP server.
Action	Verify the HTTP server is valid.

14099: Pipe name duplicated.

Cause	A pipe of the same name already exists.
Action	Create a new pipe name or reuse the existing pipe.

14100: Failed to create a pipe.

Cause	Pipe creation failed due to system limit and redundant pipe creation.
Action	Contact the system administrator.

14101: DBMS_PIPE package buffer size exceeded.

Cause	DBMS_PIPE package buffer size exceeded; no more data can be entered.
Action	Empty the data in the buffer by calling the DBMS_PIPE.SEND_MESSAGE function.

14102: Read buffer in the DBMS_PIPE package is empty.

Cause	All data in the buffer read from the DBMS_PIPE.RECEIVE_MESSAGE function has been read.
Action	None

14103: The requested data type is different from the actual data type.

Cause	The requested data type is different from the actual data type.
Action	Call the DBMS_PIPE.UNPACK_MESSAGE procedure by using a valid message type.

14104: DBMS_PIPE internal error.

Cause	DBMS_PIPE internal error.
Action	Contact the system administrator.

14105: Cannot create a policy for the object of the SYS user.

Cause	There was an attempt to create a policy for the object of the SYS user.
Action	This command cannot be executed.

14106: Policy '%2\$s' already exists in table '%1\$s'.

Cause	The policy name already exists.
Action	Check the policy name.

14107: Policy '%2\$s' does not exist in table '%1\$s'.

Cause	The policy does not exist.
Action	Check the name of the policy.

14108: Cannot execute policy function.

Cause	Cannot execute policy function.
Action	Check fine-grained audit policy.

14109: Authority to access the pipe is required.

Cause	The pipe was privately created by a different user.
Action	Contact the user who created the pipe.

14110: The collection bound with DBMS_SQL.BIND_ARRAY is empty.

Cause	If the collection bound with DBMS_SQL.BIND_ARRAY is empty, batch update cannot be performed.
Action	Fill the bound collection with data.

14111: The type of a column to be obtained with DBMS_SQL.COLUMN_VALUE_LONG is not LONG.

Cause	DBMS_SQL.COLUMN_VALUE_LONG can be used only for LONG type columns.
Action	Check the column type.

14112: An invalid SQL name was specified.

Cause	The argument is an invalid SQL name.
Action	Refer to a description of DBMS_ASSERT in the manual and specify a valid argument.

14113: An invalid qualified SQL name was specified.

Cause	The argument is invalid for a qualified SQL name.
Action	Refer to a description of DBMS_ASSERT in the manual and specify a valid argument.

14114: Internal error.

Cause	Internal system error.
Action	Contact the system administrator.

14115: An invalid column name was specified in SORT_LIST.

Cause	An invalid column name was specified in SORT_LIST.
Action	SORT_LIST may only contain ENQ_TIME and PRIORITY.

14116: Failed to drop the queue table because queues exist in the queue table.

Cause	All queues in a queue table must be dropped before the queue table can be dropped.
Action	Drop all of the queues using the drop_queue() command or with the force option.

14117: The queue table does not exist.

Cause	The queue table does not exist.
Action	Check if the queue table exists using the USER_QUEUE_TABLES view.

14118: The schema defined in queue_name does not match the schema in queue_table.

Cause	The schema defined in queue_name does not match the schema in queue_table.
Action	Specify two arguments that have the same schema name.

14119: The queue already exists.

Cause	The queue already exists.
Action	Change the queue name. Search the USER_QUEUES view to see the current queues.

14120: The argument pairs have no effect on queues.

Cause	The enqueue/dequeue pair is invalid.
Action	One of the arguments must be TRUE.

14121: The agent is already specified as a subscriber of the queue.

Cause	The agent is already specified as a subscriber of the queue.
Action	Use a different agent name.

14122: The enqueue function of the queue is disabled.

Cause	The enqueue function of the queue is disabled.
Action	Enable the queue using the start_queue() command.

14123: There is no recipient for the message.

Cause	Attempted to enqueue to queues that can serve multiple consumers, but a subscriber or a recipient was not defined for the queue.
Action	Specify a recipient or register a subscriber in the queue before attempting to enqueue.

14124: Both the message ID and the dequeue condition/correlation ID are defined in the dequeue option.

Cause	The dequeue option can be specified with either a message ID or a dequeue condition/correlation ID, but not both.
Action	Specify at most one option.

14125: A timeout occurred while dequeuing a message.

Cause	A timeout occurred while dequeuing a message.
Action	Try dequeuing again. Correct the wait time specified in the dequeue option if insufficient.

14126: The dequeue function of the queue is disabled.

Cause	The dequeue function of the queue is disabled.
Action	Enable the queue using the start_queue() command.

14127: A consumer cannot be specified for a single-consumer queue or an exception queue.

Cause	A consumer was specified while registering a notification for a single-consumer queue or an exception queue.
Action	Do not specify a consumer when registering a subscription name.

14128: Failed to find the registration.

Cause	Failed to find the specified registration.
Action	Verify the specified subscription name and callback string are valid.

14129: consumer_name was not defined.

Cause	Attempted to dequeue to queues that can serve multiple consumers, but consumer_name was not defined in the dequeue option.
--------------	--

Action	Specify consumer_name in the dequeue option.
---------------	--

14130: Invalid path: \"%1\$s\" is NULL or does not exist.

Cause	The directory name or path is invalid.
Action	Verify that the path name is correct.

14131: The specified visibility value is invalid.

Cause	Visibility must be set to ON_COMMIT or IMMEDIATE.
Action	Specify ON_COMMIT or IMMEDIATE for visibility.

14132: The specified privilege is invalid.

Cause	The specified privilege to be granted or revoked is invalid.
Action	Specify a valid privilege.

14133: Queues must be stopped before they can be dropped.

Cause	The queue is not stopped. (enqueue or dequeue has been enabled.)
Action	Disable both enqueue and dequeue using the stop_queue() command.

14134: msgid cannot be specified in dequeue_options.

Cause	msgid cannot be specified in dequeue_options when calling dequeue_array.
Action	Remove the specified msgid from dequeue_options.

14135: Invalid svr env name: env name is NULL or does not exist.

Cause	The server env name is invalid.
Action	Verify that the svr env name is correct.

14136: The package cannot be used.

Cause	The package has not been initialized.
Action	Verify that the database server has started normally.

14137: Cannot send the message to the pipe because it is too large.

Cause	The size of the message is greater than the maximum size of the pipe.
Action	Reduce the size of the message, or increase the maximum size of the pipe.

14138: A consumer name is defined for a single-consumer queue.

Cause	A consumer name can only be defined for multi-consumer queues.
Action	Remove the consumer_name from the dequeue options.

14139: The queue does not exist.

Cause	The queue does not exist.
Action	Check whether the queue exists through the USER_QUEUES view.

14140: Unable to stop the queue because there is a transaction in progress.

Cause	STOP_QUEUE will fail if there is a transaction in progress when WAIT is set to false.
Action	Set WAIT to true, and then retry to execute the STOP_QUEUE command. The command will wait until all transactions are committed before stopping the queue.

14141: The policy does not exist.

Cause	The policy does not exist.
Action	Re-check the name of the schema, schema object, and policy name.

14142: The policy already exists.

Cause	The policy already exists.
Action	Re-check the name of the schema, schema object, and policy.

14143: Locked by another user.

Cause	A lock has already been obtained by another user.
Action	Try later.

14144: Invalid builtin function number - '%1\$d'.

Cause	A patch for previous versions may exist or a patch was applied incorrectly.
Action	'ALTER SYSTEM RECOMPILE ALL;' is required. Contact the technical support team.

14145: This queue was not created as multiple consumer queue.

Cause	A queue with this name exists, but it is not a multiple consumer queue.
Action	None

14146: The HTTP request is incorrect.

Cause	An incorrect HTTP package subprogram has been used.
Action	The program must be recreated.

14147: The end of the HTTP response has been reached.

Cause	The end of the HTTP response has been reached.
Action	None

14148: The HTTP request has failed.

Cause	The HTTP request cannot be executed.
--------------	--------------------------------------

Action	None
---------------	------

14149: An attempt to convert an unsupported character set.

Cause	The character set is not supported.
Action	None

14150: Invalid write: a single line cannot exceed %1\$d bytes.

Cause	The amount of data to be written to a single line exceeds the maximum allowed.
Action	The length of a line cannot exceed the maximum. The maximum size is specified in the max_linesize parameter.

14151: Policy is disabled.

Cause	Policy is disabled.
Action	Check the status of the policy.

14152: Timeout occurred while using a pipe.

Cause	Timeout occurred while using a pipe.
Action	Try again.

14153: ABORT_EXECUTION was called in the debugger session.

Cause	ABORT_EXECUTION was called in the debugger session.
Action	None

14154: SQL translation profile '%1\$s' already exists.

Cause	Specified profile already exists.
Action	Check the profile name.

14155: SQL translation profile '%1\$s' does not exist.

Cause	Specified profile does not exist.
Action	Check the profile name.

14156: SQL statement or error code cannot be translated.

Cause	Custom translation of this SQL statement or error code is not registered.
Action	Check custom translation.

14157: Synonyms cannot be used in column-level VPD.

Cause	Synonyms cannot be used in column-level VPD.
Action	Check the argument of the procedure.

14158: Column does not exist.

Cause	Specified column does not exist.
Action	Check the argument of the procedure.

14159: Invalid parameter was used for the AnyData type operation.

Cause	Invalid parameter was used.
Action	Use a valid parameter.

14160: Invalid method was used for the AnyData type operation.

Cause	Invalid method was used for the type operation.
Action	Refer to a valid example to apply a valid method to the operation.

14161: Type does not match in the AnyData type operation.

Cause	An invalid type was used to access AnyData.
--------------	---

Action	Attempt operation using a valid type.
---------------	---------------------------------------

14162: An error occurred due to an invalid context during XML processing.

Cause	An invalid context was passed as an argument of XMLGEN.GETXML.
Action	Check if the context is configured correctly.

14163: A negative value was assigned to a variable, which does not allow a negative value, during XML processing.

Cause	A negative value was assigned to a variable that does not allow a negative value.
Action	Assign a non-negative value to the variable.

14164: A node was inserted into an invalid location.

Cause	An insert that violates the DOM Tree structure was executed.
Action	Check the node relationships.

14165: A node created in another document was used in the current document.

Cause	A node that does not belong to the document was used.
Action	Include the node in the current document or create a new node.

14166: Cannot use the specified character string.

Cause	A character string that is not allowed in XML was used.
Action	Use a character string allowed in XML.

14167: Cannot execute the operation.

Cause	An invalid DOM handle was used.
Action	Use a valid DOM handle.

14168: An error has occurred while processing XML. %1\$s

Cause	A DOM processing error has occurred.
Action	Check the DOM processing rules.

14169: Package function is currently unavailable.

Cause	Package function is currently unavailable.
Action	Check the package related parameters.

14170: An invalid operation occurred.

Cause	The order of the API calls or the application implementation is incorrect.
Action	Check whether it needs to be preceded by another operation, or how to use the operation.

14171: A transient error occurred due to a problem such as a network connection error. %1\$d : %2\$s

Cause	An error response code in the 400-499 range occurred.
Action	Check the response code and text for error details.

14172: A permanent error occurred due to a defect such as a mail server error. %1\$d : %2\$s

Cause	An error response code in the 500-599 range occurred.
Action	Check the response code and text for error details.

14173: The string input for the XML tag is too long.

Cause	The size of the user-entered string is more than 130 bytes.
Action	Enter a string that is less than 130 bytes.

14174: The column name input does not exist.

Cause	The user-entered an invalid column name.
Action	Enter a valid column name.

14175: There is no enclosing tag for the XML document.

Cause	Rowsettag and Rowtag are both set to NULL.
Action	Enter a non-NULL value for Rowsettag or Rowtag.

14176: Cannot create a valid XML document.

Cause	If Rowsettag or Rowtag is NULL, then the query result must be a single column or a single row.
Action	Either enter a non-NULL value for both Rowsettag and Rowtag, or use a query whose result is a single row or a single column.

14177: The column that corresponds to the rowid attribute value does not exist.

Cause	A column that does not exist in the query result has been set to the rowid attribute value.
Action	Rowid attribute value must be selected among the columns that exist in the query result.

14178: The column that corresponds to the rowid attribute value is a non-scalar column.

Cause	Rowid attribute value can only be set in a scalar column.
Action	Set one of the scalar columns to the rowid attribute value.

14179: The query result is empty.

Cause	The query result is empty, and the "Raise No Rows Exception flag" is set to "true".
Action	Change the "Raise No Rows Exception" flag to "false" by using DBMS_XMLQUERY.SETRAISENOROWSEXCEPTION.

14180: There are escape characters in the string input for the XML tag.

Cause	If the "SQL to XML Name Escaping" flag is set to "false", then the "escape" character cannot be used in the tag.
Action	Either enter a string without an escape character, or change the "SQL to XML Name Escaping" flag to "true" by using DBMS_XMLQUERY.SETSQLTOXMLNAMEESCAPING.

14181: The name of the bind value does not exist.

Cause	The bind value does not exist in the query used to create the context.
Action	Enter the name of the bind variable that exists in the query used to create the context.

14182: Invalid create or replace statement, the following are the allowed types: PROCEDURE, FUNCTION, PACKAGE or PACKAGE BODY

Cause	The input DDL must be the create or replace statement.
Action	Use one of the following types: PROCEDURE, FUNCTION, PACKAGE or PACKAGE BODY

14183: Wrapping failed.

Cause	Wrapping the create or replace statement is failed.
Action	Check the system log.

14184: Creating procedure or package failed. rc=%1\$d

Cause	Creating procedure or package is failed. rc=%1\$d
Action	Check the system log.

14185: Trigger not found.

Cause	Trigger which you specified is not found.
Action	Please check the trigger name and its owner name.

14186: Hierarchical workspace not supported.

Cause	Hierarchical workspace is not supported yet.
Action	Please use workspace in single level

14187: The node type is invalid.

Cause	The node type is invalid.
Action	Use a valid node type.

14188: An error occurred while calling a DOM API.

Cause	An error occurred while calling an external API.
Action	Check the program that calls the DOM API.

14189: DBMS_CMGT package not supported.

Cause	Following feature not supported.
Action	Check requirements for DBMS_CMGT

14190: An error occurred during streaming.

Cause	An error occurred during streaming.
--------------	-------------------------------------

Action	None
---------------	------

14191: Invalid data.

Cause	Invalid data.
Action	None

14192: The compression results exceed the maximum RAW size.

Cause	The compression results exceed the maximum RAW size.
Action	None

14193: An error occurred during compression.

Cause	An error occurred during compression.
Action	None

14194: An error occurred during decompression.

Cause	An error occurred during decompression.
Action	None

14195: Insufficient memory.

Cause	Insufficient memory.
Action	None

14196: Network exist error.

Cause	Network with same name already exists.
Action	Try different network name.

14197: Node table exist error.

Cause	Node table with same name already exist.
Action	Try different node table name.

14198: Link table exist error.

Cause	Link table with same name already exist.
Action	Try different link table name.

14199: Path table exist error.

Cause	Path table with same name already exist.
Action	Try different path table name.

14200: Pathlink table exist error.

Cause	Pathlink table with same name already exist.
Action	Try different pathlink table name.

14201: Network not exist error.

Cause	Network does not exist error.
Action	Check network name.

14202: The size of the data to read is too large.

Cause	An error occurred while attempting to read the data whose size is greater than that of bfile.
Action	Enter a valid size of data.

14203: User session ID does not exist.

Cause	The user session ID no longer exists, probably because the session was logged out.
--------------	--

Action	Use a valid session ID.
---------------	-------------------------

14204: This function is deprecated.

Cause	This function is no longer supported.
Action	This function cannot be used in the current version.

14205: The specified audit event/action already exists.

Cause	The audit event/action had been created before.
Action	Check the audit event/action specifications.

14206: The specified audit event ID does not exist.

Cause	The audit event ID is not correct or has not been made.
Action	Create audit event before adding event action.

14207: The specified alert name does not exist.

Cause	The alert name is not correct or has not been registered.
Action	Regist alert first.

14208: Invalid parameter was used for the alert package.

Cause	Invalid parameter was used.
Action	Use a valid parameter.

14209: No alert is registered.

Cause	No alert is registered.
Action	Register an alert first.

14210: The specified alert does not exist.

Cause	The specified alert does not exist.
Action	Register an alert first.

14211: attempting to wait on uncommitted signal from same session

Cause	attempting to wait on uncommitted signal from same session
Action	Commit first.

14212: Invalid character set name.

Cause	Invalid character set name.
Action	Enter a valid character set name.

14213: URLs with a fixed-width multibyte character set is not allowed.

Cause	A fixed-width multi-byte character set cannot be used.
Action	Use a URL character set that is not a fixed-width multibyte character set.

14214: Invalid input value.

Cause	The length of the input string cannot exceed the value of TB_VARCHAR2_SIZE_PSM_MAX divided by the length of a single Unicode character.
Action	Use an input string with a valid length.

14215: HTTP client error %1\$s

Cause	HTTP status code cannot be between 400 and 499.
Action	Enter a valid value.

14216: HTTP server error %1\$s

Cause	HTTP status code cannot be between 500 and 599.
Action	Enter a valid value.

14217: Invalid index or size.

Cause	The index or its size is a negative value or greater than the set value.
Action	Modify the index or its size.

14218: Invalid text range.

Cause	The specified range of text does not fit into a DOMString.
Action	Modify the text range.

14219: Data cannot be specified in the node.

Cause	An attempt was made to specify data for a node that does not support the data.
Action	Modify the source code.

14220: Object cannot be modified.

Cause	An attempt was made to modify an object that cannot be modified.
Action	Modify the source code.

14221: Unable to find the node.

Cause	An attempt was made to reference a node in the current context where it does not exist.
Action	Reference a node that exists in the context.

14222: Unsupported operation.

Cause	The requested operation is not supported.
--------------	---

Action	The operation will be implemented in the next version.
---------------	--

14223: An attempt was made to add an invalid attribute.

Cause	An attempt was made to add an attribute that is already in use.
Action	Add a valid attribute.

14224: Incorrect syntax.

Cause	Invalid syntax was used.
Action	Modify the source code.

14225: Invalid modification.

Cause	An attempt was made to modify an object type.
Action	Use a correct modification method.

14226: Object cannot be created or modified.

Cause	An attempt was made to create or modify an object that cannot be used in the current namespace.
Action	Create or modify an object that can be used in the current namespace.

14227: Invalid object access.

Cause	A parameter or operation is not supported by the current object.
Action	Use a parameter or operation that is supported by the current object.

14228: Invalid node.

Cause	The insertBefore or removeChild method invalidated the node.
Action	Use a valid node.

14229: Invalid select item in the hierarchical query.

Cause	There is an invalid select item in the hierarchical query.
Action	Check the hierarchical query.

14230: Invalid table name '%1\$s'.

Cause	The table name does not exist.
Action	Check the table name.

14231: Invalid context name.

Cause	The context does not exist.
Action	Check the context name.

14232: Invalid key column specified for the deletexml function.

Cause	The deletexml function requires a key column.
Action	Enter a non-null value for the key column.

14233: Invalid context.

Cause	The context value is invalid.
Action	Check the context name.

14234: The tag name is too long.

Cause	The specified tag name exceeds the allowed maximum length
Action	Enter a tag name within the length limit.

14235: Invalid column specified for the updatexml function.

Cause	The updatexml function requires a key column.
--------------	---

Action	Enter a non-null value for the key column.
---------------	--

14236: The DML that will be created with the XML is too long.

Cause	The DML exceeds the allowed maximum length.
Action	Either shorten the XML tag names or the XML document itself.

14237: Invalid XML format.

Cause	The specified XML header or XML format is invalid.
Action	Enter a valid XML string.

14238: Invalid XML document.

Cause	The XML document to insert into the table failed to validate against the XML schema.
Action	Use an XML document that conforms to the XML schema.

14239: Non-existing column name.

Cause	The specified column name does exist in the table.
Action	Specify a column name that exists in the table.

14240: Another schema is already registered under the specified URL.

Cause	To register a new schema, you must specify a unique URL.
Action	Enter a unique URL.

14241: There is an object that is dependent on the specified schema.

Cause	A schema with a dependent object cannot be deleted.
--------------	---

Action	Delete the dependent object or modify the delete option.
---------------	--

14242: Unable to find the specified schema.

Cause	Only a registered schema can be deleted.
Action	Modify the query.

14243: Null or invalid schema URL.

Cause	You must specify a valid schema URL.
Action	Modify the query.

14244: Invalid schema format.

Cause	The schema content must be constructed with valid syntax.
Action	Use a schema with valid format.

14245: Non-existent user.

Cause	The user does not exist.
Action	Specify a valid username.

14246: Unable to apply redaction policy.

Cause	Redaction policy cannot be applied on this object.
Action	Specify a table or view object.

14247: Non-existent object.

Cause	The object does not exist.
Action	Specify a valid object.

14248: Invalid policy name.

Cause	The policy name is invalid.
Action	Specify a valid policy name.

14249: The redaction policy is already enabled.

Cause	The redaction policy is already enabled.
Action	The redaction policy is already enabled.

14250: The redaction policy is already disabled.

Cause	The redaction policy is already disabled.
Action	The redaction policy is already disabled.

14251: The object does not have a redaction policy.

Cause	The object does not have a redaction policy.
Action	The operation can only be performed on an object with a redaction policy.

14252: Invalid column.

Cause	Unable to find the column.
Action	Specify a valid column name.

14253: Redaction policy already exists.

Cause	The column already has a redaction policy.
Action	Use the MODIFY_COLUMN procedure to modify the column.

14254: Redaction policy does not exist.

Cause	The column does not have a redaction policy.
--------------	--

Action	Use the ADD_COLUMN procedure to add a redaction policy on the column.
---------------	---

14255: Invalid policy description.

Cause	The policy description is invalid.
Action	Specify a valid policy description.

14256: Invalid column description.

Cause	The column description is invalid.
Action	Specify a valid column description.

14257: Redaction policy already exists.

Cause	The object already has a redaction policy.
Action	To add a new redaction policy on the object, drop the existing policy.

14258: Invalid redaction function type.

Cause	An invalid function type argument was specified for the ADD_POLICY procedure.
Action	Specify a valid function type.

14259: Invalid redaction parameters("%1\$s").

Cause	One or more redaction parameters are invalid.
Action	Specify the parameters correctly.

14260: Mismatched input and output lengths.

Cause	The input and output lengths of the redaction arguments do not match.
Action	Use regular expression redaction instead of partial redaction.

14261: Inconsistent block TYPE or SGMT_ID, or inconsistent Last(I3 or extent map) block's information.

Cause	Check the ILOG for the DBA of the block.
Action	

14262: Invalid SEQUENCE DEVIATION value.

Cause	The SEQUENCE DEVIATION must be set to BEFORE or TOP.
Action	

14263: Invalid PRIORITY specified when using SEQUENCE DEVIATION.

Cause	The priority of the message, which referenced in SEQUENCE DEVIATION, must be less than or equal to that of the relative message.
Action	

14264: Relative msg id required.

Cause	If SEQUENCE DEVIATION is BEFORE, the relative msg id must be specified.
Action	

14265: The scheduler object already exists.

Cause	The scheduler object already exists.
Action	Change the object name. Search the DBMS_SCHEDULER view to see the current object.

14266: The name of scheduler object cannot be NULL.

Cause	The name of scheduler object cannot be NULL.
Action	Insert the name of object.

14267: PROGRAM_TYPE cannot be NULL.

Cause	PROGRAM_TYPE cannot be NULL.
Action	Insert PROGRAM_TYPE when CREATE_PROGRAM.

14268: PROGRAM_ACTION cannot be NULL.

Cause	PROGRAM_ACTION cannot be NULL.
Action	Insert PROGRAM_ACTION when CREATE_PROGRAM.

14269: REPEAT_INTERVAL cannot be NULL.

Cause	REPEAT_INTERVAL cannot be NULL.
Action	Insert REPEAT_INTERVAL when CREATE_SCHEDULE.

14270: The scheduler object does not exists.

Cause	The scheduler object does not exists.
Action	Search the DBMS_SCHEDULER view to see the current object.

14271: Enqueue is not supported for an exception queue.

Cause	Enqueue operation is not supported for an exception queue.
Action	Specify another queue.

14272: Enqueue cannot be enabled for an exception queue.

Cause	Only dequeue operation can be enabled for an exception queue.
Action	Only enable dequeue in the start_queue() command.

14273: Subscriber is not supported for an exception queue.

Cause	Subscriber cannot be associated with an exception queue.
--------------	--

Action	Specify another queue.
---------------	------------------------

14274: Register procedure does not support exception queue.

Cause	Exception queue cannot be specified in the register procedure.
Action	Specify another queue.

14275: Exception queue does not support max_retries and retry_delay.

Cause	The max_retries and retry_delay parameters cannot be set on an exception queue.
Action	Check the queue type.

14276: Exception queue does not support retention_time.

Cause	The retention_time parameter cannot be set on an exception queue.
Action	Check the queue type.

14277: Enqueue is not supported for an exception queue.

Cause	Enqueue operation is not supported for an exception queue.
Action	Specify another queue.

14278: Invalid parameter values.

Cause	Max_retries and/or retry_delay are set to a negative value.
Action	Max_retries and retry_delay must be greater than or equal to 0.

14279: Invalid parameter value.

Cause	Retention_time is set to a negative value.
Action	Retention_time must be greater than or equal to 0.

14280: Invalid queue name.

Cause	The queue name starts with an invalid character.
Action	Specify a valid queue name.

14281: PROGRAM_TYPE can be only PSM_BLOCK.

Cause	PROGRAM_TYPE can be only PSM_BLOCK.
Action	Insert correct PROGRAM_TYPE when CREATE_PROGRAM.

14282: Invalid REPEAT_INTERVAL value.

Cause	Invalid REPEAT_INTERVAL value.
Action	Specify a valid REPEAT_INTERVAL when CREATE_SCHEDULE.

14283: Invalid parameter value: %1\$s.

Cause	The specified string parameter value is invalid.
Action	Specify a valid string parameter value.

14284: No policy option specified.

Cause	The policy option is NULL, but no default schema or policy option exists.
Action	Specify a valid option, or alter the schema or policy to set a valid default option.

14285: Undefined level %1\$s for the policy.

Cause	The specified level is not defined for the policy.
Action	Change the level.

14286: Unable to find policy: %1\$s.

Cause	The specified policy does not exist.
--------------	--------------------------------------

Action	Enter an existing policy name or create a new policy.
---------------	---

14287: Invalid label string: %1\$s.

Cause	The label string cannot be converted to a valid internal label for the policy.
Action	Change the label string.

14288: Invalid policy option: %1\$s.

Cause	The specified policy option is invalid.
Action	Change the policy option.

14289: Duplicate policy option: %1\$s.

Cause	The specified policy option already exists in the option string.
Action	Remove the duplicate policy option.

14290: Invalid combination of policy options.

Cause	The specified policy options are contradictory to each other.
Action	Enter compatible policy options.

14291: Unable to change a column name of a policy in use.

Cause	An attempt was made to change a column name of a policy that has been applied to schemas or tables.
Action	Before changing the column name, disable the policy from the schemas or tables first.

14292: Undefined compartment %1\$s for policy.

Cause	The specified compartment is not defined for the policy.
Action	Modify the compartment string.

14293: Undefined group %1\$s for policy.

Cause	The specified group is not defined for the policy.
Action	Modify the group string.

14294: LBAC error: %1\$s

Cause	An error occurred due to LBAC enforcement.
Action	Correct the problem identified in the error message.

14295: Label %1\$s does not exist for policy.

Cause	The specified label tag or value did not identify a label for the policy.
Action	Enter a label tag or value that is in use by the policy.

14296: Label %1\$s already exists.

Cause	The specified label value already exists.
Action	Modify the label to change the tag or type.

14297: Unable to find user level for user %1\$s and policy.

Cause	There is no level specified for the user.
Action	Enter the maximum and minimum labels for the user.

14298: Policy column %1\$s already used by an existing policy.

Cause	An attempt was made to create a policy with the same column name as an existing policy.
Action	Use a different name for the policy column or delete the existing policy.

14299: Existing policy role for policy %1\$s.

Cause	A role named policy_DBA already exists.
--------------	---

Action	Use a different policy name or delete the existing policy.
---------------	--

14300: The specified schema does not exist.

Cause	The specified schema does not exist.
Action	Check the value of 'object_schema'.

14301: Cannot create/modify/drop a policy for the object of the SYS user.

Cause	There was an attempt to create a policy for the object of the SYS user.
Action	This command cannot be executed.

14302: The specified table or view does not exist.

Cause	The specified table or view does not exist.
Action	Check the value of 'object_name'.

14303: The specified policy name already exists.

Cause	The specified policy name already exists.
Action	Check the value of 'policy_name'.

14304: The specified policy name does not exist.

Cause	The specified policy name does not exist.
Action	Check the value of 'policy_name'.

14305: Invalid column specified.

Cause	The specified list of columns must be columns of the specified object.
Action	Check the value of 'audit_column'.

14306: Invalid handler module specified.

Cause	The specified value of handler module is syntactically incorrect.
Action	Check the value of 'handler_module'.

14307: Invalid statement type(s) specified.

Cause	The specified values of statement types are syntactically incorrect.
Action	Check the value of 'statement_types'.

14308: Invalid audit trail specified.

Cause	The specified value of audit trail is not valid.
Action	Check the value of 'audit_trail'.

14309: Invalid audit column option specified.

Cause	The specified value of audit column option is not valid.
Action	Check the value of 'audit_column_opts'.

14310: Reached a maximum number of fine-grained audit policies on the same object.

Cause	The number of fga policies reached 256 on the specified object.
Action	Delete one of the registered fga policies in order to add a new policy.

14311: SQL Profile already exists.

Cause	Specified SQL Profile already exists.
Action	Check DBA_SQL_PROFILES and use different name or category.

14312: SQL Profile doesn't exist.

Cause	Specified SQL Profile doesn't exist.
Action	Check name or category in DBA_SQL_PROFILES.

14313: invalid attribute name specified.

Cause	Invalid attribute name was specified for altering SQL profile.
Action	Verify attribute name.

14314: invalid attribute value specified.

Cause	Invalid attribute value was specified for altering SQL profile.
Action	Verify attribute value according to the attribute.

14315: Invalid argument.

Cause	The specified argument is invalid.
Action	Modify the argument.

14316: Invalid operation call.

Cause	This operation cannot be called in the current context.
Action	Modify the DBMS_METADATA code.

14317: Invalid argument for METADATA handle.

Cause	The specified argument is not valid for METADATA handle.
Action	Modify the argument.

14318: Invalid operation call for METADATA transform handle.

Cause	To call this operation, you must add a METADATA transform handle appropriate for the operation.
Action	Modify the DBMS_METADATA code.

14319: Object not found.

Cause	The object does not exist.
Action	Modify the argument.

14320: Cannot return implicit result through the specified statement.

Cause	An attempt was made to return an implicit result through a statement other than PSM or DML.
Action	An implicit result can only be returned through a PSM or DML statement.

14321: Invalid table for chunking.

Cause	Table was not a physical table or the table was an IOT.
Action	Use an existing table which is not an IOT.

14322: Invalid state for create chunks.

Cause	Task was not in the CREATED state.
Action	Make sure that the task is in the CREATED state.

14323: Invalid status.

Cause	Invalid value was set to the chunk status.
Action	Make sure that the status value is valid.

14324: Invalid state for run task.

Cause	Task was not in the CHUNKED state.
Action	Make sure that the task is in the CHUNKED state.

14325: Invalid state for resume task.

Cause	Task was not in the FINISHED_WITH_ERROR or CRASHED state.
Action	Make sure that the task is in the FINISHED_WITH_ERROR or CRASHED state.

14326: Parameter value error.

Cause	The input argument was null or it exceeded the maximum length limit.
Action	Make sure that the argument is not null and its length is within the limit.

14327: Duplicate task name.

Cause	A task with the same name was already in existence.
Action	Use another name.

14328: Task not found.

Cause	The task did not exist.
Action	Use an existing task.

14329: Chunk not found.

Cause	The specified chunk did not exist.
Action	Specify an existing chunk.

14330: The calendaring syntax is incorrect.

Cause	Failed to parse the calendaring syntax.
--------------	---

Action	Check the calendaring syntax again.
---------------	-------------------------------------

14331: The **FREQ** clause in the calendaring syntax is incorrect.

Cause	The FREQ clause is incorrect, or it is an invalid argument.
Action	Check the clause again.

14332: The **INTERVAL** clause in the calendaring syntax is incorrect.

Cause	The INTERVAL value is outside the range of 1 to 99, or not numeric.
Action	Check the clause again.

14333: The **BYMONTH** clause in the calendaring syntax is incorrect.

Cause	The BYMONTH clause is incorrect, or the month value is not valid.
Action	Check the clause again.

14334: Invalid **WEEKNO** clause of Calendaring Syntax.

Cause	Invalid WEEKNO clause of Calendaring Syntax.
Action	Check the clause again.

14335: Invalid **BYYEARDAY** clause of Calendaring Syntax.

Cause	Invalid BYYEARDAY clause of Calendaring Syntax.
Action	Check the clause again.

14336: Invalid **BYDATE** clause of Calendaring Syntax.

Cause	Invalid BYDATE clause of Calendaring Syntax.
Action	Check the clause again.

14337: The BYMONTHDAY clause in the calendaring syntax is in correct.

Cause	The BYMONTHDAY clause is incorrect, or the numeric value is outside the range of 0 to 31.
Action	Check the clause again.

14338: The BYDAY clause in the calendaring syntax is incorrect.

Cause	The BYDAY clause is incorrect, or the day value is not valid.
Action	Check the clause again.

14339: The BYHOUR clause in the calendaring syntax is incorrect.

Cause	The BYHOUR clause is incorrect, or the numeric value is outside the range of 0 to 23.
Action	Check the clause again.

14340: The BYMINUTE clause in the calendaring syntax is incorrect.

Cause	The BYMINUTE clause is incorrect, or the numeric value is outside the range of 0 to 59.
Action	Check the clause again.

14341: The BYSECOND clause in the calendaring syntax is incorrect.

Cause	The BYSECOND syntax is incorrect, or the numeric value is outside the range of 0 to 59.
Action	Check the clause again.

14342: Invalid BYSETPOS clause of Calendaring Syntax.

Cause	Invalid BYSETPOS clause of Calendaring Syntax.
Action	Check the clause again.

14343: Invalid INCLUDE clause of Calendaring Syntax.

Cause	Invalid INCLUDE clause of Calendaring Syntax.
Action	Check the clause again.

14344: Invalid EXCLUDE clause of Calendaring Syntax.

Cause	Invalid EXCLUDE clause of Calendaring Syntax.
Action	Check Calendaring Syntax again.

14345: Invalid PERIODS clause of Calendaring Syntax.

Cause	Invalid PERIODS clause of Calendaring Syntax.
Action	Check the clause again.

14346: Invalid BYPERIOD clause of Calendaring Syntax.

Cause	Invalid BYPERIOD clause of Calendaring Syntax.
Action	Check the clause again.

14347: Cannot apply Label Security policies or set authorizations for system schemas.

Cause	An attempt was made to either apply a Label Security policy or to set authorization for the SYS or LBACSYS user.
Action	Apply Label Security policies and set authorizations only for non-system users.

14348: Invalid audit option.

Cause	That option entered is not a valid audit option for the specified policy.
Action	Enter a valid audit option.

14349: Invalid audit type: %1\$s

Cause	The audit type must be BY ACCESS or BY SESSION.
Action	Enter a valid audit type.

14350: Invalid audit success option: %1\$s

Cause	The audit success option must be SUCCESSFUL or NOT SUCCESSFUL.
Action	Enter a valid audit success option.

14351: The authority is insufficient for managing the policy %1\$s.

Cause	An attempt was made to perform management for the policy, but the %1\$s_DBA role had not been granted.
Action	Grant the user the %1\$s_DBA role for the specified policy.

14352: NULL or invalid user label: %1\$s

Cause	The entered label is NULL or not within the user's authorizations.
Action	Enter the labels authorized for the user.

14353: No user levels found for user %1\$s and policy %2\$s.

Cause	No levels have been specified for the user.
Action	Enter the maximum and minimum labels for the user.

14354: No authorization for read or write on specified groups or compartments.

Cause	You included groups or compartments that are not found in the user's lists of groups and compartments authorized for read or write access.
Action	Include groups or compartments authorized for read or write access in the user's lists of groups and compartments.

14355: The specified unit is not supported.

Cause	SYSGIS.UNITS_OF_MEASURE doesn't have data of specified units.
Action	Check the rows of UNITS_OF_MEASURE table.

14356: Duplicate JOB_NAME exists.

Cause	The same JOB_NAME already exists.
Action	Retry after changing the JOB_NAME or delete the existing job with the same name.

14357: Program is not found.

Cause	The program name passed as an argument does not exist.
Action	Retry with a valid program name.

14358: Schedule is not found.

Cause	The schedule name passed as an argument does not exist.
Action	Retry with a valid schedule name.

14359: Invalid block type.

Cause	The block type is not valid.
Action	Check if the block type is valid.

14360: Failed to execute DDL. : %1\$s

Cause	The DDL execution in the goldilocks DB failed.
Action	Enter correct DDL statements.

14361: Connection information already exists.

Cause	Cannot add a new connection because of the already existing information.
--------------	--

Action	Remove the existing information to add a new connection.
---------------	--

14362: No connection information exists.

Cause	Connection information must be registered to use the package.
Action	Register the connection information.

14363: Connection information is invalid

Cause	Cannot connect to the goldilocks DB because the information provided is invalid.
Action	Enter valid connection details.

14364: Object cannot be found.

Cause	Unable to find the object in the goldilocks DB.
Action	Enter the correct object name.

14365: Schedule has an invalid END_DATE.

Cause	An attempt was made to enable a job or window that has an invalid end_date. Either the end_date is before the start_date or the end_date is in the past.
Action	Alter the job or window so that the end date becomes valid (possibly null) and then reissue the command.

14366: The specified path \"%1\$s\" is invalid. No matching directory object exists, or the directory path is not accessible.

Cause	The given directory object name does not correspond to any existing directory object, or the directory object points to an invalid location.
Action	Verify that the directory object exists and that its associated path is correct.

제14장 15000 ~ 15999

15001: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

15002: Parsing failed.

Cause	Parsing failed.
Action	Check the syntax.

15003: Pragma check failed.

Cause	Failed during pragma check; two parameters that should match, did not.
Action	Modify the parameters to match.

15004: Parse tree checking failed.

Cause	Failed during the parse tree check; the parse trees of two parameters do not match.
Action	Check the parameters used in the statement and modify them.

15005: Unable to open the command file. Run gen_psm_cmd.sh.

Cause	Unable to open the psm_commands file for PSM compilation.
Action	Verify that the psm_commands file exists under the config directory, or contact the technical support team.

15006: Nested comment detected.

Cause	The comment is duplicated.
Action	Check the comment.

15007: Unterminated comment detected.

Cause	The comment is not terminated.
Action	Check the comment and terminate it properly.

15008: Unterminated string detected.

Cause	The string is not terminated.
Action	Check the string and terminate it properly.

15009: Invalid ID: length cannot be 0.

Cause	The ID length is 0.
Action	Check the ID and ensure the length is greater than 0.

15010: Newline cannot be used in quoted ID.

Cause	The ID string is declared over several lines.
Action	Declare the ID on one line.

15011: Unhandled character.

Cause	Unknown character.
Action	Verify that a character is not out of place.

15012: Default expression is required.

Cause	No default expression has been defined.
--------------	---

Action	Define a default expression.
---------------	------------------------------

15013: Type constraint is required.

Cause	No type constraint has been defined.
Action	Define a type constraint.

15014: Expression is required.

Cause	No expression has been defined.
Action	Define an expression.

15015: Body of subprogram unit '%1\$s' is required.

Cause	No subprogram body has been defined.
Action	Define the subprogram body.

15016: Package body '%1\$s' is required.

Cause	No package body has been defined.
Action	Define the package body.

15017: Non-query expressions are not allowed.

Cause	An SQL statement that is not a SELECT statement was used.
Action	Modify the SQL statement to use a SELECT statement.

15018: Missing INTO clause.

Cause	INTO clause is missing.
Action	Specify an INTO clause.

15019: Missing RETURN clause.

Cause	RETURN clause is missing.
Action	Specify a RETURN clause.

15020: Character unit (CHAR or BYTE) is not allowed.

Cause	Character unit (CHAR or BYTE) is not allowed.
Action	Change the data type.

15021: Schema name is not allowed.

Cause	Schema name is not allowed.
Action	Do not specify a schema name.

15022: AUTHID clause is not allowed.

Cause	AUTHID clause is not allowed.
Action	Do not specify an AUTHID.

15023: Default expression is not allowed.

Cause	Default expression is not allowed.
Action	Delete the default expression.

15024: HANDLER cannot be specified after OTHERS.

Cause	A HANDLER clause cannot be used after OTHERS.
Action	Move the clause to a different location or delete it.

15025: Expression is not allowed.

Cause	Expression is not allowed.
--------------	----------------------------

Action	Do not specify an expression.
---------------	-------------------------------

15026: Specification is not allowed.

Cause	Specification is not allowed.
Action	Move the specification to a different location or delete it.

15027: RETURN is not allowed.

Cause	RETURN clause is not allowed.
Action	Delete the RETURN clause.

15028: INTO clause is not allowed.

Cause	INTO clause is not allowed.
Action	Delete the INTO clause.

15029: OUT parameter is not allowed.

Cause	OUT parameter is not allowed.
Action	Delete the parameter or use an IN parameter.

15030: REVERSE is not allowed.

Cause	REVERSE character is not allowed.
Action	Delete the REVERSE character.

15031: Dynamic SQL is not allowed.

Cause	Dynamic SQL statements are not allowed.
Action	Modify or delete the SQL statement.

15032: Unable to open IN mode parameter cursor.

Cause	Cannot open the cursor of IN parameter.
Action	Delete OPEN, or specify an OUT or IN/OUT parameter cursor.

15033: Bind parameter can only be used in the trigger.

Cause	The bind parameter was used in the DDL outside the trigger.
Action	Delete the bind parameter.

15034: PRAGMA clause is not allowed.

Cause	The specified PRAGMA clause is not allowed in this area.
Action	Modify or delete the PRAGMA clause.

15035: Number is out of range.

Cause	The number is out of range.
Action	Check the value.

15036: Type constraint is out of range.

Cause	A type constraint is out of range.
Action	Verify that the type constraints are valid.

15037: Label mismatch.

Cause	The labels do not match.
Action	Ensure that the labels match.

15038: Type mismatch.

Cause	The data types do not match.
--------------	------------------------------

Action	Verify the data types are compatible.
---------------	---------------------------------------

15039: Parameter mismatch.

Cause	The declaration and the called parameter do not match.
Action	Verify that the parameter is correct.

15040: Specification mismatch.

Cause	The declaration and the definition do not match.
Action	Verify that the declaration is correct.

15041: Multiple subprograms match the specified argument(s).

Cause	There are many subprograms that match the specified argument(s).
Action	Modify the argument(s).

15042: No subprogram matches the specified argument(s).

Cause	No subprogram matches the specified argument(s).
Action	Modify the argument(s).

15043: INTO list mismatch.

Cause	The number of parameters in the INTO clause does not match the query.
Action	Ensure the number of parameters in the INTO clause matches the query.

15044: Undefined identifier '%1\$s'.

Cause	Undefined identifier.
Action	Define the identifier.

15045: Unknown attribute name.

Cause	Unknown attribute name.
Action	Verify the attribute name is correct.

15046: Identifier is out of scope.

Cause	The identifier is out of scope.
Action	Modify the identifier scope or delete it.

15047: Dot operator (.) cannot be used with this ID type.

Cause	The dot operator (.) cannot be used for this ID; the ID type is not a record, block label, procedure, or username.
Action	Ensure the dot operator is used with the correct ID types.

15048: Parenthesis operator cannot be used with this ID type.

Cause	Cannot use a parenthesis operator for this ID; the ID is not a by table.
Action	Ensure the parenthesis operator is used with the correct ID types.

15049: Constant value was expected.

Cause	The value specified is not a constant.
Action	Use a constant value.

15050: Missing value.

Cause	A value was expected but not found.
Action	Specify a value.

15051: Missing cursor.

Cause	A cursor was expected but not found.
Action	Specify a cursor.

15052: Missing label.

Cause	A label was expected but not found.
Action	Specify a label.

15053: Missing type.

Cause	A type was expected but not found.
Action	Specify a type.

15054: Missing exception.

Cause	An exception was expected but not found.
Action	Specify an exception.

15055: Expression or constant cannot be an LVALUE.

Cause	Cannot use an assignment expression for the corresponding expression.
Action	Use another expression or modify the current expression.

15056: Invalid cursor: static cursor was expected.

Cause	A static cursor was expected, but a reference cursor was found.
Action	Specify a static cursor.

15057: Invalid cursor: reference cursor was expected.

Cause	A reference cursor was expected, but a static cursor was found.
--------------	---

Action	Specify a reference cursor.
---------------	-----------------------------

15058: Missing procedure.

Cause	A procedure was expected but not found.
Action	Specify a procedure.

15059: Missing identifier.

Cause	An identifier was expected but not found.
Action	Specify an identifier.

15060: Missing declaration.

Cause	A declaration was expected but not found.
Action	Specify a declaration.

15061: Missing loop label.

Cause	A loop label was expected but not found.
Action	Specify a loop label.

15062: Missing record.

Cause	A record was expected but not found.
Action	Specify a record.

15063: Duplicate identifier '%1\$s' exists.

Cause	An identifier with this name already exists.
Action	Modify the identifier name.

15064: Duplicate parameter name exists.

Cause	A parameter with this name already exists.
Action	Modify the parameter name.

15065: Duplicate handler clause exists.

Cause	A handler clause with this name already exists.
Action	Modify the clause name.

15066: A positional argument is not allowed after named arguments.

Cause	Positional arguments cannot come after a named argument.
Action	Delete or move the positional argument.

15067: Invalid type constraint.

Cause	An invalid type constraint was detected.
Action	Modify the type constraint.

15068: Invalid attribute.

Cause	Invalid attribute.
Action	Modify the attribute.

15069: Invalid DBMS error code for pragma exception_init.

Cause	An invalid error code was used for pragma exception_init.
Action	Modify the error code.

15070: Invalid pragma.

Cause	Invalid pragma.
Action	Modify the pragma.

15071: Invalid table index type.

Cause	Only BINARY_INTEGER, PLS_INTEGER, and character types are allowed for the table index type.
Action	Modify the table index type.

15072: Invalid declaration location.

Cause	The location of the declaration is wrong, The location must precede the body.
Action	Declaration must be specified before the definition.

15073: Invalid overloading.

Cause	Overloading is invalid here.
Action	Modify the procedure.

15074: Invalid RETURN clause.

Cause	Invalid RETURN clause.
Action	Correct the RETURN clause.

15075: Invalid GOTO clause.

Cause	Invalid GOTO clause.
Action	Correct the GOTO clause.

15076: Invalid EXIT clause in loop.

Cause	Invalid EXIT clause in loop.
Action	Correct the EXIT clause.

15077: Invalid CASE statement: return value cannot be NULL.

Cause	The return value of a CASE expression cannot be NULL.
Action	Modify the CASE statement.

15078: Invalid function call or collection variable access.

Cause	An invalid attempt was made to call an invalid function or access a collection variable.
Action	Modify the statement to use a valid function call or access an array.

15079: Invalid parameter.

Cause	Invalid parameter.
Action	Modify the parameter.

15080: Invalid SQL statement.

Cause	Invalid SQL statement.
Action	Correct the SQL statement.

15081: Invalid collection method.

Cause	Invalid use of collection type method.
Action	Check the return type and parameters of the method.

15082: Invalid return type.

Cause	Invalid return type.
--------------	----------------------

Action	Specify a different return type
---------------	---------------------------------

15083: Invalid collection variable index.

Cause	Invalid use of index of the collection variable.
Action	Modify the index.

15084: LONG or LONG RAW data types cannot be used as subprogram parameter type.

Cause	Cannot use LONG or LONG RAW for a parameter type.
Action	Modify the parameter type or use another subprogram.

15085: Program did not return a value.

Cause	The program terminated abnormally.
Action	Contact the system administrator.

15086: User-defined exception.

Cause	A user-defined error.
Action	Check the user-defined error statement.

15087: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

15088: Critical error occurred while handling another error.

Cause	A critical error occurred.
Action	Contact the system administrator.

15089: Type conversion failed.

Cause	Failed in type conversion.
Action	Check the type.

15090: Unable to access uninitialized variable.

Cause	An uninitialized variable was accessed.
Action	Initialize the variable.

15091: Body of object %1\$u was not found.

Cause	A binary for executing the function does not exist.
Action	Recreate the function.

15092: Parameter exceeded 32K size limit.

Cause	The size of the parameter exceeded the maximum of 32K.
Action	Decrease the parameter size or use a different parameter.

15093: NULL value cannot be passed to NOT NULL constrained parameter.

Cause	The NULL value cannot be used for this parameter.
Action	Specify a value other than NULL.

15094: Parse tree size overflow.

Cause	The program length exceeded the maximum length allowed.
Action	Shorten the program or create it as a package.

15095: Trigger/function cannot access table '%1\$s' while it is being modified.

Cause	The called trigger or subprogram refers to the table.
Action	Modify the trigger or subprogram to eliminate table references.

15096: INSERT/UPDATE/DELETE is restricted in this context.

Cause	Procedures called within the query cannot contain DML statements.
Action	Remove the DML from the procedure or use a different procedure.

15097: DDL/TCS is restricted in this context.

Cause	Procedures called from a DML statement or query cannot contain DDL or TCS statements.
Action	Remove DDL or TCS statements from the DML statement (or query) or use another sub program.

15098: Variable has not been initialized.

Cause	An attempt was made to assign a value to an uninitialized variable.
Action	Initialize the variable first.

15099: Missing case statement.

Cause	The ELSE statement does not exist, or the matching condition is missing.
Action	Specify an ELSE statement or check the condition clause.

15100: Table or array has not been initialized.

Cause	Unable to call functions (other than EXISTS) or assign values to uninitialized tables or arrays.
Action	Initialize the table or array first.

15101: Cursor is already open.

Cause	Unable to open currently opened cursors.
Action	The cursor is already open.

15102: Invalid cursor operation.

Cause	Invalid cursor operation.
Action	Check the status of the cursor.

15103: Invalid user ID or password.

Cause	Invalid user ID or password.
Action	Verify that the user ID and password are correct, and then try relogging.

15104: No matching data found.

Cause	No result rows were found.
Action	Check the SQL statement or the access statement related to the collection.

15105: Not logged on to server.

Cause	There is no active connection to the server.
Action	Log on to the server and try again.

15106: Internal error.

Cause	PSM internal error.
Action	Contact the system administrator.

15107: Row type mismatch.

Cause	The host cursor variable type and the PSM internal cursor variable type do not match.
--------------	---

Action	Verify that the cursor type in use is correct.
---------------	--

15108: SELF has not been initialized.

Cause	Unable to call the MEMBER function of an uninitialized object.
Action	Initialize the object first.

15109: Memory error.

Cause	Not enough memory or invalid memory data.
Action	Contact the system administrator.

15110: Subscript is out of range.

Cause	An index is greater than the maximum length of the array or beyond the bounds of the table.
Action	Specify a smaller index.

15111: Subscript is out of range.

Cause	An index is less than zero or greater than the maximum length of the array.
Action	Modify the index to smaller than the declared size in the collection.

15112: Invalid ROWID.

Cause	The string is not a valid ROWID.
Action	Modify the string to be a valid ROWID.

15113: Resource timeout.

Cause	Assigning server resources timed out.
Action	Contact the system administrator.

15114: Too many rows returned.

Cause	There is more than one result row for a SELECT INTO query.
Action	Correct the SELECT statement.

15115: Invalid value.

Cause	The value is invalid.
Action	Verify that the value is a valid type and length.

15116: %1\$s.

Cause	The user-defined error was not processed in an EXCEPTION clause but sent to the user.
Action	Verify that the actual cause of the error matches the cause listed above. If necessary, add an EXCEPTION clause.

15117: Too many shared libraries were opened.

Cause	Too many shared libraries were opened at one time.
Action	Rewrite the program to use fewer shared libraries.

15119: Bind variable '%1\$s' was not found.

Cause	The bind variable could not be found.
Action	Verify the specified bind variable exists.

15120: PSM and server version mismatch error.

Cause	The PSM and server build versions do not match.
Action	Rebuild the whole PSM with the DDL statement ALTER SYSTEM RECOMPILE ALL.

15121: Parse tree is too large.

Cause	The large parse tree size caused a compilation failure.
Action	Modify the PSM.

15122: Integer value is out of range: overflow or underflow error.

Cause	The integer value was too large or too small.
Action	Check the operation.

15123: No exception to reraise.

Cause	There is no exception to reraise.
Action	Process all exceptions, and verify 'reraise' was performed.

15124: Index is out of range: cannot be greater than [%1\$d].

Cause	The specified index is out of range.
Action	Check the limit of the length of the collection variable.

15125: Primitive data type is not allowed in a BULK...INTO clause.

Cause	Primitive data type variable is not allowed.
Action	Use a collection variable.

15126: DML without bind parameters is not allowed.

Cause	In a FORALL clause, DML without bind parameters is not allowed.
Action	Use a bind parameter.

15127: Invalid use of queries.

Cause	In a FORALL clause, queries are not allowed.
--------------	--

Action	In order to use queries, use FOR/LOOP/CSR_FOR_LOOP statements.
---------------	--

15128: Invalid data type: must be a collection type.

Cause	Invalid use of data type.
Action	Use a collection variable.

15129: Invalid element data type: must be a PLS_INTEGER or BINARY_INTEGER.

Cause	Invalid element data type.
Action	Use a PLS_INTEGER or BINARY_INTEGER data type.

15130: FORALL clause failed.

Cause	An error occurred while executing a FORALL clause.
Action	Contact the technical support team.

15131: Invalid index type for FORALL clause.

Cause	Invalid index type was used in the FORALL clause.
Action	Use a PLS_INTEGER or BINARY_INTEGER data type.

15132: Composite and scalar data types cannot be used together in an INTO clause.

Cause	In an INTO clause, a composite data type and a scalar data type cannot be used together.
Action	Use either a scalar data type or a composite data type.

15133: Invalid ROWID.

Cause	Invalid ROWID.
--------------	----------------

Action	Verify that a valid ROWID value was transmitted.
---------------	--

15134: Record field variable is not allowed in a FORALL clause.

Cause	A field variable of a record is not allowed in a FORALL clause.
Action	Specify a record variable or a different variable.

15135: Element was not found at index [%1\$d].

Cause	No element was found at the specified index number.
Action	Verify that the index is valid.

15136: Undefined library name '%1\$s'.

Cause	The library name is not defined.
Action	Verify that the library name is correct.

15137: Invalid protocol.

Cause	The protocol is not defined.
Action	Contact the technical support team.

15138: Generic I/O error: %1\$s.

Cause	An error occurred during communication with External Procedure Agent.
Action	Contact the technical support team.

15139: I/O read error.

Cause	An error occurred during communication with External Procedure Agent.
Action	Contact the technical support team.

15140: I/O write error.

Cause	An error occurred during communication with External Procedure Agent.
Action	Contact the technical support team.

15141: Cannot to start External Procedure Agent.

Cause	Cannot to start the EPA (External Procedure Agent) process.
Action	Contact the technical support team.

15142: Execution of subprogram '%1\$s' failed.

Cause	Failed to execute the external procedure.
Action	Refer to the error code of EPA (External Procedure Agent).

15143: No RETURN clause specified.

Cause	No RETURN clause was specified.
Action	Specify a RETURN clause.

15144: Too many temporary variables specified.

Cause	The statement uses too many temporary variables in interpret mode.
Action	Divide or modify the statement to decrease the number of temporary variables.

15145: Too many expressions specified.

Cause	The statement uses too many expressions in interpret mode.
Action	Divide or modify the expressions.

15146: PSM compilation error.

Cause	Failed to compile the given PSM.
--------------	----------------------------------

Action	Check the error, and modify the PSM.
---------------	--------------------------------------

15147: Identifier is too long: must be less than 4000 bytes.

Cause	The length of identifier exceeds the maximum (4,000 bytes).
Action	Shorten the identifier.

15148: Invalid object '%1\$s'.

Cause	The object condition is invalid.
Action	Check the object condition, and recreate it if necessary.

15149: Serialization of a collection variable failed.

Cause	The number of elements exceeds the maximum allowed (16,777,216).
Action	Lessen the number of elements.

15150: 'Insufficient memory' error occurred during PSM execution.

Cause	'Not enough memory' error occurred during PSM execution.
Action	Modify the program to decrease memory use.

15151: Bind parameter count mismatch.

Cause	The number of specified bind parameters is invalid.
Action	Verify that the PSM and bind parameters match.

15161: Java compilation error.

Cause	Failed to compile the Java sources in the given PSM.
Action	Check the error, and modify the Java source.

15162: DML statement must have bulk in-bind parameter in a FORALL clause.

Cause	No input mode bulk parameter exists among the parameters passed to a FORALL clause.
Action	Verify that the collection is bound correctly for the FORALL clause.

15163: Unhandled exception at %1\$s line %2\$d.

Cause	A backtrace occurred because the exception was not handled.
Action	Investigate the cause from the PSM module where the exception occurred, and add appropriate exception handling code.

15164: Invalid byte code for object '%1\$d': invalid magic number.

Cause	Invalid byte code. This error may occur if the byte code was damaged, or the version is too old.
Action	Recreate the PSM object. The PSM cannot be executed due to the invalid byte code.

15165: PSM object '%1\$d' is incompatible with current server version.

Cause	The PSM version is not compatible with the current server version.
Action	Create a new PSM object.

15166: MAXLEN cannot be used for IN parameters.

Cause	MAXLEN cannot be used for IN parameters.
Action	MAXLEN is valid for OUT, IN/OUT, and RETURN parameters.

15167: Invalid return type of pipelined function: must have a valid collection type.

Cause	The pipelined function contains an invalid return type.
--------------	---

Action	Ensure the collection type returned by the pipe function is valid.
---------------	--

15168: Pipelined function may not return an expression.

Cause	An attempt was made to return an expression from a pipelined function.
Action	A pipelined function cannot return an expression. Modify the function.

15169: Pipe row function can only be used in pipelined function.

Cause	An attempt was made to use a pipe row function outside a pipelined function.
Action	Pipe row function can be used only in a pipelined function.

15170: %1\$s

Cause	Invalid error code.
Action	Check the error message.

15171: Object body '%1\$s' is required.

Cause	No object body has been defined.
Action	Define the object body.

15172: Object has not been initialized.

Cause	Unable to call function/procedures or assign values to uninitialized objects.
Action	Initialize the object by using the constructor function first.

15173: Constructor of object does not exist.

Cause	Constructor of object does not exist.
Action	Add a constructor of the object.

15174: Constructor name does not match with the type name.

Cause	Constructor name does not match with the type name.
Action	Modify the constructor name.

15175: Constructor must return SELF AS RESULT.

Cause	Constructor must return SELF AS RESULT.
Action	Set SELF AS RETURN as a return type of constructor.

15176: Specification of subprogram unit '%1\$s' is required.

Cause	Object type member subprograms need to be declared in the object specification.
Action	Define the subprogram spec in the object type specification.

15177: Object type '%1\$s' is recursively declared.

Cause	Object type cannot be self-referenced.
Action	Do not declare the object type recursively.

15178: Exceeds the maximum record field count limit.

Cause	Exceeds the maximum record field count limit.
Action	Declare less than 32568 fields per record.

15180: The PSM recursive level is too deep.

Cause	The PSM recursive level is too deep.
Action	Modify the '_PSM_RECURSIVE_LVL' parameter.

15181: Invalid collection variable access.

Cause	An invalid attempt was made to access a non-collection variable using ().
--------------	---

Action	Modify the statement to access a collection-type array.
---------------	---

15182: Invalid collection method call.

Cause	An invalid attempt was made to call a non-void collection method using ().
Action	Remove () when calling a non-void collection method.

15183: An error occurred while wrapping PSM source code.

Cause	An unexpected error occurred while wrapping PSM source code.
Action	Contact the system administrator.

15184: An error occurred while unwrapping PSM source code.

Cause	An unexpected error occurred while unwrapping PSM source code.
Action	Contact the system administrator.

15185: Unable to declare external procedure.

Cause	The number of parameters in the external procedure is too large.
Action	Reduce the number of parameters in the external procedure and try again.

15186: EXTERNAL PROCEDURE cannot recursively issue a CALLBACK function.

Cause	An EXTERNAL PROCEDURE recursively issuing a CALLBACK function is not supported.
Action	Contact the technical support team.

15187: Java source compilation has failed. %1\$s.

Cause	Java source compilation has failed.
Action	Java source compilation has failed.

15188: Batch update in PSM has failed.

Cause	Failure occurred in the batch update operation where PSM's FORALL statement or DBMS_SQL package was instantiated.
Action	Verify the SQL statement is suitable for the batch update. If suitable, contact the technical support team.

15189: PP has been invalidated during the batch update operation within PSM.

Cause	PP has been invalidated during the batch update operation where PSM's FORALL statement or DBMS_SQL package was used.
Action	Contact the technical support team.

15190: Insufficient privileges to create EXTERNAL PROCEDURE in DIRECT EXECUTE mode.

Cause	User does not have an appropriate permission to create EXTERNAL PROCEDURE in DIRECT_EXECUTE mode.
Action	SYSDBA permission is required.

15191: The duplicate index '%1\$s' has been used incorrectly in the FORALL statement.

Cause	Only an automatic value is allowed to access the collection using a duplicate index in the FORALL statement.
Action	Remove the arithmetical operation used for accessing the collection.

15192: Failed to optimize PSM Constant Folding.

Cause	There is an expression that cannot be handled while optimizing PSM Constant Folding.
Action	Disable the option when optimizing PSM Constant Folding.

15193: Failed to compile the external procedure: the %1\$s package could not be found.

Cause	To execute the external procedure, the %1\$s package is required.
Action	Contact the system administrator.

15194: The cursor '%1\$s' has not been declared as FOR UPDATE. The cursor cannot be used for a CURRENT OF section.

Cause	Only the cursor of the query declared as FOR UPDATE can perform a positioned update.
Action	Insert a FOR UPDATE section to the query specified in the cursor.

15195: An operation that is not permitted within EXTERNAL PROCEDURE was executed.

Cause	An operation that is not permitted within EXTERNAL PROCEDURE was executed.
Action	Modify the EXTERNAL PROCEDURE.

15196: RESULT_CACHE OPTION is not allowed.

Cause	Refer to the manual.
Action	RESULT_CACHE OPTION cannot be used.

15197: A Java source name cannot be used as an ID.

Cause	A Java source name was used as a PSM ID.
Action	Modify the PSM source.

15198: PSM compiler internal error.

Cause	PSM compiler internal error.
Action	Contact the technical support team.

15199: The return type of the MAP method is invalid.

Cause	MAP methods must have a scalar return type.
Action	Modify the signature of the MAP method.

15200: The parameter of the MAP method is invalid.

Cause	MAP methods can only use the SELF parameter.
Action	Modify the signature of the MAP method.

15201: The return of the ORDER method is invalid.

Cause	ORDER methods must have an integer return type.
Action	Modify the signature of the ORDER method.

15202: The parameter of the ORDER method is invalid.

Cause	ORDER methods can only use the SELF parameter or objects that have the same type.
Action	Modify the signature of the ORDER method.

15203: The signature of the MAP or ORDER method is invalid.

Cause	A function can only contain a single MAP or ORDER function.
Action	Modify the declaration of the object type.

15204: Invalid Object specification.

Cause	The current specification is invalid in Object.
Action	Modify the signature of the object type.

15205: The object specification does not contain a declaration for the method '%1\$s', which is defined in the object body.

Cause	The object specification does not contain a declaration for the method '%1\$s', which is defined in the object body.
Action	Cannot compile. The object specification or object body must be modified.

15206: The method '%1\$s', declared in the object specification, must be defined.

Cause	The method '%1\$s', declared in the object specification, must be defined.
Action	Cannot compile. The object specification or object body must be modified

15207: Duplicate method names exist.

Cause	Duplicate method names are defined in the object specification.
Action	Cannot compile. The object specification must be modified.

15208: The value of this object type cannot be compared.

Cause	MAP and ORDER methods are not defined.
Action	The value of this object type can be compared using MAP and ORDER methods.

15209: Unable to find a loop to execute the CONTINUE statement.

Cause	The CONTINUE statement was not used in a loop.
Action	Execute the CONTINUE statement in loop.

15210: This mode is not supported in batch psm.

Cause	The _USE_SUCCESS_WITH_INFO_IN_BATCH iparam must be enabled in batch psm.
Action	Set the _USE_SUCCESS_WITH_INFO_IN_BATCH iparam to YES.

15211: The return type of the bulk cursor is invalid.

Cause	The number of columns returned by the bulk cursor does not match the return type.
Action	The operation cannot be performed on the cursor.

15212: Anon PP is invalidated.

Cause	Anon PP is invalidated.
Action	Contact the technical support team.

15213: Psm RemoteDB internal error.

Cause	Psm RemoteDB internal error.
Action	Contact the technical support team.

15214: Unable to make the aggregation function.

Cause	The return type is a composite type, the parameter is 'OUT' or 'IN OUT', or the parameter type is a composite type or a lob type.
Action	Redefine the function.

15215: The composite type of a bind parameter is invalid.

Cause	A composite type that cannot be used was bound.
Action	Check the bind parameter.

15216: Unable to execute the pipelined function.

Cause	There is no available session to execute the pipelined function.
Action	Re-execute the function after securing an available session.

15217: Improper use of an aggregate function or a pipelined table function.

Cause	Aggregate and table functions cannot be used as a general function.
Action	Modify the PSM program.

15218: The table row data type and value do not match the data type.

Cause	The number of table columns and values do not match the number of data fields.
Action	Cannot be supported. The UPDATE/INSERT statement must be modified.

15219: The object method cannot be called.

Cause	Accessed an object instance that has not been created.
Action	Check whether the instance has been created.

15220: Used an invalid continue clause in the loop.

Cause	Used an invalid continue clause in the loop.
Action	Modify the continue clause.

15221: Cannot execute the function.

Cause	This function is no longer provided.
Action	Contact the technical support team for more detailed information.

15222: Attempted to inherit from a non-object type.

Cause	A non-object type cannot be inherited.
Action	Check that the type you are trying to inherit from is an object type.

15223: Attempted to inherit from a final object type.

Cause	A final object type cannot be inherited.
Action	Check the attributes of the object type that you are trying to inherit from.

15224: The specified OID is invalid.

Cause	The hex string of the OID is invalid.
Action	Enter a valid hex string.

15225: Duplicate attribute name.

Cause	An attribute with the same name already exists.
Action	Cannot compile the specified statement.

15226: Unable to resolve the specified ex-expression as '%1\$s' type.

Cause	The ex-expression type is not a parent/child type of '%1\$s'.
Action	The ex-expression cannot be compiled or executed.

15227: A method cannot be 'FINAL' and 'NOT INSTANTIABLE'.

Cause	A method cannot be declared as both 'FINAL' and 'NOT INSTANTIABLE'.
Action	Modify the method definition.

15228: An 'INSTANTIABLE' object type cannot have a 'NOT INSTANTIABLE' method.

Cause	An 'INSTANTIABLE' object type cannot have a 'NOT INSTANTIABLE' method.
Action	Modify the method definition.

15229: This method cannot be overridden.

Cause	There is no method to override.
Action	To override a method, the method must exist in its parent object type.

15230: The return clause does not specify 'SELF AS RESULT'.

Cause	The constructor must use the clause 'RETURN SELF AS RESULT'.
Action	Modify the return clause to 'RETURN SELF AS RESULT'.

15231: An error occurred while processing the batch DML.

Cause	One or more errors occurred while processing the batch DML.
Action	Check the error(s).

15232: \$ERROR-'%1\$s'.

Cause	\$ERROR-'%1\$s'.
Action	\$ERROR-'%1\$s'.

15233: Invalid use of dynamic SQL.

Cause	RETURNING INTO clause is missing from the query.
Action	Change the query.

15234: A non-static expression was used.

Cause	Only static expressions are allowed.
Action	Use a static expression.

15235: Duplicate Compound Trigger Section.

Cause	A duplicate Compound Trigger Section already exists.
--------------	--

Action	Modify the Compound Trigger Section.
---------------	--------------------------------------

15236: Invalid Compound Trigger Section.

Cause	Only views can have a row instead section.
Action	Modify the Compound Trigger Section.

15237: Invalid use of refcursor in a CURSOR FOR LOOP statement.

Cause	Refcursor cannot be used in a CURSOR FOR LOOP statement.
Action	Modify the CURSOR FOR LOOP statement.

15238: PRAGMA SERIALLY_REUSABLE must be declared in both the package specification and body.

Cause	PRAGMA SERIALLY_REUSABLE is not declared in the package specification or the package body.
Action	Declare PRAGMA SERIALLY_REUSABLE in the missing part of the package.

15239: PRAGMA SERIALLY_REUSABLE must be declared in the package specification.

Cause	This PRAGMA clause is not allowed in the current part of the package.
Action	Change or delete the PRAGMA clause.

15240: Unable to access the SERIALLY REUSABLE '%1\$s' package.

Cause	The program attempted to access a SERIALLY REUSABLE package in PSM called from SQL context.
Action	Remove references to SERIALLY REUSABLE packages from the program.

15241: RemoteDB name is too long.

Cause	RemoteDB name is too long.
Action	Check the RemoteDB name.

15242: Lob arguments are not permitted in calls to remote database.

Cause	Use of lob argument in call to remote database.
Action	Do not use lob argument in call to remote database.

15243: Object type '%1\$s' has no attributes.

Cause	An attempt was made to define an object type that has no attributes.
Action	To define an object type, it must have at least one attribute.

15244: The trigger does not support columns of nested object type.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

15245: References to data of the LONG or LONG RAW type are not allowed in triggers.

Cause	The trigger references data of the LONG or LONG RAW type.
Action	Do not make any references to LONG or LONG RAW data within triggers.

15246: The RESULT_CACHE option is not supported. Reason: %1\$s.

Cause	The function violates a restriction of RESULT_CACHE, leading to a compilation error.
--------------	--

Action	Ensure the function satisfies all prerequisites for RESULT_CACHE. If it does not, remove the option.
---------------	--

제15장 16000 ~ 16999

**16001: Unable to allocate the shared memory:
_PPC_MAX_CHUNK_SIZE is too small.**

Cause	Unable to allocate the shared memory: _PPC_MAX_CHUNK_SIZE is too small.
Action	Increase the value of _PPC_MAX_CHUNK_SIZE.

제16장 17000 ~ 17999

17001: Login failed: invalid user name or password.

Cause	Invalid user name or password.
Action	Verify that the user name and password are correct.

17002: Password has expired.

Cause	Password has expired.
Action	Update the password and then try again.

17004: Permission denied.

Cause	The action is unauthorized.
Action	Obtain proper authorization and try again.

17005: The cascade option is required before revoking privileges.

Cause	Constraints for using the corresponding reference object privilege exist.
Action	Specify the cascade option.

17006: Account is locked.

Cause	The user's account is locked.
Action	Unlock the account.

17007: Password file is corrupted or missing: Unable to log in.

Cause	The password file is invalid or does not exist.
--------------	---

Action	A password file is created automatically if the server is behaving normally. Contact the technical support team.
---------------	--

17008: Unable to log in: server is booting up or shutting down.

Cause	Cannot log in when the server is booting or shutting down.
Action	Log on after the boot process finishes.

17009: Cannot change the password.

Cause	Password cannot be changed.
Action	Check the values of PASSWORD_REUSE_TIME and PASSWORD_REUSE_MAX in user profile settings. Ensure the password string is not too simple.

17010: The password has expired(grace).

Cause	The password has expired(grace).
Action	Update the password and then try again.

17011: Logon denied as CREATE SESSION privilege is not granted.

Cause	The user does not have CREATE SESSION privilege.
Action	Grant CREATE SESSION privilege to the user.

17012: Data integrity check about a TDE column failed.

Cause	A TDE column has been modified by an adversary.
Action	Please, contact your DBA.

17013: TDE encryption failed.

Cause	TDE encryption failed.
Action	Please, refer to tracelog.

17014: TDE decryption failed.

Cause	TDE decryption failed.
Action	Please, refer to tracelog.

17015: Cannot login with the crypto level %1\$d.

Cause	The crypto level configured does not meet its prerequisite.
Action	Check the crypto level and its requirements.

17016: Proxy login not allowed.

Cause	A proxy user is not authorized to connect as a client.
Action	Check requirements and limitations of proxy users.

17017: Parameter number of USER password verify function is not supported.

Cause	Parameter number of USER password verify function is not supported.
Action	Check parameter number of USER password verify function.

17018: Remote DBA login not allowed.

Cause	A DBA is not authorized to connect as a remote client.
Action	Check requirements and limitations of DBA users.

17019: Cannot open session with user '%1\$s'.

Cause	The maximum number of sessions are already open.
Action	Close opened sessions or check profile of user.

17020: Cannot login during database creation.

Cause	Login is not permitted while create database is on progress.
Action	Please try again after database is created.

17021: Insufficient privileges. System privilege '%1\$s' is required.

Cause	The action is unauthorized.
Action	Obtain proper authorization and try again.

제17장 18000 ~ 18999

18001: System call error: %1\$d (%2\$s).

Cause	An error occurred in system call.
Action	Check the system call arguments.

18002: open('%2\$s') failed -- %1\$s.

Cause	The file does not exist or file open privileges are required.
Action	Modify file and directory permissions.

18003: write() failed -- %1\$s.

Cause	Failed to write to the file
Action	Verify the disk is operating normally. If the disk is full, free up disk space.

18004: write() failed -- disk full.

Cause	Failed to write to the file.
Action	Check that the disk is running normally. If the disk is full, free up disk space.

18005: link('%2\$s', '%3\$s') failed -- %1\$s.

Cause	Failed to link the file.
Action	Modify file and directory permissions.

18006: rename('%2\$s', '%3\$s') failed -- %1\$s.

Cause	The file does not exist or file editing privileges are required.
--------------	--

Action	Modify file and directory permissions.
---------------	--

18007: mkdir('%2\$s') failed -- %1\$s.

Cause	Failed to create the directory.
Action	Modify the permissions in the parent directory.

18008: fork() failed -- %1\$s.

Cause	Failed to create a process.
Action	Increase system resources, or check the OS settings.

18009: exec*('%2\$s') failed -- %1\$s.

Cause	Failed to convert the process.
Action	Increase system resources, or check the OS settings.

18010: waitpid(%2\$d) failed -- %1\$s.

Cause	The child process was terminated abnormally.
Action	Check the execution environment.

18011: system('%2\$s') failed -- %1\$s.

Cause	Failed to execute internal commands.
Action	Increase system resources, or check the OS settings.

18012: %1\$s(): child process exited with return code %2\$d.

Cause	Invalid execution result from child process.
Action	Contact the system administrator.

18013: %1\$s(): child process terminated abnormally with signal %2\$d.

Cause	The child process terminated abnormally.
Action	Check the execution environment.

18014: %1\$s(): child process stopped with signal %2\$d.

Cause	The child process terminated abnormally.
Action	Check the execution environment.

18015: dlopen('%2\$s') failed -- %1\$s.

Cause	The shared library does not exist or access privileges are required.
Action	Modify the file and directory permissions, recreate the corresponding schema object, or execute ALTER RECOMPILE.

18016: dlsym('%2\$s') failed -- %1\$s.

Cause	Cannot read a symbol in the created shared library.
Action	Recreate the corresponding schema object or execute ALTER RECOMPILE.

18017: Unknown I/O error.

Cause	An I/O error of unknown cause occurred.
Action	Enable logging to get more information about the error.

18018: write() failed -- file is too large.

Cause	Failed to write to a file because the file is too big.
Action	Verify that the disk is running normally. If the disk is full, free up disk space.

18019: Socket I/O timeout.

Cause	Timeout during I/O operation.
Action	Check for any communication problems between the server and the client.

18020: A health check request has been received.

Cause	Skip logging authentication error for health check request.
Action	This is not an error case.

18021: mmap() failed -- %1\$s.

Cause	An error occurred during mmap().
Action	Check the error code.

18022: getrlimit('%2\$s') failed -- %1\$s.

Cause	Possible cause: Incorrect resource type, insufficient permission, or system error.
Action	Verify the resource type and permissions, and check the logs if necessary.

18023: setrlimit('%2\$s') failed -- %1\$s.

Cause	Possible cause: Incorrect resource type, insufficient permission, or allowable scope exceeded.
Action	Verify the resource type, permissions, and specified value. Check the logs if necessary.

18024: Socket I/O error: %1\$s

Cause	Socket I/O error: %1\$s
Action	Check network configuration with accompanying error message for more details.

18025: Pipe I/O error: %1\$s

Cause	Pipe I/O error: %1\$s
Action	Examine the accompanying error message for additional details.

제18장 21000 ~ 21999

21001: Unable to start transaction.

Cause	Cannot start the transaction.
Action	Check the cause of the failure and try again.

21002: No more undo space available.

Cause	Insufficient space remains in the undo tablespace.
Action	Free up space in the tablespace and specify autoextend in the datafile.

21003: Snapshot is too old.

Cause	The snapshot is too old to read.
Action	Check the cause of the failure and try again.

21004: No more extent available in tablespace '%1\$s'.

Cause	Unable to create an additional extent in this table.
Action	Free up space in the tablespace and specify autoextend in the datafile.

21005: Unable to initialize datafile %1\$s ('%2\$d' in tablespace '%3\$s').

Cause	Cannot initialize the datafile.
Action	Check the properties of the datafile.

21006: Unable to extend datafile '%1\$d' in tablespace '%2\$s'.

Cause	Cannot extend the datafile.
Action	Adjust the datafile so that it can be extended.

21007: Unable to shrink datafile '%1\$d' in tablespace '%2\$s'.

Cause	Cannot shrink the datafile.
Action	Remove segments occupying the datafile and then try again.

21008: Savepoint '%1\$s' was not found.

Cause	The specified savepoint does not exist.
Action	Specify a valid savepoint.

21009: No tempfile was found.

Cause	No file exists in the temporary tablespace.
Action	Add files in the temporary tablespace and then try again.

21010: Tablespace %1\$s was not found.

Cause	The specified tablespace does not exist.
Action	Specify a valid tablespace.

21011: Seqno overflow: %1\$d undo segment.

Cause	Cannot continue to increase the sequence numbers of undo segments. The transaction is too long.
Action	Raise the uniform size of the undo tablespace, or use the AUTOALLOCATE option.

21012: Unable to serialize access for this transaction.

Cause	An attempt was made to access the modified data after the transactions began.
Action	The transaction is not accessible.

21013: Undo segment was not found in the UNDO tablespace.

Cause	The undo segment does not exist.
Action	Specify a valid undo segment.

21014: No space available in SYSTEM tablespace.

Cause	Cannot extend the undo segment of SYSTEM tablespace.
Action	Increase the size of the SYSTEM tablespace.

21015: Unable to create a system undo segment.

Cause	Unable to create an undo segment in the SYSTEM tablespace.
Action	Check the cause of the failure and try again.

21016: Insufficient processes (%1\$d) for transaction recovery (at least %2\$d needed).

Cause	Cannot recover non-committed transactions. The number of processes is insufficient.
Action	Increase the number of working processes and threads.

21017: Unable to bring undo segment (#%1\$d) on/offline: %2\$s.

Cause	Cannot bring the undo segment online or offline.
Action	Specify a valid segment.

21018: Undo segment was not found: '%1\$d'.

Cause	The specified undo segment does not exist.
Action	Specify a valid segment.

21019: Lock held by in-doubt distributed transaction.

Cause	Lock is held by an in-doubt transaction.
Action	Fix the in-doubt transaction and then try again.

21020: Unable to specify undo tablespace %1\$s as default undo tablespace.

Cause	The specified undo tablespace cannot be used as the default undo tablespace.
Action	Ensure that the specified tablespace is an undo tablespace and is not dropped or offline.

21021: Unable to use tablespace %1\$d.

Cause	Cannot use the specified temporary tablespace because it was dropped or currently being dropped.
Action	Specify another temporary tablespace.

21022: No prepared transaction found with transaction ID %1\$s.

Cause	Cannot find a prepared transaction with the requested transaction ID.
Action	Specify a valid ID.

21023: Unable to execute specified operation during TX recovery.

Cause	Cannot execute the operation because transaction is not completely recovered.
Action	Try again after the transaction recovery is complete.

21024: Unable to begin new transaction in current server mode.

Cause	Tasks cannot be performed in the current server mode.
Action	Start the server in NORMAL mode and then execute the task.

21025: Unable to extend segment: maximum number of extensions reached.

Cause	The number of extensions has reached the maximum limit specified in the segment.
Action	Raise the value of the MAXEXTENTS property of the segment.

21026: Sequence of undo segment %1\$d has limit of %2\$d.

Cause	The undo segment does not exist.
Action	Check the cause of the failure and try again.

21027: Unable to use temp tablespace in current server mode.

Cause	Cannot use a temporary tablespace in the current server mode.
Action	Start the server in NORMAL mode.

21028: Unable to bring minimum number of undo segments online.

Cause	The number of online undo segments exceeded the maximum limit.
Action	Increase the value of _USGMT_ONLINE_MAX parameter, or decrease the value of _USGMT_ONLINE_MIN parameter.

21029: Invalid specification for UNDO_TABLESPACE parameter.

Cause	The UNDO_TABLESPACE parameter is specified incorrectly.
Action	Specify a valid value in the UNDO_TABLESPACE parameter.

21030: DML operation is not permitted.

Cause	DML operation is not permitted.
Action	The transaction has been opened in read-only mode. Commit or roll back before trying again.

21031: Cannot allocate ITL for PE transaction.

Cause	Failed to allocate ITL for PE transaction.
Action	Try again.

21032: Failed to perform two-phase commit for the massive cluster system.

Cause	Failed in the slave node. The corresponding slave tx has failed.
Action	Check the reason and whether the slave node is alive. Try again.

21033: Cannot access a transaction (%1\$d.%2\$d.%3\$d).

Cause	Cannot access a transaction (%1\$d.%2\$d.%3\$d).
Action	Commit or roll back the transaction and then try again. Or make the status of the corresponding offline tablespace online.

21034: There is no snapshot that corresponds to the specified time.

Cause	There is no value that corresponds to the specified time in the mapping table.
Action	Increase the value of UNDO_RETENTION to store more snapshots.

21038: Unable to drop the datafile. %1\$s ('%2\$s' in tablespace '%3\$s').

Cause	Unable to drop the datafile.
--------------	------------------------------

Action	Check the tablespace and the datafiles.
---------------	---

21039: The space quota for tablespace '%3\$s' is exceeded (user_id=%1\$s, number of blocks attempted to allocate=%2\$d).

Cause	Due to the quota configuration, additional blocks cannot be allocated within the tablespace.
Action	Check the quota configuration.

21040: Unable to execute specified operation during in-doubt TX recovery.

Cause	Cannot execute the operation because in-doubt transaction is not completely recovered.
Action	Fix the in-doubt transaction and then try again.

21042: Unable to begin new transaction in read only server mode.

Cause	Tasks cannot be performed in the current server mode.
Action	Start the server in READ WRITE mode and then execute the task.

21043: No such temporary file exists in the temporary tablespace.

Cause	No such temporary file exists in the temporary tablespace.
Action	Check the file name.

21044: The TEMP_TS_CNT_MAX is less than the number of existing temporary tablespaces.

Cause	Retry the operation using a valid TEMP_TS_CNT_MAX value.
Action	

21045: Unable to bring minimum number of undo segments online.

Cause	The number of online undo segments exceeded the maximum limit.
Action	Increase the value of USGMT_ONLINE_MAX parameter, or decrease the value of USGMT_ONLINE_MIN parameter.

21046: The snapshot is too old to be used for flashback query.

Cause	Since the snapshot is too old, undo log for it is no longer available.
Action	Increase the value of _FLASHBACK_QUERY_SNAPSHOT_LIMIT.

21047: The snapshot became too old after changes in the undo tablespace.

Cause	The undo log is no longer available due to this alteration.
Action	Verify any recent changes made to the undo tablespace and retry.

21048: The query has been canceled due to a suspected hang of the CR build.

Cause	The execution of the CR build took too long.
Action	Retry the canceled query.

21049: The segment for dba '%1\$d_%2\$d' is not found or is invalid

Cause	The specified segment was not found or is an invalid type
Action	Specify a valid arguments.

21050: TEMP_GRANULE_SIZE is too large.

Cause	The TEMP_GRANULE_SIZE value exceeds the expected size for TEMP file id: '%1\$d'.
Action	Check the slog, and either increase TEMP file id: '%1\$d' capacity or reduce TEMP_GRANULE_SIZE.

21052: The session(%1\$d) successfully extended the datafile(%2\$d) in the undo tablespace(%3\$d), but no space was allocated for the file.

Cause	The session should have been allocated space for the extended file. Root cause analysis is required to determine why space allocation failed.
Action	Ensure that datafiles for the undo tablespace are extended in advance.

21053: The specified transaction ID(%1\$d.%2\$d.%3\$d) is invalid.

Cause	The ID may have been entered incorrectly, or the transaction might have already been rolled back or committed.
Action	Check USN, SLOT, and WRAP in v\$transaction, then re-enter the correct ID.

21054: Cannot create a deferred undo segment about tablespace(%1\$d).

Cause	The failure may have been due to insufficient space for system tablespace.
Action	Retry tablespace offline.

21055: Unable to extend segment ID(%1\$u): Current segment size is %2\$uKB, requested size is %3\$uKB, but MAXSIZE is %4\$uKB.

Cause	The size of the segment has reached the maximum limit.
Action	Raise the value of the MAXSIZE property of the segment.

21056: Unable to perform a consistent read on the block (tsid: %1\$u, dba: %2\$u_%3\$u, blktype: %4\$u).

Cause	An invalid consistent read request was detected.
Action	Contact the technical support team.

제19장 22000 ~ 22999

22001: Unrecognized virtual table name '%1\$s'.

Cause	The virtual table does not exist.
Action	The definition of dynamic performance view (DPV) may be wrong. Run 'system.sh' from the server to rebuild DPV.

22002: Virtual table '%1\$s' has inconsistent definitions.

Cause	The virtual table definitions do not match those of the current server version.
Action	The definition of dynamic performance view (DPV) may be wrong. Run 'system.sh' from the server to rebuild DPV.

22003: Virtual table '%1\$s' is not supported in current boot mode.

Cause	The virtual table is not supported in the current boot mode.
Action	Some virtual tables can only be implemented in certain boot modes. Check the boot mode again.

22004: Failed to allocate a working thread to process the global view.

Cause	There are insufficient working threads available to process the global view.
Action	To search for the global view, an available working thread must exist in the remote node.

제20장 23000 ~ 23999

23001: Unterminated comment.

Cause	The comment was not terminated.
Action	Check the comment.

23002: Missing single quote.

Cause	A closing single quotation mark is missing.
Action	Check the use of single quotation marks.

23003: Missing double quote.

Cause	A closing double quotation mark is missing.
Action	Check the use of double quotation marks.

23004: Invalid identifier.

Cause	Invalid identifier.
Action	Verify that the identifier is valid.

23005: Invalid concatenate operator.

Cause	Invalid concatenate operator.
Action	Verify that a double-pipe concatenation operator

23006: Invalid not equal (!=) operator.

Cause	Invalid comparison operator.
--------------	------------------------------

Action	Verify that one of the following was used: "!=", "^=", "~=" or "<>".
---------------	--

23007: Identifier is too long.

Cause	The identifier length exceeds the maximum allowed.
Action	Ensure the identifier contains less than 30 characters.

23008: String literal is too long.

Cause	The string constant is longer than 4,000 bytes.
Action	Ensure the string constant is shorter than 4,000 bytes.

23009: Missing parenthesis.

Cause	A closing parenthesis is missing.
Action	Check the use of parentheses.

23010: Identifier is too long (maximum of %1\$d characters allowed).

Cause	The length of the identifier exceeded the maximum allowed.
Action	Shorten the identifier.

23011: Quoted string was not properly terminated.

Cause	Terminating delimiter for quoted string was not found.
Action	Check whether the terminating delimiter correctly pairs with the beginning one.

제21장 24000 ~ 24999

24001: Unable to open control file.

Cause	Failed to open the control file.
Action	Check the file path and permissions and try again.

24002: Too many %1\$s.

Cause	The number of DB files exceeds the specified number.
Action	Contact the technical support team.

24003: Unable to read control file.

Cause	Cannot read the control file.
Action	Check the file path and permissions and try again.

24004: Unable to write to control file.

Cause	Cannot write to the control file.
Action	Check the file path and permissions and try again.

24005: Unable to create controlfile.

Cause	Failed to create a control file.
Action	Check the file path and permissions and try again.

24006: Unable to load controlfile %1\$s.

Cause	Cannot load the control file.
--------------	-------------------------------

Action	Check the file path and permissions and try again.
---------------	--

24007: Invalid control file record %1\$d.%2\$d.

Cause	The record was not found in the control file.
Action	Verify that the correct control file is specified and try again.

24008: Unable to add tablespace name %1\$s.

Cause	Failed to add a tablespace.
Action	Verify the tablespace name is not a duplicate.

24009: Tablespace %1\$s is not empty.

Cause	The tablespace is not empty.
Action	Check data files in the tablespace and try again.

24010: Tablespace %1\$s is in online backup mode.

Cause	The tablespace is involved in an online backup.
Action	Try again after the online backup is complete.

24011: Tablespace %1\$s is not in online backup mode.

Cause	The tablespace is not involved in an online backup.
Action	Try again after an online backup has started.

24012: No such tablespace %1\$d.

Cause	Failed to add the tablespace.
Action	Verify a tablespace exists and try again.

24013: No space left in tablespace %1\$d.

Cause	No space is left in the control file.
Action	Check the control file and try again.

24014: Datafile %1\$d is not online.

Cause	Cannot use the datafile.
Action	Contact the technical support team.

24015: Datafile %1\$d was not found.

Cause	Cannot find the datafile.
Action	Contact the technical support team.

24016: Datafile %1\$d in tablespace %2\$d was not found.

Cause	Cannot find the datafile.
Action	Contact the technical support team.

24017: No datafile left.

Cause	No datafile left.
Action	Check the control file and try again.

24018: CF-DD correction is required due to wrong CF/DD info or added/dropped datafiles while recovery process.

Cause	CF-DD correction is required due to wrong CF/DD info or added/dropped datafiles while recovery process.
Action	Contact the technical support team for the guide.

24019: Critical error occurred.

Cause	A critical error occurred in the control file.
Action	Contact the technical support team.

24020: No such logfile ID %1\$d.

Cause	Cannot find the ID of the log file.
Action	Check the log file and try again.

24021: Unable to add additional log files.

Cause	Cannot add log files.
Action	Check the values of MAXLOGGROUPS and MAXLOGMEMBERS.

24022: Duplicate log file ID %1\$d exists.

Cause	The log file ID is already in use.
Action	Choose a new logfile ID and try again.

24023: Unable to drop log file %1\$s.

Cause	Failed to delete the log file.
Action	Locate the cause of the failure and try again.

24024: Unable to drop log member %1\$s.

Cause	Failed to delete the log member.
Action	Check the number of log files and see if they are archived.

24025: Unable to drop system tablespace datafile %1\$d.

Cause	Cannot drop the datafile of the system tablespace.
--------------	--

Action	Check the datafile to be deleted.
---------------	-----------------------------------

24026: Blocksize (%1\$d) does not match DB_BLOCK_SIZE (%2\$d).

Cause	DB_BLOCK_SIZE is invalid.
Action	Modify DB_BLOCK_SIZE and try again.

24027: Invalid DB_NAME value in .tip file: '%1\$s' should be '%2\$s'.

Cause	The DB name does not match with the control file.
Action	Check the [database sid].tip file and the control file.

24028: Unable to begin online backup '%1\$s' - %2\$s.

Cause	Online backup is available only in archive log mode.
Action	Change the DB setting to archive log mode.

24029: Unable to shut down: file %1\$d ('%2\$s') has online backup set.

Cause	Online backup is being processed.
Action	End the online backup and close DB.

24030: Unable to create more tablespace.

Cause	Cannot create more tablespace.
Action	Check the value of MAXDATAFILES and modify it if necessary.

24031: Unable to create more data files.

Cause	Cannot create more data files.
Action	Check the value of MAXDATAFILES and modify it if necessary.

24032: Archive filename is too long: must be less than %1\$d.

Cause	The absolute path of the archive is too long.
Action	Specify a shorter name or absolute path.

24033: Unable to add log member %1\$s.

Cause	Cannot add a log member.
Action	Check the value of MAXLOGMEMBERS and modify it if necessary.

24034: Unable to change datafile #%1\$d status: %2\$s.

Cause	Cannot change the condition of the data file.
Action	Contact the technical support team.

24035: Unable to read file %1\$d at this time.

Cause	The datafile is offline.
Action	Set the file to online and try again.

24036: Unable to modify file %1\$d.

Cause	The datafile is read-only.
Action	Change the read/write settings of the file and try again.

24037: Incompatible control file version.

Cause	The control file is not compatible.
Action	Check the version information of the control file and the server.

24038: Tablespace '%1\$s' is offline.

Cause	The tablespace must be online.
--------------	--------------------------------

Action	Set the tablespace to online and try again.
---------------	---

24039: Unable to modify tablespace '%1\$s'.

Cause	The tablespace is read-only.
Action	Change the tablespace settings and try again.

24040: Unable to set tablespace '%1\$s' as read-only: %2\$s.

Cause	Cannot set the tablespace as read-only.
Action	Check the tablespace type and try again.

24041: Unable to set datafile #'%1\$d' as read-only: %2\$s.

Cause	Cannot set the datafile as read-only.
Action	Check the data file type and try again.

24042: Tablespace '%1\$s' is not read only: %2\$s.

Cause	Cannot make the tablespace read-only.
Action	Check the tablespace settings and try again.

24043: Unable to clear logfile: %1\$s.

Cause	Cannot clear the logfile.
Action	Contact the technical support team.

24044: Redo thread #'%1\$d' is too big (max %2\$d).

Cause	No space available for redo threads.
Action	Contact the technical support team.

24045: Unable to change thread #%1\$d status: %2\$s.

Cause	Cannot modify the properties of the redo/flashback thread.
Action	Check the condition of the redo/flashback thread and try again.

24046: Tablespace '%1\$s' is a temporary tablespace.

Cause	Temporary tablespace.
Action	Contact the technical support team.

24047: Tablespace '%1\$s' is in the middle of backup.

Cause	The tablespace is involved in an online backup.
Action	Try again after the online backup is complete.

24048: File %1\$d is in the middle of backup.

Cause	The datafile is involved in an online backup.
Action	Try again after the online backup is complete.

24049: Unable to open datafile #%1\$d: %2\$s.

Cause	Cannot open the datafile because datafile information does not match the control file.
Action	Check the condition of the control file and the datafile and try again.

24050: Database cannot be run in single instance mode.

Cause	Cannot run the database in single instance mode.
Action	Use cluster database.

24051: Cannot take tablespace '%1\$s' offline.

Cause	Cannot take the tablespace offline.
--------------	-------------------------------------

Action	Check the condition of the tablespace and try again.
---------------	--

24052: Only allowed if media recover is enabled.

Cause	Media recover is not enabled.
Action	Check the log mode of the database and try again.

24053: Cannot recover the redo thread #%1\$d because it is closed.

Cause	Cannot recover the redo thread.
Action	Check the log files that belong to the redo thread.

24054: The comp version of the control file does not match.

Cause	The comp version of the control file does not match that of a server.
Action	Check the comp versions of the control file and the server, and recreate a control file if necessary.

24055: None of the tablespaces are in the online backup mode.

Cause	Cannot perform end backup.
Action	Try again after an online backup is started.

24056: Flashback thread #%1\$d is too big (max %2\$d).

Cause	No space available for flashback threads.
Action	Contact the technical support team.

24057: No such redo thread %1\$d.

Cause	Cannot find the redo thread.
Action	Check the configuration and try again.

24058: No such backup set %1\$d.

Cause	Cannot find the backup set.
Action	Verify that the backup set exists and try again.

24059: Tablespace %1\$s not in backup set %2\$d.

Cause	Cannot find the tablespace in the given backup set.
Action	Check the backup set.

24060: No such controlfile section %1\$s.

Cause	Cannot find the given section.
Action	Verify that the given section exists and try again.

24061: Controlfile section %1\$s has more entries than %2\$d.

Cause	Cannot resize the given section.
Action	Try again with a larger size.

24062: Invalid tsid bitmap.

Cause	Invalid tsid bitmap.
Action	Verify that tsid bitmap is in correct format.

24063: Backup set %1\$u already exists.

Cause	Cannot add backup set.
Action	Retry after deleting backupset.

24064: The backup archive log file %1\$s is not valid.

Cause	The backup archive log file %1\$s is not valid.
--------------	---

Action	Retry the operation with a valid backup archive log file.
---------------	---

24065: Failed to open backup directory %1\$s.

Cause	Failed to open backup directory %1\$s.
Action	Retry the operation with a valid backup directory.

24066: Failed to get free backup set record number in the control file.

Cause	Failed to get free backup set record number in the control file.
Action	Retry the backup operation after deleting old backup sets.

24067: The base backup set #%%1\$d for the backup set #%%2\$d does not exist.

Cause	The base backup set #%%1\$d for the backup set #%%2\$d does not exist.
Action	Retry the operation after performing a full backup.

24068: The latest backup set #%%1\$d is backed up without archive logs.

Cause	The latest backup set #%%1\$d is backed up without archive logs.
Action	Retry without using --with-archivelog option.

24069: Can't find the target archive log in CF.

Cause	Can't find the target archive log in CF.
Action	Check whether the target archive log exists in CF.

24070: Failed to get free backup archivelog record number in the control file.

Cause	Failed to get free backup archivelog record number in the control file.
Action	Retry the backup operation after deleting old backup archivelog.

24071: Datafile backup is successful, but cannot backup archivelogs.

Cause	Datafile backup is successful, but cannot backup archivelogs.
Action	Database must be single or share same LOG_ARCHIVE_DEST on Active Storage.

24072: A cleanup is being performed for the previous RMGR operation.

Cause	A cleanup is being performed for the previous RMGR operation.
Action	Retry the operation after a while.

24073: The thread count specified for parallel operation exceeds the thread count limit (thread count limit = %1\$d).

Cause	The thread count specified for parallel operation exceeds the thread count limit (thread count limit = %1\$d).
Action	Retry the operation with a valid thread count.

24074: Thread allocation failed because the thread count specified for parallel operation exceeds the idle thread count (idle thread count = %1\$d).

Cause	Thread allocation failed because the thread count specified for parallel operation exceeds the idle thread count (idle thread count = %1\$d).
Action	Retry the operation with a valid thread count.

24075: Failed to perform end backup operation (tsid = %1\$d).

Cause	Failed to perform end backup operation (tsid = %1\$d).
Action	Retry the operation after performing end backup.

24076: Invalid dfid (dfid = %1\$d).

Cause	Invalid dfid (dfid = %1\$d).
Action	Retry the operation with a valid dfid.

24077: The validation target datafile does not exist (dfid = %1\$d).

Cause	The validation target datafile does not exist (dfid = %1\$d).
Action	Retry the operation with a valid dfid.

24078: The validation target datafile is inaccessible (dfid = %1\$d).

Cause	The validation target datafile is inaccessible (dfid = %1\$d).
Action	Retry the operation with a valid dfid.

24079: The validation is canceled and cleanup is ongoing.

Cause	The validation is canceled and cleanup is ongoing.
Action	Retry the operation.

24080: The previous RMGR validation is ongoing.

Cause	The previous RMGR validation is ongoing.
Action	Retry the operation after a while.

24081: Thread allocation failed because the thread count specified for paralleloperation exceeds the netbackup limit (netbackup limit count = %1\$d).

Cause	Thread allocation failed because the thread count specified for paralleloperation exceeds the netbackup limit (netbackup limit count = %1\$d).
Action	Retry the operation with a valid thread count.

24082: Netbackup parameters are not properly specified in tip file (%1\$s).

Cause	Netbackup parameters are not properly specified in tip file (%1\$s).
Action	Retry the operation after specifying netbackup parameters properly in tip file.

24083: Failed to get DOP of netbackup.

Cause	Failed to get DOP of netbackup.
Action	Retry the operation after checking the connection with the netbackup master.server.

24084: Failed to open a netbackup session.

Cause	Failed to open a netbackup session.
Action	Retry the operation after checking the connection with the netbackup master.server.

24085: Failed to commit the netbackup TX. The current backup operation is canceled.

Cause	Failed to commit the netbackup TX. The current backup operation is canceled.
Action	Retry the operation after checking the connection with the netbackup master.server.

24086: Failed to delete the backupset, or could not find it in Net Backup storage.

Cause	Failed to delete the backupset, or could not find it in NetBackup storage.
Action	Check the connection and files at NetBackup storage, or delete the backupset with '--cf-only' option.

24087: Cannot access netbackup storages.

USE_NBU_FOR_BACKUPSET or NBU_ARCHIVELOG_SEARCH is not specified in tip file.

Cause	Cannot access netbackup storages. USE_NBU_FOR_BACKUPSET or NBU_ARCHIVELOG_SEARCH is not specified in tip file.
Action	Retry the operation after specifying USE_NBU_FOR_BACKUPSET and NBU_ARCHIVELOG_SEARCH in tip file.

24088: NBU_CLIENT_COUNT must be in the range of 1-10 (current value: %1\$d).

Cause	NBU_CLIENT_COUNT must be in the range of 1-10 (current value: %1\$d).
Action	Retry the operation after checking NBU_CLIENT_COUNT.

24089: NBU_BACKUP_INST_SID must be set to the instance ID of NBU_CLIENT_HOSTNAME_0 in tip file (current settings: NBU_BACKUP_INST_SID=%1\$s, NBU_CLIENT_HOSTNAME_0=%1\$s).

Cause	NBU_BACKUP_INST_SID must be set to the instance ID of NBU_CLIENT_HOSTNAME_0 in tip file (current settings: NBU_BACKUP_INST_SID=%1\$s, NBU_CLIENT_HOSTNAME_0=%1\$s).
Action	Retry the operation after checking NBU_BACKUP_INST_SID and NBU_CLIENT_HOSTNAME_0 in tip file.

24090: Failed to get the hostname of system.

Cause	Failed to get the hostname of system.
Action	Retry the operation after checking the hostname of system.

24091: Netbackup parameter is inconsistent (%1\$s).

Cause	Netbackup parameter is inconsistent (%1\$s).
Action	Retry the operation after checking the netbackup parameter in tip file.

24092: Netbackup processes are still performing the previous operation (ongoing process count = %1\$d).

Cause	Netbackup processes are still performing the previous operation (ongoing process count = %1\$d).
Action	Retry the operation after a while.

24093: NetBackup operation is canceled/stopped. NetBackup slaves aborts.

Cause	NetBackup operation is canceled/stopped. NetBackup slaves aborts.
Action	NetBackup operation is canceled/stopped. NetBackup slaves aborts.

24095: Data file is more recent than control file. Get current control file, or recreate control file and try again.

Cause	CF SEQ in DF header is larger than CF SEQ in CF header.
Action	Check whether given control file is backup file, or recreate the control file.

24096: Failed to assign datafile (dfid = %1\$u)

Cause	Failed to assign datafile (dfid = %1\$u)
--------------	--

Action	Check if the given datafile exists in the backup set
---------------	--

24097: Failed to find the archive logs after the last archive log backup.

Cause	Failed to find the archive logs after the last archive log backup.
Action	Check if the target archive logs are in the backup_dest directory.

24098: Failed to find a tablespace to backup/restore.

Cause	Failed to find a tablespace to backup/restore.
Action	Check if the rmgr options are too much for the tablespaces available.

24099: Memory tablespace already exists.

Cause	Memory tablespace already exists.
Action	Drop the existing memory tablespace first.

24100: Memory tablespace cannot have datafiles more than '%1\$d'.

Cause	Memory tablespace has too many datafiles.
Action	Check the number of datafiles.

24101: No free space for memory tablespace.

Cause	The size of memory tablespace exceeds the maximum size allowed.
Action	Check the size of memory tablespace.

24102: Current log file %1\$d is still open.

Cause	Cannot disable the corresponding redo thread.
Action	Check the configuration or, tbdwn normally and try it on MOUNT mode.

24103: Failed to find a readonly or an offline tablespace with the given option.

Cause	Failed to find a readonly or an offline tablespace with the given option.
Action	Check the status of the tablespaces and --skip-readonly / --skip-offline options.

24104: If datafiles are the backups, please restore the backup controlfile together or re-create a new controlfile.

Cause	The controlfile ckpt_tsn(%1\$s) and the datafiles' ckpt_tsn(%2\$s) do not match.
Action	Please check the backup controlfile or the online redo logs after the backup.

24105: The option '--for-standby' needs the latest backup set to be FOR_STANDBY.

Cause	The option '--for-standby' needs the latest backup set to be FOR_STANDBY.
Action	The option '--for-standby' needs the latest backup set to be FOR_STANDBY.

24106: Using netbackup dummy library. Do not use netbackup with dummy library.

Cause	Using netbackup dummy library. Do not use netbackup with dummy library.
Action	Using netbackup dummy library. Do not use netbackup with dummy library.

24107: Failed to add tablespace: could not acquire tablespace section record.

Cause	Cannot acquire tablespace section record in controlfile.
Action	Try again after previous addition of tablespace is resolved.

24108: RMGR VALIDATION FAILED

Cause	RMGR VALIDATION FAILED
Action	Retry the operation after a while.

24109: Backup set(%1\$d) not found. Specify the path actually located.

Cause	Backup set(%1\$d) not found. Specify the path actually located.
Action	Backup set(%1\$d) not found. Specify the path actually located.

24110: NBU_CLIENT_HOSTNAME_0 must start with the hostname first with case sensitive. (current settings: NBU_CLIENT_HOSTNAME_0=%1\$s, hostname=%2\$s).

Cause	NBU_CLIENT_HOSTNAME_0 must start with the hostname first with case sensitive. (current settings: NBU_CLIENT_HOSTNAME_0=%1\$s, hostname=%2\$s).
Action	Retry the operation after checking NBU_CLIENT_HOSTNAME_0 and hostname in tip file.

24111: Backup datafiles need more redo logs at least until END_BACKUP to recover.

Cause	Backup datafiles need more redo logs at least until END_BACKUP to recover.
Action	Please restore more archive/online redo logs for appropriate recovery.

24112: Redo logfile generation time between the nodes is abnormal. Please check the system time.

Cause	Highly possibly, the system time between the nodes may vary.
Action	For now, please recover the DB with TSN based recovery (until change).

24113: All log files of this thread are never used at least once. (thread id=%1\$d).

Cause	All log files of this thread are never used at least once. (thread id=%1\$d).
Action	Please, check all the log files' seqno and try again.

24114: Backing up archive log files from NetBackup(%1\$s) to NetBackup is forbidden.

Cause	Backing up archive log files from NetBackup(%1\$s) to NetBackup is forbidden.
Action	Change the NBU parameters or execute '--with-archivelog'

24115: Backing up archive log files with '--delete-original' needs all standby nodes connected.

Cause	Backing up archive log files with '--delete-original' needs all standby nodes connected.
Action	Please check all standby nodes are connected to all DB instances.

24116: Can't find any backup archive logfile between %1\$s and %2\$s in CF (thread: %3\$s, resetlogs: %4\$d).

Cause	Can't find any backup archive logfile between %1\$s and %2\$s in CF (thread: %3\$s, reset logs: %4\$d).
Action	Please check thread id, resetlogs, v\$backup_archived_log, and actual backup path whether any exists.

24117: Tablespace '%1\$s' must be offline for Online Media Recovery.

Cause	Tablespace '%1\$s' must be offline for Online Media Recovery.
Action	Set the tablespace '%1\$s' to offline and try recovery again.

24118: All the specified tablespaces must be offline.

Cause	All the specified tablespaces must be offline.
Action	All the specified tablespaces must be offline.

24119: NetBackup operation is canceled/stopped. NetBackup slaves abort.

Cause	NetBackup operation is canceled/stopped. NetBackup slaves abort.
Action	NetBackup operation is canceled/stopped. NetBackup slaves abort.

24120: Unexpected block number(%1\$u) of the block is read. (expected:%2\$u)

Cause	Unexpected block number(%1\$u) of the block is read. (expected:%2\$u)
Action	Confirm the actual block is not corrupted on the disk.

24121: Failed to find backup file %1\$s among backup paths %2\$s.

Cause	Failed to find backup file %1\$s among backup paths %2\$s.
Action	Retry the operation with a valid backup directory and file.

24122: No such backup archivelog set %1\$d.

Cause	Cannot find the backup archivelog set.
Action	Verify that the backup archivelog set exists and try again.

24123: Failed to find marker before change "UINT64_FMT(1\$)" for thread %2\$d.

Cause	Failed to perform flashback database operation.
Action	Check flashback marker status and list.

24124: Flashback logging is not on.

Cause	Flashback logging is not on.
Action	Activate flashback logging and retry.

24125: No such flashback thread %1\$d.

Cause	Cannot find the flashback thread.
Action	Check the configuration and try again.

24126: Could only flashed back to the marker tsn %1\$u, because CF-DD correction is required due to dropped datafiles. %2\$s

Cause	Could only flashed back to the marker tsn %1\$u, because CF-DD correction is required due to dropped datafiles.
Action	%2\$s

24127: Database flashed back to TSN %1\$u, but CF-DD correction is required because the datafiles that were dropped later exist now. %2\$s

Cause	Database flashed back to TSN %1\$u, but CF-DD correction is required because the datafiles that were dropped later exist now. %2\$s
Action	%2\$s

24128: Flashback database must be done beforehand.

Cause	Flashback database must be done beforehand.
Action	Please check if the database has been flashed back in advance.

24129: Shrunk datafile(TS #%1\$u, DF #%2\$u) cannot be flashed back and should be taken offline.

Cause	Shrunk datafile(TS #%1\$u, DF #%2\$u) cannot be flashed back and should be taken offline.
Action	Take shrunk datafiles offline and try again.

24130: Due to CF-DD correction, some TS/DF which turned into read-write or online need recovery. Please request %1\$s.

Cause	Due to CF-DD correction, some TS/DF which turned into read-write or online need recovery. Please request %1\$s.
Action	Please request %1\$s.

24131: Can't find the target archive log in CF to %1\$s (%2\$s: %3\$d).

Cause	Can't find the target archive log in CF to %1\$s (%2\$s: %3\$d).
Action	Check whether the target archive log exists in CF or use '--arc-dest-force' option.

24132: Can't add a flashback marker due to some instance down.

Cause	All nodes must be open to add a flashback marker.
Action	Check all nodes are open and try again.

24133: Can't find the online flashback logfile in group #%1\$u to be recovered by media recovery.

Cause	All the online flashback logfiles must exist or the flashback logging must be off.
Action	Restore the online flashback logfiles or turn off the flashback logging.

24134: Standby Redo thread #%1\$d is too big (max %2\$d).

Cause	No space available for standby redo threads.
--------------	--

Action	Contact the technical support team.
---------------	-------------------------------------

24135: If the database flashed back at least once, reboot is required after Media Recovery.

Cause	If the database flashed back at least once, reboot is required after Media Recovery.
Action	Reboot the database.

24136: Archived log thread %1\$u, sequence %2\$u already exists.

Cause	Cannot add archived log into the Control File.
Action	Contact R&D or re-generate the control file.

24137: Log history thread %1\$u, sequence %2\$u already exists.

Cause	Cannot add log history into the Control File.
Action	Contact R&D or re-generate the control file.

24138: Failed to execute the rmgr client command.

Cause	Failed to execute the rmgr client command.
Action	Check the client trace log.

24139: Unexpected block(%1\$u) is read. (expected:%2\$u, tsid: %3\$u, dfid: %4\$u)

Cause	Unexpected block(%1\$u) is read. (expected:%2\$u, tsid: %3\$u, dfid: %4\$u)
Action	Confirm the actual block is not corrupted on the disk.

24140: Cannot raise to read only server mode because temporary tablespace not exists.

Cause	Does not exist temporary tablespace information in controlfile.
Action	Check the control file for temporary tablespace.

24141: Cannot create the standby replication because the backup set is invalid.

Cause	Cannot find all end backup cvs until the recovery stop point.
Action	Check the backup procedures and retry backup correctly.

24142: Standby needs media recovery.

Cause	Standby terminated abnormally.
Action	Perform media recovery.

24143: The maximum number of instances of controlfile and IPARAM(MAX_INSTANCE_COUNT) does not match.

Cause	The maximum number of instances of controlfile and IPARAM(MAX_INSTANCE_COUNT) does not match.
Action	Modify the value of IPARAM(MAX_INSTANCE_COUNT) or recreate the controlfile.

24144: NetBackup backup/restore timed out.

Cause	NetBackup backup/restore timed out.
Action	Check the NetBackup status.

24145: Cannot recover because begin/end backup is in progress.

Cause	Cannot recover because begin/end backup is in progress.
--------------	---

Action	Try again after the online backup is complete.
---------------	--

24146: Tablespace '%1\$s' is online.

Cause	The tablespace must be offline.
Action	Set the tablespace to offline and try again.

24147: Metadata of log files in CF cache is duplicated or corrupt.

Cause	Some metadata of log files is duplicated or corrupt.
Action	Please contact the support team.

24148: Unable to modify file %1\$d.

Cause	The datafile is being created (in creation).
Action	Try again after the datafile %1\$d is successfully created.

24149: New blocks found in logfile in group #%1\$d after %2\$u by THREAD #%3\$d.

Cause	New blocks found in logfile in group #%1\$d after %2\$u by THREAD #%3\$d.
Action	Investigate if THREAD #%3\$d is still in use.

24150: Cannot take datafile #%1\$d offline.

Cause	Cannot take the datafile offline.
Action	Check the condition of the datafile and try again.

24151: Checkpoint progress cannot be cleared.

Cause	Checkpoint progress cannot be cleared.
Action	Please contact the support team.

24152: File DB_NAME('%1\$s') does not match control file DB_NAME('%2\$s').

Cause	The DB_NAME('%1\$s') of the file does not match the DB_NAME('%2\$s') in the control file.
Action	Verify and ensure that the DB_NAME for both the file and the control file are correct.

24153: File DB_ID(%1\$d) does not match control file DB_ID(%2\$d).

Cause	The DB_ID(%1\$d) of the file does not match DB_ID(%2\$d) in the control file.
Action	Verify and ensure that the DB_ID for both the file and the control file are correct.

24154: Current demo license is issued after the DB creation.

Cause	Demo license is after DB creation is prohibited.
Action	Create a new DB with newly issued demo license or bring contracted official license.

제22장 25000 ~ 25999

25001: XA protocol error.

Cause	Invalid XA protocol.
Action	Verify the protocol is valid.

25002: XA transaction branch was not found.

Cause	The XA branch does not exist.
Action	Verify the XID is correct.

25003: Unable to associate the XA transaction branch: local transaction is ongoing.

Cause	Failed to perform the XA command because an ongoing local transaction exists.
Action	Commit or roll back the local transaction first, and then perform the XA command.

25004: XA asynchronous feature is not supported by server.

Cause	An attempt was made to use an XA asynchronous command.
Action	XA asynchronous commands are not supported.

25005: Invalid arguments were specified.

Cause	An invalid flag was included in the XA command.
Action	Check the flag again.

25006: XA transaction branch is in rollback-only status for an unspecified reason.

Cause	The XA branch is in rollback-only status.
Action	Try xa_rollback.

25007: XA transaction branch is read-only.

Cause	The XA branch is in read-only status because no active transaction exists.
Action	Automatically terminate the branch.

25008: Duplicate XID exists.

Cause	There is another XA branch with the same XID.
Action	Check the XID or try again with another XID.

25009: Resource manager has indicated a problem with an XA branch.

Cause	Cannot perform the task because the global TX and XA branch loose_coupling properties mismatch.
Action	Verify that the XA command is correct or roll back the branch and try again.

25010: Transaction branch has been heuristically committed.

Cause	The XA branch has already been committed.
Action	Verify that the XA command is valid, or remove the terminated XA branch with xa_forget.

25011: Transaction branch has been heuristically rolled back.

Cause	The XA branch has already been heuristically rolled back.
Action	Verify that the XA command is valid, or remove the terminated XA branch with xa_forget.

25012: Transaction branch has been heuristically committed or rolled back.

Cause	The XA branch was already committed or rolled back.
Action	Verify that the XA command is valid, or remove the terminated XA branch with xa_forget.

25013: XA branch has timed out (sesswt).

Cause	The transaction was rolled back because the requested command could not be completed before session waiting time expired.
Action	Try again.

25014: No prepared XA transaction found with transaction ID %1\$s.

Cause	Cannot find a prepared XA transaction with the requested transaction ID.
Action	Verify the transaction ID is valid.

25015: Unable to create more XA branches: maximum number of branches reached.

Cause	Cannot create any more XA branches - limit set in XA_MAX_BRANCH_CNT has been reached.
Action	Try later.

제23장 26000 ~ 26999

26003: LOB object is too large.

Cause	The LOB type data is too large.
Action	Check if the size of the LOB type object is larger than the maximum limit (4GB * DB block size).

26004: Offset is out of range.

Cause	The LOB offset is greater than the length of the LOB.
Action	Specify a valid offset.

26005: Trim length is out of range.

Cause	The trim length is greater than the length of the LOB.
Action	Specify a valid length.

26006: LOB is read-only.

Cause	An attempt was made to write to a LOB opened in read-only mode.
Action	Open the LOB in read/write mode.

26007: Row containing LOB column is not locked.

Cause	The row that contains a LOB column to be used in a read/write mode is not locked.
Action	Lock the row and reopen it.

26008: LOB was not found.

Cause	The specified LOB data does not exist.
Action	The row may have been deleted. Verify that the LOB data exists and try again.

26009: Invalid LOB locator specified.

Cause	The DBA or ROWNO of the specified LOB locator is invalid.
Action	Try again with a valid LOB locator.

26010: Unable to write with a terminated transaction.

Cause	Cannot write to a LOB using a terminated transaction.
Action	Open the LOB data after restarting the transaction.

26012: Invalid LOB locator length.

Cause	The length of the specified LOB locator is invalid.
Action	Try again with a valid LOB locator.

26013: Invalid LOB locator segment ID.

Cause	The segment ID of the specified LOB locator is invalid.
Action	Try again with a valid LOB locator.

26014: Invalid LOB ID of LOB locator.

Cause	The LOB ID of the specified LOB locator is invalid.
Action	Try again with a valid LOB locator.

26019: Uninitialized LOB locator was specified.

Cause	The LOB locator has not been initialized.
--------------	---

Action	Initialize then search for the LOB.
---------------	-------------------------------------

26020: Cannot read a LOB object in a remote server.

Cause	Cannot read a LOB object in a remote server.
Action	Change the query.

26021: No data in the LOB index.

Cause	DML failed because there is no data in the LOB index.
Action	Recover the LOB index data.

제24장 27000 ~ 27999

27001: Invalid table information specified.

Cause	Invalid table information is returned when the transaction is in prepared state.
Action	Enter correct table information.

27002: Given data does not complete a row.

Cause	The last row of the given data stream is not complete.
Action	Send the remaining data.

27003: Data stream is invalid.

Cause	The data stream is invalid.
Action	Send the correct data.

27004: Invalid LONG column position.

Cause	The position of the LONG column is invalid.
Action	Place the LONG column in the last part of the table.

27005: Direct path buffer is empty.

Cause	The DPL buffer is empty.
Action	The data has not yet been loaded. Load the data and then flush it.

27006: A transaction already exists.

Cause	A transaction already exists before the direct path has started.
--------------	--

Action	Commit or roll back the existing transaction.
---------------	---

27007: Partitioned tables are not supported.

Cause	Direct path loading is not supported for partitioned tables.
Action	REMOVED.

27008: Unsupported table schema.

Cause	Direct path loading is not supported for the schema.
Action	Use conventional loading method instead.

27009: DPL is not yet prepared.

Cause	DPL has not been started.
Action	Start a prepare protocol first.

27010: Cannot perform DPL for temporary table.

Cause	Cannot perform DPL for temporary table.
Action	Only CPL is supported for temporary table.

27011: The table has too many columns.

Cause	The table has too many columns.
Action	Use the conventional loading method.

27012: DPL failed due to lack of resources.

Cause	DPL failed due to lack of resources.
Action	Free sufficient resources and continue.

27013: Unsupported table schema.

Cause	Parallel DPL is not supported for the schema.
Action	DPL is not supported for an indexed table.

27014: DPL failed due to message uncompression error.

Cause	DPL failed due to message uncompression error.
Action	Check if client library settings are correct.

27015: DPL failed while rebuilding index on dp finish phase.

Cause	DPL failed while rebuilding index on dp finish phase.
Action	Check sys.log to determine the cause of the problem.

27016: The expression information is not valid.

Cause	DPL failed because the expression information was set incorrectly.
Action	Correct the expression information.

27017: Saving data is not supported during Parallel DPL.

Cause	Saving data is not supported during Parallel DPL.
Action	Remove the save option.

제25장 28000 ~ 28999

28009: Unable to access LONG or LOB columns through RemoteDB.

Cause	An attempt was made use RemoteDB to refer to an object with LONG or LOB columns.
Action	Modify the query.

28010: Maximum number of group_ids (255) has been reached.

Cause	No more than 255 group_ids are allowed at a time.
Action	Modify the query.

28011: Pivot type expression %1\$s cannot be used here.

Cause	The pivot type expression was used in an invalid location.
Action	Modify the query.

28012: Index '%1\$s.%2\$s' is in an unusable state.

Cause	DML statements cannot be executed on an unusable index.
Action	Change the condition of the index.

28013: Index '%1\$s.%2\$s' is in an unusable state.

Cause	Index hints cannot be specified on an unusable index.
Action	Change the condition of the index.

28014: Duplicate outline.

Cause	The outline name cannot be used because the name is already in use.
Action	Use another outline name.

28015: Column '%1\$s.%2\$s' has invalid statistics.

Cause	Column '%1\$s.%2\$s' has invalid statistics.
Action	Delete or regather statistics using the dbms_stat package.

28016: Feature not yet implemented.

Cause	This feature is not yet implemented.
Action	Check whether a feature which is not yet implemented was used.

28017: Logical error in transformer.

Cause	
Action	

28018: Invalid ndv on column '%1\$s.%2\$s' frequency histogram (Current value: %3\$d).

Cause	Each frequency histogram ndv value must be 0 or 1.
Action	Delete or regather statistics using the dbms_stats package.

28019: Maximum number of group keys(128) has been reached.

Cause	No morder than 128 group keys are allow for parallel group by.
Action	Set the parameter _OPT_ENABLE_GROUP_BY_PARALLEL to N.

28020: Too many expressions used.

Cause	Too many expressions are used, which may cause out-of-memory in optimizer.
Action	Reduce the number of expressions in the SQL statement, or adjust the value of parameter <code>_OPT_BM_MEMORY_LIMIT_RATIO</code> (if OOM is not expected).

28021: Too many number of pp nodes.

Cause	Too many number of pp nodes used.
Action	Reduce the number of pp nodes in the SQL statement, or adjust the value of parameter <code>_OPT_PPN_ID_MAX_SIZE</code> .

28022: The table already has a rowid.

Cause	The table cannot have duplicate rowids.
Action	Need to check if there is a logical problem.

제26장 29000 ~ 29999

29001: Lock failed (op: %1\$s, step: %2\$s, lock: %3\$s, ec: %4\$d).

Cause	The lock operation failed.
Action	Locate the cause of the failure and try again.

29002: Unlock failed (op: %1\$s, step: %2\$s, ec: %3\$d).

Cause	The unlock operation failed.
Action	Locate the cause of the failure and try again.

29003: Failed to connect to CM (Cluster Manager).

Cause	Failed to connect to CM.
Action	Verify that the CM connections settings (e.g. IP address and port number) in [database sid].tip file are valid.

29004: The INC message buffer size is too small (current_size: %1\$d, required_size: %2\$d).

Cause	The INC message buffer size is too small.
Action	Increase the INC message buffer size (_INC_BUF_MSG_SIZE).

제27장 30000 ~ 30999

30001: The disk space, \"%1\$s**\", does not exist or has not been mounted.**

Cause	The disk space does not exist, or has not been mounted to the current TAS instance.
Action	Check that the disk space name is correct, the disk space exists, and the disk space has been mounted to the current TAS instance.

30002: The TAS disk, \"%1\$s**\", does not exist.**

Cause	The TAS disk is not found.
Action	Check the TAS disk name.

30003: The failure group, \"%1\$s**\", does not exist in the disk space, \"**%2\$s**\".**

Cause	The name does not match the failure group name of the disks in the disk space.
Action	Check the failure group name.

30004: The TAS file, '%1\$s**', does not exist.**

Cause	The TAS file is not found.
Action	Check the TAS file name.

30005: The disk path '%1\$s**' does not exist among the discovered disks.**

Cause	The disk path does not exist among the disks discovered by the TAS instance.
--------------	--

Action	Enter a disk path discovered by using the TAS_DISKSTRING parameter, or check the TAS_DISKSTRING parameter.
---------------	--

30006: Cannot create the diskpace.

Cause	Cannot create the given diskpace.
Action	For more information, refer to the logs.

30007: The maximum number of disks that can be used is %1\$d.

Cause	The diskpace is already using the maximum number of disks.
Action	Drop existing disk(s) from the diskpace or create a new diskpace.

30008: Cannot open the disk, '%1\$s'.

Cause	Cannot open the given disk.
Action	For more information, refer to the logs.

30009: The disk, '%1\$s', has already been mounted.

Cause	An attempt was made to add a disk, which is from another diskpace mounted on the current instance, to the diskpace.
Action	Use another disk. Unless the diskpace of the disk is unmounted, the FORCE option has no effect.

30010: The diskpace name, '%1\$s', is already being used by another diskpace.

Cause	The name specified with CREATE DISKSPACE is already being used by another diskpace.
Action	Select another name.

30011: The size of the disk, '%1\$s', is smaller than %2\$d MB.

Cause	The disk size is too small to add the disk to the disk space.
Action	Check if the system settings are correct.

30012: Failed to remove the disk space, '%1\$s'.

Cause	Failed to remove the disk space.
Action	For more information, refer to the logs.

30013: The disk space has not been mounted.

Cause	TAS was booted without creating a disk space.
Action	After booting TAS in nomount mode, create a disk space and then reboot the TAS.

30014: The path, '%1\$s', is invalid.

Cause	The path prefix (+) or path delimiter (/) is not valid.
Action	Check the path character array.

30015: The name, '%1\$s', is too long.

Cause	The TAS disk path is too long.
Action	Specify a TAS disk path of 256 characters or less.

30016: Failed to write the disk header.

Cause	Failed to open the disk, perform disk I/O, or the magic value does not match.
Action	For more information, refer to the logs.

30017: Failed to add the disk.

Cause	Failed to add the disk.
--------------	-------------------------

Action	Check the tracelog to fix the problem and then try again.
---------------	---

30018: Failed to remove the disk.

Cause	Failed to drop the disk.
Action	Check the tracelog to fix the problem and then try again.

30019: Failed to create the file, '%1\$s\'.

Cause	Failed to create the file.
Action	Check the tracelog to fix the problem and then try again.

30020: Failed to delete the file, '%1\$s\'.

Cause	Failed to delete the file.
Action	Check the tracelog to fix the problem and then try again.

30021: Failed to change the file size.

Cause	Failed to change the file size.
Action	Check the tracelog to fix the problem and then try again.

30022: Failed to connect to the local port.

Cause	Failed to connect to the IP address and port.
Action	Check that the specified port is not already occupied and then try again.

30023: Unknown network I/O error (TAS).

Cause	Unknown network error has occurred.
Action	Check that the network equipment is operating normally and then try again.

30024: A general TAS error occurred.

Cause	A TAS internal error occurred.
Action	Contact the technical support team.

30025: The disk size entered, %1\$u MB, is larger than the actual disk size of %2\$u MB.

Cause	The disk size entered is larger than the actual disk size.
Action	Enter a valid size.

30026: The disk name '%1\$s' is already in use.

Cause	The specified name is already in use.
Action	Enter another disk name.

30027: The disk path '%1\$s' was entered multiple times.

Cause	The specified path was entered multiple times.
Action	The disk path can only be entered once.

30028: The file path '%1\$s' does not exist on the disk space '%2\$s'.

Cause	The disk space specified in '%1\$s' does not match that specified in the DDL statement.
Action	Set a valid disk space.

30029: The disk size is not entered.

Cause	The character device size must be entered.
Action	Enter a valid size.

30030: Cannot allocate space from an offline disk.

Cause	One or more disks are offline.
Action	Remove the offline disks or bring them online.

30031: The entered user name '%1\$s' does not exist.

Cause	Attempted to execute a command for a TAS user that does not exist.
Action	Use an existing TAS user name, or add a new TAS user.

30032: The user name '%1\$s' already exists.

Cause	Attempted to use a name that is a duplicate of an existing TAS user.
Action	Create a new unique TAS user name.

30033: The entered group name '%1\$s' does not exist.

Cause	Attempted to execute a command for a TAS group that does not exist.
Action	Use an existing TAS group name, or add a new TAS group.

30034: The group name '%1\$s' already exists.

Cause	Attempted to use a name that is a duplicate of an existing name.
Action	Create a new unique TAS group name.

30035: Specified disk space '%1\$s' is not the master disk space.

Cause	An attempt was made to execute a command on a disk space that is not the master disk space.
Action	Execute the command on the master disk space.

제28장 60000 ~ 60999

60001: Internal error occurred at %1\$s:%2\$d.

Cause	An internal error occurred.
Action	Contact the technical support team.

60002: Invalid command. Enter HELP or HELP <command>.

Cause	Invalid command.
Action	Verify the command is correct.

60003: Unterminated string.

Cause	The string is not terminated.
Action	Check that quotation marks are used correctly.

60004: Integer value is out of range (%1\$d..%2\$d).

Cause	The integer value is out of range.
Action	Specify a number within the range.

60005: Column type does not match.

Cause	Column type does not match.
Action	Check the column type.

60006: No modifications to be saved.

Cause	Nothing was modified, so no changes will be saved.
--------------	--

Action	Use the command after performing other commands more than once.
---------------	---

60007: Command buffer is empty.

Cause	Command buffer is empty.
Action	Execute an arbitrary command and then retry.

60008: Identifier is too long.

Cause	The identifier length exceeds the maximum allowed.
Action	Ensure the identifier contains less than 129 bytes.

60009: Foreign key does not match.

Cause	The foreign key or a primary key of the referenced table does not match.
Action	Match the constraints between the two tables.

60010: External API error: %1\$s.

Cause	Failed to execute external library function.
Action	Check the error message.

60011: String value is out of range (<= %1\$d bytes).

Cause	The string value exceeded the maximum length allowed.
Action	Specify a string within the range.

60012: Generic I/O error.

Cause	An I/O error occurred during communication with other process.
Action	Contact the technical support team.

60013: Parameter syntax error: %1\$s.

Cause	Syntax error occurred.
Action	Check the error message.

60014: License error: %1\$s.

Cause	License check failed.
Action	Check the error message.

60015: The agent process already exists.

Cause	The agent process already exists.
Action	Terminate the agent process or check whether the .proc.mgr file exists.

60016: The agent process already attached.

Cause	The agent process already attached.
Action	Use DETACH command first.

60017: The mandatory parameter '%1\$s' is missing.

Cause	A mandatory parameter must be defined.
Action	Check the parameter file.

60018: The instance identifier '%1\$s' already exists.

Cause	The instance identifier is already in use.
Action	Use another instance identifier.

60019: Unable to open a connection.

Cause	The maximum number of connections are already open.
--------------	---

Action	Close the other open connections, or shut down the process, and restart the process.
---------------	--

60020: The process '%1\$s' already exists.

Cause	The requested process already exists.
Action	Terminate the process first.

60100: Invalid option '%1\$s'.

Cause	Invalid option.
Action	Verify the option is correct.

60101: Invalid time value.

Cause	Time value is invalid or does not match the format.
Action	Check the time value or check that the value matches the TIMEFORMAT parameter.

60102: Invalid time format.

Cause	Invalid time format.
Action	Refer to the SQL Reference Guide to check that the format is valid.

60103: Unable to handle unexpected incoming message type %1\$d.

Cause	An unexpected protocol was received.
Action	Check that the protocol is from a valid context.

60104: The directory '%1\$s' is invalid.

Cause	The directory must be an absolute path.
Action	Check the directory.

60105: Invalid parameter '%1\$s': %2\$s.

Cause	Invalid parameter.
Action	Check the error message.

60106: Wallet is already open.

Cause	The wallet is already open.
Action	Proceed to the step following the opening of the wallet.

60200: Failed to create the directory '%1\$s': %2\$s.

Cause	Failed to create directory.
Action	Check the error message.

60201: Failed to open the file '%1\$s': %2\$s.

Cause	Failed to open file.
Action	Check the error message.

60202: Failed to execute shell command: %1\$s.

Cause	Failed to execute shell command.
Action	Check the error message.

60203: Failed to create process: %1\$s.

Cause	Failed to create process.
Action	Check the error message.

60204: Failed to create thread: %1\$s.

Cause	Failed to create thread.
--------------	--------------------------

Action	Check the error message.
---------------	--------------------------

60205: Failed to create a thread key: %1\$s.

Cause	Failed to create a thread key.
Action	Check the error message.

60206: Failed to create socket: %1\$s.

Cause	Failed to create socket.
Action	Check the error message.

60207: Failed to create pipe: %1\$s.

Cause	Failed to create pipe.
Action	Check the error message.

60208: Failed to allocate TLS structure (errno:%1\$d).

Cause	Failed to allocate TLS structure.
Action	Check the error message.

60209: Failed to connect to the %1\$s process.

Cause	Failed to connect to the process.
Action	Check the connection information or if the process is running.

60300: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

60301: Not connected to the process.

Cause	Not connected to the process or connection was lost.
Action	Verify there is an active connection to the process.

60302: Environment variable %1\$s does not set.

Cause	Environment variable %1\$s has not been defined.
Action	Define the variable.

60303: HELP for '%1\$s' does not exist.

Cause	There is no HELP for the subject.
Action	Try another subject.

60304: The agent process does not exist.

Cause	The agent process does not exist.
Action	Start the agent process first.

60305: Column '%1\$s' does not fit.

Cause	The column is too long to fit on the line.
Action	Lengthen the line or shorten the column.

60306: Numeric column was not found.

Cause	Failed to find numeric column in the given table.
Action	Verify the primary key or the entire column.

60307: Primary key was not found.

Cause	Failed to find primary key in the given table.
--------------	--

Action	Verify the numeric column or the entire column.
---------------	---

60308: Node was not found.

Cause	Failed to find given node.
Action	Add a node and then execute.

60309: Parameter '%1\$s' was not found.

Cause	Failed to find the parameter.
Action	Verify the parameter exist.

60310: Unable to find the instance ID.

Cause	Unable to find the instance ID in the instance map or running processes.
Action	Check the instance ID.

60311: Unable to find the process.

Cause	Unable to find the process that meets the specified condition in the instance map.
Action	Check the instance ID or Process Number.

60312: Unable to find the '%1\$s' file.

Cause	Unable to find the rule config file.
Action	Check config directory.

60313: Wallet is not open.

Cause	Wallet is not yet open.
Action	Try again after opening the wallet.

60314: Port Number of 'prs_top.map' and '%1\$s' are not same.

Cause	Port Number of 'prs_top.map' and '%1\$s' are not same.
Action	Check the Port Number.

60400: Failed to verify: %1\$s.

Cause	Failed to verify.
Action	Check the error message.

60401: Failed to push rows: %1\$s.

Cause	Failed to push rows.
Action	Check the error message.

60402: Failed to encrypt a plaintext.

Cause	Failed to encrypt a plaintext.
Action	Contact the technical support team.

60403: Failed to decrypt a ciphertext.

Cause	Failed to decrypt a ciphertext.
Action	Contact the technical support team.

60404: Config parameter %1\$s and %2\$s are incompatible.

Cause	Incompatible options are used in .cfg file
Action	Check the config file.

60405: Failed to open wallet.

Cause	Failed to open wallet.
--------------	------------------------

Action	Check the password, or request the security administrator to create a new wallet.
---------------	---

60406: Failed to cipher init.

Cause	Failed to cipher init.
Action	Contact the technical support team.

60407: Failed to cipher update.

Cause	Failed to cipher update.
Action	Contact the technical support team.

60408: All DCR min or max columns must have default value set

Cause	All DCR min or max columns must have default value set
Action	Set default value for the corresponding DCR column. Check the manual.

60409: read('%2\$s') failed -- %1\$s.

Cause	Failed to read the file.
Action	Check if the file can be accessed.

60410: stat('%2\$s') failed -- %1\$s.

Cause	Failed to read stat of the file.
Action	Check if the file can be accessed.

60411: Dead process '%1\$s' '%2\$s' '%3\$d' exists. Please shutdown the previous process.

Cause	Dead process exists.
Action	Check if previous process still exists.

60412: Event initialization failed.

Cause	Event initialization failed.
Action	Check logs of the process.

60413: Socket listen initialization failed.

Cause	Socket listen initialization failed.
Action	Check logs of the process.

60414: fetching the global key from source database failed.

Cause	fetching the global key from source database failed.
Action	checking _VT_TTE_GLOBAL_KEY view in source database and db connection.

60415: The agent process does not exist.

Cause	The agent process does not exist.
Action	Start the agent process first.

제29장 70000 ~ 70999

70001: SQL buffer is empty.

Cause	The SQL buffer is empty.
Action	Retry the command after executing a SQL statement multiple iterations.

70002: Failed to open the file '%1\$s': %2\$s.

Cause	Failed to open the file.
Action	Check the file name and path.

70003: Invalid command. Enter HELP or HELP <command>.

Cause	Invalid command.
Action	Verify the command is correct.

70004: Not connected to the server.

Cause	Not connected to the server or connection was lost.
Action	Verify there is an active connection to the server.

70005: Invalid object name '%1\$s'.

Cause	An object with the specified name was not found.
Action	Verify the object name is correct.

70006: Invalid schema name '%1\$s'.

Cause	The specified schema name does not exist.
--------------	---

Action	Verify the schema name is correct.
---------------	------------------------------------

70007: Invalid parameter name.

Cause	The environment variable specified for SET statement does not exist.
Action	Verify the variable name is correct.

70008: Invalid integer value.

Cause	The integer value is invalid for a SET environment variable.
Action	Specify a positive integer value.

70009: Invalid string value.

Cause	The string value is invalid for a SET environment variable.
Action	Specify a string value smaller than 128.

70010: Parameter accepts only ON or OFF as values.

Cause	The parameter accepts only ON or OFF as a value.
Action	Make sure to use ON or OFF for the parameter.

70011: Invalid parameter value or type.

Cause	Invalid parameter value or type.
Action	Check the parameter value or type.

70012: Failed to set AUTOCOMMIT mode.

Cause	Failed to set AUTOCOMMIT mode.
Action	Ensure that the AUTOCOMMIT mode is correct.

70013: No modifications to be saved.

Cause	Nothing was modified, so no changes will be saved.
Action	Use the command after performing the SQL statement more than once.

70014: BLOB type cannot be displayed by SQL utility.

Cause	The SQL utility cannot display BLOB data.
Action	Check to see if it contains a BLOB type.

70016: New password and confirmation password do not match.

Cause	The password that was re-entered for confirmation does not match the new password.
Action	Ensure the confirmation password was typed correctly.

70017: Missing or invalid password.

Cause	The password is missing or invalid.
Action	Verify that the correct password was provided.

70018: Invalid AUTOTRACE mode.

Cause	Invalid AUTOTRACE mode.
Action	Verify the AUTOTRACE mode is correctly specified.

70019: Unable to describe invalid object.

Cause	Cannot describe an invalid object.
Action	Verify the object is valid.

70020: Specified object was not found.

Cause	The object does not exist.
--------------	----------------------------

Action	Verify that the object exists.
---------------	--------------------------------

70021: Unable to set SERVEROUTPUT mode.

Cause	Failed to specify a SERVEROUTPUT environment variable.
Action	Verify the DBMS_OUTPUT package exists.

70022: Not yet implemented.

Cause	This function has yet to be implemented.
Action	This function will be supported in the next version.

70023: Unable to set AUTOTRACE mode.

Cause	Failed to specify an AUTOTRACE environment variable.
Action	Contact the technical support team.

70024: Invalid format '%1\$s'.

Cause	Invalid format type.
Action	Refer to "SQL Reference Guide" to check the validity of the format.

70025: Password is too long.

Cause	The password must be less than or equal to 64 characters.
Action	Choose a new password.

70026: Filename is too long.

Cause	The file name must be less than or equal to 256 characters.
Action	Choose a new filename.

70027: Unable to execute shell command.

Cause	Cannot execute the shell command.
Action	Refer to "Administrator Guide" to check the validity of the shell command.

70028: Invalid shutdown mode.

Cause	Invalid shutdown mode.
Action	Refer to "Administrator Guide" to check the validity of the shutdown mode.

70029: Database name is too long.

Cause	The DB name must be less than or equal to 40 characters.
Action	Choose a new DB name.

70034: Stat table creation failed.

Cause	Failed to create a stat table.
Action	Check the user's permissions for table creation.

70035: Unable to display plan: check PLUSTRACE role.

Cause	Failed to display the plan of the SQL statement.
Action	A PLUSTRACE role must be specified.

70036: Unable to gather statistics: check PLUSTRACE role.

Cause	Failed to display statistics.
Action	A PLUSTRACE role must be specified.

70037: Missing or invalid username.

Cause	The user name is missing or invalid.
--------------	--------------------------------------

Action	A user name must be at least one character long.
---------------	--

70038: Username is too long.

Cause	The user name must be less than or equal to 128 characters.
Action	Choose a new username..

70039: Number is invalid or out of range.

Cause	The number is invalid or not an integer.
Action	Use an integer that is within the allowed range.

70040: HELP for '%1\$s' does not exist.

Cause	There is no HELP for the subject.
Action	Try another subject.

70041: Invalid first or last line number.

Cause	The first or last line number is invalid.
Action	Check the line value.

70042: Internal error occurred '%1\$s'.

Cause	An internal error occurred.
Action	Contact the technical support team.

70043: Undeclared variable '%1\$s'.

Cause	Undeclared variable.
Action	Verify that the variable name is correct.

70044: Invalid type.

Cause	An invalid type was used.
Action	Refer to "SQL Reference Guide" to verify the validity of the type.

70045: Declared variable was not found.

Cause	The declared variable was not found.
Action	Declare the variable first.

70047: Input is too long.

Cause	The entered value must be less than or equal to 128 characters.
Action	Re-enter the input.

70048: Invalid bind parameter '%1\$s'.

Cause	Invalid bind variable.
Action	Verify that the name or type of the bind variable is correct.

70050: Format value is too long.

Cause	The format value must be less than or equal to 64 characters.
Action	Re-enter the format value.

70051: Environment variable is too long.

Cause	The environment variable must be less than or equal to 64 characters.
Action	Choose a new environment variable name.

70052: Not yet implemented.

Cause	This function has yet to be implemented.
--------------	--

Action	This function will be supported in the next version.
---------------	--

70053: Invalid expression.

Cause	Invalid expression.
Action	Refer to "SQL Reference Guide" to verify the validity of the expression.

70054: Pattern '%1\$s' was not found.

Cause	The pattern does not exist in the current line.
Action	Check if parts of the current line correspond to the pattern.

70055: Invalid column '%1\$s'.

Cause	Invalid column name.
Action	Verify that the column exists.

70056: Type constraint is out of range.

Cause	Type constraint is out of range.
Action	Refer to "SQL Reference Guide" to check the conditions for defining a type.

70057: Column '%1\$s' does not fit on the line.

Cause	The column is too long to fit on the line.
Action	Lengthen the line or shorten the column.

70058: Invalid use of DESCRIBE command.

Cause	A DESCRIBE command cannot be used for a sequence.
Action	Use another command.

70059: Invalid option '%1\$s'.

Cause	Invalid option.
Action	Specify a valid option.

70060: Failed to execute DESCRIBE [%1\$d].

Cause	Failed to execute a DESCRIBE command.
Action	Check the error message.

70061: Failed to execute LS [%1\$d].

Cause	Failed to call the list of objects.
Action	Check the error message.

70062: Failed to execute SHOW [%1\$d].

Cause	Failed to execute a SHOW command.
Action	Check the error message.

70063: Failed to execute COUNT [%1\$d].

Cause	Failed to execute a COUNT command.
Action	Check the error message.

70064: Substitution variable '%1\$s' was not found.

Cause	The substitution variable was not found.
Action	Declare a substitution variable first.

70065: Unterminated string.

Cause	The string is not terminated.
--------------	-------------------------------

Action	Check that quotation marks are used correctly.
---------------	--

70066: Operation is not allowed.

Cause	The operation is not allowed.
Action	Check permissions.

70067: Environment variable '%1\$s' is empty.

Cause	An empty environment variable is used.
Action	Use an environment variable containing a value.

70068: Failed to fetch a bind variable by using the RETURNING clause.

Cause	Failed to fetch a bind variable by using the RETURNING clause.
Action	Check the error message.

70069: Too many rows returned for the RETURNING clause.

Cause	More than one row returned for the RETURNING clause.
Action	Use a SQL statement that returns a single row.

70070: Invalid escape value.

Cause	The escape value is invalid for a SET environment variable.
Action	Use a symbol with a length of 1 excluding character, numeric, and blank characters.

70071: Invalid cursor identifier of the variable '%1\$s'.

Cause	Previously printed or invalid cursor identifier.
Action	Save the cursor identifier again.

70072: Variable name is too long.

Cause	The variable name must be less than or equal to 128 characters.
Action	Choose a new variable name.

70073: Integer value is out of range (%1\$d..%2\$d).

Cause	The integer value is out of range for a SET environment variable.
Action	Specify a number within the range.

70074: Cannot recognize the wallet file.

Cause	Input file name is incorrect or empty.
Action	Check the environment variable, and verify the file name is correct.

70075: Failed to generate a security key.

Cause	Failed to generate a security key.
Action	Contact the technical support team.

70076: Unable to display the plan: Failed to retrieve the SQL ID to select the plan.

Cause	Failed to retrieve the SQL ID of the last executed query in the current session.
Action	Execute the query again or contact the technical support team.

70077: The given value, '%1\$s', does not match the format, '%2\$s'.

Cause	The entered value does not match the predefined format.
Action	Change the format or modify the entered value.

70078: Unable to display plan: failed to retrieve the SQL ID.

Cause	Failed to retrieve the SQL ID of the last executed query in the current session.
Action	Execute the query again or contact the technical support team.

70079: Invalid string value.

Cause	The length of the specified string in the SET command must be 1.
Action	Modify the length of the string.

70080: Invalid character value.

Cause	The specified character in the SET command cannot be alphanumeric or white-space.
Action	Modify the character value.

70081: Export format is too long.

Cause	The export format must be less than or equal to 16 characters.
Action	Modify the format value.

70082: The '%1\$s' command has been disabled.

Cause	The command has been disabled by the system administrator.
Action	Contact the system administrator.

70083: The file '%1\$s' already exists.

Cause	The specified file name already exists.
Action	Either overwrite or delete the existing file.

70084: Invalid variable name '%1\$s'

Cause	The variable name must be alphanumeric and/or include underscores.
--------------	--

Action	Modify the variable name.
---------------	---------------------------

70085: The variable '%1\$s' is not a number.

Cause	The variable used in an EXIT command must be a number.
Action	Use a different number variable or change the existing value to a number.

70086: inconsistent datatypes : expected '%1\$s' got '%2\$s'.

Cause	Failed to fetch a bind variable in RETURNING clause by inconsistent datatypes.
Action	Check the error message.

제30장 80000 ~ 80999

80001: Syntax error occurred in command line.

Cause	A syntax error occurred in a parameter in the command line.
Action	Specify the parameter correctly.

80002: Syntax error occurred at control parameter.

Cause	A syntax error occurred in a control parameter.
Action	Specify the parameter correctly.

80003: Column end offset must be larger than the start offset at line %1\$d in control parameter.

Cause	The start offset references a location after the end offset.
Action	Fix the start and end column offsets.

80004: Standard input stream failed.

Cause	Cannot read data entered in the standard input.
Action	Enter the correct information in the standard input.

80005: Column information is not specified.

Cause	Information about columns in the table is not specified.
Action	Specify column information.

80006: Character set not supported by Loader utility.

Cause	The specified character set is not supported in the Loader utility.
Action	Specify a character set supported by the Loader utility.

80007: Unable to initialize handle.

Cause	Cannot initialize the handle.
Action	Specify the handle correctly.

80008: Unable to open control file.

Cause	Cannot open the control file.
Action	Verify the control file exists at the specified path.

80009: Control file is too large.

Cause	The control file is too large.
Action	Ensure the controls file is less than 10KB.

80010: Unable to close control file.

Cause	Cannot close the control file.
Action	Verify the control file exists at the specified path.

80011: Unable to open data file.

Cause	Cannot open the data file.
Action	Verify the data file exists at the specified path.

80012: Unable to close data file.

Cause	Cannot close the data file.
--------------	-----------------------------

Action	Verify the data file exists at the specified path.
---------------	--

80013: Unable to open log file.

Cause	Cannot open the log file.
Action	Verify the log file exists at the specified path.

80014: Unable to close log file.

Cause	Cannot close the log file.
Action	Verify the log file exists at the specified path.

80015: Unable to open error file.

Cause	Cannot open the error file.
Action	Verify the error file exists at the specified path.

80016: Unable to close error file.

Cause	Cannot close the error file.
Action	Verify the error file exists at the specified path.

80017: Unable to open binary data file.

Cause	Cannot open a binary data file.
Action	Verify the binary data file exists at the specified path.

80018: Unable to close binary data file.

Cause	Cannot close a binary data file.
Action	Verify the binary data file exists at the specified path.

80019: Unable to load binary data larger than raw column size.

Cause	The binary data file is too large.
Action	Use a large data type like BLOB or LONG RAW.

80020: Data file name required.

Cause	No data file name was specified.
Action	Specify a data file name.

80021: Table was not found.

Cause	The table does not exist.
Action	Check the table name.

80022: Table name required.

Cause	No table name was specified.
Action	Enter a table name in the control file.

80023: Invalid column name \"%1\$s\".

Cause	The column name is invalid.
Action	Verify that the column name exists in the table.

80024: Unsupported data type in Loader utility.

Cause	The data type is not supported by the Loader utility.
Action	Check the data type.

80025: Column data exceeds data buffer size.

Cause	The column data is larger than the buffer.
--------------	--

Action	Increase the buffer size.
---------------	---------------------------

80026: Data file indicator was not found.

Cause	Cannot find the data file at the specified location.
Action	Verify that the path of the data file is valid.

80027: Unable to locate first column in data file.

Cause	Cannot find the first column in the data file.
Action	Verify that the path of the data file is valid.

80028: Unable to close external LOB or LONG data file.

Cause	Cannot close a LONG or LOB file.
Action	Verify the path of the file is valid.

80029: Unable to copy data to stream buffer in direct path load.

Cause	Cannot copy data to the DPL stream buffer.
Action	Check the size and availability of the data.

80030: Datafile has fewer lines than the number specified to skip.

Cause	The data file is smaller than the number of lines to skip.
Action	Check the data file.

80031: Error occurred while reading data file.

Cause	An error occurred while reading a data file.
Action	Check the path and modification of the data file.

80032: Invalid enclosed string was used.

Cause	An invalid enclosed string was used.
Action	Use a valid enclosed string.

80033: Data file has more errors than the maximum allowed (default: 50).

Cause	The data file has more record errors than allowed.
Action	Modify the ERRORS parameter on the command line, or modify data.

80034: Failed to load DPL stream.

Cause	Cannot connect the DPL stream to server.
Action	Check the CLI error context.

80035: Field terminator was not found.

Cause	The field delimiter does not exist.
Action	Specify a field delimiter.

80036: Failed to fetch additional rows: End of file was reached.

Cause	Reached the end of the data file.
Action	Check the current offset of the data file.

80048: Unable to jump to specific offset in datafile.

Cause	Cannot find a particular offset of the data file.
Action	Verify that the data file in the specified path is valid.

80049: Failed to insert data to database system.

Cause	Cannot load the data to DB.
Action	Check the CLI error context.

80050: Failed to assign outfile.

Cause	The data type cannot be read from an external file.
Action	Data types that can be read from an external file are BLOB, CLOB, LONG, LONG RAW and BINARY.

80051: Failed to alter DPL INDEX creation method.

Cause	An error occurred while changing the method to create a DPL INDEX.
Action	Contact the system administrator.

80052: Failed to convert from Loader utility data type to database data type.

Cause	Cannot convert the specified Loader utility data type to DB server data type.
Action	Contact the system administrator.

80053: Some relatively positioned columns are not present in the record.

Cause	Some column values do not exist in the record.
Action	To bind the non-existing columns with NULL, use the TRAILING NULLCOLS option.

80054: Error occurred while writing data file.

Cause	Failed to write the data file.
Action	Verify the data file path are modifications are correct.

80055: Unable to copy data to the connection information buffer.

Cause	An attempt was made to copy data that is larger than the (MAXLENGTH: 62).
Action	Check the buffer length and data.

80056: Column buffer size must be larger than the difference between start offset and end offset.

Cause	The buffer size of the column is smaller than the start and end offset difference.
Action	Specify a larger buffer size, or set the location information database.

80057: LOB file field delimiter was not found.

Cause	The LOB file field delimiter does not exist.
Action	Specify a field delimiter.

80058: The LOB file field delimiter is the same as the field terminator.

Cause	The LOB file field delimiter must be different from the field terminator.
Action	Specify a different LOB file field delimiter.

80059: The LOB file field delimiter was not found in data file.

Cause	The LOB file field delimiter does not exist in the data file.
Action	Specify a field delimiter found in the data file.

80060: The LOB file delimiter is the same as the field terminator.

Cause	The LOB file delimiter must be different from the field terminator.
Action	Specify a different LOB file field delimiter.

80061: The LOB file delimiter was not found in data file.

Cause	The LOB file delimiter does not exist in the data file.
Action	Specify a delimiter found in the data file.

80062: Invalid date/time format.

Cause	Invalid date/time format.
Action	Use the format supported by the DBMS server.

80063: Bind parameter was not found.

Cause	The bind parameter name does not exist in the columns.
Action	Use a string found among the column names.

80064: Duplicate filename in Loader utility.

Cause	Among control file, Infile, badfile, and logfile, two or more files have the same name.
Action	Check the file names and rename the duplicate(s).

80065: NOT NULL constraint violated.

Cause	An attempt was made to insert the NULL value into a column where the NOT NULL constraint is specified.
Action	Remove the NOT NULL constraint, or insert a value that is not NULL.

80066: Not yet implemented.

Cause	This function has not been implemented.
Action	This function will be supported in the next version.

80067: Cannot recognize the wallet file.

Cause	Input file name is incorrect or empty.
Action	Check the environment variable or input the file correctly.

80068: Unknown SQL function or function parameter.

Cause	Check SQL function or function parameter.
Action	Check SQL function or function parameter.

80069: Data save error in direct path loading mode.

Cause	Check bad file and log file.
Action	Check bad file and log file.

80070: Too many table names exist.

Cause	Set specific table names.
Action	Verify more than one SYNONYM are binded to different tables.

80071: Unable to use column with expression in DPL mode (DIRECT=Y).

Cause	This function is not supported.
Action	Use column with expression in CPL mode (DIRECT=N).

80072: DIRECT=Y option should be specified when DPL_LOG=Y or DPL_PARALLEL=Y.

Cause	If DPL_LOG=Y or DPL_PARALLEL=Y, DIRECT=Y should be also specified.
Action	Specify the DIRECT=Y option.

80073: Filename is too long.

Cause	The file name must be less than or equal to 256 characters.
Action	Choose a new filename.

80074: Invalid column index.

Cause	The column index is out of range.
Action	The column index must be greater than 0 and less than or equal to the number of columns.

80075: Unable to open %1\$s file: %2\$s.

Cause	Cannot open the %1\$s file.
Action	Verify the %1\$s file exists at the specified path.

80077: DIRECT=Y option should be specified when DPL_LOG=Y or PARALLEL>1.

Cause	If DPL_LOG=Y or PARALLEL>1, DIRECT=Y should be also specified.
Action	Specify the DIRECT=Y option.

80078: The environment variable '%1\$s' cannot be used.

Cause	The environment variable '%1\$s' cannot be used with the PARALLEL parameter.
Action	Delete the environment variable.

80079: I/O connect error.

Cause	An error occurred during communication with Proxy Server.
Action	Contact the technical support team.

80080: I/O listen error.

Cause	An error occurred during communication with Proxy Client.
Action	Contact the technical support team.

80081: I/O accept error.

Cause	An error occurred during communication with Proxy Client.
Action	Contact the technical support team.

80082: I/O read error.

Cause	An error occurred during communication.
Action	Contact the technical support team.

80083: Invalid nls_date_language.

Cause	Invalid nls_date_language.
Action	Use the nls_date_language supported by the DBMS server.

80084: Parallel and fast build indexes options cannot be used simultaneously.

Cause	Parallel and fast build indexes options cannot be used simultaneously.
Action	Use only one option between 'parallel' and 'fast build indexes'.

80085: Missing byteorder option in control file.

Cause	Missing byteorder option in control file.
Action	Write 'BYTEORDER (LITTLE/BIG) ENDIAN' phrase in control file.

제31장 90000 ~ 90999

90100: Runtime error occurred.

Cause	A JVM runtime error occurred.
Action	Check location of the error occurrence.

90200: Failed to load resource(s).

Cause	Failed to load resources.
Action	Check the resources.

90201: Unsupported operation.

Cause	The operation is not supported by JDBC driver.
Action	Check if the operation is supported by JDBC driver.

90202: Failed to read bind parameter(s).

Cause	Failed to read a bind parameter from the server.
Action	Check the bind parameter of SQL statement.

90203: Unsupported server version.

Cause	An attempt was made to connect to an unsupported version of a server.
Action	Check that the driver version and server version are compatible.

90400: Communication error.

Cause	An error occurred during communication with the server.
--------------	---

Action	Verify no problem exists while communicating with the server.
---------------	---

90401: Connection refused by the server.

Cause	Disconnected from the server.
Action	Reconnect to the server.

90402: Communication protocol error.

Cause	An error occurred relaying to the communication protocol.
Action	Check the server connection.

90403: Server has closed the connection.

Cause	The connection was closed by the server.
Action	Check the server connection, and try to reconnect.

90404: Internal protocol state error.

Cause	There was an error communicating with the server.
Action	Check the server connection.

90405: I/O error while reading from the server.

Cause	An I/O error occurred while reading data from the server.
Action	Check the server connection.

90406: I/O error while writing to the server.

Cause	An I/O error occurred while writing data to the server.
Action	Check the server connection.

90407: I/O error while flushing data.

Cause	An I/O error occurred while writing data to the server.
Action	Check the server connection.

90408: Unsupported I/O encoding method.

Cause	The I/O encoding method is not supported by the server.
Action	Check the encoding.

90409: I/O error while closing stream.

Cause	An I/O error occurred while closing a stream.
Action	Check the server connection.

90410: I/O error caused by a corrupted message header.

Cause	The header of the message from the server is corrupted.
Action	Check the message.

90411: Connection to server was interrupted but the fail-over successfully reconnected.

Cause	The server connection was terminated but a new connection was made to a server instance with the same DNS name.
Action	The job being executed by the user was canceled and must be restarted.

90500: Server error.

Cause	The server is in an error state.
Action	Check the condition of the server.

90501: Server failed to boot up.

Cause	Failed to start up the server.
Action	Verify that the environment can support server startup.

90502: User authentication failed: invalid user ID or password.

Cause	User authentication failed.
Action	Verify that the user ID and password are correct.

90503: Failed to close session.

Cause	Failed to close a session.
Action	Check the server connection.

90504: Failed to open session.

Cause	Failed to open a session.
Action	Check the server connection.

90505: Failed to close connection.

Cause	Failed to close a connection to the server..
Action	Check that the server connection is valid.

90506: Failed to create prepared statement.

Cause	Failed to create a prepared statement.
Action	Check the SQL statement.

90507: Failed to close cursor.

Cause	Cannot close the cursor of the server.
--------------	--

Action	Check the condition of the cursor.
---------------	------------------------------------

90508: Failed to execute SQL statement.

Cause	Failed to execute the SQL statement.
Action	Check the SQL statement.

90509: Failed to fetch data from the server.

Cause	Failed to fetch data from the server.
Action	Check the condition of the cursor.

90510: Failed to commit.

Cause	Failed to execute a commit command.
Action	Check the condition of the transaction.

90511: Failed to rollback.

Cause	Failed to execute a rollback command.
Action	Check the condition of the transaction.

90512: Failed to set autocommit.

Cause	Failed to execute an autocommit command.
Action	Check the condition of the transaction.

90513: Failed to set isolation level.

Cause	Failed to set the isolation level.
Action	Check an available isolation level.

90514: Failed to set savepoint.

Cause	Failed to set a savepoint.
Action	Check the condition of the transaction.

90515: Batch update failed.

Cause	Failed in batch update.
Action	Check the statement used in the batch update.

90516: Failed to read LOB.

Cause	Failed to read LOB data.
Action	Check the LOB locator.

90517: Failed to write LOB.

Cause	Failed to write LOB data.
Action	Check the LOB locator.

90518: Failed to search by INSTR.

Cause	Failed to find LOB data.
Action	Check the LOB locator.

90519: Failed to search by INLOB.

Cause	Failed to find LOB data.
Action	Check the LOB locator.

90520: Failed to truncate.

Cause	Failed to truncate LOB data.
--------------	------------------------------

Action	Check the LOB locator.
---------------	------------------------

90521: Failed to open LOB.

Cause	Failed to open LOB data.
Action	Check the LOB locator.

90522: Failed to close LOB.

Cause	Failed to close LOB data.
Action	Check the LOB locator.

90523: Failed to get LOB length.

Cause	Failed to get the length of a LOB.
Action	Check the LOB locator.

90524: Failed to create temporary LOB.

Cause	Failed to create a temporary LOB.
Action	Check the LOB locator.

90525: Failed to delete temporary LOB.

Cause	Failed to delete a temporary LOB.
Action	Check the LOB locator.

90526: Failed to cancel transaction.

Cause	Failed to cancel a transaction.
Action	Check the condition of the transaction.

90527: Failed to start XA transaction.

Cause	Failed to start an XA transaction.
Action	Check the condition of the distributed transaction.

90528: Failed to end XA transaction.

Cause	Failed to end an XA transaction.
Action	Check the condition of the distributed transaction.

90529: Failed to prepare XA transaction.

Cause	Failed to prepare an XA transaction.
Action	Check the condition of the distributed transaction.

90530: Failed to commit XA transaction.

Cause	Failed to commit an XA transaction.
Action	Check the condition of the distributed transaction.

90531: Failed to rollback XA transaction.

Cause	Failed to rollback an XA transaction.
Action	Check the condition of the distributed transaction.

90532: Failed to recover XA transaction.

Cause	Failed to recover an XA transaction.
Action	Check the condition of the distributed transaction.

90533: Failed to transfer deferred data.

Cause	Failed in deferred transfer.
--------------	------------------------------

Action	Check if the data is valid.
---------------	-----------------------------

90534: Failed to read LONG data.

Cause	Failed to read LONG data.
Action	Check if the LONG data is valid.

90535: Failed to get information about previously executed SQL statement.

Cause	Failed to get information about the previously executed SQL statement.
Action	Verify the SQL statement is valid.

90536: Failed to prepare Direct Path Load.

Cause	Failed to prepare a Direct Path Load.
Action	Check the metadata of the table to be uploaded.

90537: Failed to upload stream in Direct Path Load.

Cause	Failed to upload the stream.
Action	Verify that the stream data is valid.

90538: DATASAVE failed in Direct Path Load.

Cause	Failed to perform DATASAVE for the stream.
Action	Verify that the action sequences for the stream are correct.

90539: FINISH failed in the Direct Path Load.

Cause	Failed to execute FINISH for the stream.
Action	Verify that the action sequences for the stream are correct.

90540: FLUSH failed in the Direct Path Load.

Cause	Failed to execute FLUSH for the stream.
Action	Verify that the action sequences for the stream are correct.

90541: ABORT failed in the Direct Path Load.

Cause	Failed to execute ABORT for the stream.
Action	Verify that the action sequences for the stream are correct.

90542: FORGET failed in XA transaction.

Cause	Failed to execute FORGET for the autonomous transaction.
Action	Check the condition of the distributed transaction.

90543: Failed to reset the current session information.

Cause	Failed to initialize the current session information of the server.
Action	Check the error message.

90544: Column count mismatched in Direct Path Load.

Cause	Column count mismatched in Direct Path Load.
Action	Check the column count.

90545: Failed to set the client information.

Cause	Failed to set the client information in the server.
Action	Check the error message.

90546: Failed to get the column description.

Cause	Failed to get the column description from the server.
--------------	---

Action	Check the error message.
---------------	--------------------------

90547: The password has expired(grace).

Cause	The password has expired(grace).
Action	Update the password and then try again.

90548: The password will expire within %1\$s days.

Cause	The password will expire within %1\$s days.
Action	Update the password.

90600: Invalid use of JDBC API.

Cause	It does not meet the JDBC standard.
Action	Check the JDBC standard.

90601: Operation is invalid in autocommit mode.

Cause	The operation cannot be used in autocommit mode.
Action	Check the operation.

90602: Operation is invalid in XA transaction mode.

Cause	The operation cannot be executed in an XA mode.
Action	Check the operation.

90603: Invalid operation: disconnected from the server.

Cause	The operation is invalid due to server disconnection.
Action	Reconnect to the server.

90604: Invalid syntax.

Cause	Invalid syntax.
Action	Check the syntax.

90605: Invalid URL.

Cause	The URL of the server is invalid.
Action	Check the URL.

90606: Unable to execute batch statement.

Cause	Cannot execute the batch statement.
Action	Verify that it is a DDL statement.

90607: No result set was returned.

Cause	No result set was returned.
Action	Check the SQL statement.

90608: Invalid input parameter.

Cause	The input parameter is invalid.
Action	Check the parameter.

90609: Invalid column index.

Cause	The column index is invalid.
Action	Check the column index.

90610: Invalid data type.

Cause	The data type is unconvertible.
--------------	---------------------------------

Action	Check the requested data type.
---------------	--------------------------------

90611: Specified column name was not found.

Cause	The column name is invalid.
Action	Ensure the column exists.

90612: Conversion rule violation between DB type and JDBC type.

Cause	The data type cannot be converted to a JDBC type.
Action	Check the data type.

90613: Number of fetched rows exceeds the maximum.

Cause	The number of rows in the fetched result set exceeds the maximum.
Action	Check the number of rows to be fetched.

90614: Invalid SQL syntax.

Cause	SQL statement syntax is invalid.
Action	Check the syntax.

90615: Stored procedure must be executed on CallableStatement.

Cause	A procedure cannot be executed in statements other than CallableStatements.
Action	Use a CallableStatement.

90616: Failed to read data from stream.

Cause	Failed to read data from the server.
Action	Check the connection with the server.

90617: OUT parameter was not found.

Cause	There is no OUT parameter.
Action	Verify that an OUT parameter exists.

90618: Invalid OUT parameter.

Cause	The OUT parameter is invalid.
Action	Verify that the OUT parameter was correctly bound.

90619: Bind data is NULL.

Cause	Data was not bound.
Action	Bind data.

90620: Operation is invalid for a forward-only result set.

Cause	An attempt was made to execute an operation which is invalid for forward-only result sets.
Action	Change the type of the result set.

90621: Operation is invalid for a read-only result set.

Cause	An attempt was made to execute an operation which is invalid for read-only result sets.
Action	Change the type of the result set.

90622: Operation is invalid for a not-fetched result set.

Cause	An attempt was made to execute an operation that is invalid without fetching rows from the server.
Action	Fetch rows first.

90623: SQL statement and result set types do not match.

Cause	The SQL statement and the result set type do not match.
Action	Check the type of the result set.

90624: Invalid cursor position.

Cause	Invalid cursor position.
Action	Check the cursor position.

90625: Result set type cannot be downgraded.

Cause	The type of the current result set is invalid for the query.
Action	Change the type of the result set.

90626: Failed to refetch records during cache refresh.

Cause	Failed to refresh records in the result set.
Action	Check the operation executed for the current result set.

90627: Not all parameters are bound.

Cause	Some specified parameters were not bound.
Action	Check non-bound parameters.

90628: Invalid string length: must be shorter than 4000 bytes.

Cause	Invalid length of string.
Action	The maximum string length is 4,000 bytes.

90629: Operation is invalid on an empty LOB.

Cause	Invalid empty LOB operation.
--------------	------------------------------

Action	Check the operation.
---------------	----------------------

90630: Operation is invalid for batchupdate.

Cause	Invalid batchupdate operation.
Action	Batch statements do not include a SELECT statement.

90631: OUT parameters are invalid for batchupdate.

Cause	An OUT parameter cannot be used in batchupdate.
Action	Delete the OUT parameter or avoid using batchupdate.

90632: Escape syntax error.

Cause	Invalid escape syntax statement.
Action	Rewrite the statement with correct escape syntax.

90633: Savepoint name was not specified.

Cause	A savepoint name was not specified.
Action	Specify a savepoint name.

90634: Savepoint identifier was not specified.

Cause	There is no identifier of the savepoint.
Action	If a savepoint name is specified, it is impossible to get an identifier.

90635: ResultSet.next() method was not invoked.

Cause	The NEXT method was not invoked in the result set.
Action	Invoke the NEXT method in the result set first.

90636: Bound data too large: must be less than 16K chars or 64K bytes.

Cause	Data larger than the specified size cannot be bound in batchupdate.
Action	Large data should be entered through execution only one time.

90637: No schema information found in Direct Path Load.

Cause	Information about schemas needed for DPL is not found.
Action	Specify schemas.

90638: No table information found in Direct Path Load.

Cause	DPL required information about tables was not found.
Action	Specify tables.

90639: No column count information found in Direct Path Load.

Cause	DPL required information about the number of columns was not found.
Action	Specify the number of columns first.

90640: No column name information found in Direct Path Load.

Cause	DPL required information about column names is missing.
Action	Specify all column names.

90641: LOG-flag information does not exist in Direct Path Load.

Cause	DPL required LOG-flag information was not found.
Action	Specify LOG-flag.

90642: Unable to convert a specified string to ROWID.

Cause	The string is not valid for ROWID .
Action	Use a valid string for ROWID.

90643: Connection is already closed.

Cause	Disconnected from the server.
Action	Reconnect to the server.

90644: Result set contains no metadata.

Cause	Metadata for the result set does not exist.
Action	Verify the result set is valid.

90645: Auto Connection Recovery is already enabled.

Cause	The ACR function for the connection is already enabled.
Action	Check if there is a duplicate call.

90646: Result set is already closed.

Cause	Unable to access the closed result set.
Action	Check if the statement is closed before referring to the result set.

90647: Result set is closed or empty.

Cause	The result set is closed or contains no column data.
Action	Confirm the result set is open and column data exists.

90648: Invalid array size for session attributes.

Cause	The array size for session attributes is invalid.
--------------	---

Action	Check the maximum value of the array size.
---------------	--

90649: Invalid name pattern.

Cause	The name pattern is invalid.
Action	Check if the string length is 0.

90650: Data is too large for the buffer.

Cause	The data is larger than the buffer size.
Action	Increase the buffer size.

90651: Failed to convert given data.

Cause	Failed to convert given data.
Action	Check the error message.

90652: Use of long literal in batchupdate is prohibited.

Cause	String sizes greater than 64K bytes are not supported in batchupdate.
Action	Use bind variables in the SQL statement.

90653: Overflow error.

Cause	Overflow error.
Action	Narrow the range of the value.

90654: Underflow error.

Cause	Underflow error.
Action	Widen the range of the value.

90655: Not allowed to bind ordinal and named parameter simultaneously.

Cause	Not allowed to bind an ordinal and a named parameter simultaneously.
Action	Use only one of two types of bind parameters.

90656: Exceeds the maximum length limit.

Cause	The specified length exceeds the maximum value.
Action	Use a value smaller than 2,147,483,647.

90657: Cannot cast this instance to the specified class

Cause	Unable to cast to the specified class.
Action	Enter a valid class for the instance.

90658: The statement is already closed.

Cause	The statement is already closed.
Action	Create a new statement.

90659: Invalid operation: Closed Statement.

Cause	Unable to execute the operation due to the closed statement.
Action	Create a new statement.

90660: Unsupported result set holdability type.

Cause	The result set holdability type is not supported.
Action	Use another result set holdability type.

90661: The partition name is not valid.

Cause	An empty partition name was used.
Action	Use a non-empty partition name.

90662: Unable to use parallel DPL.

Cause	The server does not support parallel DPL.
Action	Connect to a server that supports parallel DPL.

90663: Data is too long to be converted to CHAR/VARCHAR data type.

Cause	The data length exceeds the allowed length of a CHAR, VARCHAR type.
Action	Modify the data length or change the data type.

90664: Failed to read in user-defined metadata.

Cause	Failed to read in user-defined metadata.
Action	Check the error message.

90665: Unable to find the specified user-defined type.

Cause	Unable to find the specified user-defined type.
Action	Check the type definitions of the server.

90666: Another kind of user-defined type with the specified name already exists.

Cause	Another kind of user-defined type with the specified name already exists.
Action	Check the type definitions of the server.

90700: Connection to server was interrupted but the fail-over successfully reconnected.

Cause	The server connection was terminated but a new connection was made to a server instance with the same DNS name.
Action	The job being executed by the user was canceled and must be restarted.

90701: Failed to recover select.

Cause	An I/O error occurred during select failover.
Action	Try again later.

90702: Unable to fetch subsequent rows.

Cause	Failover was not able to restore the result set to its original state to continue fetching rows.
Action	Re-execute the query to fetch from the first row.

90820: Cannot create a SyncProvider instance.

Cause	Unable to create the SyncProvider object.
Action	Check the error message.

90821: Cannot find the FROM clause to get the table name.

Cause	Unable to find the FROM clause in the specified SQL statement.
Action	Use a statement containing the FROM clause.

90822: Current row is not inserting.

Cause	The current row is not under the INSERT operation.
Action	Start the INSERT operation before using it.

90823: NULL ResultSet cannot populate.

Cause	Unable to create the RowSet with the NULL result set.
Action	Use a value other than NULL.

90824: Current row is not updating.

Cause	The current row is not under the UPDATE operation.
Action	Start the UPDATE operation before using it.

90825: The RowSet cannot write.

Cause	Unable to write data in the current RowSet.
Action	Change the RowSet state to the editable state.

90826: Command is NULL.

Cause	No command is saved in the RowSet.
Action	Set the command and execute it.

90827: Connection is closed.

Cause	Not connected to the database.
Action	Connect to the database.

90828: Failed to connect through the DataSource.

Cause	Failed to connect with the user information.
Action	Check the error message.

90829: Failed to convert the data to the specified type.

Cause	Failed to convert the data to the specified type.
--------------	---

Action	Check the error message.
---------------	--------------------------

90830: Failed to create the object copy.

Cause	Failed to create the object copy.
Action	Check the error message.

90831: Failed to map to the collection object.

Cause	Failed to map to the collection object.
Action	Check the error message.

90832: Failed to set the column index.

Cause	Failed to set the column index.
Action	Check the error message.

90833: Failed to set the column name.

Cause	Failed to set the column name.
Action	Check the error message.

90834: Invalid column index.

Cause	Invalid column index.
Action	Check if the column index is smaller than 1 or larger than the number of columns.

90835: Invalid column name.

Cause	Invalid column name.
Action	Check the column name.

90836: Invalid column type.

Cause	Invalid column type.
Action	Check if the requested type and the actual column type are compatible.

90837: Invalid cursor position.

Cause	Invalid cursor position.
Action	Use next() or previous() beforehand.

90838: Invalid fetch direction.

Cause	Invalid fetch direction.
Action	Only FETCH_FORWARD, FETCH_REVERSE, and FETCH_UNKNOWN are available.

90839: Invalid number of key columns.

Cause	Invalid number of key columns.
Action	The number of key columns must not be NULL and be less than the actual number of columns.

90840: Invalid column index.

Cause	Invalid column index.
Action	Use a numeric value larger than 0.

90841: Invalid column name.

Cause	Invalid column name.
Action	Use a value that is neither NULL nor an empty character string.

90842: Invalid object class.

Cause	Invalid object class.
Action	Check the error message.

90843: Invalid page size.

Cause	Invalid page size.
Action	Use a value that is larger than 0 and smaller than the maximum number of rows.

90844: Invalid parameter index.

Cause	Invalid parameter index.
Action	An index value of less than 1 is invalid.

90845: Invalid parameter name.

Cause	Invalid parameter name.
Action	Check if the parameter name exists.

90846: Invalid parameter type.

Cause	Invalid parameter type.
Action	Check the error message.

90847: Invalid row index.

Cause	Invalid row index.
Action	Use a value that is larger than 1 or smaller than the number of actual rows.

90848: Invalid number of rows.

Cause	Invalid number of rows.
--------------	-------------------------

Action	Use a value that is larger than 0 or larger than the fetchSize.
---------------	---

90849: Invalid RowSet.

Cause	Unable to execute the operation to the specified rowset.
Action	Use a rowset of another type.

90850: Invalid ResultSet.

Cause	Unable to execute the operation on the specified result set.
Action	Use a different result set.

90851: The current row is inserting.

Cause	The current row is under the INSERT operation.
Action	Complete or cancel the INSERT operation.

90852: The DataSourceName or URL is missing.

Cause	Either the DataSource name or URL is not specified.
Action	Check each item.

90853: Previous page operation is missing.

Cause	Previous paging operation does not exist.
Action	Execute the paging operation beforehand.

90854: The user name or password is missing.

Cause	Either the user name or password is not specified.
Action	Check each item.

90855: Unable to update the current column.

Cause	Unable to update the current column.
Action	Update a different column or cancel the current operation.

90856: Unable to display the deleted rows.

Cause	Unable to display the deleted rows.
Action	Use another rowset or set the visibility to false.

90857: No row was changed.

Cause	No row was changed.
Action	Use when the row data has changed.

90858: The specified row has not been deleted.

Cause	The specified row has not been deleted.
Action	Use after the row has been deleted.

90859: The result set does not exist.

Cause	The result set does not exist.
Action	Check if the result set was created.

90860: No column index matches.

Cause	No column index matches.
Action	Match the column index.

90861: No column name matches.

Cause	No column name matches.
--------------	-------------------------

Action	Match the column name.
---------------	------------------------

90862: The specified row has never been inserted.

Cause	The specified row has not been inserted.
Action	Insert the row.

90863: The specified row has never been updated.

Cause	The specified row has not been updated.
Action	Update the row.

90864: The filter conditions are not satisfied.

Cause	The filter conditions are not satisfied.
Action	Check if the data satisfies the filter conditions.

90865: All columns are not set.

Cause	All column data are not set.
Action	Ensure all column data have been set.

90866: The column index has not been set.

Cause	The column index has not been set.
Action	Set the column index beforehand.

90867: The column name has not been set.

Cause	The column name has not been set.
Action	Set the column name.

90868: Too few rows to populate.

Cause	The number of rows is too small.
Action	Use a result set which has a larger number of rows.

90900: LOB is already closed.

Cause	LOB data is already closed.
Action	Check if an invalid operation was executed on the closed LOB data.

90901: Unable to read LOB data.

Cause	Failed to read LOB data.
Action	Check the LOB locator.

90902: Cannot read a LOB object in a remote server.

Cause	Cannot read a LOB object in a remote server.
Action	Change the query.

90920: XML object has already been freed.

Cause	XML object resource has already been freed.
Action	Check if the XML object resource is free before execution.

90921: XML object can be used for writing data only.

Cause	An attempt was made to use a write-only XML object for another purpose.
Action	The XML object can be used only for writing data. Ensure the XML object was created properly.

90922: XML data has already been read.

Cause	XML data has already been read by a user request.
Action	Check if all XML data has been read before execution.

90923: XML object can be used for reading data only.

Cause	An attempt was made to use a read-only XML object for another purpose.
Action	The XML object can be used only for reading data. Ensure the XML object was created properly.

90924: XML data has already been set.

Cause	XML data has already been set by a user request.
Action	Check if all XML data is set before execution.

90925: Failed to free XML object.

Cause	Failed to free the XML object resource.
Action	Check the error message.

90926: Failed to initialize XML object.

Cause	Failed to initialize the XML object.
Action	Check the error message.

90927: Failed to read XML data from stream.

Cause	Failed to read data from the stream.
Action	Check the error message.

90928: Unsupported class.

Cause	The class is not supported.
Action	Use the DOM/SAX/StAX/Stream classes only.

90929: XML object contains no data.

Cause	No data is stored in the XML object.
Action	Store data first.

90930: Unable to set a NULL value.

Cause	An attempt was made to use a NULL value.
Action	Specify a non-NULL value.

제32장 110000 ~ 110999

110001: Invalid license.

Cause	The license is invalid.
Action	Invalid license. If a demo version is being used, check the license expiration date.

110002: Requested feature is not provided by the current license.

Cause	The function is not provided under the current license.
Action	Check the edition and contact the technical support team to upgrade the license.

제33장 120000 ~ 120999

Reserved for Future Use

제34장 130000 ~ 130999

130001: Invalid protocol.

Cause	Invalid protocol.
Action	Verify that the protocol is valid and that the message transmission sequence is correct.

130002: Login failed: invalid user ID or password.

Cause	Failed to login.
Action	Verify that the user ID and password are correct.

130003: ExecuteDirect call failed.

Cause	Failed to execute the SQL statement.
Action	Check that the statement is correct.

130005: Authentication failed.

Cause	Failed to login.
Action	Check to see if there are any errors in the authentication gateway.

130006: Failed to open cursor.

Cause	Failed to open the cursor in the gateway.
Action	Contact the technical support team.

130007: Invalid cursor.

Cause	Invalid cursor.
--------------	-----------------

Action	Contact the technical support team.
---------------	-------------------------------------

130008: Fetch failed.

Cause	Fetch failed.
Action	Contact the technical support team.

130009: Remote DBMS system(target DB) connected to the DBMS server returned the message: %1\$s.

Cause	The message was received from a database system connected to the gateway.
Action	Check the message received from the target database system.

130010: Successful completion message received from DB system: %1\$s.

Cause	The target database system connected to the gateway has successfully completed the function.
Action	Check the message received from the target database system.

130011: Warning message received from DB system: %1\$s.

Cause	The target database system connected to the gateway completed the function with a warning message.
Action	Check the message received from the target database system.

130012: Cursor operation conflict in DB system: %1\$s.

Cause	Cursor operation conflict occurred within the target database system connected to the gateway.
Action	Check the message received from the target database system.

130013: Disconnect error received from DB system: %1\$s.

Cause	Failed to disconnect from the target database system which is connected to the gateway.
Action	Check the message received from the target database system.

130014: NULL values eliminated in the set function in DB system: %1\$s.

Cause	NULL values have been eliminated from a set function in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130015: String data was right truncated in DB system: %1\$s.

Cause	String data right truncation occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130016: Insufficient item descriptor areas in DB system: %1\$s.

Cause	There are too few item descriptor areas for the result set or gateway.
Action	Check the message received from the target database system.

130017: Privilege not revoked in DB system: %1\$s.

Cause	Failed to revoke the privilege in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130018: Privilege not granted in DB system: %1\$s.

Cause	Failed to grant the privilege in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130019: Implicit zero-bit padding in DB system: %1\$s.

Cause	Implicit zero-bit padding in the target DB system connected to the gateway.
Action	Check the message received from the target database system.

130020: Search condition for information schema is too long in DB system: %1\$s.

Cause	The search condition for schema information is too long in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130021: Query expression for information schema is too long in DB system: %1\$s.

Cause	The query expression for schema information is too long in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130022: No matching data found in DB system: %1\$s.

Cause	There is no data satisfying the condition in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130023: Dynamic SQL error in DB system: %1\$s.

Cause	Failed to execute the dynamic SQL statement in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130024: Dynamic SQL error in DB system - USING clause does not match parameter specs: %1\$s.

Cause	The dynamic SQL statement to be executed in the target parameter does not match parameter specification.
Action	Check the message received from the target database system.

130025: Dynamic SQL error in DB system - cursor specification cannot be executed: %1\$s.

Cause	The cursor specification cannot be executed in the dynamic gateway.
Action	Check the message received from the target database system.

130026: Dynamic SQL error in DB system - USING clause required for dynamic parameters: %1\$s.

Cause	A USING clause is required for a dynamic SQL statement in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130027: Dynamic SQL error in DB system - prepared statement not a cursor specification: %1\$s.

Cause	A prepared statement which does not have a cursor in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130028: Dynamic SQL error in DB system - restricted data type attribute violation: %1\$s.

Cause	Data type error has occurred in a dynamic SQL statement in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130029: Dynamic SQL error in DB system - USING clause required for result fields: %1\$s.

Cause	A USING clause must be used to receive the resulting data from a gateway.
Action	Check the message received from the target database system.

130030: Dynamic SQL error in DB system - invalid descriptor count: %1\$s.

Cause	The number of descriptors shown in the dynamic SQL statement is invalid.
Action	Check the message received from the target database system.

130031: Dynamic SQL error in DB system - invalid descriptor index: %1\$s.

Cause	Invalid descriptor index in the dynamic SQL statement of the target database system connected to the gateway.
Action	Check the message received from the target database system.

130032: Connection exception in DB system: %1\$s.

Cause	An exception has occurred in a connection with the target database system.
Action	Check the message received from the target database system.

130033: SQL client could not establish SQL connection with DB system: %1\$s.

Cause	Failed to connect to the target database system.
Action	Check the message received from the target database system.

130034: Connection name already in use on target DB system: %1\$s.

Cause	The name of the connection with the target database system is already in use.
Action	Check the message received from the target database system.

130035: Connection to target DB system does not exist: %1\$s.

Cause	A connection to the target database system does not exist.
Action	Check the message received from the target database system.

130036: DB server rejected SQL connection: %1\$s.

Cause	Connection to the target database system has been rejected.
Action	Check the message received from the target database system.

130037: Connection failure error received from target DB system: %1\$s.

Cause	Failed to connect with the target database system.
Action	Check the message received from the target database system.

130038: Transaction resolution unknown in DB system: %1\$s.

Cause	Unknown transaction in the target database system.
Action	Check the message received from the target database system.

130039: Feature not supported in DB system: %1\$s.

Cause	Feature is not provided by the target database system connected to the gateway.
Action	Check the message received from the target database system.

130041: Cardinality violation in DB system: %1\$s.

Cause	In the target database system connected to the gateway, the sub query contains more than two records.
Action	Check the message received from the target database system.

130042: Data exception in DB system: %1\$s.

Cause	A data error occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130043: Data exception in DB system: string data - right truncation %1\$s.

Cause	Right truncation of string data occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130044: Data exception in DB system: null value - no indicator parameter %1\$s.

Cause	There is no parameter indicator in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130045: Data exception in DB system: numeric value out of range %1\$s.

Cause	Some numeric data to be expressed in the target database system connected to the gateway is out of range.
Action	Check the message received from the target database system.

130046: Data exception in DB system: error in assignment %1\$s.

Cause	The data was not assigned in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130047: Data exception in DB system: invalid date-time format %1\$s.

Cause	Invalid date or time format in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130048: Data exception in DB system: date-time field overflow %1\$s.

Cause	A date or time data overflow problem occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130049: Data exception in DB system: invalid time zone displacement value %1\$s.

Cause	Invalid time zone setting in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130050: Data exception in DB system: substring error %1\$s.

Cause	An error occurred while extracting a substring in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130051: Data exception in DB system: division by zero %1\$s.

Cause	An attempt was made to divide by zero in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130052: Data exception in DB system: INTERVAL field overflow %1\$s.

Cause	An INTERVAL data overflow problem occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130053: Data exception in DB system: invalid character value for cast %1\$s.

Cause	An invalid character value for case was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130054: Data exception in DB system: invalid escape character %1\$s.

Cause	An invalid escape character was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130055: Data exception in DB system: character not in repertoire %1\$s.

Cause	Invalid character data was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130056: Data exception in DB system: indicator overflow %1\$s.

Cause	An indicator overflow problem occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130057: Data exception in DB system: invalid parameter value %1\$s.

Cause	An invalid parameter value was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130058: Data exception in DB system: unterminated C string %1\$s.

Cause	An unterminated C string was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130059: Data exception in DB system: invalid escape sequence %1\$s.

Cause	An invalid escape sequence was used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130060: Data exception in DB system: string data length mismatch %1\$s.

Cause	Mismatched string data length in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130061: Data exception in DB system: trim error %1\$s.

Cause	Failed to trim the character string in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130062: Integrity constraint violation in DB system: %1\$s.

Cause	Some data in the target database connected to the gateway violates integrity constraints.
Action	Check the message received from the target database system.

130063: Invalid cursor state in DB system: %1\$s.

Cause	An invalid cursor state exists in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130064: Invalid transaction state in DB system: %1\$s.

Cause	An invalid transaction state exists in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130065: Invalid SQL statement name in DB system: %1\$s.

Cause	An invalid statement name exists in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130066: Triggered data change violation in DB system: %1\$s.

Cause	Invalid use of trigger in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130067: Invalid authorization specification in DB system: %1\$s.

Cause	An invalid authorization specification exists in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130069: Dependent privilege descriptors still exist in DB system: %1\$s.

Cause	Dependent privilege descriptors still exist in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130070: Invalid character set name in DB system: %1\$s.

Cause	The specified character set is not supported in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130071: Invalid transaction termination in DB system: %1\$s.

Cause	An invalid transaction termination occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130072: Invalid connection name in DB system: %1\$s.

Cause	An invalid connection name has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130073: Invalid SQL descriptor name in DB system: %1\$s.

Cause	An invalid SQL descriptor has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130074: Invalid cursor name in DB system: %1\$s.

Cause	An invalid cursor name has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130075: Invalid condition number DB system: %1\$s.

Cause	An invalid condition number has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130077: Ambiguous cursor name in DB system: %1\$s.

Cause	An ambiguous cursor name has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130078: Invalid catalog name in DB system: %1\$s.

Cause	An invalid catalog name has been used in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130079: Invalid schema name in DB system: %1\$s.

Cause	An invalid schema name has been used in the target database system connected to the gateway.
--------------	--

Action	Check the message received from the target database system.
---------------	---

130080: Transaction rollback error in DB system: %1\$s.

Cause	A transaction rollback error has occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130081: Transaction rollback error in DB system: serialization failure %1\$s.

Cause	A serialization failure between transactions has occurred in the target database system connected to the gateway.
Action	Check the message received from the target database system.

130082: Transaction rollback error in DB system: integrity constraint violation %1\$s.

Cause	A transaction of the target database system connected to the gateway violated integrity constraints.
Action	Check the message received from the target database system.

130083: Transaction rollback error in DB system: statement completion is unknown %1\$s.

Cause	The termination of a transaction in the target database system connected to the gateway has not yet been confirmed.
Action	Check the message received from the target database system.

130084: Syntax error or access rule violation in DB system: %1\$s.

Cause	In the target database system connected to the gateway, bad syntax was used, or an invalid object was accessed.
--------------	---

Action	Check the message received from the target database system.
---------------	---

130085: WITH CHECK option violation in DB system: %1\$s.

Cause	An invalid use of the WITH CHECK option occurred in a view of the target database system connected to the gateway.
Action	Check the message received from the target database system.

130086: Oracle system error: %1\$s.

Cause	An Oracle system error has occurred.
Action	Check the message received from the target database system.

130087: Oracle resource error: %1\$s.

Cause	An error occurred in the Oracle resources connected to the gateway.
Action	Check the message received from the target database system.

130088: Oracle multi-threaded server or detached process error: %1\$s.

Cause	An error has occurred in the Oracle server or process connected to the gateway.
Action	Check the message received from the target database system.

130089: Oracle XA protocol or two-task interface error: %1\$s.

Cause	An error has occurred in the Oracle XA protocol or the two-task interface connected to the gateway.
Action	Check the message received from the target database system.

130090: Oracle control file, database file, redo file, archival recovery, or media recovery error: %1\$s.

Cause	An error has occurred in the Oracle control file or database file during archive or media recovery.
Action	Check the message received from the target database system.

130091: Oracle PL/SQL error: %1\$s.

Cause	An error has occurred while executing Oracle PL/SQL connected to the gateway.
Action	Check the message received from the target database system.

130092: Oracle SQL*Net driver error: %1\$s.

Cause	An error has occurred in the Oracle SQL*Net driver connected to the gateway.
Action	Check the message received from the target database system.

130093: Oracle licensing error: %1\$s.

Cause	A problem occurred in the license of the Oracle database connected to the gateway.
Action	Check the message received from the target database system.

130094: Oracle SQL*Connect error: %1\$s.

Cause	An error occurred in Oracle SQL*Connect.
Action	Check the message received from the target database system.

130095: SQL phase execution error: %1\$s.

Cause	An error has occurred while executing an SQL statement in the Oracle database connected to the gateway.
Action	Check the message received from the target database system.

130096: Unsupported datatype in table.

Cause	Invalid data type in the target database table.
Action	Check to see if LONG, CLOB or BLOB types exist in the table.

130097: Explicit prepare failed.

Cause	Failed to execute 'prepare' in the target database.
Action	Check if there are any SQL syntax errors.

130098: Global transaction cannot be started.

Cause	Failed to start a global transaction for the target database.
Action	Check the error message from the target database system.

130099: Global transaction cannot be prepared.

Cause	Target database system has failed to prepare a global transaction.
Action	Check the error message from the target database system.

130100: Global transaction cannot be committed.

Cause	Target database system has failed to commit a global transaction.
Action	Check the error message from the target database system.

130101: Global transaction cannot be rolled back.

Cause	Target database system has failed to rollback a global transaction.
Action	Check the error message from the target database system.

130102: Execute call failed.

Cause	Failed to execute the statement.
--------------	----------------------------------

Action	Check if the statement is correct.
---------------	------------------------------------

130103: BindParam call failed.

Cause	Failed to execute the statement.
Action	Check if the statement is correct.

130104: New connection has been requested, although connection is already established.

Cause	Another connection was requested while connecting with server.
Action	Check the connection with the gateway.

130105: Unable to start gateway process.

Cause	Failed to start a gateway process.
Action	Ensure gateway process execution is permitted (e.g. permissions).

130106: Successful completion message received from DB system: %1\$s.

Cause	The target database system connected to the gateway has successfully completed the function.
Action	Check the message received from the target database system.

130107: Failed to allocate the environment handle.

Cause	The target database failed to allocate the top-level handle.
Action	Check if the environmental variables required in the target database system are configured properly.

130108: Invalid LONG column position.

Cause	The position of the LONG column is invalid.
Action	Specify the LONG column at the end of the SELECT list.

제35장 140000 ~ 140999

140002: Invalid protocol.

Cause	An invalid protocol was used.
Action	Make sure the protocol exists and that message transmission sequence is correct.

140003: Successful completion message.

Cause	The procedure was invoked successfully.
Action	Check the result.

140004: Failed to open library ('%1\$s') - %2\$s.

Cause	Failed to open the library.
Action	Check the error message.

140006: Unexpected external procedure failed.

Cause	Failed to execute an external function.
Action	Check the cause of the failure and try again.

140008: Invalid class name ('%1\$s').

Cause	The specified class was not found at the class path.
Action	Verify that the class name and path are correct.

140009: Function ('%1\$s') call failed - %2\$s.

Cause	Failed to call the function.
--------------	------------------------------

Action	Check the error message.
---------------	--------------------------

140010: Invalid error code - %1\$u.

Cause	The specified error code was not found.
Action	Check the error code.

140011: Invalid error code - %1\$u.

Cause	The specified error code was not found.
Action	Check the error code.

140012: External procedure execution failure caused by user - %1\$s.

Cause	Failed to execute the external procedure.
Action	The error was caused by the user during the execution of the external procedure.

140013: OUT parameter length overflow.

Cause	The OUT parameter length exceeds the maximum allowed.
Action	Check the error message.

140014: Not supported SQL type in external procedure

Cause	External Procedure does not support the SQL type.
Action	Check the SQL types supported by External Procedure.

140015: The length of the user library path is too long.

Cause	The length of the user library path is too long.
Action	Check the library path.

140016: The length of the user function name is too long.

Cause	The length of the user function name is too long.
Action	Check the function name.

140017: External Procedure Agent gets a signal when it was in recv().

Cause	External Procedure Agent gets a signal when it was in recv().
Action	It is not an error.

제36장 150000 ~ 150999

150002: Invalid protocol.

Cause	An invalid protocol was used.
Action	Ensure the protocol exists and the message transmission sequence is correct.

150003: Successful completion message.

Cause	The procedure was successfully invoked.
Action	Check the result.

150004: Invalid library path.

Cause	The library path is invalid.
Action	Check the library path.

150005: Invalid function name.

Cause	The specified function was not found in the library.
Action	Check the function name.

150006: External procedure failed unexpectedly.

Cause	Failed to execute an external function.
Action	Investigate the cause of the failure and try again.

150008: Invalid class name.

Cause	The specified class was not found in the specified class path.
--------------	--

Action	Check the class name and path.
---------------	--------------------------------

제37장 160000 ~ 160999

160001: The data file does not exist.

Cause	The data file to be used in the Export/Import utility functions does not exist.
Action	Verify the data file exists or the data file was specified correctly.

160002: The message file does not exist.

Cause	The message file to be used in the Export/Import utility functions does not exist.
Action	Verify the message file exists or the message file was specified correctly.

160003: The bad file does not exist.

Cause	The error file to be used in the Export/Import utility functions does not exist.
Action	Verify the error file exists or the error file was specified correctly.

160004: Meta information does not exist.

Cause	The meta information to be used in the Export/Import utility functions does not exist.
Action	Verify the meta information was set correctly in the API structure.

160005: The specified argument is NULL.

Cause	Null is used in the parameter of the Export/Import utility functions.
Action	Verify the parameter value used in API calls is NULL.

160006: The action string does not exist.

Cause	The command to be used in the Export/Import utility functions does not exist.
--------------	---

Action	Verify the command was set correctly in the API structure.
---------------	--

제38장 190000 ~ 190999

190001: protocol failure (type=%1\$d)

Cause	The communications protocol does not match client layer
Action	Verify the protocol is valid.

190002: socket read failure (errno=%1\$d)

Cause	No responsee has arrived from client(listen thread)
Action	Verify the client(listen thread) is running

제39장 400000 ~ 400999

400001: Java class loading has failed. (%1\$s), for more details, refer to the stdout error file.

Cause	The jar files used in HBASE must be set in the environment variable.
Action	Modify the CLASSPATH.

400002: jni error (%1\$s)

Cause	jni error
Action	jni error

400003: A table connection error (%1\$s) has occurred in HBASE. For more details about the table connection error, check the stdout error file.

Cause	The table name and column family must exist in HBASE.
Action	Modify the definition of the HBASE table, and the column family of the query.

400004: The (%1\$s) column is not assigned to a column family.

Cause	A column must be assigned to a column family in order to perform a query on an HBASE TABLE.
Action	Add the column, which is used in the query, to a column family. (columnfamily\$column)

400005: The target column is not defined.

Cause	A target column must be specified when data is inserted into an HBASE TABLE.
Action	Specify the target column to insert the data. (columnfamily\$column)

400006: A ROWKEY column is required.

Cause	A ROWKEY column must be specified when inserting data into an HBASE TABLE.
Action	Add a ROWKEY column.

제40장 410000 ~ 410999

410001: The specified storage server name, '%1\$s', is not identical to the storage server name, '%2\$s', that was set in a tip file.

Cause	An invalid storage server name was used in a statement for creating a storage server.
Action	Set the storage server name identically to the name set in the SSVR_NAME of a tip file, or omit the name.

410002: This DDL statement is not permitted in storage server mode.

Cause	In the storage server mode, this DDL cannot be executed.
Action	This DDL cannot be executed.

410003: The disk name, '%1\$s', is invalid.

Cause	The name is duplicated or a disk with the specified name could not be found.
Action	Check the disk name.

410004: The disk path, '%1\$s', is invalid.

Cause	The path is invalid or a disk at the specified path could not be found.
Action	Check the disk path.

410005: Failed to create file.

Cause	Check the tracelog to view the causes of failure.
Action	Retry after resolving errors.

410006: Invalid fetch information.

Cause	Incorrect fetch information was fetched in DB.
Action	Retry after resolving error.

410007: Specified tip SSVR_WTHR_CNT value is too small.

Cause	SSVR_WTHR_CNT is smaller than sdisk count.
Action	Retry after increasing the SSVR_WTHR_CNT value.

410008: Invalid gdisk ID.

Cause	Invalid gdisk ID was used to request DB read/write.
Action	Retry after resolving error.

410009: Invalid gdisk ID.

Cause	Invalid gdisk ID was used to request DB read/write.
Action	Retry after resolving error.

410010: Insufficient permissions on the disk, '%1\$s'.

Cause	Read/write permissions are required for the disk.
Action	Grant read/write permissions on the disk.

410011: Failed to create the disk.

Cause	Check the available disk space.
Action	Retry the operation after setting the disk size to a value within the available disk space.

410012: Failed to drop the storage disk.

Cause	There is a grid disk that is included in the storage disk.
--------------	--

Action	Retry the operation after dropping all grid disks that are included in the storage disk.
---------------	--

410013: Invalid gdisk arguments.

Cause	Specified gdisk information is invalid.
Action	Check whether the range overlaps with a previously created gdisk or whether the information fits 32k alignment.

410014: get IP by hostname failed.

Cause	Failed to get IP from hostname.
Action	Check whether _RDS_NW_IP is valid.

410015: send msg failed.

Cause	Failed to send message.
Action	Check the network status and log.

410016: send msg failed.

Cause	Failed to receive message.
Action	Check the network status and log.

410017: sync sfc failed.

Cause	Flashcache was not synchronized for the modified block.
Action	Check whether synchronization was performed in another session.

410018: create sfc failed.

Cause	Failed to create SFC.
Action	Check whether a duplicate SFC was created or whether SFC was created in MOUNT mode.

410019: drop sfc failed.

Cause	Failed to delete SFC.
Action	Check whether the SFC to be deleted exists or whether SFC was deleted in MOUNT mode.

410020: Insufficient permissions on the flash, '%1\$s'.

Cause	Read/write permissions are required for the flash.
Action	Grant read/write permissions on the flash.

410021: The flash path, '%1\$s', is invalid.

Cause	The path is invalid or a flash at the specified path could not be found.
Action	Check the flash path.

410022: The share value is less than 1 or greater than %1\$d.

Cause	The share value is invalid.
Action	Modify the share value.

410023: The level value is less than 1 or greater than %1\$d.

Cause	The level value is invalid.
Action	Specify the level to a value between 1 and 8.

410024: The allocation value is less than 1 or greater than 100.

Cause	The allocation value is invalid.
Action	Modify the allocation value.

410025: The sum of the share values exceeds %1\$d.

Cause	The sum of the share values is too large.
--------------	---

Action	Decrease the total share value.
---------------	---------------------------------

410026: The allocation sum of level %1\$d exceeds 100.

Cause	The allocation sum exceeds 100.
Action	Modify the allocation value.

410027: The number of directives of the DB plan that uses share exceeds %1\$d.

Cause	The number of directives of the DB plan that uses share is too high.
Action	Decrease the number of directives of the DB plan that uses share.

410028: The number of directives of the DB plan that uses level exceeds %1\$d.

Cause	The number of directives of the DB plan that uses level is too high.
Action	Decrease the number of directives of the DB plan that uses level.

410029: The number of directives of the category plan exceeds %1\$d.

Cause	The number of directives of the category plan is too high.
Action	Decrease the number of directives of the category plan.

410030: The directive name '%1\$s' is a duplicate.

Cause	The directive name is a duplicate.
Action	Change the directive name.

410031: The OTHER directive is missing.

Cause	The OTHER directive is missing.
Action	Specify the OTHER directive.

410032: The flash log size, %1\$d GB, is invalid.

Cause	The size of flash log is invalid.
Action	Change the directive flash log size.

410033: Specified flash device size, %1\$d GB, is too small.

Cause	Specified flash device size is too small.
Action	Increase the directive flash device size.

410034: The specified disk path, '%1\$s', is already in use by another disk.

Cause	The specified disk path is already in use by another disk.
Action	Check the disk path.

410035: Not enough memory to load the Flashcache.

Cause	Check the storage server's shared memory size.
Action	Retry the operation after increasing the shared memory size.

410036: Invalid Flashcache name length. (Name: %1\$s, Max name length: %2\$uBytes)

Cause	Failed to load because the name length of is too long.
Action	Retry the operation after setting the Flashcache name length to less than max name length.

410037: Invalid Flashcache path length. (Name: %1\$s, Max path length: %2\$uBytes)

Cause	Failed to load because the path length of is too long.
Action	Retry the operation after setting the Flashcache path length to less than max path length.

410038: Unable to find the Flashcache '%1\$s'.

Cause	Check that the Flashcache path and permissions are set correctly.
Action	Retry the operation after setting the Flashcache path and permissions to valid values.

410039: Invalid Flashcache header.

Cause	Invalid Flashcache header format. The Flashcache has not been formatted.
Action	Retry the operation after checking that the Flashcache is not corrupt or has not been forcibly replaced.

410040: Invalid Flashcache version. (Version: %1\$s(Previous), %2\$s(Current))

Cause	Failed to load because the Flashcache header version and current version are not compatible.
Action	Switch to the previous version and drop the Flashcache, and then switch back to the current version and recreate the Flashcache.

410041: Invalid Flashcache journal size. (Journal size: %1\$uBytes(Required) %2\$uBytes(Parameter))

Cause	Failed to format the Flashcache because its journal size is less than the required minimum size.
Action	Retry the operation after setting the Flashcache journal size to at least the minimum size required.

410042: Invalid Flashcache meta block size. (Meta blocksize: %1\$uBytes(Header), %2\$uBytes(Parameter))

Cause	The meta block size specified in the parameter and the Flashcache header are different.
Action	Retry the operation after setting the meta block size parameter to the meta block size set in the Flashcache header.

410043: Invalid Flashcache bin block size. (Bin blocksize: %1\$uBytes(Header), %2\$uBytes(Parameter))

Cause	The bin block size specified in the parameter and the Flashcache header are different.
Action	Retry the operation after setting the bin block size parameter to the bin block size set in the Flashcache header.

410044: Invalid Flashcache bin size (Bin size: %1\$uBytes(Header), %2\$uBytes(Parameter)).

Cause	The bin size specified in the parameter and the Flashcache header are different.
Action	Retry the operation after setting the bin size parameter to the bin size set in the Flashcache header.

410045: Function offloading is not supported.

Cause	Unable to find a storage server to execute function offloading to.
Action	Function offloading is only supported in storage server mode.

410046: SDM is null.

Cause	SDM is null.
Action	A dump cannot be performed when SDM is null.

410047: The disk id, \'%1\$d\', is invalid.

Cause	The id is duplicated or a disk with the specified id could not be found.
Action	Check the disk id.

410048: The specified disk id, \'%1\$d\', is already in use by another disk.

Cause	The specified disk id is already in use by another disk.
Action	Check the disk id.

410049: Unable to process nondata block: file# %1\$u, block# %2\$u.

Cause	Unable to process nondata block.
Action	Check the invalid block.

410050: Unable to process inconsistent block: file# %1\$u, block# %2\$u.

Cause	Unable to process inconsistent block.
Action	Check the invalid block.

410051: Fail to concat in processing cu block: file# %1\$u, block# %2\$u.

Cause	Fail to concat in processing cu block.
Action	Check the invalid block.

410052: Failed to create a connection resource between the database server and storage server.

Cause	Failed to create a connection resource between the database server and storage server.
--------------	--

Action	Check memory usage and log(connection resource creation fail log).
---------------	--

410053: Failed to establish a connection with the database server due to an error on the storage server.

Cause	Failed to establish a connection with the database server due to an error on the storage server.
Action	Check whether the TCP/IB network is operating normally.

410054: An internal error occurred in the executor layer on the storage server.

Cause	An internal error occurred in the executor layer on the storage server.
Action	Check the pp dump for further details.

410055: Failed to read/write on the storage server.

Cause	An I/O error occurred on the storage server.
Action	Check the logs of storage server to get more information about the error.

410056: Failed to deserialize on the storage server.

Cause	An EX error occurred on the storage server.
Action	Check the logs of storage server to get more information about the error.

제41장 528000 ~ 528999

528005: Logical error in optimizer.

Cause	Logical error in optimizer.
Action	Contact the technical support team.

